Rainfall probabilities, stronger baselines and feature ablation

The selected conditional-distribution model is evaluated on development folds. The historical classifier and its known 2024 test are retained as separate evidence.


Findings

Selected continuous candidate: **cdf_persistence_d8_leaf1000**, development equal-threshold/year Brier **0.016795**. Strong persistence baseline: 0.017939; climate baseline: 0.028989; global frequency: 0.029194; historical tree: 0.017585. Relative Brier reduction is 6.38% versus persistence and 42.47% versus frequency. These are probability-error reductions relative to named baselines, not accuracy improvements or superiority on every metric.

Data, selection and test policy

Use freshly reconstructed inputs matching the original 10% fixed-hash training/full eligible validation anchors for each E2 fold. No new 2024 labels or scores are used. Original post-filter join and sample signatures are recorded; all candidates share keys. Selection uses five original cuts and equal year weights; only continuous-CDF candidates are deployment-eligible. Discrete tree/RF results are openly reported diagnostics. Held-out cuts 0.25/0.75/1.5/3 are not used to fit or select. A new 2017–2023 refit is saved after lock, but its evidence is development validation; there is no claim of a new untouched final test.

Candidate	2021	2022	2023	Mean Brier	Continuous eligible
frequency_cdf	0.028542	0.029113	0.029928	0.029194	True
climatology_cdf	0.028416	0.028968	0.029584	0.028989	True
persistence_cdf	0.017216	0.018134	0.018467	0.017939	True
cdf_recent_d8	0.016166	0.017101	0.017271	0.016846	True
cdf_persistence_d8	0.016121	0.017084	0.017232	0.016812	True
cdf_calendar_d8	0.016202	0.017073	0.017251	0.016842	True
cdf_full_d5	0.016259	0.017175	0.017448	0.016961	True
cdf_full_d8	0.016202	0.017073	0.017251	0.016842	True
cdf_persistence_d8_leaf1000	0.016097	0.017067	0.017221	0.016795	True
cdf_persistence_d8_leaf250	0.016189	0.017126	0.017281	0.016865	True
threshold_tree_d8	0.016579	0.017585	0.017895	0.017353	False
random_forest_small	0.018098	0.019147	0.019618	0.018954	False



Development comparison

Candidate	Mean Brier	Mean log loss	Mean PR-AUC	Mean ROC-AUC
frequency_cdf	0.029194	0.130588	0.030478	0.500000
climatology_cdf	0.028989	0.128169	0.049425	0.610753
persistence_cdf	0.017939	0.079660	0.544264	0.816221
cdf_recent_d8	0.016846	0.074189	0.574488	0.846418
cdf_persistence_d8	0.016812	0.074096	0.575936	0.846505
cdf_calendar_d8	0.016842	0.072624	0.562884	0.894917
cdf_full_d5	0.016961	0.073453	0.558996	0.885623
cdf_full_d8	0.016842	0.072624	0.562883	0.894933
cdf_persistence_d8_leaf1000	0.016795	0.073989	0.575114	0.846531
cdf_persistence_d8_leaf250	0.016865	0.074290	0.574482	0.846500
threshold_tree_d8	0.017353	0.080014	0.559288	0.828428
random_forest_small	0.018954	0.082222	0.556613	0.839224

Additional ranking/log-loss metrics are diagnostics, not replacement selection criteria. A lower Brier does not imply superiority for every cut/year/ranking measure. Complete per-cut/year metrics are retained.

Arbitrary threshold design

Training-only conditional empirical distributions provide P(S>h)=1-F(h) for finite nonnegative Decimal(38,18) thresholds. Right-sided CDF lookup makes equality negative. For tree candidates Spark DecisionTreeRegressor fits log1p future amount using past features, then exact training amounts form leaf CDFs. Fixed prior weights are 50 anchors for leaves and 200 for baseline groups. No validation outcomes are written back into predictions. This naturally gives threshold-specific probabilities and nonincreasing stepwise survival curves without post-hoc isotonic correction; arbitrary input is not a claim of a smooth curve. Nine checked cuts lie in 0..5 mm; arbitrary input acceptance and monotonicity do not prove every threshold or extreme-tail reliability. Beyond maximum training amount, empirical probability is zero with no proven tail guarantee.

Untrained/selection-excluded cut (mm)	Mean Brier	Mean PR-AUC	Mean log loss
0.25	0.022515	0.680357	0.097211
0.75	0.017284	0.627793	0.076924
1.5	0.012813	0.553890	0.059034
3	0.008762	0.472734	0.042336

Minimum leaf-size comparison

The supplementary development experiment freezes minInstancesPerNode at 250, 500 and 1000, holding 22 persistence features, depth 8, seed, folds, primary cuts, prior and row identities fixed. Thirty earlier candidate/fold cells are explicitly reused, and six new cells fit the two added sizes. The main rule keeps the original candidate within absolute 1e-5 of the best, then prefers 1000 over 250. This is an incremental search on already-observed development years, not an independent test. No 2024 score selects the result.

Minimum leaf anchors	Mean Brier	Delta vs 500	Mean PR-AUC	Mean log loss	Mean ECE
250	0.016865	0.000053	0.574482	0.074290	0.002410
500	0.016812	0.000000	0.575936	0.074096	0.002096
1000	0.016795	-0.000017	0.575114	0.073989	0.001819

Selected leaf size is 1000. Mean PR-AUC is 0.575114, versus 0.575936 for leaf500; mean fixed-bin ECE is 0.001819, versus 0.002096. The Brier-selected model need not improve every ranking metric, and the small differences are not claimed statistically significant.

C input reconstruction acceptance


The C reconstruction script was executed from an extracted source directory using the existing formal A data and B feature Parquet. It regenerated the three development TRAIN/VALIDATION inputs and final 2017–2023 TRAIN only. Counts and two role-wise row-hash sums across all keys, targets and features match the historical anchors; these signatures are diagnostics, not cryptographic proof of row equality. Parquet bytes are expected to differ. New leaf candidates train on the rebuilt inputs; final model refit/reload and compact checks also complete. This accepts the C part of the missing-anchor workflow, not fresh-machine full A/B reproduction or Windows execution.

Controlled feature contribution experiment

All depth-8 CDF ablations hold rows, seed, min leaf size 500, bins, prior and shared feature ordering fixed. This feature ablation precedes the separate leaf-size search. The threshold is a CDF query, not a tree input. Sequential differences test recent amount -> persistence -> periodic time -> station. Negative Brier delta means adding that group helps under this design; positive means it does not. These are model/data-conditional associations, not causal attribution. Impurity weights are separately saved but are not used as contribution evidence.

Feature group	Mean Brier	Delta from previous	Relative reduction
Recent amount features only (14)	0.016846	NA	NA
Add wetness/persistence (22)	0.016812	-0.000034	0.001990
Add cyclic time (26)	0.016842	0.000030	-0.001775
Add training-only station coding (26 + station)	0.016842	0.000000	-0.000001

Calibration and low-risk discrimination




Low-probability development reliability


The 2023 plot zooms to 0..5% and point size shows support. Complete bin counts are in each fold calibration CSV; fixed-bin ECE and low-region rates are in selected_calibration_summary.csv. The appendix gives the exact n for every point shown in the 2023 low-probability plot. Low-region membership depends on each model prediction, so its support can differ; it is not a common held-fixed subgroup comparison. Dry/wet history group tables provide that common covariate-defined comparison. No held-out calibrator is fitted.

Cut/mm	Original ECE	Selected ECE	Selected low mean p	Selected low observed rate
0	0.016184	0.002969	0.020037	0.020952
0.5	0.004827	0.001976	0.010161	0.010826
1	0.003437	0.002026	0.007667	0.008366
2	0.005694	0.001396	0.005958	0.006462
5	0.009469	0.000730	0.003259	0.003584

Group performance and coverage



Observed-anchor sample flow



Group Brier

Groups are 12 months, five stations chosen from first-fold training counts, and complete-history all-dry/any-wet states. Exact per-year/cut rows include n, positives, Brier, mean p, fixed-bin ECE, approximate PR/ROC-AUC, eligible count and observed denominator. Group AUC uses 1,000 equal-probability histogram bins and is explicitly approximate; overall AUC uses Spark MLlib numBins=1000. No subgroup is chosen using test outcomes. Coverage is of observed anchors, not the ideal station calendar; unknown history is retained in the coverage ledger but is unscored.

Group	Equal-cut/year Brier	Approximate PR-AUC	Mean observed coverage
history:dry	0.009236	0.504682	0.997436
history:wet	0.095812	0.743110	0.996209
month:1	0.022054	0.585831	0.986302
month:10	0.015065	0.535515	0.991655
month:11	0.020817	0.584223	0.991760
month:12	0.021228	0.537458	0.988788
month:2	0.015319	0.497674	0.988228
month:3	0.017689	0.598573	0.991018
month:4	0.016958	0.547426	0.992813
month:5	0.012869	0.535460	0.992972
month:6	0.016491	0.521667	0.994474
month:7	0.013469	0.546301	0.991547
month:8	0.017219	0.556388	0.991386
month:9	0.013865	0.616486	0.992004
station:S113	0.015176	0.547013	0.995828
station:S120	0.017745	0.580044	0.995401
station:S77	0.016741	0.574152	0.972816
station:S88	0.017730	0.567055	0.990772
station:S94	0.016078	0.561237	0.995448

Reproduction and immutable evidence

Fresh-process model reload reconstructs 100 anchors from only past observations and compares 1,000 probabilities at ten cuts, including 3.14159 mm. Maximum error: 0.000000. Invalid station/time/history/threshold handling and monotonic examples pass. The model, report, ZIP, requirements lock and metadata stay inside this run. Finalization reads the executing Python environment via importlib.metadata, without private uv or OS-specific virtual-environment paths. All original source-run file hashes, including 2024 scores/model, pass preservation checks. Current evidence navigation identifies successful receipts without deleting historical failures.

Computing environment and timing

Python 3.11.17, Spark 3.5.7, Java 17.0.20.1; macOS-14.1-arm64-arm-64bit; 14 logical CPUs. Each process: local[2], 6g heap, 128 shuffle partitions, 32 MiB reads. At most two fold processes overlapped. Peaks were not measured; timings are not benchmarks. Candidate timing includes fit/CDF estimation, saves, scoring and metrics; excludes shared hashes/startup, reports and packaging. Training timing includes preprocessing. Exact fold JSON and candidate_timing_summary.csv define the measured scopes.

Remaining limitations and AI use

Development results motivated by review are now known and should not be relabelled untouched. Fixed train sampling and small candidate set limit conclusions. Overlapping windows/weather across stations are correlated; no independent-row bootstrap or significance claims are used. Observed gaps, composition changes and training leaf support affect performance. Event-time availability and official interval meaning remain assumptions; live deployment latency is unverified. OpenAI Codex assisted implementation, execution, tests, figures and drafting. All scores come from actual saved Spark outputs; member review is still required.

Official model references: Spark DecisionTreeRegressor and Spark RandomForestClassifier.

Appendix: selected continuous model, 2021

Cut/mm	n	Event rate	Brier	Log loss	PR-AUC	ROC-AUC
0.0	6976044	0.060931	0.030033	0.126427	0.711561	0.842452
0.25	6976044	0.042799	0.021276	0.092676	0.692554	0.861727
0.5	6976044	0.035763	0.018574	0.082097	0.664752	0.861192
0.75	6976044	0.031126	0.016755	0.074959	0.641330	0.859055
1.0	6976044	0.025885	0.014719	0.066706	0.606510	0.855212
1.5	6976044	0.021097	0.012644	0.058253	0.568850	0.850465
2.0	6976044	0.017239	0.010882	0.051110	0.531067	0.844238
3.0	6976044	0.012973	0.008613	0.041776	0.484888	0.838400
5.0	6976044	0.008877	0.006276	0.031134	0.425757	0.840389

Appendix: selected continuous model, 2022

Cut/mm	n	Event rate	Brier	Log loss	PR-AUC	ROC-AUC
0.0	7072758	0.064804	0.033472	0.138865	0.689036	0.831978
0.25	7072758	0.044063	0.023148	0.099966	0.664498	0.850638
0.5	7072758	0.035889	0.019605	0.086493	0.635263	0.849580
0.75	7072758	0.030773	0.017315	0.077611	0.613045	0.847743
1.0	7072758	0.025229	0.014905	0.068068	0.577917	0.842889
1.5	7072758	0.020505	0.012651	0.059044	0.543579	0.837805
2.0	7072758	0.016969	0.010838	0.051617	0.514408	0.834181
3.0	7072758	0.013176	0.008821	0.042835	0.472150	0.832588
5.0	7072758	0.009109	0.006518	0.031972	0.410555	0.839019

Appendix: selected continuous model, 2023

Cut/mm	n	Event rate	Brier	Log loss	PR-AUC	ROC-AUC
0.0	6686625	0.066713	0.033326	0.137072	0.707493	0.843928
0.25	6686625	0.045559	0.023122	0.098993	0.684018	0.862187
0.5	6686625	0.037479	0.019862	0.086427	0.655063	0.862454
0.75	6686625	0.032254	0.017782	0.078203	0.629006	0.861366
1.0	6686625	0.026297	0.015341	0.068594	0.590120	0.857619
1.5	6686625	0.021309	0.013145	0.059805	0.549242	0.852919
2.0	6686625	0.017291	0.011247	0.052205	0.507950	0.847608
3.0	6686625	0.012949	0.008853	0.042399	0.461164	0.842544
5.0	6686625	0.008702	0.006329	0.031055	0.399262	0.845219

Appendix: exact sample count for every plotted low-probability point (2023)

Model	Cut/mm	Bin	n	Mean p	Observed rate
Historical tree	0	3	6,273,227	0.010323	0.026913
Selected model	0	4	6,080,591	0.020324	0.021151
Historical tree	0.5	3	6,273,227	0.010323	0.011734
Selected model	0.5	2	6,080,591	0.009796	0.010196
Selected model	0.5	4	130,423	0.037971	0.046173
Historical tree	1	3	6,273,227	0.010323	0.008240
Selected model	1	2	6,080,591	0.007068	0.007338
Selected model	1	3	81,581	0.017711	0.023253
Selected model	1	4	158,269	0.032974	0.038972
Historical tree	2	3	6,273,227	0.010323	0.005691
Selected model	2	2	6,103,843	0.005037	0.005167
Selected model	2	3	181,278	0.014344	0.017989
Selected model	2	4	172,908	0.034253	0.041062
Historical tree	5	3	6,273,227	0.010323	0.002857
Selected model	5	1	6,141,931	0.002593	0.002650
Selected model	5	2	190,584	0.007050	0.008306
Selected model	5	3	113,152	0.014816	0.018868
Selected model	5	4	95,194	0.028774	0.032408