

adjust回传2（冗余）

基于 Spring boot框架

项目背景

adjust回传数据，分析广告投放，只做为冗余

adjust回传2

项目	说明	描述
svn	https://192.168.0.126/svn/tech_web/bigdata/adjust_resp	
服务器	119.28.41.240	
发布目录	/data/web/adjust_resp	
登录账号	hqweb	
绑定域名	dynamic-adjust-log.blustargames.com	腾讯LB
链接	https://dynamic-adjust-log.blustargames.com/ajevent/qkslg	

快速开始

1. 环境要求

- JDK: 21
- Maven: 3.0+

2. 配置修改

- 目录结构

```
[root@cloud3 adjust_resp]# ll
total 20
-rw-rw-r-- 1 hqweb hqweb 6 Apr 7 17:08 application.pid
drwxr-xr-x 2 hqweb hqweb 4096 Mar 27 10:35 bin
drwxr-xr-x 3 hqweb hqweb 4096 Jun 9 18:11 config
drwxr-xr-x 3 hqweb hqweb 4096 Apr 7 17:07 lib
drwxr-xr-x 2 hqweb hqweb 4096 Apr 7 17:08 logs
```

- bin目录start.sh

```
#!/bin/sh

APP_HOME=`cd $(dirname $0)/..; pwd`
cd $APP_HOME

echo $APP_HOME

pid_file="$APP_HOME"/application.pid
echo $pid_file
timeout=40
elapsed=0
interval=2

if [ -f $pid_file ]; then
    echo "$APP_HOME already running!"
    exit 0
fi

SPRING_OPT="${SPRING_OPT} -Dspring.profiles.active=prod"

JAVA_OPT="${JAVA_OPT} -server"
JAVA_OPT="${JAVA_OPT} -Dfile.encoding=UTF-8 -Duser.timezone=GMT+8 -
Djava.security.egd=file:/dev/./urandom"

JAVA_OPT="${JAVA_OPT} -Djasypt.encryptor.password=64c0fbad2021d608aet7402b3a194cd4"

JAVA_OPT="${JAVA_OPT} -Xmx4096m -Xms4096m -XX:MetaspaceSize=256m -
XX:AutoBoxCacheMax=20000 -XX:+AlwaysPreTouch -XX:InitialCodeCacheSize=128m -
XX:ReservedCodeCacheSize=128m"
JAVA_OPT="${JAVA_OPT} -Xmn2176m -XX:MaxGCPauseMillis=150 -XX:MaxTenuringThreshold=6"

JAVA_OPT="${JAVA_OPT} -XX:+DisableExplicitGC"
JAVA_OPT="${JAVA_OPT} -XX:+HeapDumpOnOutOfMemoryError -XX:HeapDumpPath=./logs -XX:-
UseGCOverheadLimit"
JAVA_OPT="${JAVA_OPT} -XX:-OmitStackTraceInFastThrow -Xlog:async -
XX:AsyncLogBufferSize=4194304 -
Xlog:gc*=info:file=${APP_HOME}/logs/gc_%t.log:utctime,level,tags:filecount=50,filesize=10
0M"

#JAVA_OPT="${JAVA_OPT} -Xnoagent -Xdebug -
Xrunjdwp:transport=dt_socket,server=y,suspend=n,address=5005"
#JAVA_OPT="${JAVA_OPT} -Djava.rmi.server.hostname=15.220.83.84 -
Dcom.sun.management.jmxremote -Dcom.sun.management.jmxremote.local.only=false -
```

```
Dcom.sun.management.jmxremote.port=5006 -Dcom.sun.management.jmxremote.rmi.port=5006 -
Dcom.sun.managementtote.ssl=false -Dcom.sun.management.jmxremote.ssl=false -
Dcom.sun.management.jmxremote.authenticate=false"
```

```
nohup /usr/local/webservices/jdk-21.0.5/bin/java ${SPRING_OPT} ${JAVA_OPT} -jar
${APP_HOME}/lib/adjust_resp.jar --server.port=9549 --
spring.pid.file=${APP_HOME}/application.pid > ${APP_HOME}/logs/start-jar.out 2>&1 &
echo "${APP_HOME} is starting,you can check the ${APP_HOME}/logs/start-jar.out"
```

```
sleep 5
```

```
pid=$(pgrep -f "adjust_resp.jar")
```

```
if [ -z "$pid" ]; then
    echo "启动失败, 进程未发现"
    exit 1
else
    echo "启动成功, 进程PID: $pid"
    echo $pid > ${APP_HOME}/application.pid
fi
```

- [bin目录shutdown.sh](#)

```
#!/bin/bash
APP_HOME=$(cd "$(dirname "$0")"/..; pwd)
pid_file="${APP_HOME}/application.pid"

echo "准备停止应用程序..."

pids=$(ps aux |grep '/data/web/adjust_resp/'|grep -E 'adjust_*.jar'| grep -v 'grep' |
awk -F ' ' '{print $2}')

if [ -z "$pids" ]; then
    echo "未找到正在运行的进程。"
else
    echo "找到进程PID: $pids, 正在终止..."
    kill -9 $pids
    echo "进程已终止。"
fi

# 删除 pid 文件
if [ -f "$pid_file" ]; then
    echo "删除 pid 文件: $pid_file"
    rm -f "$pid_file"
else
    echo "pid 文件不存在, 无需删除。"
fi

echo "应用程序已关闭完毕。"
```

- config目录结构

```
[hqweb@cloud3 config]$ ll
total 16
-rw-r--r-- 1 hqweb hqweb 557 Mar 27 10:23 application-prod.yml
-rw-r--r-- 1 hqweb hqweb 106 Mar 25 15:52 application.yml
drwxr-xr-x 2 hqweb hqweb 4096 Mar 26 13:37 bak
-rw-r--r-- 1 hqweb hqweb 3299 Mar 27 10:43 logback-spring.xml
```

- application.yml

```
spring:
  config:
    import: application-${spring.profiles.active}.yml
  profiles:
    active: prod
```

- application-prod.yml

```
spring:
  application:
    name: ajevent
  mvc:
    pathmatch:
      matching-strategy: path_pattern_parser
  pid:
    file: /data/web/adjust_resp/application.pid
server:
  address: 0.0.0.0
  port: 9549
  shutdown: graceful
  undertow:
    threads:
      io: 16
      worker: 160
    direct-buffers: true
  adjust:
    threadPool:
      corePoolSize: 32
      maxPoolSize: 64
      queueCapacity: 5000000
      keepAliveSeconds: 300
  logging:
    config: ./config/logback-spring.xml
    file:
      path: /data1/logs/resp/
    level:
      root: info
```

- logback-spring.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <!-- 基础配置 -->
```

```

<property name="LOG_ROOT" value="/data1/logs/ajevent"/>
<property name="log.pattern.ajevent" value="%d{yyyy-MM-dd HH:mm:ss},%msg%n"/>
<property name="CHARSET" value="UTF-8" />
<property name="MAX_FILE_SIZE" value="1GB" />

<property name="console.pattern"
    value="%clr(%d{yyyy-MM-dd HH:mm:ss.SSS}){bright_red},%clr(%level)
{highlight},%thread,%X{TRACE_ID},%clr(%F){cyan},%clr(%M){yellow}:%clr(%L)
{bright_magenta},%clr(%msg%n){bright_blue}"/>

<!-- 动态日志路径 -->
<springProperty scope="context" name="APP_NAME" source="spring.application.name"/>

<!-- SiftingAppender 配置 -->
<appender name="SIFT" class="ch.qos.logback.classic.sift.SiftingAppender">
    <discriminator>
        <key>projectCode</key>
        <defaultValue>common</defaultValue>
    </discriminator>

    <sift>
        <appender name="FILE-${projectCode}"
class="ch.qos.logback.core.rolling.RollingFileAppender">
            <prudent>>false</prudent>
            <rollingPolicy
class="ch.qos.logback.core.rolling.SizeAndTimeBasedRollingPolicy">
                <fileNamePattern>${LOG_ROOT}/${projectCode}/${APP_NAME}.%d{yyyy-MM-
dd}.%i.log</fileNamePattern>
                <maxFileSize>${MAX_FILE_SIZE}</maxFileSize>
                <cleanHistoryOnStart>>true</cleanHistoryOnStart>
            </rollingPolicy>
            <encoder>
                <charset>${CHARSET}</charset>
                <pattern>${log.pattern.ajevent}</pattern>
            </encoder>
            <filter class="ch.qos.logback.classic.filter.LevelFilter">
                <level>INFO</level>
                <onMatch>ACCEPT</onMatch>
                <onMismatch>DENY</onMismatch>
            </filter>
        </appender>
    </sift>
</appender>

<!-- 错误日志 Appender: 独立记录 ERROR -->
<appender name="ERROR_SIFT" class="ch.qos.logback.classic.sift.SiftingAppender">
    <discriminator>
        <key>projectCode</key>
        <defaultValue>common</defaultValue>
    </discriminator>
    <sift>
        <appender name="ERROR_FILE-${projectCode}"
class="ch.qos.logback.core.rolling.RollingFileAppender">
            <file>${LOG_ROOT}/${projectCode}/error.log</file>
            <rollingPolicy
class="ch.qos.logback.core.rolling.SizeAndTimeBasedRollingPolicy">
                <fileNamePattern>${LOG_ROOT}/${projectCode}/error.%d{yyyy-MM-

```

```

dd).%i.log</fileNamePattern>
    <maxFileSize>${MAX_FILE_SIZE}</maxFileSize>
</rollingPolicy>
<encoder>
    <charset>${CHARSET}</charset>
    <pattern>${log.pattern.ajevent}</pattern>
</encoder>
<filter class="ch.qos.logback.classic.filter.ThresholdFilter">
    <level>ERROR</level>
</filter>
</appender>
</sift>
</appender>

<!-- 日志根节点配置 -->
<root level="INFO">
    <appender-ref ref="SIFT"/>
    <appender-ref ref="ERROR_SIFT"/>
</root>
</configuration>

```

3. 完整回传地址

```

https://dynamic-adjust-log.blustargames.com/ajevent/qkslg?
sign=29f30ca5ddeec8c4b45e5d3d40519b84&timestamp={created_at}&timezone=
{timezone}&environment={environment}&app_id={app_id}&app_name=
{app_name}&app_name_dashboard={app_name_dashboard}&app_version={app_version}&sdk_version=
{sdk_version}&adid={adid}&idfa={idfa}&idfv={idfv}&android_id={android_id}&gps_adid=
{gps_adid}&mac_md5={mac_md5}&partner_parameters={partner_parameters}&os_name=
{os_name}&store={store}&ip_address={ip_address}&country={country}&city=
{city}&activity_kind={activity_kind}&event={event}&event_name=
{event_name}&publisher_parameters={publisher_parameters}&time_spent={time_spent}&revenue=
{revenue}&currency={currency}&revenue_usd_cents={revenue_usd_cents}&revenue_cny_cents=
{revenue_cny_cents}&click_time={click_time}&impression_time=
{impression_time}&engagement_time={engagement_time}&installed_at=
{installed_at}&reattributed_at={reattributed_at}&reinstalled_at=
{reinstalled_at}&uninstalled_at={uninstalled_at}&conversion_duration=
{conversion_duration}&click_referer={click_referer}&match_type=
{match_type}&rejection_reason={rejection_reason}&is_organic={is_organic}&tracker=
{tracker}&tracker_name={tracker_name}&network_name={network_name}&campaign_name=
{campaign_name}&adgroup_name={adgroup_name}&creative_name={creative_name}&cost_type=
{cost_type}&event_cost_id={event_cost_id}&cost_amount={cost_amount}&cost_currency=
{cost_currency}&fb_ins_ref={fb_install_referrer}&fb_ins_ref_account_id=
{fb_install_referrer_account_id}&fb_ins_ref_publisher_platform=
{fb_install_referrer_publisher_platform}&fb_ins_ref_campaign_group_id=
{fb_install_referrer_campaign_group_id}&fb_ins_ref_campaign_group_name=
{fb_install_referrer_campaign_group_name}&fb_ins_ref_campaign_id=
{fb_install_referrer_campaign_id}&fb_ins_ref_campaign_name=
{fb_install_referrer_campaign_name}&fb_ins_ref_adgroup_id=
{fb_install_referrer_adgroup_id}&fb_ins_ref_adgroup_name=
{fb_install_referrer_adgroup_name}&fb_ins_ref_ad_id=
{fb_install_referrer_ad_id}&fb_ins_ref_ad_objective_name=
{fb_install_referrer_ad_objective_name}&meta_install_referrer=
{meta_install_referrer}&google_ads_campaign_id=
{google_ads_campaign_id}&google_ads_campaign_name=
{google_ads_campaign_name}&google_ads_campaign_type=

```

```
{google_ads_campaign_type}&google_ads_adgroup_id=
{google_ads_adgroup_id}&google_ads_adgroup_name=
{google_ads_adgroup_name}&google_ads_creative_id=
{google_ads_creative_id}&google_ads_network_type=
{google_ads_network_type}&google_ads_network_subtype=
{google_ads_network_subtype}&google_ads_keyword=
{google_ads_keyword}&google_ads_matchtype={google_ads_matchtype}&google_ads_video_id=
{google_ads_video_id}&google_ads_placement={google_ads_placement}&label={label}&tweet_id=
{tweet_id}&twitter_line_item_id={twitter_line_item_id}&prediction_label=
{prediction_label}&predicted_value={predicted_value}&prediction_period_days=
{prediction_period_days}&isp={isp}&connection_type={connection_type}&network_type=
{network_type}&device_manufacturer={device_manufacturer}&device_type=
{device_type}&device_name={device_name}&device_model={device_model}&os_version=
{os_version}&language={language}&region={region}
```