

Uncovering LLM Lineage via Static Fingerprints: Progress, Gaps, and Opportunities

Anonymous Author(s)

Abstract

CCS Concepts

• **Do Not Use This Code → Generate the Correct Terms for Your Paper**; *Generate the Correct Terms for Your Paper*; Generate the Correct Terms for Your Paper; Generate the Correct Terms for Your Paper.

Keywords

Do, Not, Use, This, Code, Put, the, Correct, Terms, for, Your, Paper

ACM Reference Format:

Anonymous Author(s). 2026. Uncovering LLM Lineage via Static Fingerprints: Progress, Gaps, and Opportunities. In . ACM, New York, NY, USA, 11 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 Introduction

Large Language Models (LLMs) have significantly transformed the landscape of artificial intelligence and software engineering. While proprietary models such as GPT and Claude dominate the consumer market, public open-source models such as DeepSeek are increasingly gaining popularity among business entities due to their enhanced transparency, lower deployment costs, reduced legal and licensing constraints, and greater flexibility for customization. Indeed, popular model-sharing platforms (e.g., Hugging Face) host over 2 million models [2], with top models receiving more than one million downloads [45].

Notably, a closer examination of the interconnections among these models reveals a significant degree of reuse [45]. In particular, many models are derived from existing base models through techniques such as fine-tuning [22], model merging [6], and quantization [94]. Such derivations enable the adaptation of general-purpose models to domain-specific scenarios, capability enhancement, and efficiency optimization. However, while enjoying the benefits, the model reusing also bring the inherited risks [13, 18, 32, 79], including legal liabilities (e.g., Intellectual Property violations) to security threats [25, 42, 44] (e.g., backdoors, jailbreaks, and prompt injection).

An effective strategy for risk mitigation is to ensure transparency in model composition, such as using AI Bills of Materials (AI-BOM) [1]. However, although platforms provide mechanisms (e.g., model cards in Hugging Face [5]) that allow contributors to document meta-information, such as model reuse details or model

performance [60], such practices are not consistently adopted proactively by model developers. This leads to incomplete disclosure of model information. For instance, prior work reports that the ninth most downloaded pretrained model on Hugging Face, with over 6.9 million monthly downloads, lacks a model card [45]. Consequently, it undermines model transparency, thereby hindering effective risk traceability and mitigation.

To address this problem, a range of model fingerprinting techniques can be leveraged. While dynamic fingerprinting approaches rely on analyzing a model’s inference behavior in response to carefully designed input queries [26, 27, 63, 65, 66, 87–91, 95, 107], they are often sensitive to input selection and may suffer from limited robustness under model modifications such as fine-tuning or compression. Therefore, we focus on the problem of *model lineage construction via static fingerprints*.

Empirical Study. We begin with an empirical study to understand the dependency prevalence and dependency types of public model reuse.

The problem of opaque model lineage is increasingly pressing. LLMs are often trained on massive datasets collected from multiple sources, combined with pre-trained models, and further fine-tuned in proprietary pipelines. This complexity obscures the relationship between models, making it difficult to trace the origin of errors, detect unintended biases, or comply with licensing requirements. Consequently, software engineers, AI practitioners, and policymakers face challenges in maintaining trust, reliability, and accountability in AI-driven systems. Despite the growing literature on supply chain analysis in traditional software and deep learning frameworks, systematic studies focused on LLM lineage remain sparse.

This paper seeks to address this gap by investigating how far current methods go in tracing and analyzing the lineage of LLMs. Specifically, we ask: (1) What techniques exist to track dependencies and derivations among LLMs? (2) How effective are these techniques in providing visibility into model origins and transformations? (3) What limitations persist, and where is further research needed? By framing LLM lineage in the context of software engineering, we aim to connect advances in AI with established practices in software maintenance, traceability, and quality assurance.

2 Motivation

The proliferation of Large Language Models (LLMs) has been dramatically accelerated by collaborative platforms like the [Hugging Face Hub](#), which serves as a central repository for model sharing. A cornerstone of this ecosystem is the iterative development of new models by building upon existing ones through techniques such as fine-tuning, merging, and quantization. This process creates a complex web of inter-model dependencies, which we define as **model genealogy** or **lineage**. A clear understanding of a model’s genealogy is paramount for ensuring traceability, reproducibility,

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference’17, July 2017, Washington, DC, USA

© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

and compliance, as derivative models often inherit biases, vulnerabilities, or licensing constraints from their predecessors.

However, the mechanisms currently available on the Hugging Face Hub for documenting this critical lineage information are frequently inconsistent, incomplete, or entirely absent. This lack of a systematic and enforceable standard for provenance documentation poses a significant barrier to researchers and developers. The most visible symptom of this issue is the difficulty, or outright impossibility, of programmatically constructing a model's lineage—a structure ideally represented as a "Model Tree". This is not a superficial interface problem but a direct consequence of fundamental flaws in how provenance data is recorded at its source.

To illustrate the severity of this challenge, we will dissect two distinct modes of documentation failure, each representing a progressively worsening degree of information obfuscation.

2.1 Problem 1: Lineage Concealed in Unstructured Text

In the most common scenario, lineage information exists but is locked within free-form text, rendering it inaccessible to automated tools. This forces researchers into a manual, error-prone process of discovery.

Case Study 1: DavidAU/NSFW_DPO_Noromaid-7b-GGUF

The Hugging Face repository of this model does not include a model tree; however, its model card explicitly states:

NSFW_DPO_Noromaid-7b-Mistral-7B-Instruct-v0.1 is a merge of the following models: mistralai/Mistral-7B-Instruct-v0.1 and athirpath/NSFW_DPO_Noromaid-7b.

Notably, the Hugging Face pages of both referenced models in the model card contain their respective model trees. This reliance on unstructured documentation makes the automated construction of a lineage graph infeasible. It imposes a significant manual burden for identifying even a direct parent and completely obstructs any large-scale, systematic analysis of the model ecosystem.

Case Study 2: timdettmers/guanaco-13b

Another example is the timdettmers/guanaco-13b model. While this model is a fine-tuned version of LLaMA, this pivotal relationship is not captured in any structured, machine-readable metadata. To discover this link, a user must manually navigate to the model's repository, open the "Model Card" (a Markdown file), and parse through natural language prose to find the statement:

Guanaco models are open-source finetuned chatbots obtained through 4-bit QLoRA tuning of LLaMA base models...

2.2 Problem 2: Lineage Outsourced to Fragile External Links

A more precarious situation arises when provenance information is not even located within the Hugging Face platform, but is instead hyperlinked to an external, third-party source.

Case Study 3: pfnet/plamo-2.1-2b-cpt

The model's homepage lacks a model tree, and its model card merely states that the model was derived by reducing the parameter size from an 8B-parameter model, without explicitly specifying the base model used for this operation. However, the model card provides links to three technical blogs for reference. By following these external links, we can infer that the mentioned 8B-parameter model is plano-2-8b.

Case Study 4: Remilistrasza/Mysterious_SDXL_Lah

Consider the Remilistrasza/Mysterious_SDXL_Lah model. Its Model Card is starkly empty of descriptive content, offering only a single hyperlink to a page on [Civitai](#), another model-sharing platform. To identify the base model, a user is forced to leave the Hugging Face ecosystem. Only upon navigating to this external page does one discover that the base model is "SDXL 1.0".

This practice introduces two severe risks: **information frag- mentation** and **link rot**. The integrity and availability of the lineage information become wholly dependent on the uptime and archival policies of an external website. Should the link become invalid (a 404 error), or the content on the remote page be altered or deleted, the model's traceable lineage is permanently severed. This practice renders the model's provenance fragile and unverifiable from within the Hugging Face ecosystem.

These documented failures, which range from information concealed in prose to its complete omission, demonstrate a clear and pressing need for an automated and reliable method to construct model genealogies. The current reliance on inconsistent and manual documentation is an unsustainable bottleneck in an ecosystem that is scaling rapidly. To bridge this critical gap, we propose an approach to automatically identify and verify the derivative relationships between models, thereby enabling robust and scalable lineage tracing.

2.3 Literature on Model Lineage Construction

As the problem of model traceability gains prominence, various methods have been proposed to detect relationships between LLMs (summarized in Table 1). However, these approaches typically over-optimize for specific operational scenarios, severely limiting their generalizability when constructing comprehensive lineage trees in the wild. First, the majority of techniques (e.g., REEF [107], MDIR [108], HuRef [105]) treat provenance as a symmetrical, pairwise similarity problem (Type "P") rather than a directional graph, failing to identify which model is the parent and which is the child (Dir. "x"). Second, they suffer from strict evaluation biases: dynamic

Table 2: Statistics of the GRANDMoTHER benchmark.

Statistic	Value
#Graphs	31
#Model pairs (edges)	248
Min / Median / Max pairs per graph	1 / 6 / 22
Avg. pairs per graph	8.0
#Models (nodes)	279
#Root models	31
#Intermediate models	44
#Leaf models	204
Share of leaf models	73.1%
Min / Avg / Max models per graph	2 / 9.0 / 23
Avg. out-degree of non-leaf models	3.31
Max fine-tuning depth	2

4 Empirical Setup

We design experiments to explore the following research questions.

- **Measurement Evaluation (RQ1):** How do different measurement metrics affect the effectiveness of LLM lineage detection?
- **Layer Contribution Analysis (RQ2):** How do different model layers influence the effectiveness of LLM lineage detection?
- **Failure Analysis (RQ3):** Why do existing methods fail to detect lineage?
- **Integration (RQ4):** using the above findings, the best performance can achieve? (80%)

Measurement Metrics. We select common measurement metrics that are used in static white-box fingerprinting. Static white-box fingerprinting captures intrinsic weight characteristics, including statistical distributions [100] (e.g., L_2 distances of model tensors [30]), directionally invariant terms [105], SVD-based spectral signatures [78], and matrix-driven homology proofs [108].

Accuracy. To comprehensively evaluate the structural recovery of model lineages, we measure performance at both the edge level and the tree level. Let $\mathcal{T}$ denote the set of all model family trees in our dataset. We define the following two metrics:

- **Micro-accuracy:** This metric evaluates the local edge prediction performance. It is defined as the total number of correctly predicted directed edges divided by the total number of ground-truth edges across all evaluated model graphs:

$$Micro-acc = \frac{\sum_{T \in \mathcal{T}} |E_{correct}^{(T)}|}{\sum_{T \in \mathcal{T}} |E_{total}^{(T)}|}$$

- **Macro-accuracy:** This metric evaluates the global topology reconstruction. It is defined as the ratio of successfully recovered model family trees (where the entire lineage topology and edge directions are perfectly matched) to the total number of model families:

$$Macro-acc = \frac{|\{T \in \mathcal{T} \mid T_{recovered} = T_{true}\}|}{|\mathcal{T}|}$$

Layers. To address RQ2, we systematically isolate the core structural components within Transformer-based Large Language Models (LLMs). Specifically, we dissect the Multi-Head Attention mechanism and the Feed-Forward Network (FFN). The attention mechanism involves projection weight matrices for the Query (W_Q), Key

(W_K), Value (W_V), and Output (W_O):

$$Attention(Q, K, V) = softmax\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$

Furthermore, we evaluate the contribution of the FFN, which typically consists of Multi-Layer Perceptron (MLP) dense layers:

$$FFN(x) = \sigma(xW_1 + b_1)W_2 + b_2$$

where σ represents a non-linear activation function. This granular breakdown enables us to systematically evaluate the fingerprinting capacity of various layer combinations and quantify their respective impacts on the effectiveness of lineage detection.

Graph Algorithms. In our experiments, we evaluate and compare several graph construction algorithms to reconstruct the model lineage topology from the computed pairwise distance and directional matrices:

- **MoTHER:** Following Horwitz et al. [30], we formulate the base lineage recovery task as finding a minimum directed spanning tree (MDST). We employ the Chu-Liu-Edmonds algorithm [14, 17] to achieve this optimal cycle-free directed routing.
- **Atlas Greedy DAG:** To account for complex, non-tree structures, we evaluate the Model Atlas framework [29]. This approach constructs a Directed Acyclic Graph (DAG) via a greedy algorithm, leveraging real-world structural priors such as temporal upload dynamics to determine edge directionality and explicitly accommodating multi-parent merged models.
- **Strict-Directional MDST:** We introduce a heavily constrained variant of the MDST. By setting the penalty for reverse edges (i.e., edges that violate the inferred directionality constraints) to infinity (∞), we strictly force the algorithm to adhere to the predicted parent-child hierarchical flow.
- **Undirected-MST:** We also implement a decoupled baseline. In the first stage, we construct a minimum spanning tree (MST) on the undirected graph using solely the distance matrix to determine topological connectivity. In the second stage, we subsequently assign directions to these established edges based on the independent directional information.

5 RQ1: Measurement Evaluation

Summary: L2+timestamp+xxgraph algorithm performs best.

6 RQ2: Layer Contribution Analysis

Summary: using QKV layer performs best. K layer contributes most.

7 RQ3: Failure Analysis

Multi-hop Analysis (RQ3): XX

8 RQ4: Integration Evaluation

9 Related Work

9.1 Model Identity Representation

Model watermarking deliberately embedded the triggers into the model to protect its intellectual property. Early mechanisms primarily targeted neural networks to defend against model extraction

Table 3: Lineage Detection Accuracy (%) w.r.t. Different Measurement Metrics, Direction Methods, and Graph Algorithms (RQ1)

Distances	Dir.	Macro-Accuracy										Micro-Accuracy									
		L2	Cos.	AM	AMx	SA	SR	PDF	Ghost	Matrix	HuRef	L2	Cos.	AM	AMx	SA	SR	PDF	Ghost	Matrix	HuRef
MoTher	K	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
	T	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Strict-Directional MDST	K	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
	T	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Undirected-MST	K	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
	T	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Atlas Greedy DAG	K	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
	T	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...

Figure 1: Distance metric distributions for different model families (RQ1).

and surrogate attacks [10, 23, 51, 52, 83, 106, 113]. Subsequent research has focused on embedding invisible and verifiable signatures

into generative models [19, 33, 34, 54, 55, 84, 96, 115] to protect AI-generated multimedia content, including images [81], videos [33],




Figure 2: Accuracy of lineage detection with different combinations of transformer block components (RQ2).




Figure 3: Accuracy2 of lineage detection with different combinations of transformer block components (RQ2).

and audio [40, 115]. Meanwhile, several studies aim to experiment watermark robustness against downstream fine-tuning [82] universal attacks [61], and forgery attacks [61]. Watermarking for LLMs was initially introduced to detect machine-generated text by biasing token selection during decoding [47]. Subsequent work has improved in terms of text quality, embedding capacity, and fine-grained detection capabilities [11, 20, 21, 31, 38, 41, 49, 56, 67, 69, 77, 86, 99, 111]. Meanwhile, adversarial studies have demonstrated evasion via paraphrasing, substitution, and cross-lingual transformations [28, 46, 80, 85]. In addition, recent approaches address challenges such as unforgeability [53] and support multi-user watermarking schemes [15]. Beyond model-level protection, emerging work extends watermarking techniques to data [64], text [112], code [74, 92], and prompts [97].

Model fingerprinting aims to build distinctive identifiers of models, encompassing both black-box behavioral profiling and white-box static analysis. Black-box fingerprinting relies on analyzing a model’s dynamic inference behavior in response to carefully crafted inputs [26, 66, 95], including modeling models’ outputs as unique vector subspaces [63, 65], functional representations [87], constructed prompts as adversarial suffixes [27, 90, 91].

White-box fingerprinting, in contrast, leverages access to internal model states to derive distinctive model profiles. Dynamic white-box approaches capture runtime characteristics, including feature representations [107], gradient tensors [88], activation differences [89], and token biases [76]. Static white-box fingerprinting captures intrinsic weight characteristics, including statistical distributions [100] (e.g., L_2 distances of model tensors [30]), directionally invariant terms [105], SVD-based spectral signatures [78], and matrix-driven homology proofs [108].

9.2 Model Relation Analysis

Building upon model fingerprinting techniques, recent research has advanced towards reconstructing the model relationships. Using dynamic white-box fingerprints, Wu et al. [88] proposes TensorGuard, which is a gradient-based fingerprinting to detect LLM lineage and classifies model families by analyzing layer-wise gradient responses to input perturbations. Besides, Oyama et al. [63] construct a model map using log-likelihood vectors from over 1,000 models. Wu et al. [87] introduces LLM DNA, a theoretically grounded, low-dimensional representation of model behavior. Using static




Figure 4: Contribution of different transformer block components (K/Q/V/O/MLP) to various distance metrics (RQ2).





Figure 5: Proportion of different types of erroneous edges in the constructed lineage graph (RQ3).

fingerprints, Zhang et al. [107] compares the pairwise feature representations of the two models using centered kernel alignment while remaining robust to model modifications like fine-tuning, pruning, and merging. Zhang et al. [108] proposes to detect and reconstructs weight correspondences using matrix analysis and statistical testing for LLM plagiarism detection without requiring inference. Based on fingerprinting and similarity analysis, recent



Red arrow: erroneous sibling edge (C → B)

Figure 6: Case study illustrating erroneous edges in the constructed lineage graph (RQ3).

research has begun to explicitly model LLM lineage. For instance, Yax et al. [98] apply phylogenetic algorithms to LLMs by leveraging output-based similarity to construct evolutionary trees that capture model relationships. Complementing this perspective, Yu et al. [101] propose neural lineage detection methods, including both learning-free and learning-based approaches, to identify parent and ancestral relationships among models. Shifting from behavioral to structural analysis, Horwitz [30] introduces MoTHER, which reconstructs lineage trees by analyzing neural network weights and

- [100] Do-hyeon Yoon, Minsoo Chun, Thomas Allen, Hans Müller, Min Wang, and Rajesh Sharma. 2025. Intrinsic Fingerprint of LLMs: Continue Training is NOT All You Need to Steal A Model! *arXiv preprint arXiv:2507.03014* (2025).
- [101] Runpeng Yu and Xinchao Wang. 2024. Neural lineage. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 4797–4807.
- [102] Sheng Yu, Wei Song, Xunchao Hu, and Heng Yin. 2024. On the correctness of metadata-based SBOM generation: A differential analysis approach. In *2024 54th Annual IEEE/IFIP International conference on dependable systems and networks (DSN)*. 29–36.
- [103] Nusrat Zahan. 2023. Software supply chain risk assessment framework. In *2023 IEEE/ACM 45th International Conference on Software Engineering: Companion Proceedings (ICSE-Companion)*. IEEE, 251–255.
- [104] Nusrat Zahan, Thomas Zimmermann, Patrice Godefroid, Brendan Murphy, Chandra Maddila, and Laurie Williams. 2022. What are weak links in the npm supply chain?. In *Proceedings of the 44th International Conference on Software Engineering: Software Engineering in Practice*. 331–340.
- [105] Boyi Zeng, Lizheng Wang, Yuncong Hu, Yi Xu, Chenghu Zhou, Xinbing Wang, Yu Yu, and Zhouhan Lin. 2024. Huref: Human-readable fingerprint for large language models. *Advances in Neural Information Processing Systems* 37 (2024), 126332–126362.
- [106] Jie Zhang, Dongdong Chen, Jing Liao, Zehua Ma, Han Fang, Weiming Zhang, Huamin Feng, Gang Hua, and Nenghai Yu. 2024. Robust model watermarking for image processing networks via structure consistency. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 46, 10 (2024), 6985–6992.
- [107] Jie Zhang, Dongrui Liu, Chen Qian, Linfeng Zhang, Yong Liu, Yu Qiao, and Jing Shao. 2024. Reef: Representation encoding fingerprints for large language models. *arXiv preprint arXiv:2410.14273* (2024).
- [108] Ruichong Zhang. 2025. Matrix-driven instant review: Confident detection and reconstruction of llm plagiarism on pc. *arXiv e-prints* (2025), arXiv–2508.
- [109] Weichao Zhang, Ruqing Zhang, Jiafeng Guo, Maarten de Rijke, Yixing Fan, and Xueqi Cheng. 2024. Pretraining data detection for large language models: A divergence-based calibration method. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*. 5263–5274.
- [110] Lida Zhao, Sen Chen, Zhengzi Xu, Chengwei Liu, Lyuye Zhang, Jiahui Wu, Jun Sun, and Yang Liu. 2023. Software composition analysis for vulnerability detection: An empirical study on Java projects. In *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering*. 960–972.
- [111] Xuandong Zhao, Chenwen Liao, Yu-Xiang Wang, and Lei Li. 2025. Efficiently identifying watermarked segments in mixed-source texts. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 6304–6316.
- [112] Tong Zhou, Xuandong Zhao, Xiaolin Xu, and Shaolei Ren. 2024. Bileve: Securing text provenance in large language models against spoofing with bi-level signature. *Advances in Neural Information Processing Systems* 37 (2024), 56054–56075.
- [113] Hongyu Zhu, Sichu Liang, Wentao Hu, Li Fangqi, Ju Jia, and Shi-Lin Wang. 2024. Reliable model watermarking: Defending against theft without compromising on evasion. In *Proceedings of the 32nd ACM International Conference on Multimedia*. 10124–10133.
- [114] Markus Zimmermann, Cristian-Alexandru Staicu, Cam Tenny, and Michael Pradel. 2019. Small world with high risks: A study of security threats in the npm ecosystem. In *28th USENIX Security symposium (USENIX security 19)*. 995–1010.
- [115] Wei Zong, Yang-Wai Chow, Willy Susilo, Joonsang Baek, and Seyit Camtepe. 2025. {AudioMarkNet}: Audio watermarking for deepfake speech detection. In *34th USENIX Security Symposium (USENIX Security 25)*. 4663–4682.