

```

1 # tests/test_message_director.py (excerpt)
2 dg = Datagram.create([12345654321], 0, 1234)
3 dg.add_uint32(0xDEADBEEF)
4 self.c2.send(dg)

```

(a) Function A

```

1 # Bitcoin transaction validation test
2 inputs = [{'txid': txid, 'vout': 1, 'sequence': 4294967296}]
3 assert_raises_rpc_error(-8, 'Invalid parameter, sequence number is out of range',
4 self.nodes[0].createrawtransaction, inputs, outputs)
5 # Valid boundary case
6 inputs = [{'txid': txid, 'vout': 1, 'sequence': 4294967294}]
7 rawtx = self.nodes[0].createrawtransaction(inputs, outputs)

```

(b) Function B

```

1 def c2s_bra(l, gcart):
2     if l == 0:
3         return gcart * 0.282094791773878143
4     elif l == 1:
5         return gcart * 0.488602511902919921
6     ...

```

(c) Function C

```

1 # Fail2ban ticket validation test
2 ticket_str = 'FailTicket: ip=193.168.0.128 time=1167605999.0
3 bantime=None'
4 ticket.setTime(1000002000.0)
5 self.assertEqual(ticket.getTime(), 1000002000.0)

```

(d) Function D