您可以从您离开的地方开始继续学习。加入一个新的班次,我们将重置您的截止日期。

加入班次

✓ 返回到第3周

X 课程

上一个

Classification and Representation

Logistic Regression Model



10 min

Co

Cost Function 3 min

Simplified Cost Function and Gradient Descent

10 min

Simplified Cost Function and Gradient Descent

3 min

Advanced Optimization

14 min

Advanced Optimization

3 min

Multiclass Classification

Review

Solving the Problem of Overfitting

Review

Simplified Cost Function and Gradient Descent

Note: [6:53 - the gradient descent equation should have a 1/m factor]

We can compress our cost function's two conditional cases into one case:

$$Cost(h_{\theta}(x), y) = -y \log(h_{\theta}(x)) - (1 - y) \log(1 - h_{\theta}(x))$$

Notice that when y is equal to 1, then the second term $(1-y)\log(1-h_{\theta}(x))$ will be zero and will not affect the result. If y is equal to 0, then the first term $-y\log(h_{\theta}(x))$ will be zero and will not affect the result.

We can fully write out our entire cost function as follows:

$$J(heta) = -rac{1}{m} \sum_{i=1}^m [y^{(i)} \log(h_ heta(x^{(i)})) + (1-y^{(i)}) \log(1-h_ heta(x^{(i)}))]$$

A vectorized implementation is:

$$egin{aligned} h &= g(X heta) \ J(heta) - rac{1}{m} \cdot \left(-y^T \log(h) - (1-y)^T \log(1-h)
ight) \end{aligned}$$

Gradient Descent

Remember that the general form of gradient descent is:

We can work out the derivative part using calculus to get:

$$egin{aligned} Repeat & \{ & & & & \ heta_j := heta_j - rac{lpha}{m} \sum_{i=1}^m (h_ heta(x^{(i)}) - y^{(i)}) x_j^{(i)} & & & \ \ \} & \end{aligned}$$

Notice that this algorithm is identical to the one we used in linear regression. We still have to simultaneously update all values in theta.

A vectorized implementation is:

$$heta := heta - rac{lpha}{m} \, X^T (g(X heta) - ec{y})$$

标记为完成