MOSFET

-30 Amps,-30 Volts P-CHANNEL MOSFET

FEATURE

- -30A,-30V,$R_{DS(ON)MAX}$=15mΩ @V_{GS}=-10V/-15A
  $R_{DS(ON)MAX}$=25mΩ @V_{GS}=-4.5V/-15A
- Low gate charge
- Low C_{iss}
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability
- RoHS 2.0 Compliant

DFN3*3







Absolute Maximum Ratings(T_C=25℃,unless otherwise noted)			
Parameter	**Symbol**	**D30P03HL**	**UNIT**
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GS}	±20	
Continuous Drain Current	I_D	-30	A
Pulsed Drain Current(Note1)	I_{DM}	-90	
Single Pulse Avalanche Energy (Note 2)	E_{AS}	151	mJ
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55to+150	℃
Maximum lead temperature for soldering purposes, 1/8″from case for 5 seconds	T_L	260	℃

Thermal Characteristics				
Parameter		**Symbol**	D30P03HL	**Units**
Thermal resistance , Junction to Case		$R_{th(J-c)}$	5.5	℃/W
Maximum Power Dissipation	T_C=25℃	P_D	22.7	W

Electrical Characteristics (T_c=25℃,unless otherwise noted)						
Parameter	**Symbol**	**Test Conditions**	**Min**	**Typ**	**Max**	**Units**
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V,I_D=-250uA	-30	—	—	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-30V,V_{GS}=0V	—	—	-1	uA
Gate-Body Leakage Current,Forward	I_{GSSF}	V_{GS}=20V,V_{DS}=0V	—	—	100	nA
Gate-Body Leakage Current,Reverse	I_{GSSR}	V_{GS}=-20V,V_{DS}=0V	—	—	-100	nA
On Characteristics						
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250uA	-1.2	—	-2.5	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=-10V,I_D=-15A	—	10	15	mΩ
		V_{GS}=-4.5V,I_D=-15A	—	18	25	
Dynamic Characteristics						
Input Capacitance	C_{iss}	V_{DS}=-15V,V_{GS}=0V, f=1.0MHZ	—	2219	—	pF
Output Capacitance	C_{oss}		—	310	—	pF
Reverse Transfer Capacitance	C_{rss}		—	216	—	pF
Switching Characteristics						
Turn-On Delay Time	$t_{d(on)}$	V_{DD}=-15V,I_D=-15A, V_{GS}=-10V, R_G=2.2Ω	—	8.6	—	ns
Turn-On Rise Time	t_r		—	6.4	—	ns
Turn-Off Delay Time	$t_{d(off)}$		—	46	—	ns
Turn-Off Fall Time	t_f		—	17	—	ns
Total Gate Charge	Qg	V_{DS}=-15V,V_{GS}=-4.5V, I_D=-13.9A	—	45	—	nC
Gate-Source Charge	Qgs		—	15	—	nC
Gate-Drain Charge	Qgd		—	10	—	nC
Drain-Source Body Diode Characteristics and Maximum Ratings						
Continuous Diode Forward Current	I_S		—	—	-30	A
Pulsed Diode Forward Current	I_{SM}		—	—	-90	A
Diode Forward Voltage	V_{SD}	I_S=-1A,V_{GS}=0V	—	—	-1.2	V

Notes

1. Repetitive Rating:pulse width limited by maximum junction temperature .
2. L=0.5mH,R_g=25Ω , T_J=25℃.
3. Pulse width≤300us;duty cycle≤2%.

Test Circuit and Waveform

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



RATINGAND CHARACTERISTIC CURVES

Figure.1 Typical Output Characteristics



Figure.2 Typical Gate Charge vs Gate to Source Voltage



Figure.3 Typical Body Diode Transfer Characteristics



Figure.4 Typical Capacitance vs Drain to Source Voltage



Figure.5 Typical Breakdown Voltage vs Junction Temperature



Figure.6 Typical Drian to Source on Resistance vs Junction Temperature



Figure.7 Maximum Forward Bias Safe Operating Area



Figure.8 Typical Drain to Source ON Resistance vs Drain Current



Figure.9 Maximum EAS vs Channel Temperature



Figure.10 Typical Threshold Voltage vs Case Temperature



Figure.11 Maximum Effective Thermal Impedance , Junction to Case



Figure.12 Maximum Power Dissipation vs Case Temperature



DFN3x3 PACKAGE OUTLINE



RECOMMENDED LAND PATERN



UNIT: mm

	MIN	NOM	MAX
A	0.70	0.85	1.00
b	0.24	0.30	0.40
c	0.10	0.15	0.25
D	3.00	3.15	3.25
D1	3.10	3.25	3.50
D2	0.30	0.40	0.50
D3	2.50	2.58	2.70
D4	2.35	2.45	2.55
E	2.90	3.00	3.10
E1	3.15	3.30	3.45
E2	1.65	1.75	1.85
E3	0.48	0.58	0.68
E4	0.23	0.40	0.50
E5	0.20	0.30	0.40
E6	0.075	0.17	0.25
e	0.55	0.65	0.75
K	0.52	0.72	0.82
L	0.25	0.40	0.55
L1	0.00	0.05	0.10
L2	0.28	0.43	0.58
L3	0.88	0.98	1.08