

Figure 3 of the GERP paper

```
#setwd("~/Documents/Github/pvpDiallel/")
knitr::opts_knit$set(root.dir=normalizePath('../'))
```

To reproduce the figures, we should set `pvpDiallel` as the root path, i.e. `setwd("~/Documents/Github/pvpDiallel/")`. And then use `knitr` package to get a pdf file. Or simply click Knit PDF icon on RStudio. Note, to produce panels into separate pdf files, we should set `getpdf` into `TRUE` (i.e. `getpdf=TRUE`) when calling the plotting functions.

First of all, determine font size and set the `getpdf` option:

```
#par(mar=c(5,4,4,2))
par(font=2, font.lab=2, font.axis=2)
fs = 1.6 # times bigger than default
fsize = 14 # absolute font size
getpdf = TRUE # get figures in separated pdf [TRUE] or not [FALSE]
```

Figure 3a and 3b

```
library(ggplot2)
```

```
## Warning: package 'ggplot2' was built under R version 3.2.4
```

```
source("lib/multiplot.R")

plot_fig3ab <- function(outfile, getpdf){
  res1 <- read.csv("cache/gerpsnp_wholeset_perse.csv")
  res2 <- read.csv("cache/gerpsnp_wholeset_bph.csv")

  res1$trait <- toupper(res1$trait)
  res2$trait <- toupper(res2$trait)

  h <- read.csv("cache/loh_pBPHmax_median.csv")
  med2 <- h
  med2$traitlw <- med2$trait
  #bymed2 <- with(trait, reorder(trait, pBPHmax, median))
  bymed2 <- med2[order(med2$h),]

  p1 <- ggplot(res1, aes(x=factor(trait, levels=bymed2$traitlw), y=h2,
                             fill=factor(mode, levels=c("a2", "d2", "h2"), labels=c("A", "D", "K")))) +
    geom_bar(position=position_dodge(), stat="identity") +
    xlab("") +
    ylim(c(0,1)) +
    ylab("Posterior Variance Explained") +
```


```

ggtitle("Trait per se") + theme_bw() +
labs(fill="Effect") +
theme(axis.text = element_text(angle = 90, hjust = 1, size=fsize),
      axis.title=element_text(size=fsize, face="bold"),
      legend.title = element_text(size=fsize, face="bold"),
      legend.text = element_text(size=fsize))

p2 <- ggplot(res2, aes(x=factor(trait, levels=bymed2$traitlw), y=h2,
                        fill=factor(mode, levels=c("a2", "d2", "h2"), labels=c("A", "D", "k")))) +
geom_bar(position=position_dodge(), stat="identity") +
xlab("") +
ylim(c(0,1)) +
ylab("Posterior Variance Explained") +
ggtitle("Heterosis") + theme_bw() +
labs(fill="Effect") +
theme(axis.text = element_text(angle = 90, hjust = 1, size=fsize),
      axis.title=element_text(size=fsize, face="bold"),
      legend.title = element_text(size=fsize, face="bold"),
      legend.text = element_text(size=fsize))

multiplot(p1, p2, cols=2)
if(getpdf){
  pdf(outfile, width=10, height=4.5)
  multiplot(p1, p2, cols=2)
  dev.off()
}
}
#####
plot_fig3ab(outfile="graphs/Fig_post_var.pdf", getpdf)

```



```

## pdf
## 2

```

Figure 3c and 3d

```

library(beanplot)
library(ggplot2)
library(plyr)

## Warning: package 'plyr' was built under R version 3.2.5

#http://www.jstatsoft.org/v28/c01/paper
mybean <- function(inputdf, mymode="a2", ...){
  res1 <- ddply(inputdf, .(trait, mode, sp, type), summarise,
    r = mean(r),
    m = median(r))
  res1 <- subset(res1, type != "null")

  res1$mode <- as.character(res1$mode)
  res1 <- subset(res1, mode == mymode)
  res1$trait <- toupper(res1$trait)
  #print(nrow(res1))
  par(lend = 1, mai = c(0.8, 0.8, 0.5, 0.5))
  res1$type <- factor(res1$type, levels = c("real", "cs"))
  res1$trait <- factor(res1$trait, levels = toupper(c("tw", "dtp", "dts", "asi", "pht", "eht", "gy")))
  beanplot(m ~ type + trait, data = res1, kernel="cosine", ll = 0.04, cex=1.5, side = "both", bw=0.02,
    border = NA, col = list(c("#d41243", "#d41243"), c("grey", "grey")), ...)
  #legend("bottomleft", fill = c("black", "grey"),
  #      legend = c("Group 2", "Group 1"))
  #return(res0)

  out <- data.frame()
  myt <- toupper(c("tw", "dtp", "dts", "asi", "pht", "eht", "gy"))
  for(myti in myt){
    real <- subset(res1, type == "real" & trait == myti)
    rand <- subset(res1, type == "cs" & trait == myti)

    message(sprintf("###>>> real [ %s ] and random [ %s ]", nrow(real), nrow(rand)))
    test <- t.test(real$r, rand$r, alternative = "greater")



    tem <- data.frame(trait=myti, realmean=mean(real$r), csmean=mean(rand$r), pval=test$p.value)
    out <- rbind(out, tem)
  }

  return(out)
}

####
plot_fig3cd <- function(outfile, getpdf){
  res01 <- read.csv("largedata/newGERPv2/res_realk_perse_42000.csv")
  res02 <- read.csv("largedata/newGERPv2/res_realk_bph_42000.csv")

  par(mfrow=c(1,2))
  #par(mar=c(5,4,4,2))
  res1 <- mybean(inputdf=res01, mymode = "h2", ylim=c(0, 1), main="Trait per se", ylab="Cross-validation")

```

pdf
2