

CPCR: Contact-Prediction Clustering-based Routing in Large-scale Urban Vehicular Delay Tolerant Networks

Wenjing Yang
School of Software
Beihang University
Beijing, P.R.China
Email: yangwenjing@sse.buaa.edu.cn

Haiquan Wang
School of Software
Beihang University
Beijing, P.R.China
Beijing Key Laboratory of
Network Technology Beijing, P.R.China
Email: whq@buaa.edu.cn

Jingtao Zhang
and Jiejie Zhao
School of Software
Beihang University
Beijing, P.R.China
Email: zjt@buaa.edu.cn
Email: zjj@buaa.edu.cn

Abstract—Routing in Public Transport Networks is particularly challenging due to the high mobility, rapidly changing topology. Though clustering of nodes can aid forwarding decision in these Delay Tolerant Networks (DTNs), centralized clustering process is extremely costly in a large network. Moreover, it is critical to choose proper metrics to cluster nodes. In this paper, we propose a contact-predict clustering-based routing algorithm, CPCR, for large-scale urban DTNs. This algorithm computes the probability for each node pair and cluster that nodes distributively into higher contact-strength clusters using nodal local contact information. Depending on the clusters, intra-cluster and inter-cluster routing strategies will be adopted. Extensive simulations indicate that CPCR maintains relatively stable clusters and enhances the routing performance. The results demonstrate that clustering-based routing algorithm is rational and promising for large-scale urban DTNs.

Keywords—clustering, inter-contact time, contact prediction, delay tolerant networks

I. INTRODUCTION

Delay Tolerant Networks (DTNs) [1], [3] is a branch of networks, where communication links only exist temporarily with a highly dynamic topology. One of such examples is vehicular network where vehicles communicate with each other in order to disseminate data using opportunistic contacts. To communicate in such an challenging environments, numerous DTN routing methods have been proposed over the last decade.

Traditional flat routing methods, such as *Direct Delivery* (DD) [11] and *Epidemic Routing* [12], become not scalable to large-scale DTNs. Meanwhile, clustering-based approaches have long been considered as an effective approach to reduce network overhead and improve scalability in traditional mobile ad hoc networks [13], [14], [15], [16] with relatively stable topology and more communication opportunity. Clustering in

DTNs is unique [17], [18], because the network topology is not always fully connected. As a result, it becomes much more challenging to formulate clusters and ensure their stability. When we consider an urban DTN, the nodal scale and mobility will further increase the cost of maintaining clusters.

Contact characteristics among nodes [19], [20], [21] have been used as one of key metrics for clustering in DTNs. Frequency and duration of historical contacts have been used as metrics to describe contact probability [22], [23], however they cannot provide very accurate estimation of the contact probability among nodes. Instead, the distribution of *inter-contact time* (ICT) has been shown to be powerful for describing contact characteristics [22], [24], [25]. ICT between two nodes directly affects the transmission delay between these two nodes, since a shorter ICT implies a greater opportunity to relay packet in a period of time.

In this paper, we propose an clustering-based routing scheme for large-scale urban DTNs. We first analyze a real-world urban vehicular tracing data set to reveal the Inter-contact time distributions of mobile vehicles in a large city. Our study confirm that both the global ICT and the individual ICT between each nodal pair follow the exponential distributions. It is demonstrated that the distribution for ICT of nodal pairs is more accuracy than the global ICT distribution. Therefore, a clustering algorithm which groups nodes by the contact probability calculated from the ICT distribution for nodal pair in real-time, and propose a new clustering-based routing scheme based on this contact predication clustering.

To summarize, our contributions in this paper can be highlighted as follows:

- Via an in-depth analysis of the Beijing taxi data set, we demonstrate that it is applicable to estimate the parameter for the ICT exponential distribution of every nodal pair. Such pair-wise ICT distribution is more accurate than the global ICT distribution, which is commonly used in several DTN routing schemes.
- A hierarchical routing algorithm, CPCR, based on a distributed clustering via contact prediction is proposed. CPCR uses direct delivery and flooding strat-

This research has been partially supported by the US National Science Foundation (NSF) under Grant No. CNS-1319915 and CNS-1343355, the National Natural Science Foundation of China (NSFC) under Grant No.61300173 and No. 61170295, the Project of Aeronautical Science Foundation of China under Grant No.2013ZC51026 and No.2011ZC51024, the Fundamental Research Funds for the Central Universities under Grant No. YWF-12-LXGY-001, and the State Key Laboratory Software Development Environment and Network Information and Computing Center of Beihang University.

egy in intra-cluster and inter-cluster routing phases, respectively.

- Extensive simulations are conducted with the Beijing taxi tracing data to evaluate the efficiency and scalability of the proposed clustering-based routing.

The rest of paper is organized as follows: Section II provides an overview of related work on DTN routing. Section III provides the theoretical basis of contact predicting and clustering via detailed analysis of the Beijing taxi traces. Section IV presents our clustering-based routing algorithm which leverages the estimated ICT distributions to clustering nodes into groups and routes the packages accordingly. Simulation results over the Beijing taxi traces are presented in Section V. Finally, Section VI concludes this paper.

II. RELATED WORK

In 2004, Jain et al. [26] first investigate the routing issues in DTNs, where messages are to be moved end-to-end across a graph that is time-varying and not full connected. Since then routing in DTNs has been heavily studied [27], [28] over the last decade. Routing algorithms can be categorized into *flat routing* or *hierarchical routing* by the network topology. Flat routing methods employ only a single routing strategy globally, while all nodes play similar roles. For example, *Epidemic Routing* [29] is a simple flooding method with zero knowledge of the network topology. Compared with some single-copy routing methods, such as *Direct Delivery* [30], *Randomized Routing* (RR) [31], Epidemic routing greatly improves delivery ratio but suffers from resource waste and even network congestion due to large data replication. In order to reduce the usage of resources, *Spray and Wait* routing [32] limits the amount of message copies in its spray phrase and lets node wait until contacted by the destination node in its wait phrase. But with such solutions, routing performance could still be poor in large-scale networks. Besides these flooding based schemes [29], [33], [34], there is also a set of DTN routing methods based on the contact information, where a smarter relay node selection is made [35], [36]. For example, *PRoPHET* is a probability-based method, where each node maintains the encounter history.

When the network scale increases and topology evolves, however, the scalability and performance of flat routing methods are limited. Under this condition, hierarchical routing organizes the networks in groups via clustering techniques. It has been shown that hierarchical routing can achieve good scalability in large-scale mobile networks. However, restricted by the dynamic topology and frequently interruptions, hierarchical routing in DTNs is still in its early stages. Liu and Wu [38] design a hierarchical DTN routing algorithm based on a strict mobility model, where all nodes move according to strict repetitive patterns. Their method is only effective such a specific mobility model and could not adapt to other mobility pattern. Ahmed and Kanhere [39] adopt encounter frequencies of public transport networks to classify nodes. Nodes only relay messages to neighboring nodes which are in the same cluster of the destination node. Then epidemic routing is used to propagate messages inside the cluster. These clustering-based hierarchical routing methods can improve the scalability, but the resource consumption of collecting and maintaining

historical information remains high. a hybrid DTN-MANET (HYMAD) routing was proposed by Whitbeck and Conan [20] for dense and highly dynamic wireless networks. This method is decentralized and only makes use of topological information exchanges between the nodes, thus limit the storage and information exchange cost. However, its intra-cluster routing using MANET method may be invalid. It can not suit for more complicated urban DTNs.

In summary, the key challenge of hierarchical routing is the clustering method, especially in large scale DTNs. To adapt to the scenario of large scale urban DTNs and solve the routing problem, a cluster-based routing algorithm is proposed.

III. CHARACTERISTICS OF LARGE-SCALE URBAN DTNS

In this section, we mainly focus on revealing the inherent characteristics of contacts and possible clustering methods in large-scale urban DTNs by analyzing a real-world trace data. We believe that these are essential properties which affect DTN routing design and verification.

A. Trace Dataset: Beijing Taxi Traces

To study urban DTNs, we use a real-world GPS dataset which were generated by 12,096 taxis in Beijing, China within one week (from June 13th to 19th, 2010). This dataset has been used by several key research and application programs of Intelligent Transportation Systems (ITS) in Beijing, China. The number of participated taxis (12,096 taxis) is 18% of the total taxis in the city. Each taxi is equipped with a GPS device and upload its information (including location, speed, direction, et al.) about every 60 seconds. There are around 1.22×10^8 records in total. For each row, the record includes a base station ID, company name, taxi ID (*id*), timestamp (*t*), current location (*l*, including both longitude and latitude), another location (out of 54 fixed locations), speed, acceleration, status of the taxi, event, and height. Out of this information, we only use the taxi ID, timestamp, and current location, i.e., (*id*, *t*, *l*), to generate the contacts among taxis for the study within this paper. Notice that GPS traces from taxis have been used recently for inferring human mobility [40] and modelling city-scale traffics [41]. Therefore, we believe that they are also suitable to characterize the contact patterns among vehicles in large-scale urban DTNs.

B. Contact Characteristics in Beijing Taxi Traces

The *inter-contact time* (ICT) is the interval time between two continuous contacts for same nodal pair. ICT implies the contacts frequency of two nodes. Researchers have focused on the study of ICT characteristics for different mobility patterns in DTNs, and lead to numerous ICT distribution results of both theoretical and real-world mobility models. Most ICT distribution models are created as exponential distributions. According to [24], [42], [43], the ICT between two mobile nodes generates exponential distributions where the exponential parameter is related to the motion characteristics. Simulations in [24], [44] based on random waypoint and random direction mobility models confirm such claims. In the real-world mobility traces of vehicular networks [5], the ICT between two vehicles also follows an exponential distribution. Similar conclusions have been found in another Shanghai taxi trace dataset studied by

[5], [45]. The contact probability between any two nodes based on the global ICT distribution is

$$P(X > x) = e^{-\lambda t}, \quad (1)$$

where the exponential parameter λ reflects the contact strength between nodes. A static λ can be estimated for the whole network by fitting the global ICT distribution to the exponential function. This simple method can measure the contact strength intuitively and efficiently, and has been frequently used in many DTN routing methods.

Paper [42] studied the ICT distributions of individual nodal pairs and find that they follow exponential distributions under three assumptions. The ICT of a node pair i and j also follows the exponential distribution with exponential parameters λ_{ij} , according to:

$$\lambda_{ij} = n_{ij} / \sum ICT_{ij}, \quad (2)$$

where n_{ij} refers to the number of contacts between nodes i and j , and $\sum ICT_{ij}$ indicates the total ICTs between these two nodes. Hence, the contact probability of nodes i and j within time period t is

$$p_{ij}(t) = P_{ij}(X \leq t) = 1 - e^{-\frac{n_{ij}}{\sum ICT_{ij}} t}. \quad (3)$$




Fig. 1. Pairwise ICT distributions of four nodal pairs in Beijing taxi dataset. Red dots are the real sample data from the dataset while blue curves are the fitted exponential distributions.

By fitting the samples of ICTs for a particular nodal pair with Equation 2, we can derive the exponential parameters λ_{ij} . The values of λ_{ij} in Beijing taxi dataset varies significantly from 0.0005 to 0.005. Figure 1 shows the exponential distributions fitting for four pairs of nodes.

To further confirm that the method based on pair-wise ICT distributions can characterize the real contact pattern better than the aggregated global ICT distribution, we also use the coefficient of determination R^2 [46] to determine the similarity degree of modelled ICT curves and real observed curves from dataset. Note that R^2 is a number between 0 and 1.0, and used to describe how well a regression line fits a set of data. An R^2 near 1.0 indicates that a regression line fits the data perfectly, while an R^2 closer to 0 indicates that a regression line does not fit the data very well.




Fig. 2. Comparison of similarities R^2 of the two estimation methods. Here, red dots are the values of R^2 for 500 node pairs, while the blue line shows the average value of these R^2 .

For the global ICT method, we attract the λ based on all contact records, and result $\lambda = 0.00077527$. For the pair-wise ICT method, we use Equation 2 to learn the individual λ_{ij} for each nodal pair. Then we calculate R^2 between the estimated distributions based on λ or λ_{ij} with the real distributions from traces of individual nodal pairs in the dataset. Figure 2 shows plots of such comparison over 500 randomly generated nodal pairs. Clearly, R^2 differs for each pair of nodes. The blue line in both plots are the average R^2 . The global ICT method has an average of R^2 at 0.717 while the pair-wise one is 0.822. This confirm that using pair-wise ICT distribution can fit the real records better and thus give better contact probability over the global fitting method. Therefore, in our proposed clustering method, we use a distributed algorithm to estimate λ_{ij} for every nodal pair.

IV. CONTACT-PREDICTION CLUSTERING-BASED ROUTING (CPCR)

Now we are ready to describe the proposed *Contact-Prediction Clustering-based Routing* method (CPCR). CPCR leverages the estimated pair-wise ICT distribution (via Equation 2) to predict the contact probability among nodes (using Equation 3), and uses such probabilities to form clusters. Based on the clustering, CPCR perform its intra- and inter-cluster routing strategies, respectively.

A. Data Structure and Notations

We first review basic data structures and notations used by CPCR. Every node creates or updates its local information upon different events, e.g., happen to contact, periodic update, or record timeout. The following data structures are used at each node.

$$\left\{ \begin{array}{l} \text{Node} = (\text{id}, \text{cid}, \text{ContactTable}, \text{GatewayTable}, \\ \quad \text{ConnectionList}, \text{MessageList}, \text{timer}) \\ \text{ContactTable} = \{\text{ContactRecord}_1, \dots, \text{ContactRecord}_n\} \\ \text{GatewayTable} = \{\text{GatewayRecord}_1, \dots, \text{GatewayRecord}_m\} \\ \text{ConnectionList} = \{\text{Connection}_1, \dots, \text{Connection}_o\} \\ \text{MessageList} = \{\text{MessageRecord}_1, \dots, \text{MessageRecord}_p\} \\ \text{ContactRecord} = (\text{id}, \text{cid}, \text{contactTimes}, \sum \text{ICT}, \text{contactProb}, t) \\ \text{GatewayRecord} = (\text{cid}, \text{gid}, \text{timeout}) \\ \text{MessageRecord} = (\text{message}, \text{FloodingClusters}) \\ \text{Connection} = (\text{remoteEndNode}, \text{message}) \end{array} \right.$$

Table I gives all notations used here.

TABLE I. NOTATIONS USED IN OUR DATA STRUCTURE.

Symbol	Description
id	unique identifier of a node
gid	unique identifier of gateway node id to another cluster
cid	unique identifier of cluster which contains the node
$ContactTable$	a table stores contact records
$GatewayTable$	a table stores gateway records
$ConnectionList$	stores all established connections
$MessageList$	stores messages and their historical info
$timer$	to remind nodes of periodic updating
$ContactRecord$	contacts to other nodes and their contact-probability
$GatewayRecord$	gateway nodes info, with a timer
$Connection$	message information and the other contacting node
$remoteEndNode$	the other contacting node
$message$	data needs to transmit
$FloodingClusters$	a collection of clusters with the message copy
$contactTimes$	contact times between two nodes
$timestamp$	time record, when connection is up or down
$\sum ICT$ or $\sum ICT_{ij}$	total ICT between two nodes (i and j)
$contactProb$	contact probability between nodes
$timeout$	a timestamp to decide whether a record expires

B. Clustering Criteria

CPCR utilizes $p_{ij}(t)$, contact probability for nodes i and j in time period t , as the clustering metric, since it implies contact strength between the two nodes. Hereafter, $p_{ij}(t)$ can be simplified as p_{ij} . The clustering criteria is given as follows:

Criterion 1 We group nodes with contact probability higher than a probability threshold η into clusters.

Criterion 2 a node conforms with the Criterion 1 for two or more clusters, the node will join the most stable cluster.

Accordingly, a cluster can be represented as a collection of nodes as follows:

$$C = \{ID_k | k = 1, 2, \dots, n; \forall i, j \in \{1, 2, 3, \dots, n\}, p_{ij}(t) > \eta\}. \quad (4)$$

Assume based on Criterion 1 node i belongs to two cluster C_m and C_n , i.e., $p_{ij} > \eta, p_{ik} > \eta$ for $\forall j, k, j \in C_m, k \in C_n$. In this case, we use the minimum contact probability in a cluster to represent the stability of that cluster. By comparing $\min(p_{m_1 m_2})$ and $\min(p_{n_1 n_2})$, $\forall m_1, m_2 \in C_m$ and $\forall n_1, n_2 \in C_n$, node i will join the cluster with higher minimum probability.

Note that two parameters t and η can affect the contact probability and thus affect the results of clustering. When η is a constant, a smaller t decreases $p_{ij}(t)$ so that fewer nodes will meet the clustering criterion. Thus, smaller but more stable clusters will be generated. As a consequence, the overhead of intra-cluster routing and clustering maintenance will decrease whereas the overhead of inter-cluster routing will increase. On the other hand, increasing η can increase the contact strength in clusters and guarantee the efficiency of intra-cluster routing, whereas, more clustering fragments will occur. Overall, reasonable values of t and η need to be configured for tradeoff between clustering and routing.

C. Distributed Clustering based on Contact Prediction

CPCR use the above clustering criteria to perform the clustering among mobile nodes. The assumption that the

Algorithm 1 Clustering Algorithm

Initialization: $timer \leftarrow CurrentTime$,
 $ContactTable \leftarrow NULL$,
 $GatewayTable \leftarrow NULL$, $cid \leftarrow id$
while $Simulation \neq end$ **do**
 if Contacting **then**
 Contacting()
 else $\{CurrentTime - timer > t\}$
 Period-Updating()
 for all $GatewayRecord \in GatewayTable$ **do**
 if $GatewayRecord.isTimeout$ **then**
 $GatewayTable.remove(GatewayRecord)$
 $timer \leftarrow CurrentTime$

Algorithm 2 Contacting

for all $Connection \in ConnectionsList$ **do**
 $OtherNodes \leftarrow Connection.remoteEndNode$
 $ContactRecord \leftarrow ContactTable[OtherNodes]$
 if $Connection = established$ **then**
 $ContactRecord.\sum ICT + = CurrentTime - ContactRecord.timestamp$
 $ContactRecord.contactTimes + = 1$
 $ContactRecord.contactProb = \exp\{-\frac{ContactRecord.contactTimes}{ContactRecord.\sum ICT} t\}$
 if $cid = OtherNodes.cid$ **then**
 $isBetterGateway(OtherNodes)$
 else $\{cid \neq OtherNodes.cid\}$
 $whetherToJoinOtherCluster(OtherNodes)$
 else $\{Connection = destoried\}$
 $ContactRecord.timestamp = CurrentTime$
 Gateway-Updating()

network topology remains static in the initial clustering phase in MANET applications, does not apply to DTNs where nodes move randomly over time. Therefore, the clustering algorithm in DTNs should be distributed, heuristic and self-maintaining. In CPCR, nodes cooperatively execute the clustering algorithm and communicate with other nodes. The concept of cluster head, which acts as a coordinator in most clustering designs, is not introduced in CPCR. In our opinion, nodes are homogeneous because of their similar communication and computation abilities in DTNs. Moreover, it is difficult to avoid redundant bottlenecks when routing with cluster heads. The detailed overall clustering method is given in Algorithm 1 which includes information exchange upon contact, periodic updating of $ContactTable$ and $GatewayTable$, and deleting related gateway records when they expire.

Initialization: Initially, each node generates a cluster only including itself. The node also sets $ContactTable$ and $GatewayTable$ empty.

Happen to Contact: When two nodes move into each other's communication range, two nodes will execute the process shown in Algorithm 2.

First, the cluster information of the other node is required. Upon contacting with node j , node i will add or update the contact record with node j and re-calculate the contact probability with node j by Equation 3. If $cid_i = cid_j$, node i add or update the record in $GatewayTable_i$. Node i will

Algorithm 3 Period-Updating

```
for all  $ContactRecord \in ContactTable$  do
   $ContactRecord.contactProb = 1 -$ 
   $\exp\{-\frac{ContactRecord.contactTimes}{ContactRecord.\sum ICT}t\}$ 
for all  $ContactRecord.cid == node.cid$  do
   $FLAG \leftarrow true$ 
  if  $ContactRecord.contactProb < \eta$  then
     $FLAG \leftarrow false, Break$ 
  if  $FLAG = false$  then
     $Node.cid \leftarrow newClusterID()$ 
     $Node.GatewayTable \leftarrow NULL$ 
  else
     $Gateway - Updating()$ 
```

decide whether or not node j can be a better gateway to cluster cid_m , when $cid_m \neq cid_j$, as follows:

- 1) Node identifies the maximum contact probability to cluster cid_j in $ContactTable_j$, which is denoted as:
 $p_j^{cid_m} = MAX \{p_{jk} | \forall k, cid_k = cid_m\}.$
- 2) If $p_{ij} \times p_j^{cid_m} > p_{i,gid_i^{cid_m}} \times p_i^{cid_m}$, node j can be a better gateway for node i to cluster cid_m , node i will update the relevant record and reset the gateway timeout.
- 3) In case that node i has no gateway to cluster cid_m , node j will be set as the gateway only if node j has any record which belongs to cluster cid_m .

If $cid_i \neq cid_j$ (i.e., i and j belong to different clusters), node i will decide whether to join cluster cid_j . The function $whetherToJoinOtherCluster(OtherNodes)$ are decided by criteria given in Section IV-B.

Periodic Updating: To obtain a more precise real-time prediction, the algorithm needs to regularly update the records in $ContactTable$ and $GatewayTable$. The periodic record updating procedure is shown in Algorithm 3.

First, the local node i updates p_{ij} in $ContactTable_i$ with the latest $contactTimes$ and $\sum ICT$. Then, it will go through clustering criteria check. If the node passes Criterion 1, it will remain in the original cluster. Updating $ContactTable$ may change node i 's probability to the other clusters. Therefore, node i will also update $GatewayTable_i$ to set the new or better gateway to other clusters. The gateway in $GatewayTable_i$ must in the same cluster of node i . If the node does not pass Criterion 1, it will leave its original cluster and construct a new isolated cluster which only includes itself. In such a situation, the node will keep its own $ContactTable$, while $GatewayTable$ will be set empty, since the old gateway records are meaningless to the new established cluster.

D. Clustering-based Routing Scheme

Based on dynamically formed clusters, our clustering-based routing procedure can be divided into intra- and inter cluster routing procedures. If destination node is in the same cluster of a node, a single-copy routing strategy will be executed as intra-cluster routing algorithm. The local node will not deliver the packet until contacted by the destination node. Considering high contact probability inside a cluster, such

direct delivery can simplify route decision making and ensure acceptable delay in the intra-cluster routing. If the local node and the destination belong to the different clusters, inter-cluster flooding approach will be used. Every cluster is considered as an abstract "node". Therefore, it ensures that a cluster can only accept no more than one copy of a message. Since CPCRR is event-driven, the routing procedure will be executed when contacts happen. When node i contacts with node j , node i will traverse every message to determine whether or not to relay the messages. The routing procedure can be described as Algorithm 4.

Algorithm 4 Clustering-based Routing

```
if  $Connection = established$  then
   $remoteNode \leftarrow Connection.remoteNode$ 
  for all  $message \in MessageList$  do
     $destination \leftarrow message.destination$ 
    if  $destination = remoteNode$  then
       $sendAndDelete(message), CONTINUE$ 
    if  $belongToSameCluster(this, destination)$  then
       $CONTINUE$ 
    if  $belongToSameCluster(destination, remoteNode)$ 
    then
       $sendAndDelete(message)$ 
    else  $\{belongToSameCluster(this, remoteNode)\}$ 
      if  $isGateway(remoteNode, destination.cid)$ 
      then
         $sendAndDelete(message)$ 
      else
         $copyAndDelete(message)$ 
```

If the message's destination is node j , node i will send the message to node j . Then, the message will be deleted (as $sendAndDelete(message)$). If the destination of the message is in the same cluster of local node, message will not be relayed until the local node meets the destination node, which can be considered as intra-cluster routing. For inter-cluster routing where the remote node j is not the destination and not in the same cluster of the local node, node j can be a relay point if it satisfies one of following circumstances:

- 1) The target cluster of the message is the same as the cluster of node j .
- 2) The node j is the gateway node from the cluster of node i to the target cluster. As the definition for gateway, we can figure out that node j belongs to the same cluster as the local node.
- 3) Three nodes (i , j , and the destination node) belong to three different clusters. In this case, local node will send a copy to the remote node, only if there is no copy in the cluster of node j . When message has been sent, node i will store a record that the $cluster_j$ has a copy of the message, avoid of sending a message to the same cluster again.

Whether two nodes are in the same cluster is determined by exploring the $ContactTable$ and $GatewayTable$ of the local node. If we can neither find a record for a destination in $ContactTable$, nor find a gateway to the target cluster, inter-cluster procedure for the third condition will be executed.

TABLE II. PARAMETER SETTINGS OF CLUSTERING EVALUATION

Parameter	Value
Simulation Time	4,000s
Buffer Size	2.5MB
Message Size	50 – 100kb
Transmission range	200m
Inter message creation time	5s
Bandwidth	256k
Node Number	1,000 or 1,500
Area	$20 \times 20 \text{ km}^2$
η	0.15, 0.3
t	200s, 400s

V. PERFORMANCE EVALUATION



In this section, we present results from three set of simulation experiments over Beijing taxi dataset to evaluate the efficiency of proposed clustering and routing method CPCR and its scalability. We first evaluate the clustering performance and determine the parameter settings of (t, η) . We then compare delivery ratio and overhead of three single-strategy routing protocols with CPCR in the large-scale urban DTNs scenario to demonstrate its routing performance. The three compared routing methods are *Epidemic Routing* [29], *Direct Delivery* (DD) [30] and *PROPHET*. Notice that Epidemic and DD are used in the inter-cluster and intra-cluster phases of CPCR respectively. PROPHET is a two-hop forwarding strategy whose forwarding strategy is also based on the estimated contact probability. Last, with different network scales, we reveal the scalability of all methods.

All routing methods are implemented in Opportunistic Networking Environment (ONE)[47] simulator which is designed for evaluating DTN routing and application protocols. It allows users to create scenarios based upon different synthetic movement models and real-world traces and offers a framework for implementing routing and application protocols (already including six well-known routing protocols). All simulation scenarios are extracted from the Beijing taxi dataset we described in Section III-A and imported to ONE as movement models.

A. Clustering Evaluation

In this section, it aims to evaluate the performance of our clustering method by using the average scale of clusters (i.e., the average node numbers in a cluster). Note that the average scale of clusters is affected by clustering rules and is an important criterion for evaluating clustering performance. Whether or when the cluster becoming stable is another criterion for evaluation. Quantifying a certain clustering criterion in different scenarios is not easy. For example, in a small-scale network with high node density, small-scale clusters may be better than large clusters for message delivery. McDonald and Znati [48] proposes a method of comparing the clustering performance when change its own factor. We adapt their approach to evaluate our clustering algorithm. Simulation parameters of our clustering algorithm are shown in Table II, in which the variable parameters are the node number, the contact probability threshold η and the contact forecast time t .

The average scale of clusters reflects the granularity of clustering, and the curve of the change of the average scale of clusters can indicate whether a cluster can become stable. Two

Fig. 3. Average scale of clusters for different η (left: 1,000 nodes; right: 1,500 nodes)Fig. 4. Average scale of clusters for different t (left: 1,000 nodes; right: 1,500 nodes)

node scales (i.e. node numbers), namely, 1,000 and 1,500, are chosen to compare the clustering performance by changing a single parameter, contact probability threshold or contact forecast time. Figures 3 and Figure 4 illustrate the change of the average scale of the cluster with time.

Figure 3 illustrates the curve of the cluster scale variation by changing η from 0.3 to 0.15, at a fixed forecast time of 400s, for both network scales. A larger network scale leads larger average scale of clusters. High node density increase the opportunity to contact so that the contact probability between nodes becomes higher than η , which also increases the degree of convergence. The η influences the average scale of clusters directly. In Figure 3 (left), the peak value of the scale is 13.6 with $\eta = 0.15$, while the peak value is 9.4 with $\eta = 0.3$. Similar trends can be found in the right subfigure of Figure 3.

Figure 4 uses the same contact threshold ($\eta = 0.3$), but its forecast time t changes from 400s to 200s. In Figure 4 (left), when $t = 200$, the cluster scale peak value is 6.8, and when $t = 400$ s, the peak reaches 9.4. This result is due to the fact that forecast time increases the contact probability value, which causes more nodes to satisfy the clustering criteria and join clusters. Similar conclusion for the case with 1,500 nodes (right subfigure in Figure 4).

In both cases, the curves can achieve stability after 2,000s. It shows that the proposed clustering algorithm can cluster the network effectively and stably. Overall, the clustering phase can organize the network into clusters which have certain degree of granularity and achieve stability, which benefits the routing task inside and across the clusters in large-scale networks.

TABLE III. PARAMETER SETTING IN SIMULATION ONE

Simulation Time	10,000s
Area	$20 \times 20 \text{ km}^2$
Nodes Number	3,000
Transmit Range	200m
Package Size	Random (50, 100)k
Buffer Size	[0.5, 1, ..., 5]M
Routing Methods	CPCR ($t = 400, \eta = 0.3$), Epidemic, PRoPHET, DD




Fig. 5. Delivery ratio and overhead of all methods with different buffer sizes

B. Routing Performance

In this set of simulations, we randomly select traces of 3,000 vehicles from the central area ($20\text{km} \times 20\text{km}$) of Beijing. As revealed in [42], the central area of the city has numerous hotspot areas, which we believe is an appropriate scenario for the clustering based-routing. We investigate delivery ratio and overhead of different routing protocols under different buffer sizes. Detail parameter settings are shown in Table III.

Figure 5(a) shows that most protocols have higher delivery ratio with increased buffer size. The proposed routing algorithm yields a higher delivery ratio than the other single-strategy protocols because in such a large-scale scenario, clustering strategy groups nodes into different clusters, which makes the network more coarse-grained. As a result, from a single node's point of view, the network scale becomes much smaller. Furthermore, a node can make its forwarding decision inside or outside of the cluster more wisely which not only saves the buffer of local nodes, but also tends to the route with higher contact probability.

Overheads are shown in Figure 5(b), which indicates the average number of copies generated by the network until a packet is successfully delivered. Direct Delivery is a single copy protocol which does not produce additional copy of packets. Epidemic Protocol duplicates a copy whenever a node contact with others, thereby producing the highest overhead among the protocols. In the clustering-based routing framework, nodes generate copies only when they meet the other nodes in different clusters where no copy of the specific packet exists, thereby controlling the overhead. On the other hand, the overhead of PROPHET Protocol is two times greater than that of the proposed algorithm because of its high forwarding probability and one-hop decision making. As a result, the clustering-based routing algorithm yields a really low overhead between those of PROPHET and Direct Delivery Protocol, and has considerable performance in large-scale real-world urban networks.




Fig. 6. Delivery ratio and overhead of all methods with different network scales

C. Scalability

Scalability is one of the major consideration of routing protocols in large-scale DTN networks. The network scale is mainly changed by the number of nodes within the network. A greater number of nodes involved in the network indicates greater overheads since many additional copies of packets and messages to synchronous routing information are generated. In this case, the network may encounter a bottleneck and the performance of most protocols may stagnate or deteriorate. In this set of simulations, the scalability of protocols is compared by varying the number of nodes from 500 to 3,000. The other parameters are remaining the same as those in Table III.

Figure 6(a) shows the delivery ratio in the network with different numbers of nodes. The performances of the single-strategy routing protocols do not improve as the number of nodes increases. In general, increasing nodes density can bring more contact opportunities which should lead to higher delivery ratio. However, if the network scale is large enough, the buffer capacity becomes limited during the single-strategy routing because of their overall forwarding behaviors, which limit the increase of delivery ratio. The clustering-based routing algorithm can adapt to the increasing scale. If the clustering parameters are constant ($t = 400, \eta = 0.3$), the number of clusters does not change considerably when the network scale increases. Instead, the size of each cluster, which is denoted by number of nodes inside each cluster, increases. Therefore, from a single node's point of view, the buffer capacities of clusters increase. When executing inter-cluster routing, each cluster is considered a bigger "node". Thus, the network maintains the small number of "nodes" which have a higher buffer capacity, thereby improving routing performances.

Figure 6(b) reveals the superior scalability of the proposed framework based on the other metric, namely, overhead growth rate. When the network is sparse, overhead of single-strategy protocols is close to that of clustering-based routing. However, as the number of nodes increases, overheads of those protocols, except that of Direct Delivery, become dramatically high. On the other hand, the proposed algorithm can restrict its overhead growth rate. The reason is similar to the one we described above for delivery ratio. In large-scale urban DTNs, the proposed algorithm can help reduce network overhead and achieve scalability thereby outperforming traditional single-strategy routing protocols.

VI. CONCLUSION

In this paper, we analyzed the contact characteristics of large-scale urban DTNs over a real-world trace data set from Beijing. Distribution of ICTs exhibits an exponential nature in

such kind of urban DTN networks. To improve the scalability of routing protocols, we proposed a clustering-based routing algorithm by using contact probability estimated from ICTs distributions as the clustering metric. The extensive simulation results demonstrated that the performance and scalability of CPCPR exceed those of traditional flat protocols.

REFERENCES

- [1] K. Fall, A delay-tolerant network architecture for challenged internets, in: *Proceedings of the 2003 conference on Applications, technologies, architectures, and protocols for computer communications*, ACM, 2003, pp. 27–34.
- [2] K. Fall, S. Farrell, DTN: an architectural retrospective, *Selected Areas in Communications*, IEEE Journal on 26 (5) (2008) 828–836. doi:10.1109/JSAC.2008.080609.
- [3] S. Ahmed, S. Salil, Characterization of a large-scale delay tolerant network, in: *Local Computer Networks (LCN)*, 2010 IEEE 35th Conference on, IEEE, 2010, pp. 56–63.
- [4] S. Saha, N. Ganguly, A. Mukherjee, Information dissemination dynamics in delay tolerant network: a bipartite network approach, in: *Proceedings of the third ACM international workshop on Mobile Opportunistic Networks*, ACM, 2012, pp. 21–28.
- [5] H. Zhu, M. Li, L. Fu, G. Xue, Y. Zhu, L. M. Ni, Impact of traffic inflows: Revealing exponential intercontact time in urban VANETs, *IEEE Trans. Parallel Distrib. Syst.* 22 (8) (2011) 1258–1266. doi:10.1109/TPDS.2010.176.
- [6] F. Li, Y. Wang, Routing in vehicular ad hoc networks: A survey, *Vehicular Technology Magazine*, IEEE 2 (2) (2007) 12–22.
- [7] F. Li, L. Zhao, X. Fan, Y. Wang, Hybrid position-based and dtn forwarding for vehicular sensor networks, *International Journal of Distributed Sensor Networks* 2012 (2012) 1–10.
- [8] J. Burgess, B. Gallagher, D. Jensen, B. N. Levine, Maxprop: Routing for vehicle-based disruption-tolerant networks, in: *INFOCOM 2006. 25th IEEE International Conference on Computer Communications. Proceedings*, Vol. 6, 2006, pp. 1–11.
- [9] H.-Y. Huang, P.-E. Luo, M. Li, D. Li, X. Li, W. Shu, M.-Y. Wu, Performance evaluation of SUVnet with real-time traffic data, *Vehicular Technology*, IEEE Transactions on 56 (6) (2007) 3381–3396.
- [10] Q. Fu, B. Krishnamachari, L. Zhang, DAWN: A density adaptive routing for deadline-based data collection in vehicular delay tolerant networks, *Tsinghua Science and Technology* 18 (3) (2013) 230–241. doi:10.1109/TST.2013.6522582.
- [11] A. J. Kleywegt, V. S. Nori, M. W. P. Savelsbergh, The stochastic inventory routing problem with direct deliveries, *Transportation Science* 36 (1) (2002) 94–118.
- [12] A. Vahdat, D. Becker, et al., Epidemic routing for partially connected ad hoc networks, Tech. rep., Technical Report CS-200006, Duke University (2000).
- [13] R. Agarwal, D. Motwani, et al., Survey of clustering algorithms for MANET, *International Journal on Computer Science and Engineering* 1 (2) (2009) 98–104.
- [14] C. Liu, Y. Liu, X. Ma, J. Gao, An application scheme of publish/subscribe system over clustering mobile ad hoc networks, in: *Wireless Communications Networking and Mobile Computing (WiCOM)*, 2010 6th International Conference on, 2010, pp. 1–4.
- [15] H. Wang, L. Mi, C. Xia, L. Lv, M. Chen, TLDV: Tree-like locator distance vector routing protocol for MANETs, in: *Educational and Information Technology (ICEIT)*, 2010 International Conference on, Vol. 2, 2010, pp. V2–291.
- [16] J. Whitbeck, V. Conan, Hymad: Hybrid DTN-MANET routing for dense and highly dynamic wireless networks, *Computer Communications* 33 (13) (2010) 1483–1492.
- [17] H. Dang, H. Wu, Clustering and cluster-based routing protocol for delay-tolerant mobile networks, *IEEE Transactions on Wireless Communications* 9 (6) (2010) 1874–1881.
- [18] A. Kernal, Y. Mohamed, Survey on routing protocols for wireless sensor network, *Elsevier Ad-hoc Network* 3 (3) (2005) 325–349.
- [19] W. Gao, G. Cao, On exploiting transient contact patterns for data forwarding in delay tolerant networks, in: *Network Protocols (ICNP)*, 2010 18th IEEE International Conference on, 2010, pp. 193–202.
- [20] J. Whitbeck, V. Conan, HYMAD: Hybrid DTN-MANET routing for dense and highly dynamic wireless networks, *Computer Communications* 33 (13) (2010) 1483–1492.
- [21] I. Carreras, D. Miorandi, I. Chlamtac, A simple model of contact patterns in delay-tolerant networks, *Wireless Networks* 16 (3) (2010) 851–862.
- [22] Y. Li, P. Hui, D. Jin, L. Su, L. Zeng, Evaluating the impact of social selfishness on the epidemic routing in delay tolerant networks, *Communications Letters*, IEEE 14 (11) (2010) 1026–1028.
- [23] T. Hossmann, T. Spyropoulos, F. Legendre, Know thy neighbor: Towards optimal mapping of contacts to social graphs for dtn routing, in: *INFOCOM*, 2010 Proceedings IEEE, 2010, pp. 1–9.
- [24] R. Groenevelt, P. Nain, G. Koole, The message delay in mobile ad hoc networks, *Performance Evaluation* 62 (1) (2005) 210–228.
- [25] Y. Li, Y. Jiang, D. Jin, L. Su, L. Zeng, D. Wu, Energy-efficient optimal opportunistic forwarding for delay-tolerant networks, *Vehicular Technology*, IEEE Transactions on 59 (9) (2010) 4500–4512.
- [26] S. Jain, K. Fall, R. Patra, Routing in a delay tolerant network, Vol. 34, ACM, 2004.
- [27] Y. Cao, Z. Sun, Routing in delay/disruption tolerant networks: A taxonomy, survey and challenges, *Communications Surveys & Tutorials*, IEEE 15 (2) (2013) 654–677.
- [28] Y. Zhu, B. Xu, X. Shi, Y. Wang, A survey of social-based routing in delay tolerant networks: Positive and negative social effects, *IEEE Communication Survey and Tutorials* 15 (1) (2013) 387–401.
- [29] A. Vahdat, D. Becker, Epidemic routing for partially connected ad hoc networks, Tech. rep., Technical Report CS-200006, Duke University (2000).
- [30] A. Balasubramanian, B. Levine, A. Venkataramani, DTN routing as a resource allocation problem, in: *ACM SIGCOMM Computer Communication Review*, Vol. 37, ACM, 2007, pp. 373–384.
- [31] F. T. Leighton, B. M. Maggs, A. G. Ranade, S. B. Rao, Randomized routing and sorting on fixed-connection networks, *Journal of Algorithms* 17 (1) (1994) 157–205.
- [32] T. Spyropoulos, K. Psounis, C. S. Raghavendra, Spray and wait: an efficient routing scheme for intermittently connected mobile networks, in: *Proceedings of the 2005 ACM SIGCOMM workshop on Delay-tolerant networking*, ACM, 2005, pp. 252–259.
- [33] M. Grossglauser, D. Tse, Mobility increases the capacity of ad-hoc wireless networks, in: *INFOCOM 2001. Twentieth Annual Joint Conference of the IEEE Computer and Communications Societies. Proceedings*, IEEE, Vol. 3, IEEE, 2001, pp. 1360–1369.
- [34] T. Spyropoulos, K. Psounis, C. S. Raghavendra, Efficient routing in intermittently connected mobile networks: the multiple-copy case, *Networking*, IEEE/ACM Transactions on 16 (1) (2008) 77–90.
- [35] A. Lindgren, A. Doria, O. Schelen, Probabilistic routing in intermittently connected networks, in: *Service Assurance with Partial and Intermittent Resources*, Service Assurance with Partial and Intermittent Resources, Springer, 2004, pp. 239–254.
- [36] J. Burgess, B. Gallagher, D. Jensen, B. N. Levine, MaxProp: Routing for vehicle-based disruption-tolerant networks., in: *INFOCOM*, Vol. 6, 2006, pp. 1–11.
- [37] H. Dang, H. Wu, Clustering and cluster-based routing protocol for delay-tolerant mobile networks, *Wireless Communications*, IEEE Transactions on 9 (6) (2010) 1874–1881.
- [38] C. Liu, J. Wu, Scalable routing in delay tolerant networks, *MOBI-HOC'07: proceeding of the 8th ACM international symposium on mobile ad hoc networking and computing* (2007) 51–60.
- [39] S. Ahmed, S. S. Kanhere, Cluster-based forwarding in delay tolerant public transport networks, in: *Local Computer Networks*, 2007. LCN 2007. 32nd IEEE Conference on, Dublin, Ireland, 2007, pp. 625 – 632.
- [40] R. Ganti, M. Srivatsa, A. Ranganathan, J. Han, Inferring human mobility patterns from taxicab location traces, in: *Proceedings of the 2013 ACM International Joint Conference on Pervasive and Ubiquitous Computing, UbiComp '13*, ACM, New York, NY, USA, 2013, pp. 459–468. doi:10.1145/2493432.2493466.

- [41] J. Aslam, S. Lim, X. Pan, D. Rus, City-scale traffic estimation from a roving sensor network, in: Proceedings of the 10th ACM Conference on Embedded Network Sensor Systems, SenSys '12, ACM, New York, NY, USA, 2012, pp. 141–154. doi:10.1145/2426656.2426671.
- [42] Y. Hu, H. Wang, C. Xia, W. Li, Y. Yang, On the distribution of inter contact time for DTNs, in: Local Computer Networks (LCN), 2012 IEEE 37th Conference on, IEEE, 2012, pp. 152–155.
- [43] Y. Jiang, Y. Li, L. Zhou, D. Jin, L. Su, L. Zeng, Optimal opportunistic forwarding with energy constraint for DTN, in: INFOCOM IEEE Conference on Computer Communications Workshops, 2010, 2010, pp. 1–2.
- [44] X. Zhang, H. Zhang, Y. Gu, Impact of source counter on dtn routing control under resource constraints, in: 2nd International Workshop on Mobile Opportunistic Networking, MobiOpp 2010, Pisa, Italy, 2010, pp. 41–50.
- [45] X. L. Zhang, J. Kurose, B. N. Levine, D. Towsley, H. G. Zhang, Study of a bus-based disruption-tolerant network: Mobility modeling and impact on routing, MOBICOM'07: proceedings of the 13th ACM international conference on mobile computing and networking (2007) 195–206.
- [46] D. J. Ozer, Correlation and the coefficient of determination., Psychological Bulletin 97 (2) (1985) 307.
- [47] A. Keraen, J. Ott, T. Karkkainen, The ONE simulator for DTN protocol evaluation, in: Proceedings of the 2nd International Conference on Simulation Tools and Techniques, ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering), 2009, p. 55.
- [48] A. B. McDonald, T. F. Znati, A mobility-based framework for adaptive clustering in wireless ad hoc networks, Selected Areas in Communications, IEEE Journal on 17 (8) (1999) 1466–1487.