

# Dynamic Maximum Depth and Klee's Measure

Jie Xue

New York University Shanghai

joint work with

Sujoy Bhore (IIT Bombay)

Subhash Suri (UCSB)

Xiongxin Yang (UCSB)

Jiumu Zhu (NYU Shanghai)


- **Maximum depth**

$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$

# Background

- **Maximum depth**


$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$



# Background

- **Maximum depth**


$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$



# Background

- **Maximum depth**


$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$



# Background

- **Maximum depth**

$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$




- **Klee's measure**

$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$

# Background

- **Klee's measure**

$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$






# Background

- **Klee's measure**


$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$



# Background


- **Klee's measure**

$\mathcal{O}$  = a set of geometric objects in  $\mathbb{R}^d$




- **Similarity between maximum depth and Klee's measure**


- **Similarity between maximum depth and Klee's measure**



- Similarity between maximum depth and Klee's measure




- Similarity between maximum depth and Klee's measure



$$\text{dep}(\mathcal{O}) = \sup_{p \in \mathbb{R}^2} \sum_{O \in \mathcal{O}} f_O(p)$$

- **Similarity between maximum depth and Klee's measure**



$$\text{dep}(\mathcal{O}) = \sup_{p \in \mathbb{R}^2} \sum_{O \in \mathcal{O}} f_O(p)$$

$$\text{Klee}(\mathcal{O}) = \int_{p \in \mathbb{R}^2} \max_{O \in \mathcal{O}} f_O(p)$$

# Background

- In this talk, we focus on (axis-parallel) **boxes** in  $\mathbb{R}^d$  for a fixed  $d$ .



# Background

- In this talk, we focus on (axis-parallel) **boxes** in  $\mathbb{R}^d$  for a fixed  $d$ .

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **maximum depth** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **Klee's measure** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.

# Background

- In this talk, we focus on (axis-parallel) **boxes** in  $\mathbb{R}^d$  for a fixed  $d$ .

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **maximum depth** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **Klee's measure** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.

- Here  $\tilde{O}(\cdot)$  hides factors  $\log^{O(1)} n$  or  $(\log^{O(1)} n)^{-1}$ .

# Background

- In this talk, we focus on (axis-parallel) **boxes** in  $\mathbb{R}^d$  for a fixed  $d$ .

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **maximum depth** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.

Theorem (Overmars and Yap FOCS'88; Chan FOCS'13)

The **Klee's measure** of  $n$  boxes in  $\mathbb{R}^d$  can be computed in  $\tilde{O}(n^{d/2})$  time.


- Here  $\tilde{O}(\cdot)$  hides factors  $\log^{O(1)} n$  or  $(\log^{O(1)} n)^{-1}$ .
- The bound  $\tilde{O}(n^{d/2})$  is believed to be **tight** up to logarithmic factors.

# Background

- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.


# Background

- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.




# Background

- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.




# Background

- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.



# Background


- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.





# Background

- We study these problems in the **fully dynamic** setting, where we are allowed to **insert/delete** boxes.



# Background

- What is the **best** update time one can hope?

# Background

- What is the **best** update time one can hope?
- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

# Background

- What is the **best** update time one can hope?
- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

$O(n^{d/2-1-\varepsilon})$  update time  $\implies O(n^{d/2-\varepsilon})$  time (static)

# Background

- What is the **best** update time one can hope?

- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

$O(n^{d/2-1-\varepsilon})$  update time  $\implies O(n^{d/2-\varepsilon})$  time (static)

- **Better lower bound:**  $\tilde{\Omega}(n^{(d-1)/2})$

# Background

- What is the **best** update time one can hope?

- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

$O(n^{d/2-1-\varepsilon})$  update time  $\implies O(n^{d/2-\varepsilon})$  time (static)

- **Better lower bound:**  $\tilde{\Omega}(n^{(d-1)/2})$

$O(n^{(d-1)/2-\varepsilon})$  update time in  $\mathbb{R}^d \implies O(n^{(d+1)/2-\varepsilon})$  time in  $\mathbb{R}^{d+1}$

# Background

- What is the **best** update time one can hope?

- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

$O(n^{d/2-1-\varepsilon})$  update time  $\implies O(n^{d/2-\varepsilon})$  time (static)

- **Better lower bound:**  $\tilde{\Omega}(n^{(d-1)/2})$

$O(n^{(d-1)/2-\varepsilon})$  update time in  $\mathbb{R}^d \implies O(n^{(d+1)/2-\varepsilon})$  time in  $\mathbb{R}^{d+1}$

## Question

Do there exist dynamic data structures with update time  $\tilde{O}(n^{(d-1)/2})$ ?

# Background

- What is the **best** update time one can hope?

- **Trivial lower bound:**  $\tilde{\Omega}(n^{d/2-1})$

$O(n^{d/2-1-\varepsilon})$  update time  $\implies O(n^{d/2-\varepsilon})$  time (static)

- **Better lower bound:**  $\tilde{\Omega}(n^{(d-1)/2})$

$O(n^{(d-1)/2-\varepsilon})$  update time in  $\mathbb{R}^d \implies O(n^{(d+1)/2-\varepsilon})$  time in  $\mathbb{R}^{d+1}$

## Question

Do there exist dynamic data structures with update time  $\tilde{O}(n^{(d-1)/2})$ ?

- For  $d = 1$ , one can achieve  $O(\log n)$  update time using **interval trees**.



# Our results

- We answer this question **affirmatively** for both problems for all fixed  $d$ .

# Our results

- We answer this question **affirmatively** for both problems for all fixed  $d$ .

## Theorem

*There exists a dynamic data structure for **maximum depth** of boxes in  $\mathbb{R}^d$  with  $\tilde{O}(n^{(d-1)/2})$  amortized update time.*

# Our results

- We answer this question **affirmatively** for both problems for all fixed  $d$ .

## Theorem

*There exists a dynamic data structure for **maximum depth** of boxes in  $\mathbb{R}^d$  with  $\tilde{O}(n^{(d-1)/2})$  amortized update time.*

## Theorem

*There exists a dynamic data structure for **Klee's measure** of boxes in  $\mathbb{R}^d$  with  $\tilde{O}(n^{(d-1)/2})$  amortized update time.*

## Warmup: Rectangles in $\mathbb{R}^2$


- $\mathcal{B}$  = a **dynamic** set of rectangles in  $\mathbb{R}^2$

## Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}$  = a **dynamic** set of rectangles in  $\mathbb{R}^2$
- Let's consider how to maintain  $\text{dep}(\mathcal{B})$  in  $\tilde{O}(\sqrt{n})$  time.

# Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}$  = a **dynamic** set of rectangles in  $\mathbb{R}^2$
- Let's consider how to maintain  $\text{dep}(\mathcal{B})$  in  $\tilde{O}(\sqrt{n})$  time.
- **Space partitioning**



# Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}$  = a **dynamic** set of rectangles in  $\mathbb{R}^2$
- Let's consider how to maintain  **$\text{dep}(\mathcal{B})$**  in  **$\tilde{O}(\sqrt{n})$**  time.
- **Space partitioning**

|                |                            |          |
|----------------|----------------------------|----------|
|                | $O(n/r)$ rectangle corners | $S_1$    |
|                | <hr/>                      |          |
|                | $O(n/r)$ rectangle corners | $S_2$    |
|                | <hr/>                      |          |
| $\mathbb{R}^2$ | $O(n/r)$ rectangle corners | $S_3$    |
|                | <hr/>                      |          |
|                |                            | $\vdots$ |
|                | <hr/>                      |          |
|                | $O(n/r)$ rectangle corners | $S_r$    |

## Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.



## Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .

## Warmup: Rectangles in $\mathbb{R}^2$


- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are **good**

## Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are good  
(No corners in  $S_i$ )


## Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are **good**  
(No corners in  $S_i$ )




## Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are **good**  
(No corners in  $S_i$ )




# Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are **good**  
(No corners in  $S_i$ )



# Warmup: Rectangles in $\mathbb{R}^2$

- For each strip  $S_i$ , maintain  $\text{dep}_{S_i}(\mathcal{B})$  individually.
- Note that  $S_i$  can intersect  $\Omega(n)$  rectangles in  $\mathcal{B}$ .
- **Intuition:** all but  $O(n/r)$  rectangles intersecting  $S_i$  are **good**  
(No corners in  $S_i$ )



Good rectangles can be viewed as intervals

## Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .



## Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$

## Warmup: Rectangles in $\mathbb{R}^2$


- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$
- $B \in \mathcal{B}_i^{\text{good}} \mapsto \text{proj}_x(B) \in \mathcal{I}_i$  with weight 1

## Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$
- $B \in \mathcal{B}_i^{\text{good}} \mapsto \text{proj}_x(B) \in \mathcal{I}_i$  with weight 1
- How do we handle the bad rectangles?

## Warmup: Rectangles in $\mathbb{R}^2$


- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$
- $B \in \mathcal{B}_i^{\text{good}} \mapsto \text{proj}_x(B) \in \mathcal{I}_i$  with weight 1
- How do we handle the **bad rectangles**?



$$f : \mathbb{R} \rightarrow \mathbb{N}_0 \quad f(x) = \text{dep}_{\{x\} \times \mathbb{R}}(\mathcal{B}_i^{\text{bad}})$$


# Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$
- $B \in \mathcal{B}_i^{\text{good}} \mapsto \text{proj}_x(B) \in \mathcal{I}_i$  with weight 1
- How do we handle the bad rectangles?



# Warmup: Rectangles in $\mathbb{R}^2$

- $\mathcal{B}_i \subseteq \mathcal{B}$  consists of the rectangles intersecting  $S_i$ .
- **Main idea:** map the rectangles in  $\mathcal{B}_i$  to a set  $\mathcal{I}_i$  of  $O(n)$  (weighted) intervals in  $\mathbb{R}^1$  such that  $\text{dep}_{S_i}(\mathcal{B}_i) = \text{dep}(\mathcal{I}_i)$
- $B \in \mathcal{B}_i^{\text{good}} \mapsto \text{proj}_x(B) \in \mathcal{I}_i$  with weight 1
- How do we handle the bad rectangles?



## Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.

## Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.
- When inserting or deleting a rectangle  $B...$




## Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.
- When inserting or deleting a rectangle  $B$ ...

Is  $B$  good w.r.t.  $S_i$ ?


## Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.
- When inserting or deleting a rectangle  $B$ ...




# Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.
- When inserting or deleting a rectangle  $B$ ...



# Warmup: Rectangles in $\mathbb{R}^2$

- We maintain  $\mathcal{I}_i$  in a dynamic maximum depth data structure  $\mathcal{D}_i$  for intervals with  $O(\log n)$  update time.
- When inserting or deleting a rectangle  $B$ ...



# Warmup: Rectangles in $\mathbb{R}^2$


- **Global update time**

# Warmup: Rectangles in $\mathbb{R}^2$

- **Global update time**
- $B$  is **bad** for **at most two**  $S_i$ 's and **good** for  $O(r)$   $S_i$ 's.


# Warmup: Rectangles in $\mathbb{R}^2$

- **Global update time**
- $B$  is **bad** for **at most two**  $S_i$ 's and **good** for  $O(r)$   $S_i$ 's.



# Warmup: Rectangles in $\mathbb{R}^2$

- **Global update time**
- $B$  is **bad** for **at most two**  $S_i$ 's and **good** for  $O(r)$   $S_i$ 's.




- $T(n, r) = O((n/r) \log n) + O(r \log n)$



# Warmup: Rectangles in $\mathbb{R}^2$

- **Global update time**
- $B$  is **bad** for **at most two**  $S_i$ 's and **good** for  $O(r)$   $S_i$ 's.



- $T(n, r) = O((n/r) \log n) + O(r \log n)$
- Setting  $r = \sqrt{n}$  gives us  $O(\sqrt{n} \log n)$  update time.

- Unfortunately, the result doesn't directly generalize to  $d \geq 3$ .


# General case

- Unfortunately, the result doesn't directly generalize to  $d \geq 3$ .
- The data structure easily generalizes (but with **worse** update time).

- Unfortunately, the result doesn't directly generalize to  $d \geq 3$ .
- The data structure easily generalizes (but with **worse** update time).
- **Some natural attempts**

- Unfortunately, the result doesn't directly generalize to  $d \geq 3$ .
- The data structure easily generalizes (but with **worse** update time).
- **Some natural attempts**

## Attempt 1




Partition in the first dim

# General case


- Unfortunately, the result doesn't directly generalize to  $d \geq 3$ .
- The data structure easily generalizes (but with **worse** update time).
- Some natural attempts**

Attempt 1



Partition in the first dim

Attempt 2



Partition in the first  $d - 1$  dim

- **Attempt 1** seems intrinsically **unfeasible**.


# General case

- **Attempt 1** seems intrinsically **unfeasible**.
- Our result for  $d \geq 3$  works in the direction of **Attempt 2**.




# General case

- **Attempt 1** seems intrinsically **unfeasible**.
- Our result for  $d \geq 3$  works in the direction of **Attempt 2**.




# General case

- **Attempt 1** seems intrinsically **unfeasible**.
- Our result for  $d \geq 3$  works in the direction of **Attempt 2**.




# General case

- **Attempt 1** seems intrinsically **unfeasible**.
- Our result for  $d \geq 3$  works in the direction of **Attempt 2**.



# General case

- **Attempt 1** seems intrinsically **unfeasible**.
- Our result for  $d \geq 3$  works in the direction of **Attempt 2**.



- When inserting/deleting a box  $B$ ...

# General case

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.

# General case

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is good.
- Update for each such cell takes  $O(\log n)$  time.

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.
- Update for each such cell takes  $O(\log n)$  time.  
 $\Rightarrow \tilde{O}(r^{d-1})$  time in total



# General case

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.
- Update for each such cell takes  $O(\log n)$  time.  
 $\Rightarrow \tilde{O}(r^{d-1})$  time in total
- There are  $O(r^{d-2})$  cells  $\square_{\vec{v}}$  for which  $B$  is **bad**.

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.
- Update for each such cell takes  $O(\log n)$  time.  
 $\Rightarrow \tilde{O}(r^{d-1})$  time in total
- There are  $O(r^{d-2})$  cells  $\square_{\vec{v}}$  for which  $B$  is **bad**.
- Update for each such cell takes  $\tilde{O}((n/r)^{d/2})$  time.
  - Recomputing the depth function  $\rightarrow \tilde{O}((n/r)^{d/2})$  time
  - Deleting/inserting the intervals  $\rightarrow \tilde{O}(n/r)$  time

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.
- Update for each such cell takes  $O(\log n)$  time.  
 $\Rightarrow \tilde{O}(r^{d-1})$  time in total
- There are  $O(r^{d-2})$  cells  $\square_{\vec{v}}$  for which  $B$  is **bad**.
- Update for each such cell takes  $\tilde{O}((n/r)^{d/2})$  time.
  - Recomputing the depth function  $\rightarrow \tilde{O}((n/r)^{d/2})$  time
  - Deleting/inserting the intervals  $\rightarrow \tilde{O}(n/r)$  time $\Rightarrow \tilde{O}(n^{d/2} r^{d/2-2})$  time in total (**can't afford!**)

# General case

- When inserting/deleting a box  $B$ ...
- There are  $O(r^{d-1})$  cells  $\square_{\vec{v}}$  for which  $B$  is **good**.
- Update for each such cell takes  $O(\log n)$  time.  
 $\Rightarrow \tilde{O}(r^{d-1})$  time in total
- There are  $O(r^{d-2})$  cells  $\square_{\vec{v}}$  for which  $B$  is **bad**.
- Update for each such cell takes  $\tilde{O}((n/r)^{d/2})$  time.
  - Recomputing the depth function  $\rightarrow \tilde{O}((n/r)^{d/2})$  time  $\leftarrow$  **Bottleneck**
  - Deleting/inserting the intervals  $\rightarrow \tilde{O}(n/r)$  time $\Rightarrow \tilde{O}(n^{d/2} r^{d/2-2})$  time in total (**can't afford!**)

# General case

- If we look at a single cell  $\square_{\vec{v}}$ , there can be  $O(n/r)$  bad boxes w.r.t.  $\square_{\vec{v}}$ , which are **totally unstructured**.

# General case


- If we look at a single cell  $\square_{\vec{v}}$ , there can be  $O(n/r)$  bad boxes w.r.t.  $\square_{\vec{v}}$ , which are **totally unstructured**.
- We have to pay  $\tilde{O}((n/r)^{d/2})$  time to compute the depth function for a single cell  $\square_{\vec{v}}$ , in the worst case.

# General case

- If we look at a single cell  $\square_{\vec{v}}$ , there can be  $O(n/r)$  bad boxes w.r.t.  $\square_{\vec{v}}$ , which are **totally unstructured**.
- We have to pay  $\tilde{O}((n/r)^{d/2})$  time to compute the depth function for a single cell  $\square_{\vec{v}}$ , in the worst case.
- **Main insight:** **globally** consider **all** cells  $\square_{\vec{v}}$

# General case


- If we look at a single cell  $\square_{\vec{v}}$ , there can be  $O(n/r)$  bad boxes w.r.t.  $\square_{\vec{v}}$ , which are **totally unstructured**.
- We have to pay  $\tilde{O}((n/r)^{d/2})$  time to compute the depth function for a single cell  $\square_{\vec{v}}$ , in the worst case.
- **Main insight:** globally consider **all** cells  $\square_{\vec{v}}$





# General case

- If we look at a single cell  $\square_{\vec{v}}$ , there can be  $O(n/r)$  bad boxes w.r.t.  $\square_{\vec{v}}$ , which are **totally unstructured**.
- We have to pay  $\tilde{O}((n/r)^{d/2})$  time to compute the depth function for a single cell  $\square_{\vec{v}}$ , in the worst case.
- **Main insight:** globally consider **all** cells  $\square_{\vec{v}}$



Most bad boxes are only bounded in one dimension

- Computing the depth function in  $\square_{\vec{v}}$  can be reduced to the **offline** dynamic problem in  $\mathbb{R}^{d-1}$ , i.e., the updates are known **beforehand**.

- Computing the depth function in  $\square_{\vec{v}}$  can be reduced to the **offline** dynamic problem in  $\mathbb{R}^{d-1}$ , i.e., the updates are known **beforehand**.

## OFFLINE DYNAMIC MAXIMUM DEPTH

**Input:** An initially empty set  $\mathcal{B}'$  of boxes in  $\mathbb{R}^{d-1}$  and a sequence of  $n$  updates to  $\mathcal{B}'$ , each of which is of one of the following two types:

- **Insertion:** Insert a new box to  $\mathcal{B}'$
- **Deletion:** Delete an existing box from  $\mathcal{B}'$

- Computing the depth function in  $\square_{\vec{v}}$  can be reduced to the **offline** dynamic problem in  $\mathbb{R}^{d-1}$ , i.e., the updates are known **beforehand**.

## OFFLINE DYNAMIC MAXIMUM DEPTH

**Input:** An initially empty set  $\mathcal{B}'$  of boxes in  $\mathbb{R}^{d-1}$  and a sequence of  $n$  updates to  $\mathcal{B}'$ , each of which is of one of the following two types:

- **Insertion:** Insert a new box to  $\mathcal{B}'$
- **Deletion:** Delete an existing box from  $\mathcal{B}'$

**Output:** A sequence  $(\delta_1, \dots, \delta_n)$ , where  $\delta_i \in \mathbb{N}_0$  is the maximum depth of  $\mathcal{B}'$  after the  $i$ -th update

- Computing the depth function in  $\square_{\nabla}$  can be reduced to the **offline** dynamic problem in  $\mathbb{R}^{d-1}$ , i.e., the updates are known **beforehand**.

## OFFLINE DYNAMIC MAXIMUM DEPTH

**Input:** An initially empty set  $\mathcal{B}'$  of boxes in  $\mathbb{R}^{d-1}$  and a sequence of  $n$  updates to  $\mathcal{B}'$ , each of which is of one of the following two types:

- **Insertion:** Insert a new box to  $\mathcal{B}'$
- **Deletion:** Delete an existing box from  $\mathcal{B}'$

**Output:** A sequence  $(\delta_1, \dots, \delta_n)$ , where  $\delta_i \in \mathbb{N}_0$  is the maximum depth of  $\mathcal{B}'$  after the  $i$ -th update


- We design an **offline** algorithm whose total update time depends on not only the number of updates **but also the structure of the boxes**.

- A box  $B$  is **trivial** in dimension  $j \in [d - 1]$  if **proj** $_j(B) = (-\infty, \infty)$ .

- A box  $B$  is **trivial** in dimension  $j \in [d-1]$  if  $\mathbf{proj}_j(B) = (-\infty, \infty)$ .
- For a permutation  $\sigma$  of  $[d-1]$ ,  $i \in [d-1]$ , and a box  $B$  in  $\mathbb{R}^{d-1}$ , we define a number  $\phi_\sigma(B, i) \in \{0, 1\}$  as follows:

# General case

- A box  $B$  is **trivial** in dimension  $j \in [d-1]$  if  $\mathbf{proj}_j(B) = (-\infty, \infty)$ .
- For a permutation  $\sigma$  of  $[d-1]$ ,  $i \in [d-1]$ , and a box  $B$  in  $\mathbb{R}^{d-1}$ , we define a number  $\phi_\sigma(B, i) \in \{0, 1\}$  as follows:





- For a set  $\mathcal{B}^*$  of boxes, define  $\Phi_\sigma(\mathcal{B}^*) = \prod_{i=1}^{d-1} (1 + \sum_{B \in \mathcal{B}^*} \phi_\sigma(B, i))$ .

- For a set  $\mathcal{B}^*$  of boxes, define  $\Phi_\sigma(\mathcal{B}^*) = \prod_{i=1}^{d-1} (1 + \sum_{B \in \mathcal{B}^*} \phi_\sigma(B, i))$ .

## Lemma (offline algorithm)

*Let  $\sigma$  be a permutation of  $[d - 1]$ . Then OFFLINE DYNAMIC MAXIMUM DEPTH in  $\mathbb{R}^{d-1}$  can be solved in  $O(n \log n \cdot \Phi_\sigma(\mathcal{B}^*))$  time, where  $\mathcal{B}^*$  is the set of all boxes involved in the update sequence.*

- For a set  $\mathcal{B}^*$  of boxes, define  $\Phi_\sigma(\mathcal{B}^*) = \prod_{i=1}^{d-1} (1 + \sum_{B \in \mathcal{B}^*} \phi_\sigma(B, i))$ .

## Lemma (offline algorithm)

Let  $\sigma$  be a permutation of  $[d - 1]$ . Then OFFLINE DYNAMIC MAXIMUM DEPTH in  $\mathbb{R}^{d-1}$  can be solved in  $O(n \log n \cdot \Phi_\sigma(\mathcal{B}^*))$  time, where  $\mathcal{B}^*$  is the set of all boxes involved in the update sequence.

- For each  $i \in [d - 1]$ , consider the boxes  $B \in \mathcal{B}^*$  with  $\phi_\sigma(B, i) = 1$ .

- For a set  $\mathcal{B}^*$  of boxes, define  $\Phi_\sigma(\mathcal{B}^*) = \prod_{i=1}^{d-1} (1 + \sum_{B \in \mathcal{B}^*} \phi_\sigma(B, i))$ .

## Lemma (offline algorithm)

Let  $\sigma$  be a permutation of  $[d - 1]$ . Then OFFLINE DYNAMIC MAXIMUM DEPTH in  $\mathbb{R}^{d-1}$  can be solved in  $O(n \log n \cdot \Phi_\sigma(\mathcal{B}^*))$  time, where  $\mathcal{B}^*$  is the set of all boxes involved in the update sequence.

- For each  $i \in [d - 1]$ , consider the boxes  $B \in \mathcal{B}^*$  with  $\phi_\sigma(B, i) = 1$ .
- Partition  $\mathbb{R}^{d-1}$  in dimension  $i$  along the  $i$ -facets of these boxes.

- For a set  $\mathcal{B}^*$  of boxes, define  $\Phi_\sigma(\mathcal{B}^*) = \prod_{i=1}^{d-1} (1 + \sum_{B \in \mathcal{B}^*} \phi_\sigma(B, i))$ .

## Lemma (offline algorithm)

Let  $\sigma$  be a permutation of  $[d - 1]$ . Then OFFLINE DYNAMIC MAXIMUM DEPTH in  $\mathbb{R}^{d-1}$  can be solved in  $O(n \log n \cdot \Phi_\sigma(\mathcal{B}^*))$  time, where  $\mathcal{B}^*$  is the set of all boxes involved in the update sequence.


- For each  $i \in [d - 1]$ , consider the boxes  $B \in \mathcal{B}^*$  with  $\phi_\sigma(B, i) = 1$ .
- Partition  $\mathbb{R}^{d-1}$  in dimension  $i$  along the  $i$ -facets of these boxes.
- This partitions  $\mathbb{R}^{d-1}$  into  $O(\Phi_\sigma(\mathcal{B}^*))$  regions. Inside each region, all boxes in  $\mathcal{B}^*$  are trivial in all but one dimensions.

# General case

- We can maintain  $\text{dep}_R(\mathcal{B}')$  for each region  $R$  in  $O(\log n)$  time.


# General case

- We can maintain  $\text{dep}_R(\mathcal{B}')$  for each region  $R$  in  $O(\log n)$  time.



# General case


- We can maintain  $\text{dep}_R(\mathcal{B}')$  for each region  $R$  in  $O(\log n)$  time.





# General case

- We can maintain  $\text{dep}_R(\mathcal{B}')$  for each region  $R$  in  $O(\log n)$  time.



$$\text{dep}_R(\mathcal{B}'_1 \cup \mathcal{B}'_2) = \text{dep}_R(\mathcal{B}'_1) + \text{dep}_R(\mathcal{B}'_2)$$

- **Back to the dynamic problem**

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...
  - For each  $\square_v$  where  $B$  is **good**, update in  $O(\log n)$  time.

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...
  - For each  $\square_{\vec{v}}$  where  $B$  is **good**, update in  $O(\log n)$  time.
  - For each  $\square_{\vec{v}}$  where  $B$  is **bad**, apply our offline algorithm with the **best** ordering  $\sigma \in \Sigma_{[d-1]}$  to compute the depth function

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...
  - For each  $\square_{\vec{v}}$  where  $B$  is **good**, update in  $O(\log n)$  time.
  - For each  $\square_{\vec{v}}$  where  $B$  is **bad**, apply our offline algorithm with the **best** ordering  $\sigma \in \Sigma_{[d-1]}$  to compute the depth function in time

$$O\left(\min_{\sigma \in \Sigma_{[d-1]}} (n/r) \log(n/r) \cdot \Phi_{\sigma}(\mathbf{proj}_{[d-1]}(\mathcal{B}_{\vec{v}}^{\text{bad}}))\right)$$

where  $\mathcal{B}_{\vec{v}}^{\text{bad}}$  is the set of **bad boxes** for  $\square_{\vec{v}}$ .

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...
  - For each  $\square_{\vec{v}}$  where  $B$  is **good**, update in  $O(\log n)$  time.
  - For each  $\square_{\vec{v}}$  where  $B$  is **bad**, apply our offline algorithm with the **best** ordering  $\sigma \in \Sigma_{[d-1]}$  to compute the depth function in time

$$O\left(\min_{\sigma \in \Sigma_{[d-1]}} (n/r) \log(n/r) \cdot \Phi_{\sigma}(\mathbf{proj}_{[d-1]}(\mathcal{B}_{\vec{v}}^{\text{bad}}))\right)$$

where  $\mathcal{B}_{\vec{v}}^{\text{bad}}$  is the set of **bad boxes** for  $\square_{\vec{v}}$ .

- Total update time =  $\tilde{O}(r^{d-1}) + \tilde{O}((n/r)^{d-1} + nr^{d-3})$

- **Back to the dynamic problem**
- When inserting/deleting a box  $B$ ...
  - For each  $\square_{\vec{v}}$  where  $B$  is **good**, update in  $O(\log n)$  time.
  - For each  $\square_{\vec{v}}$  where  $B$  is **bad**, apply our offline algorithm with the **best** ordering  $\sigma \in \Sigma_{[d-1]}$  to compute the depth function in time

$$O\left(\min_{\sigma \in \Sigma_{[d-1]}} (n/r) \log(n/r) \cdot \Phi_{\sigma}(\mathbf{proj}_{[d-1]}(\mathcal{B}_{\vec{v}}^{\text{bad}}))\right)$$

where  $\mathcal{B}_{\vec{v}}^{\text{bad}}$  is the set of **bad boxes** for  $\square_{\vec{v}}$ .

- Total update time =  $\tilde{O}(r^{d-1}) + \tilde{O}((n/r)^{d-1} + nr^{d-3})$
- Setting  $r = \sqrt{n}$  gives us  $\tilde{O}(n^{(d-1)/2})$  update time.



# Open questions

# Open questions

- Better preprocessing time and space?

# Open questions

- Better preprocessing time and space?
- Problems for other shapes (e.g., disks)?

# Open questions

- Better preprocessing time and space?
- Problems for other shapes (e.g., disks)?
- Approximate data structures?

Thank you!  
Q & A