

Cross-modal Contrastive Learning for Multimodal Fake News Detection

Longzheng Wang^{1,2}, Chuang Zhang^{1*}, Hongbo Xu¹, Shuai Zhang¹, Xiaohan Xu^{1,2} and Siqi Wang^{1,2}

¹Institute of Information Engineering, Chinese Academy of Sciences

²School of Cyber Security, University of Chinese Academy of Sciences

{wanglongzheng, zhangchuang, hbxu, zhangshuai0612, xuxiaohan, wangsiqi2022}@iie.ac.cn

Abstract

Automatic detection of multimodal fake news has gained a widespread attention recently. Many existing approaches seek to fuse unimodal features to produce multimodal news representations. However, the potential of powerful cross-modal contrastive learning methods for fake news detection has not been well exploited. Besides, how to aggregate features from different modalities to boost the performance of the decision-making process is still an open question. To address that, we propose COOLANT, a cross-modal contrastive learning framework for multimodal fake news detection, aiming to achieve more accurate image-text alignment. To further improve the alignment precision, we leverage an auxiliary task to soften the loss term of negative samples during the contrast process. A cross-modal fusion module is developed to learn the cross-modality correlations. An attention mechanism with an attention guidance module is implemented to help effectively and interpretably aggregate the aligned unimodal representations and the cross-modality correlations. Finally, we evaluate the COOLANT and conduct a comparative study on two widely used datasets, Twitter and Weibo. The experimental results demonstrate that our COOLANT outperforms previous approaches by a large margin and achieves new state-of-the-art results on the two datasets.

1 Introduction

With the proliferation of Online Social Networks (OSNs) such as Twitter and Weibo, individuals can freely share daily information and express their opinions and emotions. However, the misuse of OSNs and the lack of proper supervision to verify the credibility of online posts have given rise to the widespread dissemination of considerable fake news [Zubiaga *et al.*, 2018]. Therefore, fake news detection has gained a widespread attention and has become a top priority recently.

Existing studies on automatic fake news detection mainly focus on textual content, either with traditional learning meth-



Figure 1: Some fake news from Twitter. (a) The image does not add substantial information while the textual contents indicate that it is possibly fake. (b) The doctored image suggests that it is probably fake news. (c) Both text and image demonstrate it is likely to be fake. (d) An instance of False Connection, which narrates a war-like situation but includes a happy emotion depicted in the image.

ods such as decision tree classifiers [Liu *et al.*, 2015] or deep learning approaches such as convolutional neural networks (CNN) [Yu *et al.*, 2017]. However, most posts on social media commonly contain rich multimodal information, and the detection based on unimodal features is far from sufficient. Figure 1 shows some examples from Twitter illustrating the reasons why these four news items were determined to be fake. Recent works seek to fuse textual and visual features to produce multimodal post representations and then boost the performance of fake news detection [Khattar *et al.*, 2019; Wu *et al.*, 2021]. Nevertheless, we argue that more advanced multimodal representation learning paradigms should be appropriately applied, since acquiring more sophisticated aligned unimodal representations and cross-modal features is a prerequisite for effective multimodal fake news detection. Besides, cross-modal features might not necessarily play a critical role in some cases [Chen *et al.*, 2022; Singhal *et al.*, 2022]. For instance, the textual contents in Fig-

*Contact Author

ure 1(a) are preposterous enough to indicate that it is fake. In contrast, the cross-modal information gap in Figure 1(d) can help improve classification accuracy. Therefore, how features from different modalities affect the decision-making process and how we can make it more effective and interpretable remain open questions.

Recently, several contrastive learning-based multimodal pre-training methods have achieved great success, suggesting that contrastive learning may be a powerful paradigm for multimodal representation learning. The representative dual-stream model CLIP [Radford *et al.*, 2021] performs contrastive vision-language pre-training on 400 million (image, text) pairs collected from the Internet. [Zhou *et al.*, 2022] directly utilized CLIP to extract aligned multimodal features, and boost the performance of multimodal fake news detection. However, CLIP-alike methods strongly rely on the assumption that the image-text pairs are of high quality [Gao *et al.*, 2022], which is not entirely compatible with multimodal fake news detection. Therefore, although these advanced technologies can be beneficial in multimodal representation learning, their application in multimodal fake news detection remains to be explored.

Taking the consideration above, we propose COOLANT, a **C**ross-modal **C**ontrastive **L**earning framework for **M**ultimodal **F**ake **N**ews **D**etection. We first construct a visual semantics level and a linguistic semantics level and then use the CLIP contrastive learning objective to ensure the alignment between image and text modalities. To further improve the alignment precision, we leverage an auxiliary task, called cross-modal consistency learning, to introduce more supervisions and bring in more fine-grained semantic information. Specifically, the CLIP contrastive learning objective ensures that the image-text pairs are in perfect one-to-one correspondence, and the consistency learning task can derive the potential semantic similarity features to soften the loss of negative samples (unpaired samples). After that, we feed the aligned unimodal representations into a cross-modal fusion module to learn the cross-modality correlations. Finally, we design an attention mechanism module to help effectively aggregate the aligned unimodal representations and the cross-modality correlations. Inspired by [Chen *et al.*, 2022], we introduce an attention guidance module to quantify the ambiguity between text and image by estimating the divergence of their representation distributions, which can help guide the attention mechanism to assign reasonable weights to modalities. In this way, COOLANT can acquire more sophisticated aligned unimodal representations and cross-modal features, and then effectively aggregate these features to boost the performance of multimodal fake news detection.

The main contributions of this paper are as follows:

- We propose COOLANT, a cross-modal contrastive learning framework for multimodal fake news detection, aiming to achieve more accurate image-text alignment.
- We soften the loss term of negative samples during the contrast process to ease the strict constraint, so as to make it more compatible with our task.
- We introduce an attention mechanism with an attention guidance module to help effectively and interpretably

aggregate features from different modalities.

- We conduct experiments on two widely used datasets, Twitter and Weibo. Experimental results demonstrate that our model outperforms previous systems by a large margin and achieves new state-of-the-art results on the two datasets.

2 Related Work

2.1 Fake News Detection

Unimodal Methods. Existing unimodal fake news detection methods mainly rely on text content analysis or image content in posts. In text content analysis, [Qian *et al.*, 2018] propose a generative model to extract new patterns and assist fake news detection by analyzing past meaningful responses of users. TM [Bhattarai *et al.*, 2021] exploits lexical and semantic properties of the text to detect fake news. Besides, verifying logical soundness [Guo *et al.*, 2018], capturing writing styles [Potthast *et al.*, 2017] or extracting rhetorical structure [Conroy *et al.*, 2015] are also widely utilized to combat fake news. For image content, [Jin *et al.*, 2016] claim that there are noticeable discriminating features in the dissemination pattern of image content between real news and fake news. MVNN [Qi *et al.*, 2019] jointly leverages visual features in the spatial domain and image features in the frequency domain features for forensics. However, these approaches ignore cross-modal characteristics such as correlation and consistency, which may undermine their overall performance on multimodal news.

Multimodal Methods. More recently, several methods based on cross-modal discriminative patterns have been proposed to obtain superior performance in fake news detection. To learn the cross-modal characteristics, EANN [Wang *et al.*, 2018] leverages an additional event discriminator to aid feature extraction. MVAE [Khattar *et al.*, 2019] introduces a multimodal variable autoencoder to learn probabilistic latent variable models and then reconstructs the original texts and low-level image features. MCAN [Wu *et al.*, 2021] stacks multiple co-attention layers to better fuse textual and visual features for fake news detection. However, studies in multimodal fake news detection have rarely considered the application of the recently emerged multimodal representation learning paradigms. Besides, some methods work on the principles of weak and strong modality. CAFE [Chen *et al.*, 2022] measures cross-modal ambiguity by evaluating the Kullback-Leibler (KL) divergence between the distributions of unimodal features. The learned ambiguity score then linearly adjusts the weight of unimodal and multimodal features before final classification. LIIMR [Singhal *et al.*, 2022] identifies the modality that presents more substantial confidence towards fake news detection. In this paper, we effectively leverage features from different modalities and make the decision process more interpretable.

2.2 Contrastive Learning

Recently, contrastive learning has achieved a great success in computer vision [He *et al.*, 2020; Chen *et al.*, 2021] and natural language processing (NLP) [Gao *et al.*, 2021;

Yan *et al.*, 2021]. It has also been adapted to vision-language multimodal representation learning. WenLan [Huo *et al.*, 2021] proposes a two-tower Chinese multimodal pre-training model and adapts MoCo [He *et al.*, 2020] into the cross-modal scenario. CLIP [Radford *et al.*, 2021] adopts a simple contrastive learning method to learn transferable visual representations by maximizing cosine similarity between image and text modalities, which enables zero-shot transfer of the model to various downstream tasks. FND-CLIP [Zhou *et al.*, 2022] uses two pre-trained CLIP encoders to extract the deep representations from the image and text for fake news detection. In this paper, we follow the dual-stream design of CLIP to form our cross-modal contrastive learning module. Different from previous works, we leverage an auxiliary cross-modal consistency learning task to measure the semantic similarity between images and texts, and then provide soft targets for the contrastive learning module.

3 Methodology

In this section, we present our proposed framework COOLANT, that leverages the cross-modal contrastive learning task to align the features from image and text modalities. The overall model structure is illustrated in Figure 2. Given image-text pairs, we first extract unimodal features by the modal-specific encoder (§3.1). Then our method consists of three main components: the cross-modal contrastive learning module (§3.2) for the alignment between image and text modalities, the cross-modal fusion module (§3.3) for learning the cross-modality corrections, and the cross-modal aggregation module (§3.4) with an attention mechanism and an attention guidance for assigning reasonable attention scores to each modality, which then boosts the performance of multimodal fake news detection.

3.1 Modal-specific Encoder

Let each input multimodal news $\mathbf{x} = [x^v, x^t] \in \mathcal{D}$, where x^v , x^t and \mathcal{D} mean image, text and dataset, respectively. Since the modal-specific encoders are not the focus of this work, we leverage pre-training techniques to encode the image x^v and the text x^t into unimodal embedding e^v and e^t , respectively.

Visual Encoder. Given a visual content x^v , we utilize the pre-trained model ResNet [He *et al.*, 2016] trained over the ImageNet database to extract regional features. The final visual embedding e^v is obtained by using a fully connected layer to transform the regional features captured by ResNet.

Text Encoder. To precisely capture both semantic and contextualised representations, we adopt BERT [Devlin *et al.*, 2018] as the core module of our textual language model. Specifically, given a text x^t with a set of words, each word is tokenized by a pre-prepared vocabulary, then we utilize BERT to obtain the aggregate sequence representation as temporal textual features. The final textual embedding e^t is obtained by transforming the temporal textual features through a fully connected layer.

3.2 Cross-modal Contrastive Learning

Features from different modalities may have huge semantic gaps, so we adopt a more advanced multimodal representa-

tion learning paradigm, cross-modal contrastive learning, to align the features from different modalities by transforming the unimodal embeddings into a shared space. Specifically, CLIP [Radford *et al.*, 2021] is one of the most representative contrastive learning-based multimodal pre-training methods, which achieves astounding results. We follow the dual-stream design of CLIP and construct a visual semantics level and a linguistic semantics level to form our cross-modal contrastive learning module. As mentioned above, CLIP-like methods strongly rely on the assumption that the image-text pairs are of high quality, i.e., the pairs are in perfect one-to-one correspondence. However, the semantic mismatch between images and text often occurs in multimodal fake news data. Therefore, we propose to leverage an auxiliary cross-modal consistency learning task, which can help measure the semantic similarity between images and texts. The consistency learning module can provide semantic similarity matrixes as soft targets for the contrastive learning module.

Consistency Learning

Inspired by several recent works [Chen *et al.*, 2022; Wei *et al.*, 2022], we design a binary classification task to identify the semantic correlation of a text-image pair. Specifically, we begin with crafting a new dataset $\mathcal{D}' = [\mathcal{D}_{\text{pos}}, \mathcal{D}_{\text{neg}}]$ on the basis of \mathcal{D} , where a text-image pair is labeled $y' = 1$ if the textual and visual embeddings are from the same piece of real news, otherwise $y' = 0$. We feed the modal-specific encoders with $\mathbf{x}' = [x^{v'}, x^{t'}] \in \mathcal{D}'$ to obtain unimodal embeddings $e^{v'}$ and $e^{t'}$. The unimodal embeddings are projected to a shared semantic space via a modality-specific multilayer perceptron (MLP) to learn shared embeddings $e_s^{v'}$ and $e_s^{t'}$. Then, the shared embeddings are fed to an average pooling layer, followed by a full-connected layer as a binary classifier. We use the cosine embedding loss with margin d as supervision:

$$\mathcal{L}_{\text{REG}} = \begin{cases} 1 - \cos(e_s^{v'}, e_s^{t'}) & \text{if } y' = 1 \\ \max(0, \cos(e_s^{v'}, e_s^{t'}) - d) & \text{if } y' = 0 \end{cases} \quad (1)$$

where $\cos(\cdot)$ denotes the normalized cosine similarity and the margin d is set as 0.2 due to empirical studies. With the gradients from back-propagation, the cross-modal consistency learning task can automatically learn a shared semantic space between multimodal embeddings, which can help measure their semantic similarity. The task can be in parallel learned with the contrastive learning task.

Contrastive Learning

For a batch of N image-text pairs $\{(x_i^v, x_i^t)\}_{i=1}^N$, where i indicates the i_{th} pair, the normalized embedded vectors $\{e_i^v, e_i^t\}_{i=1}^N$ of the same dimension are obtained by the modal-specific encoders. Similar to CLIP [Radford *et al.*, 2021], the contrastive learning module is trained to predict which of the $N \times N$ possible image-text pairings across a batch actually occurred. Our contrastive losses, with the formulation of InfoNCE [Oord *et al.*, 2018], are designed to achieve the alignment between visual representation and textual representation. Specifically, for the i_{th} pair, the predicted vision-to-text similarity $p_i^{v \rightarrow t} = \{p_{ij}^{v \rightarrow t}\}_{j=1}^N$ and text-to-vision similarity




Figure 2: Model Architecture Overview of COOLANT. The model consists of three main modules: **(a) Cross-modal Contrastive Learning:** Given image-text pairs from the original dataset \mathcal{D} , we first extract unimodal features by the modal-specific encoder. Then we use the CLIP contrastive learning objective to ensure the alignment between image and text modalities. To further improve the alignment precision, we leverage an auxiliary cross-modal consistency learning task based on the dataset \mathcal{D}' to provide semantic similarity matrixes as soft targets for the contrastive learning task. **(b) Cross-modal Fusion:** We feed the aligned unimodal representations into the cross-modal fusion neural network to learn the cross-modality correlations. **(c) Cross-modal Aggregation:** We apply an attention mechanism module to reweight the aligned unimodal representations and the cross-modality correlations. A VAE-based model is proposed to learn the ambiguity of different modalities and guide the assignment of the attention mechanism module.

$p_i^{t \rightarrow v} = \{p_{ij}^{t \rightarrow v}\}_{j=1}^N$ can be calculated through:

$$\begin{aligned} p_{ij}^{v \rightarrow t} &= \frac{\exp(\text{sim}(e_i^v, e_j^t)/\tau)}{\sum_{j=1}^N \exp(\text{sim}(e_i^v, e_j^t)/\tau)} \\ p_{ij}^{t \rightarrow v} &= \frac{\exp(\text{sim}(e_i^t, e_j^v)/\tau)}{\sum_{j=1}^N \exp(\text{sim}(e_i^t, e_j^v)/\tau)} \end{aligned} \quad (2)$$

where τ is a learnable temperature parameter initialized with 0.07 and the function $\text{sim}(\cdot)$ conducts dot product to measure the similarity scores. The corresponding one-hot label vectors of the ground-truth $\mathbf{y}_i^{v \rightarrow t} = \{y_{ij}^{v \rightarrow t}\}_{j=1}^N$ and $\mathbf{y}_i^{t \rightarrow v} = \{y_{ij}^{t \rightarrow v}\}_{j=1}^N$, with positive pair denoted by 1 and negatives by 0, are used as the targets to calculate cross-entropy:

$$\mathcal{L}^{v \rightarrow t} = -\frac{1}{N} \sum_{i=1}^N \sum_{j=1}^N y_{ij}^{v \rightarrow t} \log p_{ij}^{v \rightarrow t} \quad (3)$$

Likewise, we can compute $\mathcal{L}^{t \rightarrow v}$ and then reach to:

$$\mathcal{L}_{NCE} = \frac{\mathcal{L}^{v \rightarrow t} + \mathcal{L}^{t \rightarrow v}}{2} \quad (4)$$

However, this kind of hard targets may not be entirely compatible with multimodal fake news detection. To further improve the alignment precision, we propose to build a more refined semantic level as soft targets to provide more accurate supervisions.

Build Target. Building upon the previous unimodal embeddings e^v and e^t , the consistency learning module can project them to shared embeddings e_s^v and e_s^t . For a batch of N image-text pairs, we propose to leverage shared embeddings $\{(e_s^v)_i, (e_s^t)_i\}_{i=1}^N$ to build the semantic similarity matrix as the soft targets. Take the semantic vision-to-text similarity

as an example. For the i_{th} pair, the semantic vision-to-text similarity $\mathbf{s}_i^{v \rightarrow t} = \{s_{ij}^{v \rightarrow t}\}_{j=1}^N$ can be calculated through:

$$s_{ij}^{v \rightarrow t} = \frac{\exp(\text{sim}((e_s^v)_i, (e_s^t)_j)/\tau)}{\sum_{j=1}^N \exp(\text{sim}((e_s^v)_i, (e_s^t)_j)/\tau)} \quad (5)$$

where τ is the temperature initialized at 0.07. Likewise, we can compute the semantic text-to-vision similarity $\mathbf{s}_i^{t \rightarrow v}$.

Semantic Matching Loss. The semantic similarity $\mathbf{s}_i^{v \rightarrow t}$ and $\mathbf{s}_i^{t \rightarrow v}$ are used as the soft targets to calculate semantic matching loss. The semantic matching loss is hence the cross entropy between the predicted similarity and soft targets as:

$$\mathcal{L}_{SEM} = -\frac{1}{2N} \sum_{i=1}^N \sum_{j=1}^N (s_{ij}^{v \rightarrow t} \log p_{ij}^{v \rightarrow t} + s_{ij}^{t \rightarrow v} \log p_{ij}^{t \rightarrow v}) \quad (6)$$

The final learning objective of the cross-modality contrastive Learning module is defined as:

$$\mathcal{L}_{CL} = \mathcal{L}_{NCE} + \lambda \mathcal{L}_{SEM} \quad (7)$$

where λ controls the contribution of the soft targets mechanism. We jointly train the cross-modality contrastive learning module to produce the semantically aligned unimodal representations m^v and m^t as the input of the cross-modal fusion module and the cross-modal aggregation module.

3.3 Cross-modal Fusion

In order to capture the semantic interactions between different modalities, we adopt the cross-modal fusion module to learn cross-modality correlations [Chen *et al.*, 2022]. Specifically, given the aligned unimodal representations m^v and m^t , we

first obtain the inter-modal attention weights by calculating the association between unimodal representations:

$$\begin{aligned} f_{t \rightarrow v} &= \text{softmax} \left([m^v] [m^t]^T / \sqrt{\dim} \right) \\ f_{v \rightarrow t} &= \text{softmax} \left([m^t] [m^v]^T / \sqrt{\dim} \right) \end{aligned} \quad (8)$$

where \dim denotes the dimension size of the unimodal representation. Then, we update the original unimodal embedding vectors by the inter-modal attention weights to obtain the explicit correlation features:

$$\begin{aligned} m_f^v &= f_{t \rightarrow v} \times m^v \\ m_f^t &= f_{v \rightarrow t} \times m^t \end{aligned} \quad (9)$$

Finally, we use an outer product between m_f^v and m_f^t to define their interaction matrix m^f :

$$m^f = m_f^v \otimes m_f^t \quad (10)$$

\otimes denotes outer product. The final correlation matrix m^f is flattened into a vector.

3.4 Cross-modal Aggregation

The input of the aggregation module is obtained by adaptively concatenating two sets of embeddings: the aligned unimodal representations m^v and m^t from the cross-modal contrastive learning module and the cross-modality correlations m^f from the cross-modal fusion module.

Attention Mechanism. Since not all modalities play an equal role in the decision-making process [Singhal *et al.*, 2022], we propose to apply an attention mechanism module to reweight these features before their aggregation. Inspired by the success of Squeeze-and-Excitation Network (SE-Net) [Hu *et al.*, 2018; Zhou *et al.*, 2022], we adopt an attention module to model modality-wise relationships and then weight each feature adaptively. Specifically, given these three $L \times 1$ features m^v , m^t and m^f , we first concatenate them into one $L \times 3$ feature, where L represents the length of the feature. We adopt global average pooling $F_{sq}(\cdot)$ to squeeze global modality information into a 1×3 vector. Then, we opt to employ a simple gating mechanism $F_{ex}(\cdot, W)$ with a sigmoid activation to fully capture modality-wise dependencies. The final output of the attention mechanism module is obtained by rescaling $F_{scale}(\cdot, \cdot)$ the $L \times 3$ feature, which will be used to obtain the attention weights $\mathbf{a} = \{a_v, a_t, a_f\}$. More details can refer to [Hu *et al.*, 2018].

Classifier. Given the unimodal representations, the cross-modality correlations and the attention weights, the final representation $\tilde{\mathbf{x}}$ can be calculated through:

$$\tilde{\mathbf{x}} = (a_v \times m^v) \oplus (a_t \times m^t) \oplus (a_f \times m^f) \quad (11)$$

where \oplus represents the concatenation operation. Then, we feed it into a fully-connected network to predict the label:

$$\hat{y} = \text{softmax}(MLP(\tilde{\mathbf{x}})) \quad (12)$$

Then we use the cross-entropy loss function as:

$$\mathcal{L}_{CLS} = -(y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})) \quad (13)$$

where y denotes the ground-truth label.

Attention Guidance. However, this kind of decision-making process is still at a black-box level, in which the network designs cannot explain why such weights are assigned to each modality. To make this process more interpretable, we utilize the Variational Autoencoder (VAE) [Khattar *et al.*, 2019] to model the latent variable and form the attention guidance module. Specifically, given the aligned unimodal features m^v and m^t , the variational posterior can be denoted as: $q(z | m) = \mathcal{N}(z | \mu(m), \sigma(m))$, in which the mean μ and variance σ can be obtained from the modal-specific encoder. Considering the distribution over the entire dataset:

$$\begin{aligned} q(z^v) &= \frac{1}{N} \sum_{i=1}^N q(z_i^v | m_i^v) \\ q(z^t) &= \frac{1}{N} \sum_{i=1}^N q(z_i^t | m_i^t) \end{aligned} \quad (14)$$

[Chen *et al.*, 2022] suggest when unimodal features present strong ambiguity, the fake news detector should pay more attention to cross-modal features, and vice versa, which is formulated as the cross-modal ambiguity learning problem. Following the definition of cross-modal ambiguity, we measure the ambiguity of different modalities in data sample \mathbf{x}_i by the averaged Kullback-Leibler (KL) divergence between the distributions of unimodal features:

$$g_i^{v \rightarrow t} = \left(\frac{D_{KL}(q(z_i^v | m_i^v) \| q(z_i^t | m_i^t))}{D_{KL}(q(z^v) \| q(z^t))} \right) \quad (15)$$

where $D_{KL}(\cdot \| \cdot)$ stands for the KL divergence. Likewise, we can compute $g_i^{t \rightarrow v}$ and then reach to:

$$g_i = \text{sigmoid}\left(\frac{1}{2}(g_i^{v \rightarrow t} + g_i^{t \rightarrow v})\right) \quad (16)$$

Then we can obtain the cross-modal ambiguity scores $\mathbf{g} = \{[1 - g_i, 1 - g_i]\}_{i=1}^N$. We develop another loss function \mathcal{L}_{AG} , which calculates the logarithmic difference between the attention weights $\mathbf{a} = \{a_v, a_t, a_f\}$ from the attention mechanism module and the ambiguity scores \mathbf{g} :

$$\mathcal{L}_{AG} = D_{KL}(\mathbf{a} \| \mathbf{g}) \quad (17)$$

By minimizing \mathcal{L}_{AG} , the attention mechanism module learns to assign reasonable attention scores to modalities which means that the module assigns each modality based on the ambiguity of different modalities.

The final learning objective of the cross-modality aggregation module is defined as:

$$\mathcal{L}_{CA} = \mathcal{L}_{CLS} + \gamma \mathcal{L}_{AG} \quad (18)$$

where γ controls the the ratio of \mathcal{L}_{AG} . We jointly train the cross-modality aggregation module to assign reasonable attention scores for each modality, and effectively leverage information from all modalities to boost the performance of multimodal fake news detection.

The final loss function for COOLANT is defined as the combination of the consistency learning loss in Eq. 1, the contrastive learning loss in Eq. 7 and the cross-modal aggregation learning loss in Eq. 18:

$$\mathcal{L} = \mathcal{L}_{REG} + \mathcal{L}_{CL} + \mathcal{L}_{CA} \quad (19)$$

	Method	Accuracy	Fake News			Real News		
			Precision	Recall	F1-score	Precision	Recall	F1-score
Twitter	EANN	0.648	0.810	0.498	0.617	0.584	0.759	0.660
	MVAE	0.745	0.801	0.719	0.758	0.689	0.777	0.730
	MKEMN	0.715	0.814	0.756	0.708	0.634	0.774	0.660
	SAFE	0.762	0.831	0.724	0.774	0.695	0.811	0.748
	MCNN	0.784	0.778	0.781	0.779	0.790	0.787	0.788
	MCAN	0.809	0.889	0.765	0.822	0.732	0.871	0.795
	CAFE	0.806	0.807	0.799	0.803	0.805	0.813	0.809
	LIIMR	0.831	0.836	0.832	0.830	-	-	-
	COOLANT	0.900	0.879	0.922	0.900	0.923	0.880	0.901
Weibo	EANN	0.827	0.847	0.812	0.829	0.807	0.843	0.825
	MVAE	0.824	0.854	0.769	0.809	0.802	0.875	0.837
	MKEMN	0.814	0.823	0.799	0.812	0.723	0.819	0.798
	SAFE	0.816	0.818	0.815	0.817	0.816	0.818	0.817
	MCNN	0.823	0.858	0.801	0.828	0.787	0.848	0.816
	MCAN	0.899	0.913	0.889	0.901	0.884	0.909	0.897
	CAFE	0.840	0.855	0.830	0.842	0.825	0.851	0.837
	LIIMR	0.900	0.882	0.823	0.847	-	-	-
	FND-CLIP	0.907	0.914	0.901	0.908	0.914	0.901	0.907
	CMC	0.908	0.940	0.869	0.899	0.876	0.945	0.907
	COOLANT	0.923	0.927	0.923	0.925	0.919	0.922	0.920

Table 1: Performance comparison between COOLANT and other methods on Twitter and Weibo datasets. Our method achieves the highest Accuracy among these methods, and its Precision, Recall, and F1-score also exceed most of the compared methods.

4 Experiments

4.1 Experimental Configurations

Datasets. Our model is evaluated on two real-world datasets: Twitter [Boididou *et al.*, 2018] and Weibo [Jin *et al.*, 2017]. The Twitter dataset was released for Verifying Multimedia Use task at MediaEval. In experiments, we keep the same data split scheme as the benchmark [Boididou *et al.*, 2018; Chen *et al.*, 2022]. The training set contains 6, 840 real tweets and 5, 007 fake tweets, and the test set contains 1, 406 posts. The Weibo dataset collected by [Jin *et al.*, 2017] contains 3749 fake news and 3783 real news for training, 1000 fake news and 996 real news for testing. In experiments, we follow the same steps in the work [Jin *et al.*, 2017; Wang *et al.*, 2018] to remove the duplicated and low-quality images to ensure the quality of the entire dataset.

Baseline. We compared our proposed COOLANT model with the following strong baselines:

- **EANN** [Wang *et al.*, 2018], which is a GAN-based model that aims to remove the event-specific features.
- **MVAE** [Khattar *et al.*, 2019], which uses a variational autoencoder coupled with a binary classifier to learn shared representations of text and image.
- **MKEMN** [Zhang *et al.*, 2019], which exploits the external knowledge-level connections to detect fake news.
- **SAFE** [Zhou *et al.*, 2020], which measures cross-modal similarity for fake news detection.
- **MCNN** [Xue *et al.*, 2021], which incorporates textual features, visual tampering features and cross-modal similarity in fake news detection.

- **MCAN** [Wu *et al.*, 2021], which stacks multiple co-attention layers to fuse the multimodal features.
- **CAFE** [Chen *et al.*, 2022], which measures cross-modal ambiguity to help adaptively aggregate unimodal features and cross-modal correlations.
- **LIIMR** [Singhal *et al.*, 2022], which leverages intra and inter modality relationships for fake news detection.
- **FND-CLIP** [Zhou *et al.*, 2022], which uses two pre-trained CLIP encoders to extract the deep representations from the image and text.
- **CMC** [Wei *et al.*, 2022], which transfers cross-modal correlation by a novel distillation method.

Implementation Details. The evaluation metrics include Accuracy, Precision, Recall, and F1-score. We use the batch size of 64 and train the model using Adam [Kingma and Ba, 2014] with an initial learning rate of 0.001 for 50 epochs with early stopping. The λ in the contrastive learning loss (Eq. 7) and the γ in the cross-modal aggregation learning loss (Eq. 18) are set to 0.2 and 0.5, respectively. All codes are implemented with PyTorch [Paszke *et al.*, 2019] and run on NVIDIA RTX TITAN.

4.2 Overall Performance

Table 1 presents the performance comparison between COOLANT and other methods on Twitter and Weibo datasets. As shown in the table, COOLANT significantly outperforms all the compared methods on every dataset in terms of *Acc* and *F1-score*, which demonstrates the effectiveness of our proposed model. Specifically, COOLANT obtains a new

	Method	Accuracy	F1 score	
			Fake News	Real News
Twitter	COOLANT	0.900	0.900	0.901
	- w/o SEM	0.883	0.883	0.884
	- w/o NCE	0.871	0.864	0.878
	- w/o CMF	0.878	0.872	0.884
	- w/o ATT	0.875	0.862	0.886
	- w/o AGU	0.894	0.885	0.901
Weibo	COOLANT	0.923	0.925	0.920
	- w/o SEM	0.912	0.912	0.911
	- w/o NCE	0.896	0.895	0.896
	- w/o CMF	0.909	0.912	0.907
	- w/o ATT	0.904	0.903	0.904
	- w/o AGU	0.906	0.907	0.906

Table 2: Ablation study on the architecture design of COOLANT on two datasets.

state-of-the-art with an accuracy of **90.0%** on Twitter dataset, achieving significant improvements with **6.9%**. COOLANT also reaches an accuracy of **92.3%**, achieving a new state-of-the-art on Weibo dataset, which is **1.5%** higher than the previous best one.

Note that FND-CLIP [Zhou *et al.*, 2022] and CMC [Wei *et al.*, 2022] are not evaluated on Twitter dataset. Since many tweets on Twitter dataset are related to a single event, which can easily lead to model overfitting. In contrast, our model can deal with this situation more effectively by the cross-modal contrastive learning module. Specifically, the contrastive learning task can help to distinguish each news item, even if they belong to the same event. Besides, the consistency learning task can derive event-invariant features to soften the target and thus benefit the detection of fake news on newly arrived events. Therefore, COOLANT can provide more sophisticated aligned unimodal representations to boost the performance of multimodal fake news detection, which also makes our approach more generalizable.

4.3 Ablation Studies

Quantitative Analysis. To evaluate the effectiveness of each component of the proposed COOLANT, we remove each one from the entire model for comparison. More specifically, the compared variants of COOLANT are implemented as follows: **1) w/o SEM:** we remove the consistency learning task and only use hard targets for the contrastive learning task to learn the aligned unimodal representations; **2) w/o NCE:** we remove the contrastive learning task and use the consistency learning task to learn the aligned unimodal representations; **3) w/o CMF:** we remove the cross-modal fusion module and replace it with simply concatenating m^v and m^t ; **4) w/o ATT:** we remove the attention mechanism module and direct aggregate the three features to obtain final feature; **5) w/o AGU:** we remove the attention guidance module.

Table 2 shows the results of ablation studies. We can find that all variants perform worse than the original COOLANT, which demonstrates the effectiveness of each component. Besides, we have the following observations: 1) COOLANT w/o NCE yields the worst performance, proving that acquiring more sophisticated aligned unimodal features is a pre-




Figure 3: T-SNE visualizations of the features before classifier that are learned by COOLANT and its five variants on the test dataset of Weibo. Dots with the same color are within the same label.

requisite for effective detection and cross-modal contrastive learning is a powerful paradigm for multimodal representation learning. 2) The performance of COOLANT w/o SEM on Twitter dataset drops more noticeably than on Weibo dataset, which verifies that soft targets can help the model to maintain the event-invariant features and detect news related to the same event more effectively.

Qualitative Analysis. Moreover, we further analyze the proposed method using t-SNE [Van der Maaten and Hinton, 2008] visualizations of the features before classifier in Figure 3, which are learned by COOLANT and its five variants on the test dataset of Weibo.

From Figure 3, we can observe that the boundary of different label dots in COOLANT is more pronounced than that in its variants, revealing that the extracted features in COOLANT are more discriminative. Note that, as shown in Figure 3(c), many features learned by COOLANT w/o NCE are still easily misclassified, which indicates that the contrastive learning task can obtain the characteristics of multiple modalities deeply and boost to distinguish fake news and real news. In addition, by comparing Figure 3(a), Figure 3(e) and Figure 3(f), we can see that effective and appropriate aggregation of features from different modalities can significantly improve the representation ability of the final features.

5 Conclusion

In this paper, we propose COOLANT, a novel cross-modal contrastive learning framework for multimodal fake news detection, which uses the CLIP contrastive learning objective to achieve more accurate image-text alignment. To further improve the alignment precision, we leverage an auxiliary task to soften the loss term of negative samples during the contrast process. After that, we feed the aligned unimodal representations into a cross-modal fusion module to learn the cross-modality correlations. An attention mechanism with an attention guidance module is implemented to help effectively and interpretably aggregate features from different modalities. Experimental results on two datasets Twitter and Weibo demonstrate that COOLANT outperforms previous approaches by a large margin and achieves new state-of-the-art results on the two datasets.

References

- [Bhattarai *et al.*, 2021] Bimal Bhattarai, Ole-Christoffer Granmo, and Lei Jiao. Explainable tsetlin machine framework for fake news detection with credibility score assessment. *arXiv preprint arXiv:2105.09114*, 2021.
- [Boididou *et al.*, 2018] Christina Boididou, Symeon Papadopoulos, Markos Zampoglou, Lazaros Apostolidis, Olga Papadopoulou, and Yiannis Kompatsiaris. Detection and visualization of misleading content on twitter. *International Journal of Multimedia Information Retrieval*, 7(1):71–86, 2018.
- [Chen *et al.*, 2021] Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9640–9649, 2021.
- [Chen *et al.*, 2022] Yixuan Chen, Dongsheng Li, Peng Zhang, Jie Sui, Qin Lv, Lu Tun, and Li Shang. Cross-modal ambiguity learning for multimodal fake news detection. In *Proceedings of the ACM Web Conference 2022*, pages 2897–2905, 2022.
- [Conroy *et al.*, 2015] Nadia K Conroy, Victoria L Rubin, and Yimin Chen. Automatic deception detection: Methods for finding fake news. *Proceedings of the association for information science and technology*, 52(1):1–4, 2015.
- [Devlin *et al.*, 2018] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- [Gao *et al.*, 2021] Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021.
- [Gao *et al.*, 2022] Yuting Gao, Jinfeng Liu, Zihan Xu, Jun Zhang, Ke Li, and Chunhua Shen. Pyramidclip: Hierarchical feature alignment for vision-language model pre-training. *arXiv preprint arXiv:2204.14095*, 2022.
- [Guo *et al.*, 2018] Han Guo, Juan Cao, Yazhi Zhang, Junbo Guo, and Jintao Li. Rumor detection with hierarchical social attention network. In *Proceedings of the 27th ACM international conference on information and knowledge management*, pages 943–951, 2018.
- [He *et al.*, 2016] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.
- [He *et al.*, 2020] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9729–9738, 2020.
- [Hu *et al.*, 2018] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7132–7141, 2018.
- [Huo *et al.*, 2021] Yuqi Huo, Manli Zhang, Guangzhen Liu, Haoyu Lu, Yizhao Gao, Guoxing Yang, Jingyuan Wen, Heng Zhang, Baogui Xu, Weihao Zheng, et al. Wenlan: Bridging vision and language by large-scale multi-modal pre-training. *arXiv preprint arXiv:2103.06561*, 2021.
- [Jin *et al.*, 2016] Zhiwei Jin, Juan Cao, Yongdong Zhang, Jianshe Zhou, and Qi Tian. Novel visual and statistical image features for microblogs news verification. *IEEE transactions on multimedia*, 19(3):598–608, 2016.
- [Jin *et al.*, 2017] Zhiwei Jin, Juan Cao, Han Guo, Yongdong Zhang, and Jiebo Luo. Multimodal fusion with recurrent neural networks for rumor detection on microblogs. In *Proceedings of the 25th ACM international conference on Multimedia*, pages 795–816, 2017.
- [Khattar *et al.*, 2019] Dhruv Khattar, Jaipal Singh Goud, Manish Gupta, and Vasudeva Varma. Mvae: Multimodal variational autoencoder for fake news detection. In *The world wide web conference*, pages 2915–2921, 2019.
- [Kingma and Ba, 2014] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.
- [Liu *et al.*, 2015] Xiaomo Liu, Armineh Nourbakhsh, Quanzhi Li, Rui Fang, and Sameena Shah. Real-time rumor debunking on twitter. In *Proceedings of the 24th ACM international on conference on information and knowledge management*, pages 1867–1870, 2015.
- [Oord *et al.*, 2018] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.
- [Paszke *et al.*, 2019] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.
- [Potthast *et al.*, 2017] Martin Potthast, Johannes Kiesel, Kevin Reinartz, Janek Bevendorff, and Benno Stein. A stylistometric inquiry into hyperpartisan and fake news. *arXiv preprint arXiv:1702.05638*, 2017.
- [Qi *et al.*, 2019] Peng Qi, Juan Cao, Tianyun Yang, Junbo Guo, and Jintao Li. Exploiting multi-domain visual information for fake news detection. In *2019 IEEE international conference on data mining (ICDM)*, pages 518–527. IEEE, 2019.
- [Qian *et al.*, 2018] Feng Qian, Chengyue Gong, Karishma Sharma, and Yan Liu. Neural user response generator: Fake news detection with collective user intelligence. In *IJCAI*, volume 18, pages 3834–3840, 2018.
- [Radford *et al.*, 2021] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

- [Singhal *et al.*, 2022] Shivangi Singhal, Tanisha Pandey, Saksham Mrig, Rajiv Ratn Shah, and Ponnurangam Kumaraguru. Leveraging intra and inter modality relationship for multimodal fake news detection. In *Companion Proceedings of the Web Conference 2022*, pages 726–734, 2022.
- [Van der Maaten and Hinton, 2008] Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.
- [Wang *et al.*, 2018] Yaqing Wang, Fenglong Ma, Zhiwei Jin, Ye Yuan, Guangxu Xun, Kishlay Jha, Lu Su, and Jing Gao. Eann: Event adversarial neural networks for multimodal fake news detection. In *Proceedings of the 24th acm sigkdd international conference on knowledge discovery & data mining*, pages 849–857, 2018.
- [Wei *et al.*, 2022] Zimian Wei, Hengyue Pan, Linbo Qiao, Xin Niu, Peijie Dong, and Dongsheng Li. Cross-modal knowledge distillation in multi-modal fake news detection. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 4733–4737. IEEE, 2022.
- [Wu *et al.*, 2021] Yang Wu, Pengwei Zhan, Yunjian Zhang, Liming Wang, and Zhen Xu. Multimodal fusion with co-attention networks for fake news detection. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 2560–2569, 2021.
- [Xue *et al.*, 2021] Junxiao Xue, Yabo Wang, Yichen Tian, Yafei Li, Lei Shi, and Lin Wei. Detecting fake news by exploring the consistency of multimodal data. *Information Processing & Management*, 58(5):102610, 2021.
- [Yan *et al.*, 2021] Yuanmeng Yan, Rumei Li, Sirui Wang, Fuzheng Zhang, Wei Wu, and Weiran Xu. Consert: A contrastive framework for self-supervised sentence representation transfer. *arXiv preprint arXiv:2105.11741*, 2021.
- [Yu *et al.*, 2017] Feng Yu, Qiang Liu, Shu Wu, Liang Wang, Tieniu Tan, et al. A convolutional approach for misinformation identification. In *IJCAI*, pages 3901–3907, 2017.
- [Zhang *et al.*, 2019] Huaiwen Zhang, Quan Fang, Shengsheng Qian, and Changsheng Xu. Multi-modal knowledge-aware event memory network for social media rumor detection. In *Proceedings of the 27th ACM international conference on multimedia*, pages 1942–1951, 2019.
- [Zhou *et al.*, 2020] Xinyi Zhou, Jindi Wu, and Reza Zafarani. Safe: Similarity-aware multi-modal fake news detection. In *Pacific-Asia Conference on Knowledge Discovery and Data Mining*, pages 354–367. Springer, 2020.
- [Zhou *et al.*, 2022] Yangming Zhou, Qichao Ying, Zhenxing Qian, Sheng Li, and Xinpeng Zhang. Multimodal fake news detection via clip-guided learning. *arXiv preprint arXiv:2205.14304*, 2022.
- [Zubiaga *et al.*, 2018] Arkaitz Zubiaga, Ahmet Aker, Kalina Bontcheva, Maria Liakata, and Rob Procter. Detection and resolution of rumours in social media: A survey. *ACM Computing Surveys (CSUR)*, 51(2):1–36, 2018.