

Arkvolt Series Products

Arkvolt Cells Powered by HiTHIUM 2025 Global Shipment of Energy Storage Batteries TOP 2.

Product Name	Diagram	Battery capacity	Cell Capacity	Rated Voltage	Net weight	Brochure	User Manual
HSM-8K16HV-2M		16076.8Wh	314Ah	576[VDC]	176kg	↓ 	↓ 

Product Features

- Opeation Voltage Range：481.6~657.0[VDC]

· Cycle Life：≥8000 cycles, @25°C, @0.5C, @90%DOD, @70%EOL

· Certifications：CE, IEC62619, IEC62040, UN38.3, MSDS, RoHS, REACH
- Maximum Charge/Discharge Current: 12.5A/12.5A

· Rating：IP65

· Dimensions：L597*W263*H1124mm



[Brochure Download](#) [User Manual Download](#)

HPB-16LV		16076.8Wh	314Ah	51.2[VDC]	123kg	↓ 	↓ 
HPB-16LV-S		16076.8Wh	314Ah	51.2[VDC]	137.5kg	↓ 	↓ 
HPC-30LV-22U		30054.4Wh	587Ah	51.2[VDC]	350kg	↓ 	↓ 
HPC-30LV-44U		30054.4Wh	587Ah	51.2[VDC]	600kg	↓ 	↓ 

Sign up for our newsletter

Get the latest updates and insights delivered to your inbox.

Send



Company

- About Us
- Contact Us
- Latest News
- Cooperation

Solution

- Residential ESS Solutions
- C&I ESS Solutions

Products

- HPB-16LV
- HPB-16LV-S
- HiTHIUM DC-Boost HV Series
- HPC-30LV-22U
- HPC-30LV-44U

Service

- After-Sales Service
- Manual Download
- Privacy Policy
- User Agreement