

Procédure du Mutlab

1 Initialisation

1.1 Réinitialisation du CBS 350 grâce à l'adresse IP par défaut

=> 192.168.1.254

username = cisco

password = cisco

2 Paramétrage de base

2.1 Définir le nom d'hôte => Mutlab1 / Mutlab2

2.2 Définir un mot de passe => mu55lab1 / mu55lab2

2.3 Définir la passerelle par défaut dans le Vlan 10 (système, réseau) pour pouvoir se connecter à l'interface web => 192.168.10.254 (mutlab1) => 192.168.10.253 (mutlab2)

Les ports 15 et 16 sont en mode trunk

Dans VLAN Management

Interface Settings

3 Vlan + @ IP

3.1 Création des Vlans :

Vlan 10 => reseau_systeme

@ IP 192.168.10.254 255.255.255.0 (Mutlab1)

192.168.10.253 255.255.255.0 (Mutlab2)

Vlan 20 => direction_dsi

@ IP 192.168.20.254 255.255.255.0

192.168.20.253 255.255.255.0

Vlan 30 => administratif

@ IP 192.168.30.254 255.255.255.0

192.168.30.253 255.255.255.0

Vlan 60 => commercial

@ IP 192.168.60.254 255.255.255.0

192.168.60.253 255.255.255.0

Vlan 300 => serveurs

@ IP 172.16.127.254 255.255.128.0

172.16.127.254 255.255.128.0

Ces interfaces permettent d'assurer le rouage inter-Vlan

☐	1		Default	Enabled	Enabled
☐	10	reseau_systeme	Static	Enabled	Enabled
☐	20	direction_dsi	Static	Enabled	Enabled
☐	30	administratif	Static	Enabled	Enabled
☐	60	commercial	Static	Enabled	Enabled
☐	300	serveurs	Static	Enabled	Enabled

Adresser des ports au Vlan 10 et 300 UNIQUEMENT

Pour le Vlan 10 :

Filter: *VLAN ID* equals to

AND *Interface Type* equals to

Interface Name	VLAN Mode	Membership Type	PVID
GE1	Access	Excluded	☐
GE2	Access	Untagged	☒
GE3	Access	Untagged	☒
GE4	Access	Untagged	☒
GE5	Access	Untagged	☒
GE6	Access	Untagged	☒

Pour le vlan 300 :

Filter: *VLAN ID* equals to 300 ▾

AND *Interface Type* equals to Port ▾

Go

Interface Name	VLAN Mode	Membership Type	PVID
GE1	Access	Excluded ▾	☐
GE2	Access	Excluded ▾	☐
GE3	Access	Excluded ▾	☐
GE4	Access	Excluded ▾	☐
GE5	Access	Excluded ▾	☐
GE6	Access	Excluded ▾	☐
GE7	Access	Excluded ▾	☐
GE8	Access	Excluded ▾	☐
GE9	Access	Untagged ▾	☒
GE10	Access	Untagged ▾	☒
GE11	Access	Untagged ▾	☒
GE12	Access	Untagged ▾	☒

4 ACL

Creer les acl dans IPv4-Based ACL

IPv4-Based ACL Table

+

☐

ACL Name

☐

acl10

☐

acl20

☐

acl30

☐

acl60

☐

acl500

☐

acl300

Pour le Vlan 10

Filter: *ACL Name* equals to acl10 v

Go

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Deny	Enabled	Any (IP)	192.168.10.0	0.0.0.255	192.168.20.0	0.0.0.255
☐	20	Deny	Enabled	Any (IP)	192.168.10.0	0.0.0.255	192.168.30.0	0.0.0.255
☐	30	Deny	Enabled	Any (IP)	192.168.10.0	0.0.0.255	192.168.60.0	0.0.0.255
☐	100	Permit	Enabled	Any (IP)	192.168.10.0	0.0.0.255	Any	Any

Pour le Vlan 20

Filter: *ACL Name* equals to

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Deny	Enabled	Any (IP)	192.168.20.0	0.0.0.255	192.168.10.0	0.0.0.255
☐	20	Deny	Enabled	Any (IP)	192.168.20.0	0.0.0.255	192.168.30.0	0.0.0.255
☐	30	Deny	Enabled	Any (IP)	192.168.20.0	0.0.0.255	192.168.60.0	0.0.0.255
☐	40	Permit	Enabled	Any (IP)	192.168.20.0	0.0.0.255	172.16.0.0	0.0.127.255

Pour le Vlan 30

Filter: *ACL Name* equals to

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Deny	Enabled	Any (IP)	192.168.30.0	0.0.0.255	192.168.10.0	0.0.0.255
☐	20	Deny	Enabled	Any (IP)	192.168.30.0	0.0.0.255	192.168.20.0	0.0.0.255
☐	30	Deny	Enabled	Any (IP)	192.168.30.0	0.0.0.255	192.168.60.0	0.0.0.255
☐	40	Permit	Enabled	Any (IP)	192.168.30.0	0.0.0.255	172.16.0.0	0.0.127.255

Pour le Vlan 60

Filter: *ACL Name* equals to

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Deny	Enabled	Any (IP)	192.168.60.0	0.0.0.255	192.168.10.0	0.0.0.255
☐	20	Deny	Enabled	Any (IP)	192.168.60.0	0.0.0.255	192.168.20.0	0.0.0.255
☐	30	Deny	Enabled	Any (IP)	192.168.60.0	0.0.0.255	192.168.30.0	0.0.0.255
☐	40	Permit	Enabled	Any (IP)	192.168.60.0	0.0.0.255	172.16.0.0	0.0.127.255

Pour le Vlan 300

Filter: *ACL Name* equals to

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Permit	Enabled	Any (IP)	Any	Any	Any	Any

Pour le Vlan 500

Filter: *ACL Name* equals to

☐	Priority	Action	Logging	Protocol	Source IP Address		Destination IP Address	
					IP Address	Wildcard Mask	IP Address	Wildcard Mask
☐	10	Permit	Disabled	Any (IP)	Any	Any	Any	Any

5 Configuration de l'interface GE1

IPv4 Interface Table



☐	Interface	IP Address Type	IP Address	Mask	Status
☐	VLAN 1	DHCP	0.0.0.0	255.255.255.255	Not received
☐	VLAN 300	Static	172.16.127.253	255.255.128.0	Valid
☐	GE1	Static	172.18.0.4	255.255.255.248	Valid
☐	VLAN 10	Static	192.168.10.253	255.255.255.0	Valid
☐	VLAN 20	Static	192.168.20.253	255.255.255.0	Valid
☐	VLAN 30	Static	192.168.30.253	255.255.255.0	Valid
☐	VLAN 60	Static	192.168.60.253	255.255.255.0	Valid

Route static pour permettre à n'importe quel hôte de passer par l'interface du Rtrout (2960)

IPv4 Static Routes Table						
  						
☐	Destination IP Prefix	Prefix Length	Route Type	Next Hop Router IP Address	Metric	Outgoing Interface
☐	0.0.0.0	0	Remote	172.18.0.2	4	GE1

Sur Rtrout

Creation de route static pour permettre a tout les hôtes de chaques Vlans a sortir par le vlan de sortie

```
R1(config)#ip rout
R1(config)#ip route
R1(config)#ip route 192.168.10.0 255.255.255.0 172.18.0.3
R1(config)#ip route 192.168.20.0 255.255.255.0 172.18.0.3
R1(config)#ip route 192.168.30.0 255.255.255.0 172.18.0.3
R1(config)#ip route 192.168.60.0 255.255.255.0 172.18.0.3
R1(config)#ip route 172.16.0.0 255.255.128.0 172.18.0.3
R1(config)#
```