
# Simulating Ultra narrowband Metasurface

Yankun (Alex) Meng




In this simulation of Paper Link, I did 1200–1600nm parameter sweep, and linear polarization. Finding the transmittance of this structure.




**Fig. 1.** Concept of high-Q phase-gradient metasurfaces. (*A*) Schematic picture of the Si metasurface. *Insets* show a single cell with detailed structural parameters. (*B*) and (*C*) show the dependence of resonant wavelength and Q factor of BIC mode on the radius of an air hole. (*D*) Resonant wavelength (*Top*) and FWHM (*Bottom*) of quasi-BIC mode as a function of rotational angle  $\theta$ . Here, the size of the air hole is fixed at r = 30 nm. *Insets* show the numerically calculated distributions of power (*Top*) and electric field (*Bottom*). (*E*) Acquired geometric phase  $\phi_{PB}$  (dots) as a function of rotational angle  $\theta$ . The solid line represents the curve of  $\phi_{PB} = 2\theta$ . (*f*) Dependence of Q factors of supercells containing N phase steps of our metasurface (dots) and conventional nonlocal metasurface (open squares). Here, the position parameter  $\rho$  is fixed at  $\rho = 80$  nm. The *Inset* shows the schematic of a conventional nonlocal metasurface structure.

Figure from paper


















# Circular Polarization






# Circular Zoomed in





# LCP / (LCP + RCP)





#### Preconditions

```
1 # Import the necessary packages
2 import matplotlib.pyplot as plt
3 import numpy as np
4 import tidy3d as td
5 import tidy3d.web as web
6 from tidy3d import material library
  import scienceplots
9 td.config.logging level = "ERROR"
1 # 0 Define a FreqRange object with desired wavelengths
2 fr = td.FreqRange.from wvl interval(wvl min=1.2, wvl max=1.6)
3 N = 501 # num points
4 fwidth = fr.fmax - fr.fmin
5 freq0 = fr.freq0
6 lda0 = td.C 0 / fr.freq0
1 # 1 Computational Domain Size
2 h = 0.210 # Height of cylinder
3 \text{ spc} = 8
4 sh = 3 # height of the SiO2
5 Lz = spc + h + spc + h
7 Px = Py = P = 0.750 \# periodicity
8 \text{ sim size} = [Px, Py, Lz]
```

```
1 # 2 Grid Resolution
2 dl = P / 32
3 horizontal grid = td.UniformGrid(dl=dl)
4 vertical_grid = td.AutoGrid(min_steps_per_wvl=32)
 5 grid_spec=td.GridSpec(
       grid_x=horizontal_grid,
       grid y=horizontal grid,
       grid_z=vertical_grid,
 9 )
 1 # 3 Structures and Materials
2 R = 0.235 # radius of the cylinder
3 r = 0.030 \# radius of the inner hole
4 p = 0.080 # distance between hole to center of circle
5 theta = np.deg2rad(90) # angle between x-axis and p vector
 7 Si = material library['cSi']['Green2008']
8 SiO2 = material library['SiO2']['Horiba']
9
10 outer cylinder = td.Cylinder(
       center=[0, 0, h / 2],
    radius=R,
       length=h,
14
       axis=2
15 )
16
17 inner_cylinder = td.Cylinder(
       center=[p*np.cos(theta), -p*np.sin(theta), h / 2],
18
       radius=r,
19
       length=h,
20
```

```
1 source = td.PlaneWave(
      source_time=td.GaussianPulse(freq0=fr.freq0, fwidth=fwidth),
      size=(td.inf, td.inf, 0),
      center=(0, 0, -Lz/2 + spc - (sh - h) - 0.5 * lda0),
      direction="+",
6
      pol_angle=0,
7)
1 monitor = td.FluxMonitor(
      center=(0, 0, Lz/2 - spc + 1.5 * lda0),
3
      size=(td.inf, td.inf, 0),
      freqs=fr.freqs(N),
      name="flux_monitor"
5
6)
```

```
bandwidth = fr.fmax - fr.fmin
run_time = 500 / bandwidth # run_time for the transmittance simulation

bc = td.BoundarySpec(
    x=td.Boundary.periodic(),
    y=td.Boundary.periodic(),
    z=td.Boundary.pml()

)
```


# Simulation

```
sim_empty = td.Simulation(
       size=sim size,
       grid_spec=grid_spec,
       structures=[substrate, dioxide],
       sources=[source],
       monitors=[monitor],
       run_time=run_time,
       boundary_spec=bc
 8
 9 )
10
   sim_actual = td.Simulation(
       size=sim_size,
12
       grid_spec=grid_spec,
13
       structures=[substrate, dioxide, atom],
14
       sources=[source],
15
       monitors=[monitor],
16
       run_time=run_time,
17
       boundary_spec=bc
18
19 )
1 sims = {
       "actual": sim_actual,
       "norm": sim_empty
 4 }
 1 sims["actual"].plot_3d()
```

### Postprocess

```
1 T_actual = batch_data["actual"]["flux_monitor"].flux
2 T_norm = batch_data["norm"]["flux_monitor"].flux

1 # this uses scienceplots to make plots look better
2 plt.style.use(['science', 'notebook', 'grid'])
3 # plot transmission, compare to paper results, look similar
4 fig, ax = plt.subplots(1, 1, figsize=(6, 4.5))
5 plt.plot(td.C_0 / fr.freqs(N) * 1000, T_actual, "r", lw=1, label="T with Metaatom")
6 plt.plot(td.C_0 / fr.freqs(N) * 1000, T_norm, "b", lw=0.5, alpha=0.5, label="T w/o Metaa plt.xlabel(r"wavelength ($nm$)")
8 plt.ylabel("Transmittance")
9 plt.legend()
10 plt.title("Transmittance vs Wavelength")
11 plt.savefig("power_geom", dpi=300)
12 plt.show()
```



#### Circular Polarization

```
def circular_polarized_plane_wave(pol):
       # define a plane wave polarized in the x direction
       plane wave x = td.PlaneWave(
            source_time=td.GaussianPulse(freq0=fr.freq0, fwidth=fwidth),
            size=(td.inf, td.inf, 0),
            center=(0, 0, -Lz/2 + spc - (sh - h) - 0.5 * lda0),
            direction="+",
            pol angle=0,
 8
10
       # determine the phase difference given the polarization
11
       if pol = "left":
12
            phase = -np.pi / 2
13
       elif pol = "right":
14
15
            phase = np.pi / 2
       else:
16
           raise ValueError("pol must be `left` or `right`")
17
18
       # define a plane wave polarized in the y direction with a phase difference
19
20
       plane wave y = td.PlaneWave(
            source_time=td.GaussianPulse(freq0=freq0, fwidth=fwidth, phase=phase),
21
            size=(td.inf, td.inf, 0),
22
            center=(0, 0, -Lz/2 + spc - (sh - h) - 0.5 * lda0),
23
24
            direction="+",
25
            pol_angle=np.pi / 2,
26
```