# Learning Numpy

Yankun (Alex) Meng



### **Lecture Outline**

- Introduction and Basics
- Array Manipulation
- Calculus / Statistical Functions

# What is NumPy?

NumPy is a package for dealing with arrays that's very fast and efficient.

#### Creating array:

```
1 arr1 = np.array([3, 5, 7, 3]) # convert list to array
2 arr2 = np.zeros(10) # array with 10 zeroes
3 arr3 = np.ones(10) # array with 10 ones
4 arrR = np.random.random(10) # sample 10 numbers from uniform distribution
5 arrG = np.random.randn(10) # sample 10 numbers from normal distribution
```



### Two most common functions

**linspace** - values equally spaced apart given the number of values

```
1 arr = np.linspace(0, 10, 100) # from 0 to 10, 100 values
```

arrange - values equally spaced apart given the spacing

```
1 arr = np.arrange(0, 10, 0.02) # from 0 to 10, spacing of 0.02
```



### **Lecture Outline**

- Introduction and Basics
- Array Manipulation
- Calculus / Statistical Functions

## Common Array Operation

#### **Element-wise operation**

```
1 arr + 2  # addition
2 arr - 5  # subtraction
3 2*arr  # multiplication
4 1/arr  # division
5 arr % 5  # Modulus
```

Let's try to do the same element-wise operation but using functions:

```
1 def f(x):
2    return x**2 * np.sin(x) / np.exp(-x)
3
4 x = np.linspace(0, 10, 100)
5 y = f(x) # Element-wise application of f
```



# Common Plotting

#### **Most basic Plotting**

```
1 x = np.linspace(0, 1, 100) # x-axis definition
2 y = x**2 # element-wise x^2
3 plt.plot(x, x**2) # plot(x, y)
4 plt.show() # show the output
```

#### Histogram

```
1 plt.hist(arr) # plotting the array as histogram
```



# Indexing and Slicing

#### **Normal Indexing**

```
1 arr = np.array([2, 4, 6, 8, 10])
2 arr[2] # return 6
3 arr[2:] # return 6, 8, 10 (including index 2)
4 arr[:-2] # return 2, 4, 6 (exluding index -2)
5 arr[1:2] # return 4
```

#### **Boolean Indexing**

```
1 arr > 5 # return a boolean array with true or false as elemenets
2 arr[arr>5] # filtering → return the elements that are true
```

#### **Using Boolean Indexing to filter data**

```
names = np.array(['Jim', 'Luke', 'Josh', 'Pete'])
first_letter_j = np.vectorize(lambda s: s[0])(names) = 'J'
print(names[first_letter_j]) # gets the names that have first letter as J
```

Now what is this doing?

# What is that doing?

```
1 first_letter_j = np.vectorize(lambda s: s[0])(names) = 'J'
```

#### **Lambda Function**

```
1 f = lambda s: s[0]
```

This is a function that says give me a string and I'll give you the first character of the string. Note that String is not an array in python, but it supports the same indexing operations as arrays.

#### What is np.vectorize?

It creates a for-loop, applies the function func to every element in the array arr, and return the result as an array.

```
1 np.vectorize(func)(arr) # this is an array
```



### **Lecture Outline**

- Introduction and Basics
- Array Manipulation
- Calculus / Statistical Functions

### Common Statistics Functions

```
1 arr = 2*np.random.randn(10000) + 10 # 2 times std dev with a shift of 10 to the right\
2 np.mean(arr) # approx 10
3 np.std(arr) # approx 2
4 np.percentile(arr, 80) # 80% numbers less than this number
```



# Integrals and Derivatives

```
1 x = np.linspace(1, 10, 100)
2 y = 1/x**2 + np.sin(x)
3 plt.plot(x, y)
```

#### **Derivatives**

```
1 dydx = np.gradient(y, x)
```

#### **Integrals**

```
1 np.cumsum([1, 2, 3, 4]) # return [1,3,6,10]
2 y_int = np.cumsum(y) * (x[1] - x[0]) # int y dx
```



### Resources Used

- [1] NumPy Tutorial
- [2] 100 numpy practice problems

