KRO-WTB04-20

Wire-to-board · 4 pos · 2.0 mm · 3 A

CATEGORY	PACKAGE	STATUS
Industrial Connectors	4P	In stock

SPECIFICATIONS

Pitch	2.0 mm
Positions	4 (1 × 4)
Current rating	3 A / contact
Voltage rating	125 V AC/DC
Wire range	AWG 26 - 22
Mating cycles	30
Contact plating	Sn over Ni
Operating temperature	-40 to +105 °C

KEY FEATURES

- 0.5 mm to 2.54 mm pitch fine-pitch designs
- Rated for 500 mating cycles minimum on board-to-board
- IP67 sealing when mated (circular series)
- Selective gold plating on contact areas

APPLICATIONS

- Automotive wiring harnesses
- Industrial automation and robotics
- Display and camera FPC routing
- Outdoor and harsh-environment equipment

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.