KRIC-RS485

Half-duplex transceiver · 20 Mbps · ±15 kV

CATEGORY	PACKAGE	STATUS
Semiconductors & Chips	SOP-8	Build to order

SPECIFICATIONS

Duplex mode	Half duplex
Data rate	20 Mbps
Supply voltage	3.0 - 3.6 V
Bus-pin protection	±15 kV ESD (HBM)
Bus load	up to 256 bus loads
Operating temperature	-40 to +125 °C
Packaging	Tape & reel · 2,500 pcs

KEY FEATURES

- Every wafer lot traceable to fab and assembly site
- 100% avalanche and final test on power devices
- Low RDS(on) trench and shield-gate processes
- Halogen-free, RoHS and REACH compliant

APPLICATIONS

- Power conversion and motor drives
- Portable device power management
- Industrial communication interfaces
- Automotive lighting and body control

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.