# KRC0805X5R106K16

X5R · 10 µF · 16 V · ±10%

| CATEGORY | PACKAGE | STATUS |
| --- | --- | --- |
| MLCC | 0805 | In stock |

## SPECIFICATIONS

| | |
| --- | --- |
| Dielectric | X5R |
| Capacitance | 10 µF |
| Rated voltage | 16 V |
| Tolerance | ±10% |
| Case size | 0805 (EIA) |
| Temperature characteristic | ±15% (-55 to +85 °C) |
| Operating temperature | -55 to +85 °C |
| Insulation resistance | >= 10 Gohm · 100 VDC, 60 s |
| Dissipation factor | <= 10% |
| Termination | Ni barrier / Sn plating |
| Packaging | Tape & reel · 3,000 pcs |

## KEY FEATURES

- Base-metal electrode construction with Ni/Sn plated terminals
- Low-ESL body design for high-frequency decoupling
- Class 1 (C0G) and Class 2 (X5R / X6S / X7R / X7S) dielectrics
- Reflow compatible, AEC-Q200 automotive grades available

## APPLICATIONS

- Power-rail decoupling
- DC-link and snubber circuits
- Automotive ECU and BMS
- Consumer and industrial electronics

**KRODOSEN Co., Ltd.** 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.