KRC0603X7S474K25

X7S · 470 nF · 25 V · ±10%

CATEGORY	PACKAGE	STATUS
MLCC	0603	In stock

SPECIFICATIONS

Dielectric	X7S
Capacitance	470 nF
Rated voltage	25 V
Tolerance	±10%
Case size	0603 (EIA)
Temperature characteristic	±22% (-55 to +125 °C)
Operating temperature	-55 to +125 °C
Insulation resistance	>= 10 Gohm · 100 VDC, 60 s
Dissipation factor	<= 5%
Termination	Ni barrier / Sn plating
Packaging	Tape & reel · 4,000 pcs

KEY FEATURES

- Base-metal electrode construction with Ni/Sn plated terminals
- Low-ESL body design for high-frequency decoupling
- Class 1 (C0G) and Class 2 (X5R / X6S / X7R / X7S) dielectrics
- Reflow compatible, AEC-Q200 automotive grades available

APPLICATIONS

- Power-rail decoupling
- DC-link and snubber circuits
- Automotive ECU and BMS
- Consumer and industrial electronics

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.