KRD-SS34

Schottky · 40 V · 3 A · 0.45 V

CATEGORY	PACKAGE	STATUS
Semiconductors & Chips	SMA	In stock

SPECIFICATIONS

Repetitive peak reverse voltage	40 V
Average forward current	3 A
Forward voltage drop	0.45 V @ 3 A
Non-repetitive surge current	100 A (8.3 ms)
Reverse recovery time	Schottky - no recovery
Junction temperature	-55 to +150 °C
Packaging	Tape & reel · 5,000 pcs

KEY FEATURES

- Every wafer lot traceable to fab and assembly site
- 100% avalanche and final test on power devices
- Low RDS(on) trench and shield-gate processes
- Halogen-free, RoHS and REACH compliant

APPLICATIONS

- Power conversion and motor drives
- Portable device power management
- Industrial communication interfaces
- Automotive lighting and body control

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.