KRO-CIR12-IP67

Circular sealed · 12 pos · IP67 · 10 A

CATEGORY	PACKAGE	STATUS
Industrial Connectors	M12	In stock

SPECIFICATIONS

Positions	12 (A-coded)
Current rating	10 A / contact
Voltage rating	30 V AC/DC
Sealing	IP67 / IP68 when mated
Contact size	Ø 1.0 mm
Mating cycles	100
Mounting	Panel mount, front fastening
Shell material	Zinc die-cast, Ni plated
Cable outer diameter	4 - 6 mm

KEY FEATURES

- 0.5 mm to 2.54 mm pitch fine-pitch designs
- Rated for 500 mating cycles minimum on board-to-board
- IP67 sealing when mated (circular series)
- Selective gold plating on contact areas

APPLICATIONS

- Automotive wiring harnesses
- Industrial automation and robotics
- Display and camera FPC routing
- Outdoor and harsh-environment equipment

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.