KRS-ALS-16D

Ambient light · 16-bit · I²C · 0.01-64 klx

CATEGORY	PACKAGE	STATUS
Sensors	2.0 × 2.0 mm	In stock

SPECIFICATIONS

Supply voltage	1.7 - 3.6 V
Resolution	16-bit
Interface	I²C, up to 400 kHz
Measurement range	0.01 - 64 klx
Accuracy	±10% (visible light)
Quiescent current	1.2 µA standby
Operating temperature	-40 to +85 °C
Packaging	Tape & reel · 3,000 pcs

KEY FEATURES

- Reflow-solderable surface-mount packages
- Tight tolerance and low long-term drift
- AEC-Q200 / AEC-Q100 automotive grades available
- Tape-and-reel packaging for automated assembly

APPLICATIONS

- Battery management and thermal monitoring
- Motor position and speed sensing
- Current sensing in inverters
- Ambient light control in smart devices

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.