KRS-HALL-A3144

Hall switch · 3.5-24 V · open collector

CATEGORY	PACKAGE	STATUS
Sensors	SOT-23	In stock

SPECIFICATIONS

Supply voltage	3.5 - 24 V
Output	Open collector, 25 mA sink
Operate point (Bop)	Bop 35 G typ.
Release point (Brp)	Brp 25 G typ.
Output current	25 mA
Operating temperature	-40 to +150 °C
Packaging	Tape & reel · 3,000 pcs

KEY FEATURES

- Reflow-solderable surface-mount packages
- Tight tolerance and low long-term drift
- AEC-Q200 / AEC-Q100 automotive grades available
- Tape-and-reel packaging for automated assembly

APPLICATIONS

- Battery management and thermal monitoring
- Motor position and speed sensing
- Current sensing in inverters
- Ambient light control in smart devices

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.