KRS-HALL-L120

Linear Hall · ratiometric 1.65-3.3 V

CATEGORY	PACKAGE	STATUS
Sensors	SOT-23	In stock

SPECIFICATIONS

Supply voltage	3.0 - 3.6 V
Quiescent output	1.65 V (ratiometric)
Sensitivity	2.5 mV/G
Linearity	±1% of full scale
Bandwidth	20 kHz
Operating temperature	-40 to +125 °C
Packaging	Tape & reel · 3,000 pcs

KEY FEATURES

- Reflow-solderable surface-mount packages
- Tight tolerance and low long-term drift
- AEC-Q200 / AEC-Q100 automotive grades available
- Tape-and-reel packaging for automated assembly

APPLICATIONS

- Battery management and thermal monitoring
- Motor position and speed sensing
- Current sensing in inverters
- Ambient light control in smart devices

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.