KRS-CUR-05A

Open-loop current · ±5 A · 2.5 V ref

CATEGORY	PACKAGE	STATUS
Sensors	SOIC-8	In stock

SPECIFICATIONS

Measurement range	±5 A
Supply voltage	4.5 - 5.5 V
Sensitivity	185 mV/A
Reference voltage	2.5 V
Isolation voltage	2.1 kV rms / 1 min
Accuracy	±1.5% of full scale
Bandwidth	80 kHz
Operating temperature	-40 to +125 °C
Packaging	Tape & reel · 2,500 pcs

KEY FEATURES

- Reflow-solderable surface-mount packages
- Tight tolerance and low long-term drift
- AEC-Q200 / AEC-Q100 automotive grades available
- Tape-and-reel packaging for automated assembly

APPLICATIONS

- Battery management and thermal monitoring
- Motor position and speed sensing
- Current sensing in inverters
- Ambient light control in smart devices

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.