KRIC-LDO1117-33

LDO · 3.3 V · 1 A · 1.1 V dropout

CATEGORY	PACKAGE	STATUS
Semiconductors & Chips	SOT-223	In stock

SPECIFICATIONS

Input voltage range	4.8 - 15 V
Output voltage	3.3 V ±1%
Output current	1 A
Dropout voltage	1.1 V @ 1 A
PSRR (1 kHz)	60 dB @ 1 kHz
Quiescent current	5 mA
Operating temperature	-40 to +125 °C
Packaging	Tape & reel · 2,500 pcs

KEY FEATURES

- Every wafer lot traceable to fab and assembly site
- 100% avalanche and final test on power devices
- Low RDS(on) trench and shield-gate processes
- Halogen-free, RoHS and REACH compliant

APPLICATIONS

- Power conversion and motor drives
- Portable device power management
- Industrial communication interfaces
- Automotive lighting and body control

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.