KRM30N06DFN

N-ch · 30 V · 6 A · RDS(on) 18 mohm

CATEGORY	PACKAGE	STATUS
Semiconductors & Chips	DFN 5×6	In stock

SPECIFICATIONS

Drain-source voltage	30 V
Continuous drain current	6 A (Tc = 25 °C)
RDS(on)	18 mohm @ VGS = 10 V
Gate threshold voltage	1.0 - 2.5 V
Total gate charge	6.8 nC
Input capacitance	520 pF
Junction temperature	-55 to +150 °C
Packaging	Tape & reel · 3,000 pcs

KEY FEATURES

- Every wafer lot traceable to fab and assembly site
- 100% avalanche and final test on power devices
- Low RDS(on) trench and shield-gate processes
- Halogen-free, RoHS and REACH compliant

APPLICATIONS

- Power conversion and motor drives
- Portable device power management
- Industrial communication interfaces
- Automotive lighting and body control

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.