KRS-NTC10K3950F

NTC · 10 kohm · ±1% · B = 3950 K

CATEGORY	PACKAGE	STATUS
Sensors	0603	In stock

SPECIFICATIONS

Resistance (25 °C)	10 kohm at 25 °C
B constant	3950 K ±1%
Tolerance	±1%
Operating temperature	-40 to +150 °C
Thermal time constant	<= 5 s (still air)
Dissipation constant	>= 1.0 mW/°C
Rated power	100 mW
Termination	Ni / Sn plated
Packaging	Tape & reel · 4,000 pcs

KEY FEATURES

- Reflow-solderable surface-mount packages
- Tight tolerance and low long-term drift
- AEC-Q200 / AEC-Q100 automotive grades available
- Tape-and-reel packaging for automated assembly

APPLICATIONS

- Battery management and thermal monitoring
- Motor position and speed sensing
- Current sensing in inverters
- Ambient light control in smart devices

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.