KRIC-ESD0504

4-line ESD array · ±15 kV air · 0.4 pF

CATEGORY	PACKAGE	STATUS
Semiconductors & Chips	SOT-23-6	In stock

SPECIFICATIONS

Protected lines	4 (bidirectional)
Reverse working voltage	5.0 V
Clamping voltage	12 V @ 1 A (8/20 µs)
Channel capacitance	0.4 pF typ.
ESD rating	±15 kV air / ±8 kV contact
Packaging	Tape & reel · 3,000 pcs

KEY FEATURES

- Every wafer lot traceable to fab and assembly site
- 100% avalanche and final test on power devices
- Low RDS(on) trench and shield-gate processes
- Halogen-free, RoHS and REACH compliant

APPLICATIONS

- Power conversion and motor drives
- Portable device power management
- Industrial communication interfaces
- Automotive lighting and body control

KRODOSEN Co., Ltd. 6F, Hanssem SangAm, 188 Seongam-ro, Mapo-gu, Seoul, Republic of Korea
T. +82 2 3152 7090~4 F. +82 2 3152 7095 E. klein@krodosen.com www.krodosen.com

PRELIMINARY DATA - KRODOSEN reserves the right to change specifications without notice. (c) KRODOSEN Co., Ltd. All rights reserved.