

The file `phddoc.dtx` for use with \LaTeX 2 $_{\epsilon}$.^{*}
It contains the code for `phddoc.cls`

Yannis Lazarides

2005/11/02

^{*}This file has version number v4.41, dated 2005/11/02.

STNETNOC FO ELBAT

```
@tocmarg=4em
@pnumwidth=1.5em
section
  indent=1.5em
subsection
  indent=3.8em
subsubsection
  indent=7.0em
```

← Contents

1

1 The LaTeX Kernel 22

- 1.1 Idiomatic LaTeX programming 23
- 1.2 Code Organization. 25
- 1.3 Autoloading 26
- 1.4 File a ldirchk.dtx 26

2 Plain TeX 28

- 2.1 Allocation of registers 30
- 2.2 Macros for setting ordinary text 39
- 2.3 Definitions related to output 46

3 Version Identification 49

4 LaTeX Kernel Definitions Module 53

4.1	Introduction	54
4.2	Saved versions of \TeX primitives	54
4.2.1	Command definitions	56
4.2.2	<code>\@cons</code> and <code>\@car</code>	57
4.3	Code	57
4.3.1	<code>csname</code> abstractions	57
4.4	List helper macros	58
4.5	Command Building	60
4.5.1	Checking if a command is definable	63
4.6	Environment Building commands	64
4.7	<code>newif</code>	65
4.8	Provide version of commands	66
4.8.1	Argument gobbling command utilities	68
4.8.2	Other argument grabbers	68
4.9	Robust commands and <code>protect</code>	69
4.9.1	Internal defining commands	72
4.9.2	Commands for Autoloading	75

5 Allocations 76

5.1	Counters	77
5.2	Scratch registers	77

6 Control Structures 79

6.1	Introduction	80
-----	--------------	----

7 Error Handling (file lterror.dtx) 83

7.1 Error handling	84
7.1.1 General commands	84
7.1.2 Package and Class error messages	87
7.1.3 Specific errors	90

8 ltspc.dtx 95

8.1 Spacing	96
8.1.1 User Commands	96
8.1.2 Vertical spacing commands	97
8.1.3 Horizontal spacing	98
8.1.4 Obsolete Commands	98
8.1.5 The code	98
8.1.6 Space removing macros	101
8.1.7 Vertical spacing	103
8.1.8 Horizontal space (and breaks)	107

9 Logos 110

10 File Handling 112

10.1 Variables, switches and internal commands	113
10.2 Safe Input Macros	120
10.3 Listing files	122

11	ltoutenc	124
11.1	Background	125
11.2	Output encodings	125
11.2.1	Output encoding files	126
11.3	Font encodings	127
11.3.1	Removing encoding-specific commands	130
11.3.2	The order of declarations	130
11.3.3	Docstrip modules	131
11.3.4	Definitions for the kernel	131
11.3.5	Default encodings	139
11.3.6	Definitions for the OT1 encoding	141
11.3.7	Definitions for the T1 encoding	143
11.3.8	Definitions for the OML encoding	148
11.3.9	Definitions for the OT4 encoding	148
11.3.10	Definitions for the TS1 encoding	150
11.3.11	The textcomp package	155
12	Counters and Lengths	165
12.1	Counters and Lengths	166
12.1.1	Environment Counter Macros	166
13	Kernel Lengths	172
13.1	File n, lengths and the llength.dtx	173
13.2	Redefinitions and Extensions by Packages	175
14	The new font selection scheme for T_EX macro packages	176
14.1	Preliminary macros	178
14.2	Macros for setting up the tables	178
14.3	Macros for loading fonts	187

15	lfsstrc	196
15.1	A driver for this document	197
15.2	The Implementation	197
15.3	Handling Options	197
15.3.1	General font loading	199

16	Setting up Fonts	210
16.1	Introduction	211
16.2	The Choice of Typesetting Engine	211
16.3	What is a character? And a glyph?	213
16.4	What's a font?	213
16.5	The low-level interface	214
16.5.1	Encoding Schemes	214
16.6	Setting several font attributes	216
16.6.1	The Postscript fonts	217
16.6.2	Additional free fonts for use with \LaTeX	221
16.6.3	Uncial fonts	221
16.7	Dingbat and Symbol Fonts	222
16.7.1	Unicode Dingbats block	223
16.8	Naming digital fonts	224
16.8.1	Karl Berry naming scheme	224
16.9	The phd package interface.	225
16.10	Viewing and selecting fonts	226
16.10.1	Typefaces that come with the standard \LaTeX distribution	226
16.11	Discussion	226
16.12	XeLaTeX and LuaLaTeX	226
16.13	Utilities for testing fonts	227
16.14	.tfm files	228
16.15	Fonts for Far East Languages	228
16.15.1	Selecting a font	228
16.16	Entering CJK text	228
16.17	Changing the font size in LaTeX	229
16.17.1	Changing the font size on the document-wide level	229
16.18	Changing the font size locally	229

17	l^{tf}ssini	230
17.1	NFSS Initialisation	232
17.1.1	Providing math <i>versions</i>	232
18	Kernel fontdef.dtx	237
18.1	Introduction	238
18.2	The fonttext.ltx file	238
18.3	Math font sizes	240
18.3.1	The math symbol assignments	240
18.3.2	Delimitercodes for characters	242
18.3.3	Symbols accessed via control sequences	242
18.3.4	Greek letters	242
18.3.5	Ordinary symbols	243
18.3.6	Large Operators	244
18.3.7	Math versions of text commands	250
18.3.8	Other special functions and parameters	250
18.3.9	The log-like functions	250
18.3.10	Parameters	251
18.4	Default cfg files	251
19	Preload	252
19.1	Introduction	253
19.2	Overview	253
19.3	Customization	253
19.4	Module switches for the DOCSTRIP program	254
19.5	A driver for this document	254
19.6	The code	254
20	The l^{tf}ntcmd module	257
20.1	Introduction	258
20.2	The implementation	260

21	Page Number	264
21.1	Page Numbering	265
21.2	Modifications and additions by packages	265
22	ltxref.dtx	266
22.1	Cross Referencing	267
22.2	Author commands	267
22.2.1	Cross Referencing	267
22.2.2	An extension of counter referencing	270
23	Miscellaneous class	272
23.1	Environments	273
23.2	Center, Flushright, Flushleft	276
23.3	Verbatim	278
24	Kernel Maths	281
24.1	Math commands based on plain T _E X	282
24.1.1	The log-like functions	282
24.1.2	Delimiters Biggggg	283

25	ltlists.dtx	296
25.1	List, and related environments	297
25.2	Generic Command	297
25.2.1	List and Trivlist	300
25.2.2	Horizontal Spacing (dimens)	302
25.2.3	Default Values	302
25.3	The \list environment	310
25.4	Typesetting the label	315
25.5	Enumerate	318
25.6	The itemize environment	319
26	L^AT_EX Box commands	322
26.1	Typesetting boxed content	323
26.2	Saving material in a box	326
26.2.1	Some low-level constructs	335
26.3	Concluding remarks	336
27	Tabbing, Tabular and Array Environments	337
27.0.1	tabbing	338
27.1	array and tabular environments	341

28	The picture Environment	347
28.1	Introduction	348
28.2	The Basic Commands	348
28.3	Text and Formulae	349
28.4	multipt and linethickness	350
28.5	Some examples	351
28.6	picture package	352
28.7	pict2e	353
28.8	xpicture	353
29	Picture Mode	354
29.1	Circles and ovals	362
29.2	Curves	367
30	Theorem Environments	370
30.1	AmS Improvements	375
31	Sectioning Commands	376
31.1	Introduction	377
31.2	The Title	377
31.3	Sectioning	378
31.3.1	Initializations	382
31.4	Table of Contents etc.	383
31.4.1	Convention	383
31.4.2	Commands	383

32	ltfloat.dtx	387
32.1	Float types	388
32.1.1	Floating Environments	388
32.2	Marginal Notes	398
32.3	Footnotes	401
33	Indices	406
33.1	Preparing an index	409
33.1.1	Subindices	410
33.2	Multi-page Indexing	410
33.3	Summary of commands	410
33.4	Indexing Class Documentation	410
34	The makeindex program	411
34.1	Output format	414
34.2	Processing	415
34.3	Customization	416
34.4	Writing custom indexing commands	417
34.5	Multiple indices	417
34.6	How to I add index to the table of contents?	417
34.7	Limitations of the MakeIndex index processor	417
34.8	The xindy index processor	418
34.8.1	Internationalization	418
35	Index and Glossary Generation	419

36 Bibliography Kernel Class 422

- 36.1 Introduction 423
- 36.2 Bibliography Generation 423
 - 36.2.1 Default definitions 426

37 LaTeX kernel page styles and related commands 427

- 37.1 Introduction 428
- 37.2 Page Style Commands 428
- 37.3 How a page style makes running heads and feet 428
- 37.4 marking conventions 428

38 Page Breaking and the Output Routine (OR) 433

In this chapter we discuss one of the most mysterious aspects of \TeX the output routine. 434



38.1	Page breaking algorithm	434
38.1.1	Typographical constraints	435
38.2	The current page and the recent contributions list	435
38.3	When is the page builder activated?	436
38.4	The depth of the current page	436
38.5	The height of a box of text	437
38.6	The height of <code>\box255</code>	437
38.6.1	Dead cycles.	437
38.6.2	\TeX 's Page Number.	438
38.6.3	The <code>\vsplit</code> operation.	438
38.7	Communicating with the OTR: Marks	439
38.8	Insertions	441
38.9	<code>\shipout</code>	441
38.10	\LaTeX output routines	444
38.11	Packages	444
38.12	hooking at shipout	445
38.13	How to place a background image	447

39	<code>ltoutput.dtx</code>	448
39.1	Introduction	449
39.2	Floats	449
39.3	Page Layout Parameters	450
39.4	Page Style Parameters	451
39.5	Float placement parameters	452
39.6	Output Routine Variables	453
39.7	Calling the output routine	453
39.8	Functions used in the output routine	454
39.9	User commands that call affect the output routine	455
39.10	Float-handling mechanisms	456
39.11	Macros and data structures for processing floats	456
39.12	Box lists for float-placement algorithms	458
39.13	Float-Placement algorithms	459
39.14	Definition of Float Boxes (inserts)	460
39.15	Page layout parameters	461
39.16	Internal registers	463
39.17	The <code>\output</code> routine	467
39.17.1	Kludgeins	490
39.18	Float control	492
39.18.1	Floats on a text page	501
39.18.2	Floats on their own page or column	502

40 How to Develop your Own Class or Package 504

40.1 Introduction	505
40.2 What is a class?	505
40.3 Identifying your class	505
40.4 Class Options	506
40.5 Set-up the font sizes	507
40.5.1 Setting up the normalsize	507
40.6 Adjusting paragraph parameters	508
40.7 Formatting Chapters and Sections	509
40.8 Adjusting the Index	510
40.9 Provide some hooks	510
40.10 The final act of kindness to your users	511

41 How to Package Your Class 511

41.0.1 The .ins file	513
41.0.2 Generating messages	515
41.1 What to put in a .dtx file	516
41.1.1 User documentation	519
41.2 General tips for defining a Class	519
41.3 Declaring Options	520
41.4 Executing Options	520
41.5 Special Commands for class files	521
41.6 A minimal class	521

42	ltclass	522
42.1	Introduction	523
42.2	User interface	523
42.2.1	Option processing	524
42.3	Class and Package interface	524
42.3.1	Class name and version	524
42.3.2	Package name and version	525
42.3.3	Requiring other packages	525
42.3.4	Declaring new options	526
42.3.5	Safe Input Macros	527
42.4	Implementation	527
42.5	Passing Options	531
42.6	Declaring Options	532
42.6.1	Hooks	539
42.6.2	Providing shipment	541
42.7	After Preamble	544
43	lthyphen	545
44	Final settings	548
44.0.1	Debugging	549
44.0.2	Typesetting parameters	549
44.0.3	Lccodes for hyphenation	551
44.1	Hyphenation	555
44.1.1	Font loading	555
44.1.2	Input encoding	556
44.1.3	Lccodes and uccodes	557
44.1.4	Initialise file list	559
44.1.5	Dumping the format	559

45 LuaTeX support (file ltluatex) 560

45.1 Overview	561
45.2 Core T _E X functionality	561
45.3 Plain T _E X interface	562
45.4 Lua functionality	562
45.4.1 Allocators in Lua	562
45.4.2 Lua access to T _E X register numbers	563
45.4.3 Module utilities	564
45.4.4 Callback management	564
45.4.5 Handlers	576
45.4.6 Public functions for callback management	578

I Latex Classes 583

46	The book.cls	585
46.1	General	587
46.2	Running Heads	590
46.3	Lists	599
46.4	The description Environment	600
46.5	Verse Environment	600
46.6	Quotation and quote environments	601
46.7	FIGURE AND TABLE ENVIRONMENTS	604
46.8	Defining the old style font commands	606
46.9	Table of contents	606
46.9.1	List of figures, tables etc	608
46.10	Bibliographies	609
46.11	The Index Environment	610
46.12	Footnotes	610
46.13	Catering for Other Languages	611
46.14	Final	611
46.15	Ending remarks	612
46.16	The .clo files	613
47	The classes module	618
47.1	A driver for this document	619
47.2	The DOCSTRIP modules	619
47.3	Initial Code	619
47.4	Declaration of Options	620
47.4.1	Setting Paper Sizes	620
47.4.2	Open bibliography	621
47.4.3	Page Layout	625
47.4.4	Lists	638
II	Book Design	649

48 Creating Book Designs 651

48.1	First Steps	652
48.1.1	Chapter Opening	652
48.1.2	The User Commands	653
48.2	Sections	654
48.3	Examples and Solutions	655
48.4	Exercises	655
48.5	Figures and diagrams	655
48.6	Geometry	658

III The Ecosystem 659

49 Key Value Interfaces 662

49.1	keyval	663
49.2	xkeyval	663
49.3	Ordinary Keys	664
49.4	Keys and values in package options	664
49.5	kvoptions	665

50 Managing Keys with PGF 666

50.1 PGF keys	667
50.2 Introduction	668
50.2.1 Comparison to Other Packages	668
50.3 Technical	669
50.3.1 Getting started	670
50.3.2 The Key Tree	672
50.3.3 Setting Keys	673
50.3.4 Keys That Execute Commands	675
50.3.5 Keys That Store Values	677
50.3.6 Keys That Are Handled	677
50.3.7 Keys That Are Unknown	678
50.3.8 Key Handlers	679
50.3.9 Handlers for Path Management	679
50.3.10 Setting Defaults	680
50.3.11 Defining Key Codes	680
50.3.12 Defining Styles	682
50.3.13 Error Keys	690

IV expl3 692

A User Manual 694

A.1 Documentation of the \LaTeX sources	696
A.2 Specification	696
A.3 Customisation	697

B Implementation Code 698


B.1 Options	700
B.1.1 Geometry parameters	700
B.2 Configuration	701
B.3 Option Processing	702
B.4 Loading book and doc	702
B.5 Useful abbreviations	703
B.6 DocInclude	704

Index 707

Latex Classes

I

Latex Classes



Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Book Design

II

Book Design



Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Creating Book Designs

In antiquity men and women saw each other as different; accordingly, they developed complex taxonomies (philosophical explanations) for understanding anatomical, physiological, emotional, and rational differences.

Some of these differences seem profoundly odd to us moderns. Modern discussions about erotic art have often concerned the place of women: to what extent are they objects of social manipulation, to what extent can they be subjects?



48.1 First Steps

In this chapter we will develop a full book template from scratch. Before we delve into it further, I would like to emphasize that the `phd` system is a bit different from classes. A `phd` style includes all the information necessary for the typesetting of a document. I have called this a style template. It is slightly different from a class system where generic commands might be included that can develop a totally different look. An identical design with perhaps different colors and fonts and other minor changes, is termed a *theme*.

Unlike book designers who would first focus on fonts, we will first give our attention to the structural elements of the book. I will be using as an example the *Linear Algebra*.




Figure 48.1: The opening chapter can leave a blank page.

Figure 48.1 shows the chapter head design. This is an interesting and challenging design that we will not easily make with the `phd` standard chapter head routines. The chapter starts with a full line and a structural element that is called *Introductory Example*. The heading of this also goes to the Table of Contents. So the chapter opening page starts with a rule and end with a rule. The ending rule in Figure 48.2 can be seen in the next figure.

48.1.1 Chapter Opening

One of the first things you will need to take care of, is to design if the style template should cater for opening at right or if it is to open at any place. Another decision you will need to make, is what to do with blank pages. Personally I dislike them and suggest, if you are going to have them to either introduce epigraphs or full page images.



Figure 48.2: The opening chapter can leave a blank page.

48.1.2 The User Commands

It is always best to start thinking about the user commands, as we go along in order to provide a user friendly interface, without the introduction of too many keys. We also need to name our template. We will name it *andrea* in honour of the Designer of the book, who was Andrea Nix. Andrea designed many of the Pearson books that were mostly textbooks and has a unique distinctive design style that can make a mathematics book fun to read.

```
\cxset{chapter template = andrea,
      chapter opening = right}
```

```
Final page layout dimensions and booleans \paperwidth 597.50787pt
\paperheight 845.04684pt
\textwidth 345.0pt
\textheight 598.0pt
\oddsidemargin 53.0pt
\evensidemargin 54.0pt
\topmargin 23.0pt
\headheight 12.0pt
\headsep 18.06749pt
\footskip 25.29494pt
\marginparwidth 96.0pt
\marginparsep 7.0pt
\columnsep 10.0pt
\columnseprule 0.0pt
\skip\footins 253
```



```
\hoffset 0.0pt
\voffset 0.0pt
\mag 1000
```

```
\@reversemargintrue
```

As we will not be sure our calculations are right or wrong (the rules can disappear at the edge of the page) I have taken 5pt out from the left or right parameters to see that we have done the calculations properly.

We also need to check on oddside pages as well. Remember the switch `\@mpar-switchfalse` will set the margin pars to be on the same size. This layout only has them on the right pages. We need to set it to false.

Another decision we need to make is if we going to draw the layout using TeX commands or one of the graphic units. Using TikZ, can be much easier, but we need to ensure we know where we are on the page. Alternatively we can use the remember picture, overlay hack to accomplish it. We will first give it a try with rules and boxes.

Now we have the dimensions of the left margin and right margin width right we can continue with the layout.

The next item we will draw is the corner frame.

45.1 Sections

48.2 Sections

The sections follow a very similar style to that of the chapter heading with rules and similar colours.




Figure 48.3: The opening chapter can leave a blank page.

The book does not use subsection. As a matter of fact most books don't consider that numbering of subsections offers an advantage to the reader.




Figure 48.4: The opening chapter can leave a blank page.

48.3 Examples and Solutions


The examples are straight forward typesetting and numbering. The specification should be that they be numbered consecutively with the example and solution in capital letters to be distinguished by the type size. The colour is to be identical. The example heading is inlined with about a quadd of space between it and the text that follow. The solution is on its own line and it is followed normally by a list which is numbered alphabetically. In other cases it is in-lined see the page at the left. We can perhaps handle this with a starred command, one for stand alone heading and another for an inlined. I will come back with some suggestions for this before, we delve into codin.

48.4 Exercises

These are modelled after sections and are also numbered. They are numbered in a different counter from that of sections and are reset at every chapter.

48.5 Figures and diagrams

The user commands should also be minimized and would follow normal LaTeX conventions, with the exception we will redefine an environment `\begin{marginfigure}`.... The margin figures are both numbered as well as unnumbered, so we will use normal LaTeX conventions to both define them as well as






Figure 48.7: The book will have a lot of examples and their solutions.




Figure 48.8: The book will have a lot of examples and their solutions.

for author commands.

48.6 Geometry

Although we spend a good part of the Chapter on page design, reviewing historical typographical paper sizes, modern book production of text books is not bound with tradition but economics. High speed printing technology uses rolls and pages can be printed up to 64 pages at a time. We will follow the books dimensions which are 7.75x10.25in. The text area occupies approximately 0.67 of the textwidth and is particularly well balanced. Many mathematical text books come out too dense and are difficult to be used by students.

The Ecosystem



The Ecosystem



Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

expl3



Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par

Fusce adipiscing justo nec ante. Nullam in enim. Pellentesque felis orci, sagittis ac, malesuada et, facilisis in, ligula. Nunc non magna sit amet mi aliquam dictum. In mi. Curabitur sollicitudin justo sed quam et quadd.par



User Manual

In antiquity men and women saw each other as different; accordingly, they developed complex taxonomies (philosophical explanations) for understanding anatomical, physiological, emotional, and rational differences.

Some of these differences seem profoundly odd to us moderns. Modern discussions about erotic art have often concerned the place of women: to what extent are they objects of social manipulation, to what extent can they be subjects?



A.1 Documentation of the L^AT_EX sources

This is a class for documenting the **phd** bundle, a collection of packages and classes that enables the typesetting of documents using a flexible user interface. You may however find it generally useful as a class for typesetting the documentation of files produced in ‘doc’ format.

The class is written as a “self-contained” docstrip file: executing `latex phd-doc.dtx` generates the **phddoc.cls** file and typesets this documentation; execute `tex l3doc.dtx` to only generate **phddoc.cls**.

Each documented file in the standard distribution comes with extension `dtx`. The appropriate class package or initex file will be extracted from the source by the docstrip system. Each `dtx` file may be directly processed with L^AT_EX 2_ε, for example

```
% latex2e docclass.dtx
%
```

would produce the documentation of the Class and package interface.

Each file that is used in producing the L^AT_EX 2_ε format (ie not including the standard class and packages) will be printed together in one document if you L^AT_EX the file `sources2e.tex`. This has the advantage that one can produce a full index of macro usage across all the source files.

If you need to customise the typesetting of any of these files, there are two options:

- You can use DOCSTRIP with the module ‘driver’ to extract a small L^AT_EX file that you may edit to use whatever class or package options you require, before inputting the source file.
- You can create a file `phddoc.cfg`. This configuration file will be read whenever the `phddoc` class is used, and so can be used to customise the typesetting of all the source files, without having to edit lots of small driver files.

The second option is usually more convenient. Various possibilities are discussed in the next section.

A.2 Specification

The class builds on the **ltxdoc**¹ class and the **doc**² package, but since they were written many authors have come up with different ideas, as to how these documents should be produced.

The L^AT_EX3 Team has also more recently developed the `l3doc` class and `l3docstrip` package for documenting the `l3` sources. Other Teams such as the developers of **pgf** prefer not to use `docstrip` and document the code and user manuals in a more traditional way, as normal documents in conjunction with external scripts written in python.

My objectives in writing this package, was to integrate the ability of the other packages in this series to document code in a flexible way. For longer books, such as a thesis, where the author might use their own developed macros, it also enables one to use such a method.

¹Carlisle, David (Mar. 2018). *The file ltxdoc.dtx for use with LaTeX2e*.

²Mittelbach, Frank (May 2018). *The doc and shortvrb package*.

This class can be considered as a framework, as it can be used to produce almost any type of document.

The objectives are as follows:

Flexibility Provide flexibility to use one of the standard \LaTeX 2 ϵ classes `article`, `book` or the KOMA classes `scrartcl`, `scrbook`, `scrreprt` as the main class. In addition to classes normally used for documents, the class also can be used for documenting \LaTeX or \LaTeX 3 packages and classes.

Style Enable the use of a fully featured key value interface for documenting the code.

Tools Provide a series of tools to create new documents, formatting and scaffolding. Currently \LaTeX distributions have a plethora of tools, mostly using perl and lately `l3build` using Lua. Perl tools have served the community well for many years. One such tool `ctanify` does not work using normal distributions as the Perl bundled in the distributions has some missing modules. Go is a cross-compilation systems language enabling scripts to be bundled for different operating systems easily, hence the choice here.³ Some of these problems with Perl on Windows can be overcome using Strawberry Perl⁴ For any conflicts follow the guidelines in `penwatch`.⁵

```
phd ctanify myclass.dtx myclass.ins README
```

A.3 Customisation

The simplest form of customisation is to pass more options to the `article` class which is loaded by `phddoc`. For instance if you wish all the documentation to be formatted for A4 paper, add the following line to `phddoc.cfg`:

```
491 % \PassOptionsToClass{a4paper}{article}
492 %
```

All the source files are in two parts, separated by `\StopEventually`. The first part (should) contain ‘user’ documentation. The second part is a full documented listing of the source code. The `doc` package provides the command `\OnlyDescription` which suppresses the code listings. This may also be used in the configuration file, but as the `doc` package is read later, you must delay the execution of `\OnlyDescription` until after the `doc` package has been read. The simplest way is to use `\AtBeginDocument`. Thus you could put the following in your `phddoc.cfg`.

```
% \AtBeginDocument{\OnlyDescription}
```

If the full source listing `sources2e.tex` is processed, then an index and change history are produced by default, however indices are not normally produced for individual files.

³See for example <https://tex.stackexchange.com/questions/256096/which-perl-to-install-for-xindy-with-miktex-on-windows>

⁴Download at <http://strawberryperl.com/>. This will also enable xindy to work on a MikTeX distribution.

⁵https://www.penwatch.net/cms/pip_conflict/

As an example, consider `ltclass.dtx`, which contains the sources for the new class and package interface commands. With no `cfg` file, a 19 page document is produced. With the above configuration a slightly more readable document (4 pages) is produced.

Conversely, if you really want to read the source listings in detail, you will want to have an index. Again the index commands provided by the `doc` package may be used, but their execution must be delayed.

```
% \AtBeginDocument{\CodelineIndex\EnableCrossrefs}
% \AtEndDocument{\PrintIndex}
```

The `doc` package writes index files to be sorted using `MakeIndex` with the `gind` style, so one would then use a command such as

```
% makeindex -s gind.ist ltclass.idx
%
```

and re-run \LaTeX .

Similarly to print a Change history, you would add

```
% \AtBeginDocument{\RecordChanges}
% \AtEndDocument{\PrintChanges}
%
```

to `phddoc.cfg`, and use `MakeIndex` with a comand such as

```
% makeindex -s gglo.ist -o ltclass.gls ltclass.glo
%
```

Finally if you do not want to list all the sections of `source2e.tex`, you can use `\includeonly` in the `cfg` file:

```
% \includeonly{ltvers,ltboxes}
%
```



Implementation Code

In antiquity men and women saw each other as different; accordingly, they developed complex taxonomies (philosophical explanations) for understanding anatomical, physiological, emotional, and rational differences.

Some of these differences seem profoundly odd to us moderns. Modern discussions about erotic art have often concerned the place of women: to what extent are they objects of social manipulation, to what extent can they be subjects?



B.1 Options

```

1  *class
2
3  %\RequirePackage{underscore}
4
5  \ExplSyntaxOn
6  \cs_gset:Npn \l_phd_version{1.00}
7  \ExplSyntaxOff

1.00
macrocode_colorize_bool Boolean to switch off the colorizing of code appearing within a macrocode environment.
                        Define the prefix of the module
8  @@=phdcl

9  \ExplSyntaxOn
10 \bool_new:N \g__phdcl_macrocode_colorize_bool
11 \bool_new:N \g__phdcl_book_bool
12 \bool_new:N \g__phdcl_article_bool
13 \bool_new:N \g__phdcl_report_bool
14 \bool_new:N \g__phdcl_scrbook_bool
15 \bool_new:N \g__phdcl_scrartcl_bool
16 \bool_new:N \g__phdcl_scrreprt_bool
17 \bool_new:N \g__phdcl_masterthesis_bool
18 \bool_new:N \g__phdcl_ldoc_bool
19 \bool_new:N \g__phdcl_ldociii_bool
20 \ExplSyntaxOff

21 \ExplSyntaxOn
22 \bool_if:NTF \g__phdcl_macrocode_colorize_bool
23   {\bool_gset_true:N \phdd_code_colorize_bool}
24   {\bool_gset_false:N \phdd_code_colorize_bool}

(End definition for \g_@@_macrocode_colorize_bool.)

```

B.1.1 Geometry parameters

```

25 \DeclareOption{a5paper}{\@latexerr{Option not supported}%
26   {}}
27
28 \DeclareOption { full }
29   {
30     \bool_gset_true:N \g_phdd_typeset_documentation_bool
31     \bool_gset_true:N \g_phdd_typeset_implementation_bool
32   }
33 \DeclareOption { onlydoc }
34   {
35     \bool_gset_true:N \g_phdd_typeset_documentation_bool
36     \bool_gset_false:N \g_phdd_typeset_implementation_bool
37   }
38 \DeclareOption{colorize}
39   {\bool_gset_true:N \phdd_code_colorize_bool}
40 \DeclareOption { check }

```

```

41 { \bool_gset_true:N \g__phdcl_checkfunc_bool }
42 \DeclareOption { nocheck }
43 { \bool_gset_false:N \g__phdcl_checkfunc_bool }
44 \DeclareOption { checktest }
45 { \bool_gset_true:N \g__phdcl_checktest_bool }
46 \DeclareOption { nochecktest }
47 { \bool_gset_false:N \g__phdcl_checktest_bool }
48 \DeclareOption { kernel }
49 { \bool_gset_true:N \g__phdcl_kernel_bool }
50 \DeclareOption { stdmodule }
51 { \bool_gset_false:N \g__phdcl_kernel_bool }
52 \DeclareOption { cm-default }
53 { \bool_gset_false:N \g__phdcl_lmodern_bool }
54 \DeclareOption { lm-default }
55 { \bool_gset_true:N \g__phdcl_lmodern_bool }
56 \DeclareOption { cs-break-off }
57 { \bool_gset_false:N \g__phdcl_cs_break_bool }
58 \DeclareOption { cs-break-nohyphen }
59 { \PassOptionsToPackage{nohyphen}{underscore} }
60 \tl_new:N \g__phdcl_doctype_tl
61 \DeclareOption { book }
62 { \tl_gput_right:Nn \g__phdcl_doctype_tl{book} }
63 \DeclareOption { scrbook }
64 { \tl_gput_right:Nn \g__phdcl_doctype_tl{book} }
65 \DeclareOption* { \PassOptionsToClass { \CurrentOption } { book } }
66 \ExecuteOptions { full, kernel, nocheck, nochecktest, lm-default }
67 \PassOptionsToClass { a4paper } { book }
68
69
70
71

```

B.2 Configuration

Input a local configuration file, if it exists, with a message to the console that this has happened. Since we distribute a `.cfg` file with the class, this should usually always be true. Therefore, check for `\ExplMakeTitle` (defined in “our” `.cfg` file) and only output the informational message if it’s not found.

```

72 \ExplSyntaxOn
73 \msg_new:nnn { phdcl } { input-cfg }
74 { Local~config~file~phdcl.cfg~loaded. }
75 \file_if_exist:nTF {phdcl.cfg}
76 {
77   \file_input:n {phdcl.cfg}
78 }
79 { \msg_info:nn { phdcl } { input-cfg } }
80 {}
81 \ExplSyntaxOff
82
83

```

```

84 \ExplSyntaxOn
85 \str_case_e:nnTF { \g__phdcl_doctype_tl }
86 {
87   { book      } {
88     %\LoadClass{book}
89     \bool_gset_true:N \g__phdcl_book_bool
90   }
91   { article  } {
92     %\LoadClass{article}
93     \bool_gset_true:N \g__phdcl_article_bool
94   }
95   { report   } {
96     %\LoadClass{report}
97     \bool_gset_true:N \g__phdcl_report_bool
98   }
99   { scrbook   } {
100    %\LoadClass{scrbook}
101    \KOMAOptions{twoside = false}
102    \bool_gset_true:N \g__phdcl_scrbook_bool
103   }
104   { scrartcl  } {
105    %\LoadClass{scrartcl}
106    \bool_gset_true:N \g__phdcl_scrartcl_bool
107   }
108   { l3doc     } { %\LoadClass{l3doc}
109   }
110   { masterthesis } {
111   }
112   { tufte      } {
113   }
114   { ltxdoc     } {
115   }
116   { memoir     } { %\LoadClass{memoir}
117   }
118   {
119   }
120
121 \ExplSyntaxOff

```

B.3 Option Processing

```

122 \ExplSyntaxOn
123 \ProcessOptions
124 %\ProcessKeysPackageOptions
125 \LoadClass{\g__phdcl_doctype_tl}
126 \ExplSyntaxOff
127

```

B.4 Loading book and doc

The original `ltxdoc` uses the `article` class. For longer documentation it is preferable to use the `book`, so for the **phddoc** class I have opted to default it to `book`.

```

128 % hypdoc is loaded with the phd-packagemanager so that
129 % the right order for packages and patches can be provided

```

```

130 \RequirePackage{doc}
131 \RequirePackage{phd}
132 \RequirePackage{phd-pkgmanager}
133 \sethyperref
134 \RequirePackage{phd-documentation} %modifies doc as necessary
135 \RequirePackage{phd-colorpalette}
136 \RequirePackage{phd-runningheads}
137 \RequirePackage{phd-toc}
138

```

Make | be a ‘short verb’ character, but not in the document preamble, where an active character may interfere with packages that are loaded.

```
139 \AtBeginDocument{\MakeShortVerb{||}}
```

As ‘doc’ documents tend to have a lot of monospaced material, Set up some tt substitutions to occur silently.

```

140 %\DeclareFontShape{OT1}{cmtt}{bx}{n}{<-> ssub * cmtt/m/n}{}
141 %\DeclareFontFamily{OMS}{cmtt}{\skewchar\font 48} % '60
142 %\DeclareFontShape{OMS}{cmtt}{m}{n}{<-> ssub * cmsy/m/n}{}
143 %\DeclareFontShape{OMS}{cmtt}{bx}{n}{<-> ssub * cmsy/b/n}{}

```

This substitution is in the standard fd file, but not silent.

```

144 \DeclareFontShape{OT1}{cmss}{m}{it}{<->ssub*cmss/m/sl}{}
145 \CodelineIndex
146 \CodelineNumbered
147 \EnableCrossrefs

```

Increase the text width slightly so that width the standard fonts 72 columns of code may appear in a macrocode environment.

```
148 %\setlength{\textwidth}{375pt}
```

Increase the marginpar width slightly, for long command names. And increase the left margin by a similar amount

```

149 %\addtolength\marginparwidth{40pt}
150 %\addtolength\oddsidemargin{40pt}
151 %\addtolength\evensidemargin{40pt}

```

```
152 \setcounter{StandardModuleDepth}{1}
```

B.5 Useful abbreviations

The [phd-documentation](#) provides numerous commands for typesetting L^AT_EX code. It is imported automatically by the phddoc class and hence the following macros are described here for convenience.

`\cmd{\foo}` Prints `\foo` verbatim. It may be used inside moving arguments. It can *not* be use to record commands that are defined as “\outer” nor is it possible to use it on conditionals such as `\iftrue` or defined by `\newif`. `\cs{\foo}` also prints `\foo`, for those who prefer that syntax. (This second form can be used to record all type of commends so the above restrictions do not apply.

```

\cmd
\cs 153 \def\cmd#1{\cs{\expandafter\cmd@to@cs\string#1}}
    154 \def\cmd@to@cs#1#2{\char\number`#2\relax}
    155

```



```

156 \DeclareRobustCommand\cls{\textcolor{thered}}
157 %\newcommand\cs[1]{\color{blue}{\texttt{\char` \ #1}}}
158
phddoc
(End definition for \cmd and \cs.)

\marg \marg{text} prints {\text}, ‘mandatory argument’.
159 %\providecommand\marg[1]{%
160 % {\ttfamily\char` \{} \meta{#1}{\ttfamily\char` \}}}
(End definition for \marg.)

\oarg \oarg{text} prints [<text>], ‘optional argument’.
161 %\providecommand\oarg[1]{%
162 % {\ttfamily[] \meta{#1}{\ttfamily[]}}
(End definition for \oarg.)

\parg \parg{te,xt} prints (<te,xt>), ‘picture mode argument’.
163 \providecommand\parg[1]{%
164 {\ttfamily{} \meta{#1}{\ttfamily{}}}
(End definition for \parg.)

```

B.6 DocInclude

```

165 %\@addtoreset{CodelineNo}{part}
166 \@addtoreset{CodelineNo}{chapter}
\DocInclude More or less exactly the same as \include, but uses \DocInput on a dtx file, not
\input on a tex file.
167 \def\partname{File}
(End definition for \DocInclude.)
168 \def\task#1#2{}
169 \endinput
170
171 \newcommand*\DocInclude[1]{%
172 \relax
173 \clearpage
174 \docincludeaux
175 \IfFileExists{#1.fdd}{%
176 \def\currentfile{#1.fdd}}{\def\currentfile{#1.dtx}
177}%
178 \ifnum\@auxout=\@partaux
179 \latexerr{\string\include\space cannot be nested}\@eha
180 \else \docinclude#1 \fi
181%
182 \def\@docinclude#1 {\clearpage
183 \if@filesw \immediate\write\@mainaux{\string\input{#1.aux}}\fi
184 \@tempswtrue\if@partsw \@tempswafalse\edef\@tempb{#1}\@for
185 \@tempa:=\@partlist\do{\ifx\@tempa\@tempb\@tempswtrue\fi}\fi
186 \if@tempswa \let\@auxout\@partaux \if@filesw
187 \immediate\openout\@partaux #1.aux
188 \immediate\write\@partaux{\relax}\fi

```



We need to save (and later restore) various index-related commands which might be changed by the included file.

```

189 \let\@phddoc@PrintIndex\PrintIndex
190 \let\PrintIndex\relax
191 \let\@phddoc@PrintChanges\PrintChanges
192 \let\PrintChanges\relax
193 \let\@phddoc@theglossary\theglossary
194 \let\@phddoc@endtheglossary\endtheglossary
195 \part{\currentfile}%
196   {\let\ttfamily\relax
197    \xdef\filekey{\filekey, \thepart={\ttfamily\currentfile}}}%
198 \DocInput{\currentfile}%
199 \let\PrintIndex\@phddoc@PrintIndex
200 \let\PrintChanges\@phddoc@PrintChanges
201 \let\theglossary\@phddoc@theglossary
202 \let\endtheglossary\@phddoc@endtheglossary
203 \clearpage
204 \@writeckpt{#1}\if@filesw \immediate\closeout\@partaux \fi
205 \else\@nameuse{cp@#1}\fi\let\@auxout\@mainaux}

```

`\codeline@wrindex`

```

206 \gdef\codeline@wrindex#1{\if@filesw
207     \immediate\write\@indexfile
208     {\string\indexentry{#1}%
209     {\filesep\number\c@CodelineNo}}\fi}%

```

(End definition for \codeline@wrindex.)

```
210 \let\filesep\@empty
```

`\aalph` Special form of `\alph` as currently `source2e.tex` includes more than 26 files .

```

211 \def\aalph#1{\@aalph{\csname c@#1\endcsname}}
212 \def\@aalph#1{%
213     \ifcase#1\or a\or b\or c\or d\or e\or f\or g\or h\or i\or
214         j\or k\or l\or m\or n\or o\or p\or q\or r\or s\or
215         t\or u\or v\or w\or x\or y\or z\or A\or B\or C\or
216         D\or E\or F\or G\or H\or I\or J\or K\or L\or M\or
217         N\or O\or P\or Q\or R\or S\or T\or U\or V\or W\or
218         X\or Y\or Z\else\@ctrerr\fi}

```

(End definition for \aalph.)

`\docincludeaux`

```

219 \def\docincludeaux{%
220     \def\thepart{\aalph{part}}\def\filesep{\thepart-}%
221     \let\filekey\@gobble
222     % add to index prologue
223     \g@addto@macro\index@prologue{%
224         \gdef\@oddfoot{\parbox{\textwidth}{\strut\footnotesize
225             \raggedright{\bfseries File Key:} \filekey}}%
226         \let\@evenfoot\@oddfoot}%
227     \global\let\docincludeaux\relax
228     %
229     \gdef\@oddfoot{%
230         \expandafter\ifx\csname ver@\currentfile\endcsname\relax

```

```
231     File \thepart: {\ttfamily\currentfile} %
232     \else
233       \GetFileInfo{\currentfile}%
234       File \thepart: {\ttfamily\filena
235       me} %
236       Date: \filedate\ %
237       Version \fileversion
238       \fi
239       \hfill\thepage}%
240 % one sided paper
241 \let\@evenfoot\@oddfoot}%

  (End definition for \docincludeaux.)

242 \def\task#1#2{}
243
244 /class
```

Index

Symbols

@@ commands:

\g_@@_macrocode_colorize_bool [8](#)

@tempa commands:

\@tempa: [185](#)

\{ [160](#)

\} [160](#)

_ [157, 236](#)

A

\aalph [211, 220](#)

\addcontentsline [414](#)

\addtolength [149, 150, 151](#)

\AtBeginDocument [139](#)

B

\bfseries [225](#)

bool commands:

\bool_gset_false [24, 36, 43, 47, 51, 53, 57](#)

\bool_gset_true [23, 30, 31, 35, 39, 41, 45, 49, 55, 89, 94, 98, 103, 107](#)

\bool_if [22](#)

\bool_new [10, 11, 12, 13, 14, 15, 16, 17, 18, 19](#)

C

\char [154, 157, 160](#)

classes

ltxdoc [407](#)

phddoc [407, 595](#)

\clearpage [173, 182, 203](#)

\closeout [204](#)

\cls [156](#)

\cmd [153](#)

\CodelineIndex [145](#)

\CodelineNumbered [146](#)

\color [157](#)

\cs [153](#)

cs commands:

\cs_gset [6](#)

\csname [211, 230](#)

\currentfile [176, 195, 197, 198, 230, 231, 233](#)

\CurrentOption [65](#)

D

\DeclareFontFamily [141](#)

\DeclareFontShape [140, 142, 143, 144](#)

\DeclareOption [25, 28, 33, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 61, 63, 65](#)

\DeclareRobustCommand [156](#)

\def [153, 154, 167, 168, 176, 182, 211, 212, 219, 220, 242](#)

\do [185](#)

\DocInclude [167, 171](#)

\docincludeaux [174, 219](#)

\DocInput [198](#)

E

\edef [184](#)

\else [180, 205, 218, 232](#)

\EnableCrossrefs [147](#)

\endcsname [211, 230](#)

\endinput [169](#)

\endtheglossary [194, 202](#)

\evensidemargin [151](#)

\ExecuteOptions [66](#)

\expandafter [153, 230](#)

\ExplMakeTitle [594](#)

\ExplSyntaxOff [7, 20, 81, 121, 126](#)

\ExplSyntaxOn [5, 9, 21, 72, 84, 122](#)

F

\fi [180, 183, 185, 188, 204, 205, 209, 218, 238](#)

file commands:

\file_if_exist:nTF [75](#)

\file_input:n [77](#)

file extensions

.ist [a413](#)

\filedate [236](#)

\filekey [197, 221, 225](#)

\filena [234](#)

files:
 gind.ist a413
 phddoc.cls a589
 sample.ist a413
 \filesep 209, 210, 220
 \fileversion 237
 \font 141
 \footnotesize 224

G

\gdef 206, 224, 229
 \GetFileInfo 233
 \global 227

H

\hfill 239

I

\ifcase 213
 \IfFileExists 175
 \ifnum 178
 \ifx 185, 230
 \immediate .. 183, 187, 188, 204, 207
 \include 179
 \index 406
 \indexentry 208

Indexing

customizing 413
 doc 407
 general 407
 multi-page 407

Indexing 407

K

\KOMAOptions 102

Kroll 406

Kroll

Leon Kroll 406

L

\let . 186, 189, 190, 191, 192, 193, 194,
 196, 199, 200, 201, 202, 205,
 210, 221, 226, 227, 241

\LoadClass . 88, 93, 97, 101, 106, 109,
 115, 125

ltxdoc (class) 407

M**main**

xindy 415
 \makeindex 406
 \makeindex 409, 588, 592
 \MakeShortVerb 139
 \marg 159
 \marginparwidth 149

\meta 160, 162, 164

msg commands:

\msg_info 79

\msg_new 73

N

\newcommand 157, 171

\number 154, 209

O

\oarg 161

\oddsidemargin 150

\openout 187

\or 213, 214, 215, 216, 217, 218

P**Packages:**

doc 407, 589

docstrip 407

imakeidx 414, 415

ltxdoc 589

makeidx 406

makeindex 413

multind 414

pgf 589

phd 589

phd-documentation 596

phddoc 590

\parbox 224

\parg 163

\part 195

\partname 167

\PassOptionsToClass 65, 67

\PassOptionsToPackage 59

phdcl internal commands:

\g_phdcl_article_bool . 12, 94

\g_phdcl_book_bool 11, 89

\g_phdcl_checkfunc_bool 41, 43

\g_phdcl_checktest_bool 45, 47

\g_phdcl_cs_break_bool 57

\g_phdcl_doctype_tl 60, 62, 64,
 85, 125

\g_phdcl_kernel_bool .. 49, 51

\g_phdcl_ldoc_bool 18

\g_phdcl_ldociii_bool 19

\g_phdcl_lmodern_bool . 53, 55

\g_phdcl_macrocode_col-

orize_bool 10,

22

\g_phdcl_masterthesis_bool 17

\g_phdcl_report_bool .. 13, 98

\g_phdcl_scrartcl_bool 15, 107

\g_phdcl_scrbook_bool 14, 103

\g_phdcl_scrreprt_bool 16



phdd commands:

`\phdd_code_colorize_bool` 23, 24, 39
`\g_phdd_typeset_documentation_bool` 30, 35
`\g_phdd_typeset_implementation_bool` 31, 36
`phddoc` (class) 407, 595
`\PrintChanges` 191, 192, 200
`\PrintIndex` 189, 190, 199
`\printindex` 406
`\ProcessKeysPackageOptions` 124
`\ProcessOptions` 123
`\providecommand` 159, 161, 163

Q**Quantum Mechanics**

`History` 406–407

R

`\raggedright` 225
`\relax` .. 154, 172, 188, 190, 192, 196, 227, 230
`\RequirePackage` . 3, 130, 131, 132, 134, 135, 136, 137

S

`\setcounter` 152
`\sethyperref` 133
`\setlength` 148
`\skewchar` 141
`\space` 179

str commands:

`\str_case_e` 85
`\string` 153, 179, 183, 208
`\strut` 224

T

`\task` 168, 242

T_EX and L^AT_EX 2_ε commands:

`\@aalph` 211, 212
`\@addtoreset` 165, 166
`\@auxout` 178, 186, 205
`\@ctrerr` 218
`\@docinclude` 180, 182
`\@eha` 179
`\@empty` 210
`\@evenfoot` 226, 241
`\@for` 184
`\@gobble` 221
`\@indexfile` 207
`\@input` 183
`\@latexerr` 25, 179

`\@mainaux` 183, 205
`\@nameuse` 205
`\@oddfoot` ... 224, 226, 229, 241
`\@partaux` 178, 186, 187, 188, 204
`\@partlist` 185
`\@phddoc@PrintChanges` 191, 200
`\@phddoc@PrintIndex` .. 189, 199
`\@phddoc@endtheglossary` .. 194, 202
`\@phddoc@theglossary` . 193, 201
`\@tempa` 185
`\@tempb` 184, 185
`\@tempswafalse` 184
`\@tempswatrue` 184, 185
`\@writeckpt` 204
`\index` 406, 407
`\c@CodelineNo` 209
`\cmd@to@cs` 153, 154
`\codeline@wrindex` 206
`\g@addto@macro` 223
`\if@filesw` .. 183, 186, 204, 206
`\if@partsw` 184
`\if@tempswa` 186
`\index@prologue` 223

`\textcolor` 156
`\texttt` 157
`\textwidth` 148, 224
`\theglossary` 193, 201
`\thepage` 239
`\thepart` 197, 220

thepart commands:

`\thepart:` 231, 234

tl commands:

`\tl_gput_right` 62, 64
`\tl_new` 60
`\ttfamily` 160, 162, 164, 196, 197, 231, 234

V**version commands:**

`\l_phd_version` 6

W

`\write` 183, 188, 207

X

`\xdef` 197
`xindy` 415