

1 in + \topmargin (17 pt) = 55.27 pt

Page 1

\headheight 12 pt

\headsep 25 pt

The xlayouts package. *

Dr. Yiannis Lazarides
yannislaz@gmail.com

2012/05/26

Abstract

Current layout packages, such as the layout and layouts packages do not easily permit, the drawing of grids. The package geometry shows a page layout, but does not make it clear what each line represents. The need for this package arose when I was developing different page layouts for chapter heads. It has a number of utilities, one of which is shown in this publication. An extensive list of styling options is provided via a key-value interface.

Contents

1 How to use the package	1 7 Float parameters	13
2 Introduction	1 8 Spread	14
3 Producing pages two-up	2 9 Try Layouts	16
4 Page Layouts	2 10 Readability	16
5 Implementation	2 11 Page Layout Diagrams	17
5.1 Dependencies	3 11.1 New lengths	18
5.2 Internationalization	4 11.2 Allowances for trims	20
5.3 New lengths and switches	4 11.3 Drawing the Trial Layout	21
5.4 Colors	5 12 Lists	28
5.5 The driver margins	8 12.1 Tabulating List values	31
5.6 Crop marks	9 13 Draw a Font box	32
5.7 Vertical lines	9 13.1 Sundry	35
5.8 Horizontal lines	9 14 Minimal Working Examples (MWE)	35
5.9 Two column document	9 14.1 List standalone diagram MWE	38
5.10 headheight and headsep	10 15 Dictionaries	39
5.11 Text height	11 16 References	42
5.12 The footskip		
5.13 Marginpar dimensions		
5.14 Classic layout diagonal lines		
6 Running head definitions		

\textheight
598 pt

*This file (xlayouts.dtx) has version number v1.0, last revised 2012/05/26.

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$

Page 2

$\text{\headheight } 12\text{ pt}$

$\text{\headsep } 25\text{ pt}$

1 How to use the package

The package is used like any other LaTeX package, by including it in the preamble:

```
\usepackage{xlayouts}
```

It is recommended that options be loaded using the `\cxset` macro.

```
% \cxset{geometry units=in}
```

2 Introduction

This package is a re-implementation of the Peter Wilson's layouts package. It follows the tradition originally implemented in the `layout.sty` of Kent McPherson. It defines the command `xlayout` that draws the page geometry on the current page. The package offers additional features, such as styling commands and diverges from tradition, in that it shows the dimension lines and value labels, making understanding of the arithmetic involved easier. It works in all the major classes.

This manual is typesets according to the conventions of the LaTeX `docstrip` utility which enables the automatic extraction of the LaTeX macro source files [GMS94].

3 Producing pages two-up

Sometimes it is instructive to view your own document in a two page view. This is probably easy with a viewer such as Acrobat Reader, but not so easy to save them on paper. We offer a facility to do this in the macros that follow:

$\text{\textheight } 598\text{ pt}$

4 Page Layouts

There are a number of ways you can include a page layout in your document.

5 Implementation

The implementation, uses PGF to set the key value parameters and TikZ to draw the layout. We try to avoid clashes with other packages by using the suffix `@cx` for all internal macros.

5.1 Dependencies

5.1.1 latex.ltx

5.1.2 xcolor.sty

`xlayouts`'s colour handling depend on the `xcolor` package. The following internal macros are used directly: `\@declaredcolor`, `\current@color`, `\set@color`, `\set@page@color`

```
1 \IfFileExists{color.sty}{%
2 \RequirePackage{color}%
3 \let\needscolor@cx\@empty
```

$\text{\footskip } 30\text{ pt}$

$\text{\marginparsep } 11\text{ pt}$

$\text{oddsidemargin } 28\text{ pt}$

$\text{\textwidth } 380\text{ pt}$

$\text{\marginparwidth } 101\text{ pt}$


$\text{driver margin } 1\text{ in}$

1 in + \topmargin (17 pt) = 55.27 pt

Page 3

\headheight 12 pt

\headsep 25 pt



\topfrac
.7

Figure 1: Test

\textheight
598 pt

```
4    \}}  
5    \RequirePackage{fp}
```

5.1.3 changepage.sty

We use the changepage to detect reliably if we are on an odd or even page.

```
6    %\IfFileExists{changepage.sty}{%  
7    \RequirePackage{xcolor}
```

The package translator from Beamer's suite is used to internationalize some strings. This can make the diagrams more useful. Unsure at this stage how to pick it automatically from babel, if babel is used.

The loading of pgf can be problematic sometimes so we try and load it here.

```
8    \RequirePackage{changepage}  
9    \RequirePackage{pgf}  
10   \RequirePackage{pgfpages}  
11   \RequirePackage{tikz}  
12   \RequirePackage{amsmath}  
13   \RequirePackage{fancyhdr}
```

\footskip 30 pt


\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in



1 in + \topmargin (17 pt) = 55.27 pt

Page 5

\headheight 12 pt

\headsep 25 pt

```
16      {\RequirePackage{translator}\typeout{Translator package loaded.}}}%
17      }%
18      {\RequirePackage[french,dutch,german,italian,english]{babel}
19      \IfFileExists{translator.sty}
20      {\RequirePackage{translator}\typeout{Translator package loaded.}}}%
21
22      \usedictionary{pages}
23      \DeclareOption{german}{\uselanguage{german}}
24      \DeclareOption{english}{\select@language{english}\uselanguage{english}}
25      \DeclareOption{italian}{\select@language{italian}\uselanguage{italian}}
26      \DeclareOption{dutch}{\select@language{dutch}\uselanguage{dutch}}
27      \DeclareOption{french}{\select@language{french}\uselanguage{french}}
28      \ProcessOptions*
```

5.3 New lengths and switches

We need a few new lengths for arranging the grid and the layout.

```
29      \newlength\shiftx@cx
30      \newlength\shifty@cx
31      \newlength\tol
32      \newlength\tol y
33      \newlength\innermargin
34      \newlength\PH
35      \setlength\PH{\paperheight}
36      \newlength\PW
37      \setlength\PW{\paperwidth}
38      \newlength\INNER
39      \newlength\TOP
40      \newlength\alphlength
```

\textheight
598 pt

5.4 Colors

```
41      \definecolor{theblue}{rgb}{0.02,0.04,0.48}
42      \definecolor{thered}{rgb}{0.65,0.04,0.07}
43      \definecolor{thegreen}{rgb}{0.06,0.44,0.08}
44      \definecolor{thelightgreen}{rgb}{0.06,0.44,0.06}
45      \definecolor{thegrey}{gray}{0.5}
46      \definecolor{thegray}{gray}{0.5}
47      \definecolor{thedarkgray}{gray}{0.95}
48      \definecolor{theshade}{gray}{0.94}
49      \definecolor{theframe}{gray}{0.75}
50      \definecolor{thecream}{rgb}{1,0.95,0.4}
51      \definecolor{spot}{rgb}{0,0.2,0.6}
52      \definecolor{boxframe}{gray}{0.8}
53      \definecolor{boxfill}{rgb}{0.95,0.95,0.99}
54      \definecolor{theooption}{rgb}{0.118,0.546,0.222}
55      \definecolor{themacro}{rgb}{0.784,0.06,0.176}
56      \definecolor{ExampleFrame}{rgb}{0.628,0.705,0.942}
57      \definecolor{ExampleBack}{rgb}{0.963,0.971,0.994}
58      \definecolor{Hyperlink}{rgb}{0.281,0.275,0.485}
59      \colorlet{thehyperlink}{theblue}
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 6

\headheight 12 pt

\headsep 25 pt

```
60 \newcommand*\defaultcolor{\color{black}}
61 \newcommand*\spotcolor{\color{spot}}
```

The @diagonal switch is used to let the user choose to draw the diagonal lines for classical layout checks we set it initially at false.

```
62 \newif\if@diagonal
63 \@diagonalfalse
64
65
66 \newif\ifdrawmarginpars
67 \drawmarginparstrue
68
69
```

\printunitsof@cx This macro has been adapted from the layouts package, it sets the units to be printed in the diagrams.

```
70 \newcommand{\printinunitsof@cx}[1]{%
71 \def\l@yunitperpt{1.0}\def\l@yunits{pt}%
72 \def\l@yta{#1}\def\l@ytb{pt}%
73 \ifx \l@yta\l@ytb
74 \def\l@yunitperpt{1.0}\def\l@yunits{pt}%
75 \else
76 \def\l@ytb{pc}%
77 \ifx \l@yta\l@ytb
78 \def\l@yunitperpt{0.083333}\def\l@yunits{pc}%
79 \else
80 \def\l@ytb{in}%
81 \ifx \l@yta\l@ytb
82 \def\l@yunitperpt{0.013837}\def\l@yunits{in}%
83 \else
84 \def\l@ytb{mm}%
85 \ifx \l@yta\l@ytb
86 \def\l@yunitperpt{0.351459}\def\l@yunits{mm}%
87 \else
88 \def\l@ytb{cm}%
89 \ifx \l@yta\l@ytb
90 \def\l@yunitperpt{0.0351459}\def\l@yunits{cm}%
91 \else
92 \def\l@ytb{bp}%
93 \ifx \l@yta\l@ytb
94 \def\l@yunitperpt{0.996264}\def\l@yunits{bp}%
95 \else
96 \def\l@ytb{dd}%
97 \ifx \l@yta\l@ytb
98 \def\l@yunitperpt{0.9345718}\def\l@yunits{dd}%
99 \else
100 \def\l@ytb{cc}%
101 \ifx \l@yta\l@ytb
102 \def\l@yunitperpt{0.0778809}\def\l@yunits{cc}%
103 %
104 % \def\l@ytb{PT}%
105 % \ifx \l@yta\l@ytb
106 % \def\l@yunitperpt{1.0}\def\l@yunits{PT}% gives problems with pgfmathpars
```

\textheight
598 pt

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 7

\headheight 12 pt

\headsep 25 pt

```
107      %              \fi
108              \fi
109              \fi
110              \fi
111      \fi
112      \fi
113      \fi
114      \fi
115      \fi
116  }
```

\convert@cx The macro \convert@cx is used internally to convert dimensions from one set of units to another. Used in dimension lines.

```
117      \newcommand\convert@cx[1]{%
118          \pgfmathparse{#1*\l@unitperpt}
119          % use pgfmath for rounding to 2 decimals
120          \pgfmathprintnumber{\pgfmathresult}\thinspace\l@units
121      }
```

\calcshift@cx Helper command to reposition the grid, note it needs to run twice to position the grid properly.

```
122      \newcommand\calcshift@cx{%
123          \pgfsys@getposition{\pgfpictureid}\@basepoint
124          \pgf@process{\pgfp@pointorigin\@basepoint}%
125          \setlength\shiftx@cx\pgf@x
126          \setlength\shifty@cx\pgf@y}
```

\CS

```
127      \newcommand\CS[1]{\footnotesize #1}
```

\textheight
598 pt

\labelit@cx The macro \labelit@cx, is the main styling command for labels on dimensions this is expected to get more intelligent in future versions.

```
128      \newcommand\labelit@cx[1]{\ttfamily\CS{\string#1} \convert@cx{#1}}
```

We define its own family of keys. !TODO A CHECK HERE

\cxset The macro \cxset is used to either define a new key or set an existing one.

```
129      \newcommand\cxset{\pgfqkeys{/xlayouts}} %Notice this is pgf q keys
```

We are now ready to start defining keys. We use PGF Keys to define the keys.

```
130      \cxset{geometry units/.code=\printinunitsof@cx{#1},
131              geometry grid color/.store in=\geometrygridcolor@cx,
132              geometry lines color/.store in=\geometrylinescolor@cx,
133              geometry label color/.store in=\geometrylabelcolor@cx,
134              geometry diagonal/.is choice,
135              geometry diagonal/true/.code=\@diagonaltrue,
136              geometry diagonal/false/.code=\@diagonalfalse,
137              geometry diagonal/none/.code=\@diagonalfalse,
138              geometry diagonal color/.store in=\diagonalcolor@cx,
139              geometry dim arrow type/.store in=\geometryarrowtype@cx,
140              geometry grid xsteps/.store in=\xsteps@cx,
141              geometry grid ysteps/.store in=\ysteps@cx,
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

```

142     geometry grid line width/.store in=\geometrygridlinewidth@cx,
143     geometry driver lines/.store in=\geometrydriverlines@cx,
144     geometry driver lines color/.store in=\geometrydriverlinescolor@cx,
145 }

```

We set some defaults to initialize the keys and prevent errors, if the user doesn't specify any parameters.

```

146     \cxset{geometry diagonal=true,
147           geometry diagonal color=blue!20,
148           geometry lines color=pink,
149           geometry label color=blue!15,
150           geometry grid color=blue!15,
151           geometry grid line width=0.8pt,
152           geometry dim arrow type=latex,
153           geometry units=pt,
154           geometry grid xsteps=9,
155           geometry grid ysteps=9,
156           geometry driver lines=dashed,
157           geometry driver lines color=blue!15}

```

`\agrid` The macro `\agrid` is the main drawing command. It draws the layout.

```

158
159     \newcommand\agrid{%
160     \tikzset{lines/.style={color=\geometrylinescolor@cx},
161             dim/.style={color=black!25,thick,>=\geometryarrowtype@cx},
162             dim label/.style={color=black,fill=\geometrylabelcolor@cx},
163             grid/.style={line width=\geometrygridlinewidth@cx,
164                           color=\geometrygridcolor@cx},
165             driver/.style={\geometrydriverlines@cx,
166                             \geometrydriverlinescolor@cx}}

```

$$\text{\textheight} 598\text{ pt}$$

```

167     \begin{tikzpicture}[remember picture, overlay]
168

```

We need to detect if the layout is on an odd or an even page. We use the macro `\checkoddpage` from the `changepage` package. For oneside documents all pages are treated as odd and we set the switch to true.

```

169     \pgfmathsetlength{\TOP}{\PH-1in-\voffset-\topmargin-\headheight-\headsep}
170     \checkoddpage%
171     % for oneside we treat them as odd
172     \if@twoside\else\oddpagetrue\fi
173     \ifoddpage
174         \innermargin\oddsidemargin
175         \pgfmathsetlength{\INNER}{1in+\innermargin+\hoffset}
176         \gdef\innermarginname{\CS{oddsidemargin}}%
177     \else
178         \innermargin\evensidemargin
179         \pgfmathsetlength{\INNER}{1in+\innermargin+\hoffset}
180         \gdef\innermarginname{\CS{evensidemargin}}%
181     \fi

```

We need to shift the whole layout in order to achieve an integral number of grids this is done with `calcshift@cx`¹.

¹See [discussion](#) at `tex.sx`

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

```
182 \calcshift@cx
183 \begin{scope}[xshift=-\shiftx@cx, yshift=-\shifty@cx]
```

We will first draw the grid. This is one of the main features of the package. We do this using the grid shape. All `\draw` commands are detailed, rather than using coordinates. This was both for me as well as future maintainers that can follow easier the steps in drawing the layout.

```
184 %
185 \draw [grid,xstep=\PW/\xsteps@cx,ystep=\PH/\ysteps@cx]
186 (current page.south west) grid ++(\PW,\PH);
```

5.5 The driver margins

Printer's cannot always print up to the edges of the paper. Knuth allowed a one inch margin for this which later got adopted into LaTeX.

`\hoffset` Adjustment to the one inch margins can be made by using `\hoffset` and `\voffset`. All major classes set these offsets at zero. Some packages such as the crop may use these to center a logical page onto the stock paper.

```
187 \draw [driver] (lin,0) -- (lin,\PH);
188 \draw [driver] (0,\PH-lin)-- ++(\PW,0);
```

5.6 Crop marks

If the option `crop` is set, the package will print crop marks. These are printed at the four corners of the paper.

```
189 %\draw [line width=0.4pt,color= green]
190 % (0+8mm,\stockheight-30mm) circle(2.5mm)++(-2.5mm,0)
191 % -- ++(20mm,0)++(-17.5mm,-2.5mm)--++(0,5mm);
192 %
193 %\draw [line width=0.4pt,color=red,]
194 % (8+25mm,\stockheight-30mm+2.5mm)-- ++(0,20mm)
195 % ++ (0,-2.5mm)circle(2.5mm) ++(-2.5mm,0mm)--++(5mm,0);
196
197
```

$$\text{\textheight} 598\text{ pt}$$

5.7 Vertical lines

For no particular reason we first draw the vertical lines. We also define some co-ordinates to reduce the verbosity of the code.

```
198 \draw [lines] (\INNER,0) -- (\INNER,\PH);
199 \draw [lines] (\INNER+\textwidth,0) -- ++(0,\PH);
200 \ifoddpage
201 \draw[lines] (\INNER+\textwidth+\marginparsep,0)
202 -- (\INNER+\marginparsep+\textwidth,\PH);
203 \draw[lines] (\INNER+\textwidth+\marginparsep+\marginparwidth,0)
204 -- (\INNER+\marginparsep+\marginparwidth+\textwidth,\PH);
205 \else
206 \draw [lines] (\INNER-\marginparsep,0) -- ++(0,\PH);
207 \draw [lines] (\INNER-\marginparsep-\marginparwidth,0) -- ++(0,\PH);
208 \fi
```

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

$$1\text{ in} + \text{\topmargin} (17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

5.8 Horizontal lines

Next we draw the horizontal lines.

```

209 \draw [lines](0,\PH-1in-\topmargin)-- ++(\PW,0);
210 \draw [lines](0,\PH-1in-\topmargin-\headheight)-- ++(\PW,0)
211 node[black,above] at ++(-0.5\PW,0){Page \thepage};
212 \draw [lines](0,\TOP) -- ++(\PW,0);
213 \draw [lines](0,\TOP-\textheight) -- ++(\PW,0);
214 \draw [lines](0,\TOP-\textheight-\footskip) -- ++(\PW,0);

```

5.9 Two column document

A two column document, just subdivides the text area into two equal parts with a gutter in between. Next we draw the vertical lines and the dimensions for two column layouts. We detect if it is a twocolumn layout using the switch `\if@twocolumn` defined by the standard classes.

```

\columnwidth
\columnsep
215 \if@twocolumn
216 \draw [lines](\INNER+\columnwidth,\TOP)-- ++(0,-\textheight);
217 \draw [lines](1in+\innermargin+\columnwidth+\columnsep,\TOP)
218 -- ++(0,-\textheight);
219 % Draw twocolumn dimension lines
220 \draw [dim,<->](\INNER, \TOP-\textheight-1.8em)
221 -- ++(\columnwidth,0) node[above, dim label]
222 at ++(-0.5\columnwidth,3pt) {\labelit@cx{\columnwidth}};
223 \draw [dim,<->](\INNER+\columnwidth, \TOP-\textheight-1.8em)
224 -- ++(\columnsep,0) node[above, dim label] at
225 ++(-0.5\columnsep,3pt) {\labelit@cx{\columnsep}};
226 \draw [dim,<->](\INNER+\columnwidth+\columnsep,
227 \PH-1in-\topmargin-\headheight-\headsep-\textheight-1.8em)
228 -- ++(\columnwidth,0) node[above, dim label] at
229 ++(-0.5\columnwidth,3pt) {\labelit@cx{\columnwidth}};
230 \fi

```

$$\text{\textheight} 598\text{ pt}$$

We then position and draw the dimension lines and labels.

```

231 \ifoddpage
232 \pgfmathsetlength\tol{1in+\innermargin+\textwidth+2\marginparsep}
233 \draw [dim, <->](\tol,\PH)-- ++(0,-1in-\topmargin);
234 \else
235 \pgfmathsetlength\tol{2\marginparsep}
236 \draw [dim, <->](\tol,\PH)-- ++(0,-1in-\topmargin);
237 \fi

```

The top margin (not to be confused with the length `\topmargin`, is the total length given by the driver margin (which is `1in` + the `\topmargin` length + the `\headheight` and `\headsep`).

```

238 \pgfmathsetlength\@tempdima{1in-\topmargin}
239 \ifoddpage
240 \draw [dim](\tol,\PH-1in-\topmargin)-- ++(0,-\headheight)
241 node[left, dim label] at
242 ++(-1ex,0.5in+0.5\topmargin+1.5em)

```

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

1 in + \topmargin (17 pt) = 55.27 pt

Page 11

\headheight 12 pt

\headsep 25 pt

```
243     {\scriptsize$1\thinspace \text{in}+\texttt{\footnotesize\textbackslash topmargin}\,
244     (\convert@cx{\topmargin})= \convert@cx{@tempdima}$};
245 \else
246     \draw [dim, <->](\tol,\PH-lin-\topmargin)-- ++(0,-\headheight)
247     node[right, dim label] at ++(lex,lin-0.5\topmargin)
248     {\scriptsize$1\thinspace \text{in}+\texttt{\footnotesize\textbackslash topmargin}
249     \, (\convert@cx{\topmargin})= \convert@cx{@tempdima}$};
250 \fi
```

5.10 headheight and headsep

The \headheight is normally a fixed amount that varies with the baseline of the the font. In the standard classes it is defined in the .clo files. We position the lines and labels on the right for odd pages and on the left for even pages.

```
251 \ifoddpage
252     \draw [dim,<->](\tol,\PH-lin-\topmargin)-- ++(0,-\headheight)
253     node[above left, dim label] at ++(-lex,0){ \labelit@cx{\headheight}};
254 % draw headsep
255     \draw [dim,<->](\tol,\PH-lin-\topmargin-\headheight)-- ++(0,-\headsep)
256     node[above left,dim label] at ++(-lex,0){\labelit@cx{\headsep}};
257 \else
258     \draw [dim,<->](\tol,\PH-lin-\topmargin)-- ++(0,-\headheight)
259     node[above right,dim label] at ++(lex,0){ \labelit@cx{\headheight}};
260 % draw headsep
261     \draw [dim,<->](\tol,\PH-lin-\topmargin-\headheight)-- ++(0,-\headsep)
262     node[above right, dim label] at ++(lex,0){\labelit@cx{\headsep}};
263 \fi
```

\textheight
598 pt

5.11 Text height

The \textheight is normally calculated to have an exact number of lines to avoid warning messages from the TeX engine.

```
264     \draw [dim, |<->](\tol,\TOP)
265     -- ++(0,-\textheight) node[right,text width=1.7cm,text centered, dim label]
266     at ++(lex,0.5\textheight){\labelit@cx{\textheight}};
```

5.12 The footskip

The footskip is also a fixed number set by the classes. We position it left or right to minimize clashes with other elements.

```
267 \ifoddpage
268     \draw [dim, |<->](\tol,\TOP-\textheight)
269     -- ++(0,-\footskip)
270     node[left, dim label] at ++(-lex,0.5\footskip){\labelit@cx{\footskip}};
271 \else
272     \draw [dim, |<->](\tol,\TOP-\textheight)
273     -- ++(0,-\footskip)
274     node[right, dim label] at ++(lex,0.5\footskip){\labelit@cx{\footskip}};
275 \fi
276
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 12

\headheight 12 pt

\headsep 25 pt

```
277 % Float parameters
278 % topfraction on left margin
279
280 \iftopfloat{%
281 \draw [dim,<->] (\INNER-0.3cm, \TOP)-- ++(0,-\topfraction\textheight)
282 node[left,text width=1.7cm,text centered, dim label]
283 at ++ (0,0.4\textheight) {\textbackslash topfraction\\ \topfraction};
284 }{}
285 % bottom fraction
286 \ifbotfloat{%
287 \draw [dim,<->] (\INNER, \TOP) ++(0,-\textheight)
288 -- ++(0,\bottomfraction\textheight)
289 node[left, text width=1.2cm, dim label] at
290 ++(-lex,-\bottomfraction*0.5\textheight){\textbackslash bottom\\fraction\\
291 \bottomfraction};
292 }{}
293 % HORIZONTAL DIMENSIONS
294 \setlength\toly{1.5cm}
295 \draw[dim,<->](0,\toly)--++(1in,0)node [dim label] at ++(-0.4in,-1.5em)
296 {\translate{drivermarginname} 1\thinspace in};
297
```

If innermargin 0pt we do not show the dimension line. Tufte-book has innermargin=0pt

```
298 \ifdim\innermargin=0pt
299 \draw[dim,](0+1in,\toly)--++(\innermargin,0) node [above, dim label]
300 at ++(-0.5\innermargin,0.5em)
301 {\innermarginname\convert@cx{\innermargin}};
302 \else
303 \draw[dim,<->](0+1in,\toly)--++(\innermargin,0) node [above, dim label]
304 at ++(-0.5\innermargin,0.5em)
305 {\innermarginname\ \convert@cx{\innermargin}};
306 \fi
307
308 \draw[dim,<->](0+1in+\innermargin,\toly)--++(\textwidth,0)
309 node[above, dim label] at ++(-0.5\textwidth,0.5em)
310 {\labelit@cx{\textwidth}};
```

\textheight
598 pt

5.13 Marginpar dimensions

\marginparwidth There are three controlling lengths that position the marginpar block. The
\marginparsep marginparwidth is troublesome, in that some classes don't really worry about
\marginparpush marginpars and they left the dimensions unchanged. For Octavo for some pa-
pers they will overflow outside the paper boundaries.

```
311 \ifoddpage
312 \draw[dim,<->](\INNER+\textwidth, \toly+1.5cm)--++(\marginparsep,0)
313 node [below, dim label] at ++(\marginparsep,-0.5em)
314 {\labelit@cx{\marginparsep}};
315 \draw[dim,<->](\INNER+\textwidth+\marginparsep, \toly)
316 --++(\marginparwidth,0)
317 node [above, dim label] at ++(-0.5\marginparwidth,0.5em)
318 {\labelit@cx{\marginparwidth}};
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 13

\headheight 12 pt

\headsep 25 pt

```
319 \else
320   \draw[dim,<->](\INNER, \toly+1.55cm)--++(-\marginparsep,0)
321     node [right, dim label] at ++(\marginparsep,0em)
322     {\labelit@cx{\marginparsep}};
323 \ifdim\marginparwidth<3cm % try be a more intelligent for placement
324   \draw[dim,<->](0+lin+\innermargin-\marginparsep-\marginparwidth,
325     \toly+.95cm)--++(\marginparwidth,0)node [right, dim label]
326     at ++(0,0em)
327     {\labelit@cx{\marginparwidth}};
328 \else
329   \draw[dim,<->](\INNER-\marginparsep-\marginparwidth, \toly+.95cm)
330     --++(\marginparwidth,0)node [above, dim label] at
331     ++(-0.5\marginparwidth,0em){\labelit@cx{\marginparwidth}};
332 \fi
333 \fi
```

5.14 Classic layout diagonal lines

We do not attempt to draw out a full classical layout, but only to draw the diagonal lines to check. This feature can be switched off. The direction of the line depends if we have an odd or even page.

```
334 \if@diagonal
335   \ifoddpage
336     \draw [\diagonalcolor@cx,thick] (\PW,0)--(0,\PH);
337   \else
338     \draw [\diagonalcolor@cx,thick] (0,0)--(\PW,\PH);
339   \fi
340 \fi
341 \end{scope}
342 \end{tikzpicture}}
```

\textheight
598 pt

6 Running head definitions

We define a page layout, grid to position the grid. We use the same for both evenhead and oddhead.

\ps@grid In LaTeX a running header is defined using a `\ps@<name>` macro. We define a pagestyle that can be use to draw the layout.

```
343 \def\ps@grid{%
344   \let\@oddfoot\@empty\let\@evenfoot\@empty
345   \def\@evenhead{\agrid}%
346   \let\@oddhead\@evenhead
347   \let\@mkboth\@gobbletwo
348   \let\chaptermark\@gobble
349   \let\sectionmark\@gobble
350 }
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

7 Float parameters

`\figureparambot` The macros `\figureparambot` attempt to draw dimension lines in figures. This is very much work in progress, as to draw them properly will need to redefine some of the internals of the output routine.

```

351 \def\figureparamsbot{%
352   \begin{tikzpicture}[remember picture, overlay]
353     \pgfmathsetlength\@tempdima{-\textfloatsep}
354     \draw[>=latex,|<->|] (0,0) --++(0,-\@tempdima)
355       node [right]
356         at ++ (lex,-0.5\textfloatsep)
357         {\CS{textfloasep} \convert@cx{\textfloatsep}};
358   \end{tikzpicture}%
359 \par
360 }
361 \def\figureparamstop{%
362   \par
363   \begin{tikzpicture}%[remember picture, overlay]
364     \pgfmathsetlength\@tempdima{-\textfloatsep}
365     \draw[>=latex,|<->|] (0,0) --++(0,\@tempdima)
366       node [right,fill=\geometrylabelcolor@cx]
367         at ++ (lex,0.5\textfloatsep)
368         {\CS{textfloasep} \convert@cx{\textfloatsep}};
369   \end{tikzpicture}%
370 }
```

\textheight
598 pt

8 Spread

The package provides a command to draw a two page spread as per the canons of page construction.

This is aimed at producing stand alone diagrams for inclusion into other packages or LaTeX notes, such a diagram is shown in Figure 3

```

371 \newlength\paperwidth@cx
372 \newlength\paperheight@cx
373 \newlength\lefttrim
374 \newlength\bottomtrim
375 \newlength\bindingcorrection
376 \setlength\paperwidth@cx{12in}
377 \setlength\paperheight@cx{18in}
378 \setlength\bindingcorrection{0.5in}
379
380 \cxset{spread xsteps/.store in=\spreadxsteps@cx,
381        spread scale/.store in=\spreadscales@cx,
382        spread width/.store in=\spreadwidth@cx}
383 %
384 %
385 \cxset{spread xsteps=9,
386        spread scale=0.25,
387        spread width=0.5\textwidth}% does not work
388
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

Page 15

\headheight 12 pt

\headsep 25 pt

\topfraction
.7




Figure 3: Diagram illustrating page geometry as per the Canons of Page Construction.

\textheight
598 pt

```
389 \tikzset{typearea/.style={color=black!85,fill=black!80,
390 font={\sffamily\bfseries}}}
391 %
```

\drawspread The macro \drawspread draws a spread, showing all lines and divisions as per classical rules.

```
392 \def\drawspread{%
393 \begin{tikzpicture}[scale=\spreadscale@cx]
394 % draw the two pages
395 \draw[xstep=(\paperwidth@cx)/\spreadxsteps@cx,
396 ystep=(\paperheight@cx)/\spreadxsteps@cx,color=gray] (0,0)
397 grid (\paperwidth@cx, \paperheight@cx);
398 \draw (0,0) rectangle (\paperwidth@cx,\paperheight@cx);
399
400 \begin{scope}[xshift=\paperwidth@cx+\bindingcorrection]
401 \draw[xstep=(\paperwidth@cx)/9,
402 ystep=(\paperheight@cx)/9,color=thegray] ++(0,0)
403 grid (\paperwidth@cx, \paperheight@cx);
404 \draw[color=black] (0,0) rectangle (\paperwidth@cx,\paperheight@cx);
405 \end{scope}
```

Next we draw the binding correction. This is drawn as a rectangle. We fill it with the same style shading as the type area.

```
406 \draw[typearea, draw] (\paperwidth@cx,0)
407 rectangle ++(\bindingcorrection, \paperheight@cx);
```

\footskip 30 pt

\marginparsep 11 pt

\oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 16

\headheight 12 pt

\headsep 25 pt

The typed area blocks are added next.

```
408 \draw[typearea] (2\paperwidth@cx/\spreadxsteps@cx,
409                 2\paperheight@cx/\spreadxsteps@cx)
410 rectangle ++(6/9*\paperwidth@cx,6*\paperheight@cx/\spreadxsteps@cx);
411
412 \draw[typearea] (\paperwidth@cx+\paperwidth@cx/9+\bindingcorrection,
413                 2\paperheight@cx/9) rectangle ++(6\paperwidth@cx/9,6\paperheight@cx/9);
414
415 \ifdim\bindingcorrection>0pt
416 \begin{scope}[typearea,color=white]
417 \draw node at
418       (\paperwidth@cx+0.5\bindingcorrection,
419        0.5\paperheight@cx)[rotate=90,inner sep=0pt,outer sep=0pt]
420       {\translate{bindingcorrectionname}};
421 \fi
422 \node at
423       (0.5\paperwidth@cx,0.5\paperheight@cx){\translate{leftpagename}};
424 \node at
425       (1.5\paperwidth@cx+\bindingcorrection,
426        0.5\paperheight@cx){\translate{rightpagename}};
427 \end{scope}
```

Next we draw the diagonals and the circles. We draw them within a scope to separate the styling from the drafting.

```
428 \begin{scope}[color=orange, line width=1pt]
429 \draw (0,0)-- (\paperwidth@cx,\paperheight@cx);
430 \draw (2\paperwidth@cx+\bindingcorrection,0)--
431       ++(-\paperwidth@cx,\paperheight@cx);
```

\textheight
598 pt

The circles are drawn in the same style as the diagonals. We do not provide an option to change this, as it will produce ugly diagrams.

```
432 \draw (0.5\paperwidth@cx,5\paperheight@cx/9)
433       circle (0.5\paperwidth@cx);
434 \draw [xshift=\paperwidth@cx+\bindingcorrection]
435       (0.5\paperwidth@cx,5\paperheight@cx/9)
436       circle (0.5\paperwidth@cx);
437 \end{scope}
438 \end{tikzpicture}
439 }
```

9 Try Layouts

The try layouts code, are helper macros to draw dimension lines on a diagram to experiment with different dimensions and layouts. In addition to this some helper commands are incorporated for readability.

10 Readability

In general the width of the typed area should not exceed 45-65 characters. This is language and reader dependent.

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

\alphabet The macro `\alphabet` returns the twenty six letters of the English language. This is used later on to calculate the length of an alphabet and provide related metrics for the readability of the text.

```
440 \def\alphabet{%
441 \normalfont\selectfont\raggedleft%
442 abcdefghijklmnopqrstuvwxyz}
```

\charactersperline The macro `charactersperline` typesets the number of characters in a line of text. We use `\pgfmithprintnumber` to format and print the number.

```
443 \newcommand\charactersperline{%
444 \settowidth{\@tempdima}{\alphabet}
445 \pgfmithparse{\textwidth/\@tempdima*26}
446 \pgfmithprintnumber{\pgfmithresult}
447 }
```

\alphabetsperline Some people are more familiar with the metric alphabets per line rather than characters per line. We provide the macro `\alphabetsperline`.

```
448 \newcommand\alphabetsperline{%
449 \settowidth{\@tempdima}{\alphabet}
450 \pgfmithparse{\textwidth/\@tempdima}
451 \pgfmithresult
452 }
```

\alphabetlength The macro `\alphabetlength` prints the length of the alphabet.

```
453 \newcommand\alphabetlength{%
454 \settowidth{\alphlength}{\alphabet}
455 \pgfmithparse{\alphlength}
456 \pgfmithprintnumber{\pgfmithresult}pt
457 }
```

$$\text{\textheight} 598\text{ pt}$$

We need to use the `fp` package to calculate the ratios, as PGF has problems with large dimensions or I am making an error

```
458 \newcommand\textarearatio{%
459 \FPmul{\result}{\strip@pt\textwidth}{\strip@pt\textheight}
460 \FPmul{\resulti}{\strip@pt\paperwidth}{\strip@pt\paperheight}
461 \FPdiv{\resultii}{\result}{\resulti}
462 \pgfmithprintnumber{\resultii}
463 }
```

```
464
465 % Calculate the ratio textheight/paperheight
466 \newcommand\textheightratio{%
467 \FPdiv{\result}{\strip@pt\textheight}{\strip@pt\paperheight}
468 \FPround{\result}{\result}{2}
469 \result
470 }
```

```
471 % Calculate textheight/paperwidth
```

```
472 \newcommand\textheighttopaperwidth{%
473 \pgfmithparse{\textheight/\paperwidth}
474 \pgfkeys{/pgf/number format/.cd,fixed,precision=2}
475
476 }
```

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

$$1\text{ in} + \text{\topmargin} (17\text{ pt}) = 55.27\text{ pt}$$

Page 18

\headheight 12 pt

\headsep 25 pt

```

477     \pgfmathprintnumber{\pgfmathresult}
478   }
479   \newcommand\numbertextlines{%
480     % baselineskip to be corrected
481     \pgfmathparse{(\textheight-\topskip)/(12)-1}\pgfmathresult
482   }

```

\printreadability

```

483   \def\printreadability{%
484     \begin{tabular}{lr}
485       Characters per line & \charactersperline\\
486       Alphabets per line & \alphabetsperline\\
487       Alphabet length & \alphabetlength\\
488       Baselineskip & \the\baselineskip\\
489       Number of text lines & \numbertextlines\\
490     \end{tabular}}

```

11 Page Layout Diagrams

This is one of the most important features of the package. Drawing and annotating a page diagram, so that you can view new geometry or use them for notes.

11.1 New lengths

We need to isolate the current page dimensions from the new trial sizes for the diagram. We redefine new lengths for all parameters with the prefix `try` and the suffix `@cx`.

\textheight
598 pt

```

491   \newlength\trypaperwidth@cx
492   \newlength\trypaperheight@cx
493   \newlength\trytextheight@cx
494   \newlength\tryheadheight@cx
495   \newlength\tryheadsep@cx
496   \newlength\tryfootskip@cx
497   \newlength\trymargin@cx
498   \newlength\trymarginbottom@cx
499   \newlength\trytopmargin@cx
500   \newlength\trimtop@cx
501   \setlength\trimtop@cx{0pt}
502   \newlength\trytextwidth@cx
503   \newlength\trymarginparwidth@cx
504   \newlength\trymarginparsep@cx
505   \newlength\tryleftmargin@cx
506   \newlength\tryinner@cx

```

The `stockheight` and `stockwidth` are used when the paper is to be trimmed they default to the dimensions for paper width and paper height, if not specified. The memoir class also defines them. If they are defined, we use the values from the class.

\stockheight
 \stockwidth

```

507   \@ifundefined{stockheight}{\global\newlength\stockheight}{\}

```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 19

\headheight 12 pt

\headsep 25 pt

```
508 \@ifundefined{stockwidth}{\global\newlength\stockwidth}{  
509  
510 \ifdim\stockheight=0pt\addtolength\stockheight{\paperheight}\fi  
511 \addtolength\stockheight{0mm}  
512 \ifdim\stockwidth=0pt\addtolength\stockwidth{\paperwidth}\fi  
513 \addtolength\stockwidth{0mm}  
514  
515 \newlength\trystockheight@cx  
516 \newlength\trystockwidth@cx  
517 \cxset{try stockwidth/.code=\setlength\trystockwidth@cx{#1},  
518 try stockheight/.code=\setlength\trystockheight@cx{#1},  
519 try stock/.code=} % a4paper etc to be developed toninght  
520 \cxset{try stockwidth=\paperwidth}  
521 \cxset{try stockheight=\paperheight}
```

We set all the trims to zero to start with.

```
522 %  
523 \newlength\trimtop  
524 \newlength\trimedge  
525 \setlength\lefttrim{5mm}  
526 \setlength\bottomtrim{10pt}  
527 \setlength\trimtop{0pt}  
528 \setlength\trimedge{0pt}  
529 %  
530 %  
531 % set defaults  
532 \setlength\trymargintop@cx{0pt}  
533 \setlength\trymarginparsep@cx{\marginparsep}  
534 \setlength\trymarginparwidth@cx{\marginparwidth}  
535 \setlength\trytextwidth@cx{0pt}  
536 \newlength\trytrimedge@cx  
537 \setlength\trytrimedge@cx{10pt}  
538  
539 \newlength\tryoddsidemargin@cx  
540 \setlength\tryoddsidemargin@cx{\oddsidemargin}  
541 \newlength\tryevensidemargin@cx  
542 \setlength\tryevensidemargin@cx{\evensidemargin}  
543 \newlength\tryinnermargin@cx  
544 % convenience lengths for drawing the layouts.  
545 \newlength\tryINNER  
546 \newlength\tryTOP  
547  
548 \newlength\margintop  
549  
550 \newcommand\thetop{%  
551 \pgfmathparse{1in+\topmargin+\headheight+\headsep}  
552 \pgfmathsetlength{\margintop}{\pgfmathresult}  
553 }  
554 %  
555  
556 \thetop  
557
```

\textheight
598 pt

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

Page 20

\headheight 12 pt

\headsep 25 pt

```

558 \newlength\marginbottom
559 \newcommand\thebottom{%
560     \pgfmathparse{\stockheight-(1in+\topmargin+\headheight+\headsep+\textheight)}
561     \pgfmathsetlength{\marginbottom}{\pgfmathresult}
562 }
563
564 \thebottom

```

We provide keys to set all trial dimensions. These default to the current document, dimensions.

```

565 \cxset{try textheight/.code=\global\setlength\trytextheight@cx{#1},
566         try textheight/.default=\textheight,
567         try headheight/.code=\global\setlength\tryheadheight@cx{#1},
568         try headheight/.default=\headheight, % T0 CHECK
569         try headsep/.code=\global\setlength\tryheadsep@cx{#1},
570         try headsep/.default=\headsep, %TODO CHECK
571         try footskip/.code=\global\setlength\tryfootskip@cx{#1},
572         try footskip/.default=\footskip,
573         try topmargin/.code=\global\setlength\trytopmargin@cx{#1},
574         try topmargin/.default=\topmargin,
575 }
576
577 \cxset{try trimtop/.code=\global\setlength\trimtop@cx{#1},
578         try trimtop/.default=\global\setlength\trimtop{0pt}},
579
580 % set all the defaults
581
582 \cxset{try textheight,
583         try headheight,
584         try headsep,
585         try footskip,
586         try topmargin=0pt, % compensate for trim
587         try trimtop=10pt}
588
589 \setlength\trytopmargin@cx{\topmargin}
590
591
592 \cxset{try textwidth/.code=\global\setlength\trytextwidth@cx{#1},
593         try trimedge/.code=\global\setlength\trytrimedge@cx{#1},
594 }
595
596 \cxset{try textwidth=\textwidth,
597         try trimedge=10pt}

```

\textheight
598 pt

\@trydiagonal The switch \@trydiagonal is used in keys to draw or skip the Page Construction Canon, diagonal line.

```

598 \newif\if@trydiagonal
599 \@trydiagonalfalse
600
601 \cxset{try diagonal/.is choice,
602         try diagonal/true/.code=\@trydiagonaltrue,
603         try diagonal/false/.code=\@trydiagonalfalse,

```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight } 12\text{ pt}$$

$$\text{\headsep } 25\text{ pt}$$

```

604         try diagonal/none/.code=\trydiagonalfalse}
605
606     \cxset{try diagonal=false}

\trygrid The try grid conditional provides a switch to switch the grid on or off. We set it
initially to true.

607     \newif\iftrygrid
608     \trygridfalse
609
610     \cxset{try grid/.is choice,
611           try grid/true/.code=\trygridtrue,
612           try grid/false/.code=\trygridfalse,
613           try grid/none/.code=\trygridfalse}
614
615     \cxset{try grid=true}

```

11.2 Allowances for trims

Throughout we are focusing on the average LaTeX user than might want to for example use A4 paper and trim down to a different size. We start from the stockwidth and stockheight and we set the paperwidth and paperheight to a smaller size to cater for these trims.

I call this process trimming in, whereas other packages such as the crop increase the paper size to allow for the trims, thus displaying a larger page. The memoir class has something similar.

```

\trypaperwidth@cx We set the length to stocksize-trimedge.
\trypaperheight@cx
616     % set the trial paper sizes as per trim sizes
617     \addtolength\trypaperwidth@cx{\trystockwidth@cx}
618     \addtolength\trypaperwidth@cx{-\trytrimedge@cx}
619     \addtolength\trypaperheight@cx{\trystockheight@cx}
620     \addtolength\trypaperheight@cx{-\trimtop@cx}
621     \addtolength\trypaperheight@cx{-\bottomtrim}

```

$$\text{\textheight } 598\text{ pt}$$

11.2.1 Calculating the Top Margin and Bottom Margin

We calculate the top and bottom margins for convenience. Remember that so far we are only dealing with default settings. If the user changes the dimensions, these will have to be recalculated.

```

622     %\addtolength\trymargintop@cx{\lin+\voffset+\trimtop@cx}
623     %\addtolength\trymargintop@cx{\dimexpr(\tryheadsep@cx+
624     %   \tryheadheight@cx+\trytopmargin@cx)}

```

11.2.2 Adjustments to text height

Since we are trimming-in, our paper height will end up being smaller than the stock paper height. One is thus faced with the decision to either make the top and bottom margins smaller to allow for the trimming or to reduce the text height accordingly.

Most people and publishers are fussy about margins, so perhaps it is better to reduce the text-height. We offer a method to the user to specify preferences later

$$\text{\footskip } 30\text{ pt}$$

$$\text{\marginparsep } 11\text{ pt}$$

$$\text{oddsidemargin } 28\text{ pt}$$

$$\text{\textwidth } 380\text{ pt}$$

$$\text{\marginparwidth } 101\text{ pt}$$

$$\text{driver margin } 1\text{ in}$$

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

on. In the meantime for the purpose of defaults, we will take all the adjustment at the bottom margin and leave the text-height untouched.

```
\trytextheight@cx Let trytextheight@cx equal to the current document \textheight value.
625 \setlength\trytextheight@cx{\textheight}
626 \setlength\trymarginbottom@cx{%
627 \dimexpr(\trystockheight@cx-1in-\trimtop@cx-\trytopmargin@cx
628 -\tryheadheight@cx-\tryheadsep@cx-\trytextheight@cx)\relax}
629
630
631 \newlength\stepx
```

11.3 Drawing the Trial Layout

The trial layout is drawn in a lengthy TikZ picture. If no new dimensions are provided by the user it will default to the values we have set it previously. That is the current layout values.

`\drawtriallayout` The macro `\drawtriallayout` draws the page diagram. It uses throughout trial dimensions.

```
632 \tikzset{dim/.style = {color=black,>=latex}}
633 \def\drawtriallayout{%
    We first need to check if we are on an odd or even page and set the geometry
    accordingly. If the document is one-side we default to drawing everything as an
    odd-side page.
634 \checkoddpage%
635 \if@twoside\else\oddpagetrue\fi
636 \ifoddpage
637 \global\setlength\tryinnermargin@cx{\tryoddsidemargin@cx}
638 \setlength\tryINNER{\dimexpr(1in+\tryinnermargin@cx+\hoffset)}
639 \else
640 \global\setlength\tryinnermargin@cx{\tryevensidemargin@cx}
641 \setlength\tryINNER{\dimexpr(1in+\tryinnermargin@cx+\hoffset)}
642 \fi
643
644 \hspace*{-2cm}\begin{tikzpicture}[scale=0.42,font={\scriptsize\rmfamily},line width=.8pt,
645 every node={color=black},
646 book trim/.style={color=theblue,fill=white},
647 dim text/.style={color=black},
648 textblock/.style={fill=gray,opacity=0.3}]
649
650 \edef\tol{-2.5\baselineskip}
651 %
652 \def\drawpaperwidthdim{%
653 \coordinate (A) at (0,\tol);
654 \coordinate (B) at (\trystockwidth@cx -\trytrimedged@cx,\tol);
655 \coordinate (C) at (0.5\trystockwidth@cx,\tol);
656 \draw [dim, |<->] (A) -- (B);
657 \node at (C) [yshift=0.5\baselineskip]
```

$$\text{\textheight} 598\text{ pt}$$

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

1 in + \topmargin (17 pt) = 55.27 pt

Page 23

\headheight 12 pt

\headsep 25 pt

```
658     {paper width = \convert@cx{\trypaperwidth@cx} $(W_p)$};
659
660     % Draw paper width dimension
661     \def\drawpaperwidththevendim{%
662         \coordinate (A) at (0+\trytrimedge@cx,\tol);
663         \coordinate (B) at (\trystockwidth@cx,\tol);
664         \coordinate (C) at (0.5\trystockwidth@cx,\tol);
665         \draw[dim, |<->|] (A) -- (B);
666         \node at (C) [yshift=0.5\baselineskip]
667         {paper width = \convert@cx{\trypaperwidth@cx} $(W_p)$};
668     }
```

11.3.1 Draw stock paper

First we draw the stockwidth and stockheight

```
669     \draw [color=thegray] (0,0) rectangle
670         ++(\trystockwidth@cx,\trystockheight@cx);
671
672     % draw the paper if trims are defined and no book size given
673     % the paper width is then defined by the dashed blue line
674     \ifoddpage
675         \draw [book trim] (0+\lefttrim,\trystockheight@cx-\trimtop@cx)
676             rectangle ++(\trystockwidth@cx-\lefttrim-\trytrimedge@cx,
677                 -\trystockheight@cx+\trimtop@cx+\bottomtrim);
678         \drawpaperwidthdim
679     \else
680         \draw [book trim] (0+\lefttrim+\trytrimedge@cx,\trystockheight@cx-\trimtop@cx)
681             rectangle ++(\trystockwidth@cx-\lefttrim-\trytrimedge@cx,
682                 -\trystockheight@cx+\trimtop@cx+\bottomtrim);
683         \drawpaperwidththevendim
684     \fi
685
```

\textheight
598 pt

11.3.2 Draw grid

Unlike the grid on page spreads we provide a conditional to switch it off if necessary. It set to true by default.

```
686     \pgfmathsetmacro{\gridx}{10}
687     \iftrygrid
688         \ifoddpage
689             \draw[xstep=(\trypaperwidth@cx-\lefttrim)/\gridx,
690                 ystep=\trypaperheight@cx/\gridx,color=thegreen!50,
691                 line width=0.4pt,yshift=\bottomtrim,xshift=\lefttrim]
692                 (0,0) grid (\trypaperwidth@cx-\lefttrim,\trypaperheight@cx);
693         \else
694             \draw[xstep=(\trypaperwidth@cx)/\gridx,
695                 ystep=\trypaperheight@cx/\gridx,color=thegreen,
696                 line width=0.4pt,yshift=\bottomtrim,xshift=\trytrimedge@cx]
697                 (0,0) grid ++(\trypaperwidth@cx,\trypaperheight@cx);
698         \fi
699     \fi
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 24

\headheight 12 pt

\headsep 25 pt

11.3.3 Drawing the binding correction

The binding correction is added to the stockheight. It will appear on the opposite site in the even page.

```
700 \ifoddpage
701 \draw (0, \trystockheight@cx + 3mm) -- ++ (0,1cm)
702 ++ (\lefttrim,-1cm) -- ++(0,1cm) ++(-1cm-\lefttrim,-0.5cm)[->,>=latex]
703 -- ++(0.5cm+\lefttrim,0);
704 \draw (0, \trystockheight@cx + 3mm)
705 ++ (0,0.5cm) -- ++ (\lefttrim,0)
706 ++(1cm,0cm)[|>,>=latex]-- ++(-1cm,0cm)
707 node[right] at ++(1cm,0)
708 {\translate{bindingcorrectionname}\ \convert@cx{\lefttrim} {\delta_b}$ };
709 \fi
710
711 % stockwidth dimension lines
712 \edef\tol{-5\baselineskip}
713 \coordinate (BD) at (0,\tol);
714 \coordinate (BD2) at (\stockwidth,-5\baselineskip);
715 \draw[dim,|<->|] (BD) -- (BD2);
716 \draw (BD) ++ (0.5\stockwidth,0)
717 node [yshift=0.5\baselineskip]
718 {stockwidth=\convert@cx{\stockwidth} $(W_s)$} ;
719
720 % top dimension at left
721 \coordinate (H1) at (-5mm,\trystockheight@cx-\trimtop@cx);
722 \coordinate (H2) at (-5mm,
723 \trystockheight@cx-1in-\trimtop@cx-\trytopmargin@cx-
724 \tryheadheight@cx-\tryheadsep@cx);
725 \draw [dim,|<->|] (H1) -- (H2);
726 \node[left,text width=1.0cm, text centered,dim text] at
727 (-5mm,\trystockheight@cx-0.5*\margintop)
728 {top\ \convert@cx{\the\margintop}\$(h_t)$};
729
730 % bottom dimension at left
731 \coordinate (H3) at (-5mm,0+\bottomtrim);
732 \coordinate (H4) at (-5mm,\trymarginbottom@cx);
733 \draw [dim,|<->|] (H3) -- (H4);
734 \node[left,text width=1.5cm,text ragged left]
735 at (-5mm,0.5*\trymarginbottom@cx)
736 {bottom\ \convert@cx{\the\trymarginbottom@cx}\
737 $(h_b)$};
738
739 % textheight at left
740 \draw[dim,<->] (-5mm, \trymarginbottom@cx)
741 -- ++ (0,\trytextheight@cx);
742 \node[left,text width=1.6cm,text centered,dim text]
743 at (-5mm,\trymarginbottom@cx+0.5\trytextheight@cx)
744 {\CS{textheight} \convert@cx{\trytextheight@cx}\
745 $(h_x)$ };
746
```

\textheight
598 pt

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

11.3.4 Book height

Book sizes are specified by the size of the final trimmed sizes. for most users there is no need to worry about trims and binding corrections, however we provide these for consistency and for books that are perhaps to be sent to an on-line bureau for printing.

```

747 \draw [dim,|<->|] (-4.7cm,\bottomtrim) --
748 (-4.7cm,0.5\trystockheight@cx-0.5\trimtop@cx)
749 node[left,text width=1.2cm,text centered,dim text]
750 {\translate{bookheightname}\ \convert@cx{\trypaperheight@cx}} --
751 (-4.7cm,\trystockheight@cx-0.5\trimtop@cx) ;

```

11.3.5 Draw the edge trim

The paper is always assumed to be trimmed at top bottom and the edge margin. We first draw the edge trim and its dimension.

```

752 \ifdim\trytrimmedge@cx>0pt
753 \ifoddpage
754 \coordinate (D) at (\trystockwidth@cx-4\trytrimmedge@cx,
755 0.10\trytextheight@cx);
756 \coordinate (E) at (\trystockwidth@cx,0.10\trytextheight@cx);
757 \draw [dim,->|] (D) -- ++(3\trytrimmedge@cx,0);
758 \draw [dim,|<-|] (E) -- ++(3\trytrimmedge@cx,0)
759 node at ++(0,0) [right,text width=2cm,dim text]
760 {\translate{trimmedgename}\
761 \convert@cx{\the\trytrimmedge@cx}
762 $(\Delta_e)$};
763 \else
764 \coordinate (D1) at (0, \trystockheight@cx+ 5mm);
765 \coordinate (E1) at ++ (\trytrimmedge@cx,\stockheight+\trimtop@cx);
766 \draw (D1) -- ++ (0, 10mm) ++(\trytrimmedge@cx,0) -- ++(0,-10mm) ;
767 \fi
768 \fi

```

$$\text{\textheight} 598\text{ pt}$$

11.3.6 The top trim

The top trim is drawn next. As it is very small normally we try not to crowd the label and the dimension lines. We will only show it if it has a value.

```

769 %\ifdim\trimtop>0pt
770 \ifdim\trimtop>0pt
771 \coordinate (F) at (0.9\trystockwidth@cx,\trystockheight@cx-\trimtop@cx-8mm);
772 \coordinate (G) at (0.9\trystockwidth@cx,\trystockheight@cx-\trimtop@cx);
773 \coordinate (H) at (0.9\trystockwidth@cx,\trystockheight@cx);
774 \draw (F)[dim,->|,>=latex] -- (G);
775 \draw (H) -- ++ (0,8mm) -- ++ (5mm,0)[|<-|,>=latex]
776 node [text width=2cm, right] at ++ (0,3pt) {\translate{trimtopname}\
777 \ \convert@cx{\the\trimtop@cx} $(\Delta_t)$};
778 %\fi

```

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

11.3.7 Driver offsets

Next we draw the driver offsets. The lines are drawn at the left side of the paper both for even and for odd paper. Of course they are meaningless if the printer is going to print them on an A3 paper for example, and then the paper is trimmed.

```

779 \draw[fill=olive] (lin,\trystockheight@cx-lin) circle (1.5mm);
780 \draw[dashed,color=olive] (lin,0) -- (lin,\trystockheight@cx);
781 \draw[dashed,color=olive] (0in,\trystockheight@cx-lin)-- ++ (\trystockwidth@cx,0);
782 \draw [dim,|<->|](0,0.3cm)-- (lin,0.3cm) node at (0.5in,0.6)[dim text] {\translate{oneinch

```

Draw the inner margin. We use innermargin which has already been set to either oddsidemargin or evensidemargin

```

783
784 % Draw left = lin + innermargin
785 \setlength\tryleftmargin@cx{\dimexpr(lin+\innermargin)}
786 \draw [dim,|<->|] (0in,1.9cm) -- (lin+\innermargin,1.9cm)
787 node at (0.6in,3.2cm)[text width=lin,dim text,text centered]
788 {\$(w_i)\$\\ \convert@cx{\tryleftmargin@cx}{\inner margin}};
789
790 \draw (lin,1.2cm)[|<->|] -- ++(\innermargin,0) node[right,dim text]
791 {\innermarginname\ \convert@cx{\the\innermargin} {\Delta_i}};
792
793
794 % add topmargin dimension
795
796 \setlength{\@tempdimc}{\dimexpr(lin-\trimtop@cx+\trytopmargin@cx)\relax} \textheight
797 \coordinate (S1) at (\trystockwidth@cx+3ex,\trystockheight@cx-\trimtop@cx); 598pt
798 \draw [dim,|<->|] (S1)
799 -- ++ (0,-\@tempdimc-\trimtop@cx)
800 node [right, dim text, text width=3.5cm] at
801 ++(2ex,0.5\@tempdimc) {\convert@cx{\@tempdimc} {\Delta_t}}$
802 \\ \textbackslash topmargin \convert@cx{\trytopmargin@cx}};

```

11.3.8 Draw the running head

The running head is drawn measuring from the top of the page.

```

803 \pgfmathsetlength{\@tempdimb}{\trystockheight@cx-
804 \trimtop@cx-lin-\trytopmargin@cx}
805
806 \draw[textblock] (\tryINNER, \@tempdimb)
807 rectangle ++ (\trytextwidth@cx,-\tryheadheight@cx);
808
809 % add headheight dimension
810 \draw [dim,-|,>=stealth] (\trystockwidth@cx+3ex, \@tempdimb)
811 -- ++(0,-\tryheadheight@cx) node [right,dim text] at
812 ++(2ex,0.3\tryheadheight@cx)
813 {\CS{headheight} \convert@cx{\the\tryheadheight@cx} {\(h_{h,h})}};
814 %
815 %% add headsep dimension
816 \draw [dim,-|,] (\trystockwidth@cx+3ex,
817 \@tempdimb-\tryheadheight@cx-\tryheadsep@cx)
818 -- ++(0,\tryheadsep@cx) node [right, dim text] at

```

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

$$1\text{ in} + \text{\topmargin}(17\text{ pt}) = 55.27\text{ pt}$$

$$\text{\headheight} 12\text{ pt}$$

$$\text{\headsep} 25\text{ pt}$$

```
819      ++(2ex,-0.8\tryheadsep@cx){\CS{headsep}
820      \convert@cx{\the\tryheadsep@cx} {(h_{h,s})}};
```

11.3.9 Type area

Next we add the type area and its dimension.

```
821      \coordinate (J) at (\tryINNER,
822      \@tempdimb-\tryheadsep@cx-\tryheadheight@cx);
823      \draw[textblock] (J) rectangle ++ (\trytextwidth@cx,-\trytextheight@cx);
824      \draw[dim,<->|,dim text] (\tryINNER,0.75\trytextheight@cx)
825      -- ++(\trytextwidth@cx, 0)
826      node at ++(-0.5\trytextwidth@cx,0.8\baselineskip){\labelit@cx{\textwidth}};
827
828      % add textheight dimension
829      \draw [dim,<->] (\trystockwidth@cx+3ex,
830      \@tempdimb-\tryheadsep@cx-\tryheadheight@cx) --
831      ++(0,-\trytextheight@cx) node [right, dim text, text width=2.5cm]
832      at ++(2ex,0.5\trytextheight@cx)
833      {\CS{textheight}}\ \convert@cx{\the\trytextheight@cx}{(h_x)}$};
```

11.3.10 Footer

Add the footer and its dimension.

```
834      \coordinate (I) at (\tryINNER,
835      \@tempdimb-\tryheadsep@cx-
836      \tryheadheight@cx-\trytextheight@cx-\tryfootskip@cx);
837      \draw[textblock] (I) rectangle ++ (\trytextwidth@cx,\tryheadheight@cx);
838      \draw [dim,<->|,>=stealth] (\trystockwidth@cx+3ex,\@tempdimb-\tryheadsep@cx-
839      \tryheadheight@cx-\trytextheight@cx) --
840      ++(0,-\tryfootskip@cx) node [right, dim text] at
841      ++(2ex,0.5\tryfootskip@cx){%
842      \labelit@cx{\tryfootskip@cx}{(h_f)}$};
843      %
844      %
845      % marginpar
846      \def\leftmarginpar{%
847      \draw [textblock] (\tryINNER+\trytextwidth@cx+\trymarginparsep@cx,
848      \@tempdimb-\tryheadsep@cx-\tryheadheight@cx) rectangle ++(\trymarginparwidth@cx,-\tr
849      \draw [dim,<->|] (\tryINNER+\trytextwidth@cx+\trymarginparsep@cx
850      +\trymarginparwidth@cx,0.75\trytextheight@cx)
851      -- ++ (-\trymarginparwidth@cx,0) node at
852      ++(0.5\trymarginparwidth@cx,0.7\baselineskip)
853      {marginparwidth} node at ++(0.5\trymarginparwidth@cx,-\baselineskip)
854      {\convert@cx{\the\trymarginparwidth@cx} {(w_{m,w})}}$};
855
856      % Draw the marginsep dimension above
857      \draw [dim,|-|] (\tryINNER+\trytextwidth@cx,0.85\trytextheight@cx)
858      -- ++ (\trymarginparsep@cx,0)
859      node[right,dim text,text width=2cm,text centered] at
860      ++(-3ex,12pt) {marginparsep\ \convert@cx{\trymarginparsep@cx} {(w_{m,s})}}$ };
861      }
```

$$\text{\textheight} 598\text{ pt}$$

$$\text{\footskip} 30\text{ pt}$$

$$\text{\marginparsep} 11\text{ pt}$$

$$\text{oddsidemargin} 28\text{ pt}$$

$$\text{\textwidth} 380\text{ pt}$$

$$\text{\marginparwidth} 101\text{ pt}$$

$$\text{driver margin} 1\text{ in}$$

1 in + \topmargin (17 pt) = 55.27 pt

Page 28

\headheight 12 pt

\headsep 25 pt

```
862 %
863 \def\rightmarginpar{%
864   \draw [textblock] (\tryINNER-\trymarginparsep@cx,
865     \@tempdimb-\tryheadsep@cx-\tryheadheight@cx)
866     rectangle ++(-\trymarginparwidth@cx,-\trytextheight@cx);
867   \draw [dim,|<->|] (\tryINNER-\trymarginparsep@cx-\trymarginparwidth@cx,
868     0.75\trytextheight@cx) -- ++ (\trymarginparwidth@cx,0) node at
869     ++(-0.5\trymarginparwidth@cx,0.5\baselineskip) {marginparwidth.} node at
870     ++(-0.5\marginparwidth,-\baselineskip){\convert@cx{\the\marginparwidth}};
871 }
872 %
873 %
874 \drawmarginparstrue
875 \ifdrawmarginpars
876   \ifoddpages
877     \leftmarginpar
878   \else
879     \rightmarginpar
880   \fi
881 \fi
```

11.3.11 Page Construction Canon Diagonal Lines

If the conditional @trydiagonal is set to true draw the diagonal lines. At false or none skip.

```
882 \if@trydiagonal
883   \ifoddpages
884     \draw [color=blue!30] (\trystockwidth@cx-\trytrimedge@cx,\bottomtrim)
885       -- (\lefttrim, \trystockheight@cx-\trimtop@cx);
886   \else
887     \draw [color=blue!30] (\trytrimedge@cx,0)
888       -- (\paperwidth,\paperheight-\trimtop@cx);
889   \fi
890 \fi
891 \end{tikzpicture}
892 }
893
```

\textheight
598 pt

12 Lists

List diagrams are developed using the techniques we have used so far for the pages. We define layouts to visualize them.

`\drawlist` The macro `\drawlist` draws an outline of an enumerated or any type of list illustrating the main parameters affecting its layout. It is based on ideas presented originally in the `layouts` package and a sample is shown in figure 4

```
894 \newlength\tempa@cx
895 \newlength\tempb@cx
896 \newlength\tempc@cx
897 \newlength\listdiagramheight
898 \newlength\listdiagramwidth
```

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in




Figure 4: List diagram, showing LaTeX geometry definitions.

```

899
900 \def\drawlistdiagram{%
901   \begin{tikzpicture}[scale=0.5,dim/.style={font={\footnotesize}},
902                     block/.style={color=thegreen}]
903   \pgfmithsetmacro{\yscale}{8}
904   \pgfmithsetlength{\tempa@cx}{\yscale*(\topsep+\parskip+\partopsep)}
905   \pgfmithsetlength{\tempb@cx}{\yscale*(\itemsep+\parsep)}
906   \pgfmithsetlength{\tempc@cx}{\yscale*(\parsep)}
907   \pgfmithsetlength{\listdiagramheight}{13cm+2*\tempa@cx+\tempb@cx+\tempc@cx}
908   \pgfmithsetlength{\listdiagramwidth}{\textwidth+10cm}

```

We first draw a block to reprsentsome text and the block on a page.

```

909 \draw[color=thegray!60] (0,0) rectangle (\listdiagramwidth,\listdiagramheight);
910 \draw[color=thegray!60] (0,0) rectangle (\listdiagramwidth, 2cm);
911 \draw (0,\listdiagramheight) rectangle (\listdiagramwidth,\listdiagramheight-2cm)
912       node at ++ (-0.5\listdiagramwidth,1cm){\translate{precedingtextname}};
913 \node at (0.5\listdiagramwidth,1cm) {\translate{followingtextname}};

```

Next we are going to draw the item shape. First we draw the rectangle with the indentation.

\putlistblock@cx

```

914 \def\putlistblock@cx##1##2{%
915   \coordinate (A) at (##1,##2);
916   \coordinate (B) at (##1-40pt,##2-20pt);
917   \draw[block] (A) -- ++ (\textwidth,0pt)
918                 -- ++ (0, 3cm)

```


1 in + \topmargin (17 pt) = 55.27 pt

Page 30

\headheight 12 pt

\headsep 25 pt

```
919      -- ++ (-\textwidth+ 30pt,0)
920      -- ++ (0, -24pt)
921      -- ++ (-30pt,0)
922      -- ++ (0,-3cm+24pt);
923  % dra wthe label rectangle
924  \draw[block,color=black] (B) ++ (-2cm, 3cm) rectangle ++ (4cm, 22pt )
925    node[dim] at ++(-2cm,-11pt) {\translate{labelname}};
926  % draw dimension lines
927  \draw (B) ++ (0, 3cm+26pt) -- ++ (0,0.8cm) ++ (2cm,-0.8cm)---++(0,0.8cm) ++ (10pt,-0.8cm)
928    ---++ (0,0.8cm); %labelsep
929  % draw arrows
930  \settowidth\@tempdima{labelwidth}
931  \draw[dim] [<->,>=latex] (B) ++ (-2cm, 3cm+26pt)++(0,0.4cm)-- ++(4cm,0)
932    node[dim] at ++ (- 2cm-\@tempdima-50pt,8pt)
933    {\labelit@cx{\labelwidth}};
934
935  \draw[dim] (B) ++ (0, 3cm+26pt+0.4cm) -- ++ (2cm+10pt,0)
936    ++ (0.5cm,0)---++(-0.5cm,0)[<->,>=latex]
937    node[right] at ++(0.45cm,0) {\labelit@cx{\labelsep}};
938  % draw itemsep
939
940  \draw[<->,>=latex] (A)++(0,1.5cm) -- ++(30pt,0) ;
941  \draw (A)++(30pt,1.20cm )---++ (0pt,1.8cm-27pt) node at ++(0,0)[below right]
942    {\labelit@cx{\itemindent}}; % draw dimline
943    \node[dim] (A) at (##1,##2)[above right] {\textsc{Item}};
944
945  % draw leftmargin and right margin
946
947  \draw[<->,>=latex] (A) ++ (-24pt,0pt) -- ++(-5cm,0pt)
948    node at ++(0,0)[above right] {\labelit@cx{\leftmargin}};
949  \draw[<->,>=latex] (A) ++ (-24pt+\textwidth,0pt) -- ++(5cm,0pt)
950    node at ++(0,0)[above left] {\labelit@cx{\rightmargin}};
951  }
952  %
953  %
954  \def\putlistparblock@cx##1##2{%
955    \coordinate (A) at (##1,##2);
956    \coordinate (B) at (##1-40pt,##2-20pt);
957    \draw[block] (A) -- ++ (\textwidth,0pt)
958      -- ++ (0, 3cm)
959      -- ++ (-\textwidth+ 20pt,0)
960      -- ++ (0, -24pt)
961      -- ++ (-20pt,0)
962      -- ++ (0,-3cm+24pt);
963
964  \draw[<->,>=latex] (A)++(0,1.5cm) -- ++(20pt,0) ;
965  \draw (A)++(20pt,1.20cm )---++ (0pt,1.8cm-27pt) node at ++(0,0)[below right]
966    {\labelit@cx{\listparindent}};
967
968  \draw[<->,>=latex] (A) ++ (-0pt,8pt) -- ++(-5cm,0pt)
969    node at ++(0,0)[above right] {\labelit@cx{\leftmargin}};
```

\textheight
598 pt

\footskip 30 pt

\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in

1 in + \topmargin (17 pt) = 55.27 pt

Page 31

\headheight 12 pt

\headsep 25 pt

```
970 \draw[<->,>=latex] (A) ++ (0pt+\textwidth,8pt) -- ++(5cm,0pt)
971 node at ++(0,0)[above left] { \labelit@cx{\rightmargin}};
972
973 \node[dim] (A) at (##1,##2)[above right] {\textsc{Item Paragraph}};
974 }
975
976 %
977 % We start by drawing the blocks. We draw three blocks, the first and last show items, wherea
978 % the middle one shows a paragraph within an item.
979 % Since values for list parameters are small, we scale everything up.
980 % |\tempa@cx = scaled topsep + parskip + partopsep|
981 % |\tempb@cx = scaled itemsep + parsep|
982 %
983 % \end{macrocode}
984 % \begin{macrocode}
985 \putlistblock@cx{5cm}{2cm+\tempa@cx} % 8cm
986 \draw [ <->,>=latex] (0.5\paperwidth, 2cm)-
987 -++(0,\tempa@cx) node at ++(0,-0.5\tempa@cx) [right]
988 {\labelit@cx{\topsep}+\labelit@cx{\parskip} +\labelit@cx{\partopsep}};
989
990 % second block
991 \putlistparblock@cx{5cm}{2cm+\tempa@cx+3cm+\tempb@cx}
992 \draw [->,>=latex] (0.5\paperwidth, 2cm+\tempa@cx+3cm+\tempb@cx) --++(0,-\tempb@cx)
993 node at ++(0,0.5\tempb@cx) [right]
994 {\labelit@cx{\itemsep}+\labelit@cx{\parsep}=
995 \pgfmathparse{\itemsep+\parsep}\convert@cx{\pgfmathresult}};
996
997 %% third block
998 \putlistblock@cx{5cm}{2cm+\tempa@cx+6cm+\tempb@cx +\tempc@cx}
999 \draw [->,>=latex] (0.5\paperwidth,2cm+\tempa@cx+6cm+\tempb@cx +\tempc@cx )
1000 --++(0,-\tempc@cx)
1001 node at ++(0,0.5\tempc@cx) [right] {\labelit@cx{\parsep}};
1002
1003 % add finally the top arrow
1004 \draw [->,>=latex] (0.5\listdiagramwidth, \listdiagramheight-2cm)--++(0,-\tempa@cx)
1005 node at ++(0,0.5\tempa@cx) [right]
1006 {\labelit@cx{\topsep}+\labelit@cx{\parskip}+\labelit@cx{\partopsep}=
1007 \pgfmathparse{\topsep+\parskip+\partopsep}\convert@cx{\pgfmathresult}};
1008
1009 %
1010 \end{tikzpicture}
1011 }
```

\textheight
598 pt

12.1 Tabulating List values

\printlistvalues The command \printlistvalues produces a short table showing the list parameters and their values (see Table 1 for an example).

```
1012 \def\printlistvalues{%
1013 \begin{tabular}{lr}
1014 \toprule
1015 Parameter & Value\\
```

\footskip 30 pt


\marginparsep 11 pt

oddsidemargin 28 pt

\textwidth 380 pt

\marginparwidth 101 pt

driver margin 1 in



Parameter	Value
leftmargin	1.83 pc
rightmargin	1.83 pc
itemindent	0 pc
labelwidth	1.42 pc
labelsep	0.42 pc
listparindent	0 pc
topsep	0.33 pc
partopsep	0.17 pc
parsep	0.17 pc
itemsep	0.17 pc

Table 1: Tabulation of LaTeX list values, for the *quotation* environment.

```
1016      \midrule
1017      leftmargin & \convert@cx{\the\leftmargin}\\
1018      rightmargin & \convert@cx{\the\rightmargin}\\
1019      itemindent & \convert@cx{\itemindent}\\
1020      labelwidth & \convert@cx{\labelwidth}\\
1021      labelsep & \convert@cx{\labelsep}\\
1022      listparindent& \convert@cx{\listparindent}\\
1023      topsep & \convert@cx{\topsep}\\
1024      partopsep & \convert@cx{\partopsep}\\
1025      parsep & \convert@cx{\parsep}\\
1026      itemsep & \convert@cx{\itemsep}\\
1027      \bottomrule
1028      \end{tabular}
1029 }
```

13 Draw a Font box

We provide a command that can draw a box and font dimensions. We will use TikZ for drafting and styling. We also provide the macro `\printfontparams` to print font parameters. This will produce a table as shown in Table 2 and Table 3.

Parameter	Value
Font encoding	T1
font family	fve
font series	m
font shape	n
font size	10
baselineskp	12.0pt

Table 2: Font details for the current document font.

1 in + \topmargin (1.42 pc) = 4.61 pc


\headheight 1 pc

\headsep 2.08 pc

Parameter	Value
fontdimen1 (slant per point) is	0.0pt
fontdimen2 (interword space)	2.86197pt
fontdimen3 (interword stretch)	1.71898pt
fontdimen4 (interword shrink)	0.68399pt
fontdimen5 (x-height)	4.67096pt
fontdimen6 (quad width)	8.99994pt
fontdimen7 (extra space)	0.68399pt

Table 3: Font dimension details for the current document font.

To draw a fontbox, we use



This draws `\font{werty}`.

\topfraction
.7

\printfontparams

```
1030 \newcommand{\printfontparams}{%
1031 \begin{tabular}{lc}
1032 \toprule
1033 Parameter & Value\\
1034 \midrule
1035 Font encoding & \f@encoding\\
1036 font family & \f@family\\
1037 font series & \f@series\\
1038 font shape & \f@shape\\
1039 font size & \f@size\\
1040 baselineskip & \f@baselineskip\\
1041 \bottomrule
1042 \end{tabular}
1043 }
```

\textheight
49.83 pc

\printfontdimensions

```
1044 \newcommand{\printfontdimensions}{%
1045 \begin{tabular}{lc}
1046 \toprule
1047 Parameter & Value\\
1048 \midrule
1049 fontdimen1 (slant per point) is & \the\fontdimen1\font\\
1050 fontdimen2 (interword space) & \the\fontdimen2\font\\
1051 fontdimen3 (interword stretch) & \the\fontdimen3\font\\
1052 fontdimen4 (interword shrink) & \the\fontdimen4\font\\
1053 fontdimen5 (x-height) & \the\fontdimen5\font\\
1054 fontdimen6 (quad width) & \the\fontdimen6\font\\
1055 fontdimen7 (extra space) & \the\fontdimen7\font\\
1056 \bottomrule
\end{tabular}
```

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 34

\headheight 1 pc

\headsep 2.08 pc

```
1057 \end{tabular}
1058 }
```

`\drawfontframe` The macro `\drawfontbox{<text>}` draws text in a box and annotates it with dimensions. A very similar macro is defined in Peter Wilson's layouts. I thought with TikZ it can be drawn more easily than the tens of lines of put in the original macros.

We define some new length to hold temporary values for the fontbox dimensions, although PGF provides its own methods.

```
1059 \newlength\xheight@cx
1060 \newlength\xwidth@cx
1061 \newlength\xdepth@cx
1062 \newlength\xtotal@cx
1063 \newsavebox{\fontbox}
```

We set a number of keys to enable styling the box.

```
1064 \cxset{fontbox font/.store in=\fontboxfont@cx,
1065       fontbox line color/.store in=\fontboxlinecolor@cx,
1066       fontbox label font/.store in=\fontboxlabelfont@cx}
1067
1068 % Set reasonable defaults
1069 %
1070 \cxset{fontbox font={\itshape\Huge},
1071       fontbox line color=thered,
1072       fontbox label font={\upshape\footnotesize}}
```

Define a macro to draw a tight frame around text. This can be used for inline text and hence we use `\tikz` to define it. We align it using `baseline=(X.base)`. See [\(How to align a series of tikz pictures at the baseline.\)](#)

See also [how to determine the vector between two co-ordinates.](#)

```
1073 \newcommand\drawfontframe[1]{%
1074   \tikz[baseline=(X.base), font=\fontboxlabelfont@cx]{%
1075     \node[rectangle,draw,inner sep=0pt,outer sep=0pt,
1076           color=\fontboxlinecolor@cx] (X)[black]{#1};
1077     \draw[\fontboxlinecolor@cx, line width=0.4pt] (X.text)
1078           circle(0.4pt)[fill=red] -- (X.base east);}
1079   }
1080   %
1081   \def\drawfontbox#1{%
1082     {\itshape\fontboxfont@cx
1083     \savebox{\fontbox}{#1}
1084     \pgfmithsetlength{\xheight@cx}{\ht\fontbox}
1085     \pgfmithsetlength{\xwidth@cx}{\wd\fontbox}
1086     \pgfmithsetlength{\xdepth@cx}{\dp\fontbox}
1087     \pgfmithsetlength{\xtotal@cx}{\xdepth@cx+\xheight@cx}
1088     \begin{tikzpicture}[scale=1,label/.style={font={\fontboxlabelfont@cx}}]
1089       \node[rectangle,draw,inner sep=0pt,outer sep=0pt] (X){#1};
1090       \draw[red, line width=0.4pt,label] (X.text) circle(1pt)[fill=red] -- (X.base east);
1091       \draw[|<->|,>=latex] ([yshift=5pt] X.north west)
1092         --([yshift=5pt] X.north east) node [label,above=-5pt,midway]{width = \convert@cx{\xwidth
```

\textheight
49.83 pc

We next draw the x-height of the text

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 35

\headheight 1 pc

\headsep 2.08 pc

```
1093      % draw the xheight
1094      \draw[|<->|,>=latex,label]([xshift=-5pt]X.base west)
1095          --([xshift=-5pt] X.north west)
1096          node [left,midway,label] {x-height=\convert@cx{\xheight@cx}};
1097      % draw depth
1098      \draw[|<->|,>=latex,label]([xshift=-5pt]X.base west)
1099          --([xshift=-5pt] X.south west)
1100          node [left,midway,label] {depth=\convert@cx{\xdepth@cx}};
1101      \draw[|<->|,>=latex]([xshift=-5pt]X.south west)
1102          --++(0,-8pt);
1103      % draw total height
1104      %
1105      \draw[|<->|,>=latex,label]([xshift=5pt]X.north east)
1106          --([xshift=5pt] X.south east)
1107          node [right,midway] {height=\convert@cx{\xtotal@cx}};
1108
1109      \end{tikzpicture}}
1110  }
```

13.1 Sundry

Here are assorted macro definitions.

`\lineloop` The (document-level) command `\lineloop` sets numbered lines until the specified count is reached. The command `\linefoot` sets a single, automatically numbered line, but with a footnote (with the specified label); it automatically increments the line counter. These commands are typically used to construct test documents.

Because the counter is globally advanced and never reset, successive calls to `\lineloop` should have an argument ever larger. The formatted output will have each line labeled with its ordinal number.

```
1111      \newcounter{linecount}
1112      \def\loop@line#1#2{%
1113          \par
1114          \hb@xt@{hsize}{%
1115              \global\advance#1\@ne
1116              \edef\@tempa{\@ifnum{100}>#1}{0}{\@ifnum{10}>#1}{0}{\number#1}%
1117              \@tempa\edef\@tempa{\special{line:\@tempa}}\@tempa
1118              \vrule depth2.5\p@#2\leaders\hrule\hfil
1119          }%
1120      }%
1121      \def\lineloop#1{%
1122          \loopwhile{\loop@line\c@linecount}{\@ifnum{#1}>\c@linecount}}%
1123      }%
1124      \def\linefoot#1{%
1125          \loop@line\c@linecount{%
1126              \footnote{%
1127                  #1\special{foot:#1}\vrule depth2.5\p@\leaders\hrule\hfill
1128              }%
1129          }%
1130      }%
```

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 36

\headheight 1 pc

\headsep 2.08 pc

14 Minimal Working Examples (MWE)

We generate a number of examples to illustrate usage and to test the code. The first example test-01.tex, uses the standard book class. It also uses a number of pictures to illustrate float parameter placement.

```
1131 \documentclass[twoside,10pt]{book}
1132 \usepackage{tikz,change page,fancyhdr,amsmath}
1133 \usepgflibrary{arrows}
1134 \usepackage{lipsum}
1135 \usepackage[german]{babel}
1136 \usepackage[german]{xlayouts}
1137 \renewcommand{\topfraction}{.6}
1138 \renewcommand{\bottomfraction}{.8}
1139 \renewcommand{\textfraction}{.04}
1140 \renewcommand{\floatpagefraction}{.9} % have a high one don't encourage it
1141 \renewcommand{\dbltopfraction}{.5}
1142 \renewcommand{\dblfloatpagefraction}{.8}
1143 \setcounter{topnumber}{9}
1144 \setcounter{bottomnumber}{9}
1145 \setcounter{totalnumber}{2}
1146 \setcounter{dbltopnumber}{1}
1147 \pagestyle{grid}
1148 \begin{document}
1149 \section{Introduction}
1150 \thispagestyle{grid}
1151 \begin{figure}[b]
1152 \ifbotfloat{\figureparamsbot}{%
1153 \iftopfloat{\figureparamstop}{}}
1154
1155 \centering
1156 \includegraphics[height=0.9\columnwidth]{./images/hine04-x}
1157 \caption{Example image to demonstrate top fraction.}
1158 \end{figure}
1159 \lipsum[1]
1160
1161 \lipsum[1]
1162
1163 This has been drawn using TikZ\footnote{A kleine program.}\footnote{Another footnote.}.
1164 \lipsum[1-2]
1165 \begin{figure}[t]
1166 \caption{Example image to demonstrate top.}
1167 \includegraphics[width=\columnwidth]{./images/hine02}%
1168 \iftopfloat{\figureparamstop}{%
1169 \end{figure}
1170 \begin{figure}[tpb]
1171 \centering
1172 \includegraphics[height=\columnwidth]{./images/hine04-x}
1173 \caption{Example image to demonstrate top fraction.}
1174 \end{figure}
1175
1176 \begin{figure}[tpb]
```

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in



1 in + \topmargin (1.42 pc) = 4.61 pc

\headheight 1 pc

\headsep 2.08 pc

```
1227 \iftopfloat{\figureparamstop}{}
1228
1229 \centering
1230 \includegraphics[height=0.9\columnwidth]{./images/hine04-x}
1231 \caption{Example image to demonstrate top fraction.}
1232 \end{figure}
1233 \lipsum[1]
1234
1235 \lipsum[1]
1236
1237 This has been drawn using TikZ\footnote{A kleine program.}\footnote{Another footnote.}.
1238 \lipsum[1-2]
1239 \begin{figure}[t]
1240 \caption{Example image to demonstrate top.}
1241 \includegraphics[width=\columnwidth]{./images/hine02}%
1242 \iftopfloat{\figureparamstop}{}
1243 \end{figure}
1244 \begin{figure}[tpb]
1245 \centering
1246 \includegraphics[height=\columnwidth]{./images/hine04-x}
1247 \caption{Example image to demonstrate top fraction.}
1248 \end{figure}
1249
1250 \begin{figure}[tpb]
1251 \centering
1252 \includegraphics[width=\columnwidth]{./images/hine04-xx}
1253 \caption{Example image to demonstrate top fraction.}
1254 \end{figure}
1255 \lipsum
1256 \clearpage
1257 \onecolumn
1258 % draws the spread
1259 \drawspread
1260
1261 \printreadability
1262 \pagestyle{plain}
1263 \newpage
1264 % draws a trial layout
1265 \drawtriallayout
1266 \newpage
1267 \drawtriallayout
1268 \end{document}
1269 %
</test-02>
```

\textheight
49.83 pc

14.1 List standalone diagram MWE

```
< *test-03>
1270 %% This file is generated automatically by xlayouts.dtx.
1271 %% It produces a standalone diagram for lists.
1272 %%
```

\footskip 2.5 pc

\marginparsep 0.92 pc

\marginparwidth 8.42 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 39

\headheight 1 pc

\headsep 2.08 pc

```
1273 \documentclass{standalone}
1274 \usepackage[italian]{babel}
1275 \usepackage[italian]{xlayouts}
1276 \begin{document}
1277 \drawlistdiagram
1278 \end{document}
</test-03>
< *test-04>
1279 %% This file is generated automatically by xlayouts.dtx.
1280 %% It produces a standalone diagram for lists.
1281 %%
1282 \documentclass{standalone}
1283 \usepackage[italian]{babel}
1284 \usepackage[italian]{xlayouts}
1285 \begin{document}
1286 \drawspread
1287 \end{document}
</test-04> < *test-05>
1288 %% This file is generated automatically by xlayouts.dtx.
1289 %% It produces a two page spread and shows the dimensions.
1290 %%
1291 \documentclass[twoside]{book}
1292 \usepackage[left=80pt,right=80pt,top=0.75in]{geometry}
1293 \usepackage[final]{graphicx}
1294 \usepackage{lipsum}
1295 \usepackage{xlayouts}
1296 \makeatletter
1297 \providecommand{\cleartoevenpage}[1][\@empty]{%
1298 \clearpage%
1299 \ifodd\c@page\null#1\clearpage\fi}
1300 \makeatother
1301 \pagestyle{grid}
1302 \begin{document}
1303 \mainmatter
1304 \null\newpage
1305 \pgfpagesuselayout{2 on 1}[a3paper,landscape,border shrink=0mm]
1306 %% first page
1307 \cleartoevenpage
1308 \checkoddpage%
1309 {\parindent0pt
1310 \vbox to 120pt{\lipsum[1]}%
1311 \includegraphics[height=0.78\textheight]{china-05}}
1312
1313 %%secondpage
1314 {\parindent0pt
1315 \vbox to 120pt{\lipsum[1]}%
1316 \hspace*{\dimexpr(-2in-\textwidth-2\evensidemargin)}
1317 \includegraphics[height=0.78\textheight]{china-05}}
1318 \hspace{2.8em}\parbox[b]{0.571\textwidth}{%
1319 \section*{\hfill CHINA PARADE \hfill\hfill}
1320 \lipsum[1-3]}
```

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

\headheight 1 pc

\headsep 2.08 pc

1321 \end{document}
</test-05>

15 Dictionaries

<*english> This file is generated automatically and it contains translation strings for the English language. it is saved in a file pages-German.dict according to the conventions of the translator package.

1322 \ProvidesDictionary{pages-English}{English}
1323 \providetranslation{headernam}{header}
1324 \providetranslation{bodyname}{body}
1325 \providetranslation{footernam}{footer}
1326 \providetranslation{marginnotenam}{margin note}
1327 \providetranslation{oneinchnam}{one inch}
1328 \providetranslation{notshownnam}{not shown}
1329 \providetranslation{drivermarginnam}{driver margin}
1330 \providetranslation{leftpagenam}{left page}
1331 \providetranslation{rightpagenam}{right page}
1332 \providetranslation{bindingcorrectionnam}{binding correction}
1333 \providetranslation{bookheightnam}{book height}
1334 \providetranslation{trimedgenam}{trim edge}
1335 \providetranslation{trimtopnam}{top trim}
1336 \providetranslation{trimbottomnam}{bottom trim}
1337 \providetranslation{precedingtextnam}{Preceding Text}
1338 \providetranslation{followingtextnam}{Following Text}
1339 \providetranslation{labelnam}{label}

\textheight
49.83 pc

</english>

<*german> This file is generated automatically and it contains translation strings for the German language. it is saved in a file pages-German.dict according to the conventions of the translator package.

1340 \ProvidesDictionary{pages-German}{German}
1341 \providetranslation{headernam}{Kopfzeile}
1342 \providetranslation{bodyname}{Haupttext}
1343 \providetranslation{footernam}{Fu{\ss}zeile}
1344 \providetranslation{marginnotenam}{Rand-\ notizen}
1345 \providetranslation{oneinchnam}{ein Zoll}
1346 \providetranslation{notshownnam}{ohne Abbildung}
1347 \providetranslation{drivermarginnam}{Fahrer-Marge}
1348 \providetranslation{leftpagenam}{Linke Seite}
1349 \providetranslation{rightpagenam}{Rechte Seite}
1350 \providetranslation{bindingcorrectionnam}{Bindekorrektur}
1351 \providetranslation{bookheightnam}{Buch H\"ohe}
1352 \providetranslation{trimedgenam}{Schnittkante}
1353 \providetranslation{trimtopnam}{Trim-Top}
1354 \providetranslation{trimbottomnam}{trim Unten}
1355 \providetranslation{precedingtextnam}{Che precede il testo}
1356 \providetranslation{followingtextnam}{Sequento il testo}
1357 \providetranslation{labelnam}{label}

</german>

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 41

\headheight 1 pc

\headsep 2.08 pc

<*italian> This file is generated automatically and it contains translation strings for the German language. it is saved in a file pages-German.dict according to the conventions of the translator package.

```
1358 \ProvidesDictionary{pages-Italian}{Italian}
1359 \providetranslation{headernamename}{testatina}
1360 \providetranslation{bodyname}{corpo}
1361 \providetranslation{footernamename}{piedino}
1362 \providetranslation{marginnotenamename}{note marginale}
1363 \providetranslation{oneinchname}{un piedino}
1364 \providetranslation{notshownname}{non mostrato}
1365 \providetranslation{drivermarginname}{conducente del margine}
1366 \providetranslation{leftpagenamename}{pagina di sinistra}
1367 \providetranslation{rightpagenamename}{pagina a destra}
1368 \providetranslation{bindingcorrectionname}{correzione vincolante}
1369 \providetranslation{bookheightname}{libro di altezza}
1370 \providetranslation{trimedgenamename}{cimosse}
1371 \providetranslation{trimtopname}{top assetto}
1372 \providetranslation{trimbottomname}{fondo assetto}
1373 \providetranslation{precedingtextname}{Che precede il testo}
1374 \providetranslation{followingtextname}{Sequeto il testo}
1375 \providetranslation{labelname}{etichetta}
```

</italian>

<*dutch> This file is generated automatically and it contains translation strings for the Dutch language. it is saved in a file pages-German.dict according to the conventions of the translator package.

```
1376 \ProvidesDictionary{pages-Dutch}{Dutch}
1377 \providetranslation{headernamename}{kopregel}
1378 \providetranslation{bodyname}{broodtekst}
1379 \providetranslation{footernamename}{voetregel}
1380 \providetranslation{marginnotenamename}{marge notities}
1381 \providetranslation{oneinchname}{een inch}
1382 \providetranslation{notshownname}{niet getoond}
1383 \providetranslation{drivermarginname}{bestuurder marge}
1384 \providetranslation{leftpagenamename}{linkerpagina}
1385 \providetranslation{rightpagenamename}{juiste pagina}
1386 \providetranslation{bindingcorrectionname}{binding correctie}
1387 \providetranslation{bookheightname}{book hoekte}
1388 \providetranslation{trimedgenamename}{snijrand}
1389 \providetranslation{trimtopname}{Trim top}
1390 \providetranslation{trimbottomname}{Trim onderkant}
```

</dutch>

<*french> This file is generated automatically and it contains translation strings for the Dutch language. it is saved in a file pages-German.dict according to the conventions of the translator package.

```
1391 \ProvidesDictionary{pages-French}{French}
1392 \providetranslation{headernamename}{kopregel}
1393 \providetranslation{bodyname}{broodtekst}
1394 \providetranslation{footernamename}{voetregel}
1395 \providetranslation{marginnotenamename}{marge notities}
1396 \providetranslation{oneinchname}{een inch}
```

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 42

\headheight 1 pc

\headsep 2.08 pc

```
1397 \providetranslation{notshownname}{niet getoond}
1398 \providetranslation{drivermarginname}{bestuurder marge}
1399 \providetranslation{leftpagename}{linkerpagina}
1400 \providetranslation{rightpagename}{juiste pagina}
1401 \providetranslation{bindingcorrectionname}{binding correctie}
1402 \providetranslation{bookheightname}{book hoekte}
1403 \providetranslation{trimedgename}{snijrand}
1404 \providetranslation{trimtopname}{Trim top}
1405 \providetranslation{trimbottomname}{Trim onderkant}

</french>
<*spanish> This file is generated automatically and it contains translation
strings for the Dutch language. it is saved in a file pages-German.dict according
to the conventions of the translator package.

1406 \ProvidesDictionary{pages-French}{French}
1407 \providetranslation{headername}{kopregel}
1408 \providetranslation{bodyname}{broodtekst}
1409 \providetranslation{footername}{voetregel}
1410 \providetranslation{marginnotename}{marge notities}
1411 \providetranslation{oneinchname}{een inch}
1412 \providetranslation{notshownname}{niet getoond}
1413 \providetranslation{drivermarginname}{bestuurder marge}
1414 \providetranslation{leftpagename}{linkerpagina}
1415 \providetranslation{rightpagename}{juiste pagina}
1416 \providetranslation{bindingcorrectionname}{binding correctie}
1417 \providetranslation{bookheightname}{book hoekte}
1418 \providetranslation{trimedgename}{snijrand}
1419 \providetranslation{trimtopname}{Trim top}
1420 \providetranslation{trimbottomname}{Trim onderkant}

</spanish>
The end of the configuration file code
```

\textheight
49.83 pc

16 References

- [ABH90] Paul W. Abrahams, Karl Berry and Kathryn A. Hargreaves. *TeX for the Impatient*. Addison-Wesley, Reading, Massachusetts, 1990. (Available from CTAN in info/impatient)
- [Ars01a] Donald Arseneau. *Titleref package (version 3.1)*. April 2001. (Available from CTN as macros/latex/contrib/misc/titleref.sty)
- [Ars01b] Donald Arseneau. *Chapterbib package (version 1.9)*. September 2001. (Available from CTN as macros/latex/contrib/misc/chapterbib.sty)
- [Ars03] Donald Arseneau. *Framed package (version 0.8a)*. July 2003. (Available from CTAN as macros/latex/contrib/misc/framed.sty)
- [Ars05] Donald Arseneau. *Placeins package (version 2.2)*. May 2005. (Available from CTN as macros/latex/contrib/placeins/placeins.sty)

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

Page 43

\headheight 1 pc

\headsep 2.08 pc

- [ArWi00] Donald Arseneau and Peter Wilson. *The ifmtarg package*. March, 2000. (Available from CTAN in /macros/latex/contrib/misc)
- [Car94] David Carlisle. *The delarray package*. March 1994. (Available from CTAN in /macros/latex/required/tools)
- [Car98a] David Carlisle. *The enumerate package*. August, 1998. (Available from CTAN in /macros/latex/required/tools)
- [Car98b] David Carlisle. *The remreset package*. August, 1998. (Available from CTAN in /macros/latex/contrib/carlisle)
- [Car99] David Carlisle. *The tabularx package*. January 1999. (Available from CTAN in /macros/latex/required/tools)
- [Car01] David Carlisle. *The dcolumn package*. May 2001. (Available from CTAN in /macros/latex/required/tools)
- [Coc02] Steven Douglas Cochran. *The subfigure package*. March, 2002. (Available from CTAN in /macros/latex/contrib/subfigure)
- [Dal99] Patrick W. Daly. *Natural Sciences Citations and References*. May, 1999. (Available from CTAN in /macros/latex/contrib/natbib)
- [Dow00] Michael J. Downes. *The patchcmd package*. July 2000. (Available from CTAN in /macros/latex/contrib/patchcmd)
- [Fai98] Robin Fairbairns. *The moreverb package*. December, 1998. (Available from CTAN in /macros/latex/contrib/moreverb)
- [Fai03] Robin Fairbairns. *footmisc — a portmanteau package for customising footnotes in LaTeX*. February 2003. (Available from CTAN in macros/latex/contrib/footmisc)
- [Fea03] Simon Fear. *Publication quality tables in LaTeX*. March, 2003. (Available from CTAN in macros/latex/contrib/booktabs)
- [Fra00] Melchior Franz. *The crop package*. February, 2000. (Available from CTAN in /macros/latex/contrib/crop)
- [GMS94] Michel Goossens, Frank Mittelbach, and Alexander Samarin. *The LaTeX Companion*. Addison-Wesley Publishing Company, 1994.
- [Knu84] Donald E. Knuth. *The TeXbook*. Addison-Wesley, Reading, Massachusetts, 1984.
- [KWG] Bil Kleb, Bill Wood, and Kevin Godby. *Tufte LaTeX*. December 2009. (Available from CTAN in macros/latex/contrib/tufte-latex/)
- [Lam94] Leslie Lamport. *LaTeX — A Document Preparation System*. Addison-Wesley, Reading, Massachusetts, 1994.
- [LMB99] Leslie Lamport, Frank Mittelbach and Johannes Braams. *Standard Document Classes for LaTeX version 2e*. September, 1999. (Available from CTAN as /macros/latex/base/classes.dtx)
- [MC98] Frank Mittelbach and David Carlisle. *A new implementation of LaTeX's tabular and array environment*. May 1998. (Available from CTAN in /macros/latex/required/tools)
- [Oos96] Piet van Oostrum. *Page layout in LaTeX*. June, 1996. (Available from CTAN in /macros/latex/contrib/fancyhdr)
- [Rah01] Sebastian Rahtz. *Section name references in LaTeX*. January 2001. (Available from CTAN in /macros/latex/contrib/hyperref)

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in

1 in + \topmargin (1.42 pc) = 4.61 pc

\headheight 1 pc

\headsep 2.08 pc

[Rah02] Sebastian Rahtz. *Hypertext marks in LaTeX*. March 2002. (Available from CTAN in /macros/latex/contrib/hyperref)

[Sch98] Martin Schröder. *The everyshi package*. August, 1998. (Available from CTAN in /macros/latex/contrib/ms)

[SRR01] Rainer Schöpf, Bernd Raichle and Chris Rowley. *A new implementation of LaTeX's verbatim and verbatim* environments*. March, 2001. (Available from CTAN in /macros/latex/required/tools)

[Wil99] Peter Wilson. *The tocvsec2 package*. January, 1999. (Available from CTAN in /macros/latex/contrib/tocvsec2)

[Wil00a] Peter Wilson. *The epigraph package*. February, 2000. (Available from CTAN in /macros/latex/contrib/epigraph)

[Wil00b] Peter Wilson. *LaTeX files for typesetting ISO standards*. February, 2000. (Available from CTAN in /macros/latex/contrib/isostds/iso)

[Wil00c] Peter Wilson. *The nextpage package*. February, 2000. (Available from CTAN in /macros/latex/contrib/misc)

[Wil00d] Peter Wilson. *The needspace package*. March, 2000. (Available from CTAN in /macros/latex/contrib/misc)

[Wil01a] Peter Wilson. *The abstract package*. February, 2001. (Available from CTAN in /macros/latex/contrib/abstract)

[Wil01b] Peter Wilson. *The chngpage package*. February, 2001. (Available from CTAN in /macros/latex/contrib/misc)

[Wil01c] Peter Wilson. *The appendix package*. March, 2001. (Available from CTAN in /macros/latex/contrib/appendix)

[Wil01d] Peter Wilson. *The ccaption package*. March, 2001. (Available from CTAN in /macros/latex/contrib/ccaption)

[Wil01e] Peter Wilson. *The chngcntr package*. March, 2001. (Available from CTAN in /macros/latex/contrib/misc)

[Wil01f] Peter Wilson. *The hanging package*. March, 2001. (Available from CTAN in /macros/latex/contrib/hanging)

[Wil01g] Peter Wilson. *The titling package*. March, 2001. (Available from CTAN in /macros/latex/contrib/titling)

[Wil01h] Peter Wilson. *The tocbibind package*. April, 2001. (Available from CTAN in /macros/latex/contrib/tocbibind)

[Wil01i] Peter Wilson. *The tocloft package*. April, 2001. (Available from CTAN in /macros/latex/contrib/tocloft)

[Wil01j] Peter Wilson. *Typesetting simple verse with LaTeX*. August, 2001. (Available from CTAN in /macros/latex/contrib/verse)

[Wil03] Peter Wilson. *ledmac: A presumptuous attempt to port EDMAC and TABMAC to LaTeX*. August 2003. (Available from CTAN in macros/latex/contrib/ledmac)

[Wil07] Peter Wilson. 'Glisterings' *TUGboat*, 28(2):229–232, 2007.

[Wil08] Peter Wilson. 'Glisterings' *TUGboat*, 29(2):324–327, 2008.

\textheight
49.83 pc

\footskip 2.5 pc

\marginparsep 0.92 pc

oddsidemargin 2.33 pc

\textwidth 31.66 pc

\marginparwidth 8.42 pc

driver margin 1 in