

Cookbook for CICD with R and GitHub Actions

Yann Say

2022-11-24

Contents

1	Intro	5
2	R CMD check	7
2.1	R-CMD-check	7
2.2	Prerequisite	7
2.3	Steps	7
3	Shiny deploy	9
3.1	shiny-deploy	9
3.2	Prerequisite	9
3.3	Steps	9
4	Test coverage	11
4.1	test-coverage	11
4.2	Prerequisite	11
4.3	Steps	11

Chapter 1

Intro

This is a small collections of step-by-step on how to set-up of r-lib GitHub Actions for CICD with R programming. It mainly use the package `usethis`(version 2.1.6). More details of the actions can be found [here](#). When I thought necessary I have added a few additional steps, e.g. when using other services from GitHub or Codecov which I thought was missing when I was trying to learn about GitHub Actions.

The book was built with **bookdown**.

Chapter 2

R CMD check

2.1 R-CMD-check

Quick how-to to set a github action for a R CMD check each time there is merge into the **main** (or **master**) branch using **r-lib** check-release.yaml or check-standard.yaml

2.2 Prerequisite

None in particular but could be good to have some tests already.

2.3 Steps

- Create your package.
- Try to test your package `devtools::test()` or `devtools::check()`
 - While this step is not really necessary, it is to make sure your tests runs once and any further problems do not come from the tests.
- Add the check-release.yaml `usethis::use_github_action("check-release")` or check-standard.yaml `usethis::use_github_action("check-standard")`
 - check-release.yaml will run R CMD check on Ubuntu and current R version

- `check-standard.yaml` will run R CMD check on 3 OS: mac and Windows with the current R version, Ubuntu with the current, development and previous version of R. This what you would want for CRAN.
- Add the badge with `usethis::use_github_actions_badge("check-release")` or `usethis::use_github_actions_badge("check-standard")`
- Push!

Chapter 3

Shiny deploy

3.1 shiny-deploy

Quick how to set a github action for a shiny deployment each time there is merge into the **main** (or **master**) branch using **r-lib** shiny-deploy.yaml

3.2 Prerequisite

Make sure you have the rsconnect information.

- <https://shiny.rstudio.com/articles/shinyapps.html>

3.3 Steps

- Create your app using **renv** (The yaml use assume **renv** is used).
 - *It is probably also a best practice to use renv.*
- Try to deploy your app (either with the publish/redeploy button) or **rsconnect::deployApp()**
 - While this step is not really necessary, it is to make sure your app runs once and any further problems do not come from the app itself.
- Add a description **usethis::use_description(check_name = F)**.
 - *check_name = F to avoid checking name valid for CRAN.*

- Add the shiny-deploy.yaml `use_github_action("shiny-deploy.yaml")`
- Edit the shiny-deploy.yaml, especially the following part.
 - You can either fill in for the APPNAME, ACCOUNT, SERVER.

```
- name: Authorize and deploy app
  env:
    # Provide your app name, account name, and server to be deployed below
    APPNAME: your-app-name
    ACCOUNT: your-account-name
    SERVER: shinyapps.io # server to deploy
  run: |
    rsconnect::setAccountInfo("${ secrets.RSCONNECT_USER }", "${ secrets.RSCONNECT_TOKEN }")
    rsconnect::deployApp(appName = "${ env.APPNAME }", account = "${ env.ACCOUNT }", server = "${ env.SERVER }")
  shell: Rscript {0}
```

- Or you can remove the `env` block and change the `rsconnect::deployApp` call.

```
- name: Authorize and deploy app
  run: |
    rsconnect::setAccountInfo("${ secrets.RSCONNECT_USER }", "${ secrets.RSCONNECT_TOKEN }")
    rsconnect::deployApp()
  shell: Rscript {0}
```

- Add 3 secrets in the repository to store you account, token and secret (see prerequisite). They should have those names
 - `RSCONNECT_USER`, `RSCONNECT_TOKEN`, and secret `RSCONNECT_SECRET`
 - You can follow these guides if needed
- Link the shiny app folder to the github repo (add the remote and origin) (if you have not done it already).
- Push!

Chapter 4

Test coverage

4.1 test-coverage

Quick how-to to set a GitHub action to get code coverage and the badge from Codecov each time there is merge into the **main** (or **master**) branch using `r-lib` `test-coverage.yaml`.


4.2 Prerequisite

Have a Codecov account link with your repository.

None in particular but could be good to have some tests as to get a coverage of something.

4.3 Steps


- Create your package.
- Link your local to the remote if it has not be done yet (make sure your project is linked to a Github repository).
- Make sure Codecov has synced with your repository. The repository should appear in the *Not yet setup* if this is the first time. The syncing between GitHub and Codecov takes a bit of time so you can go for a coffee or



- Try to test your package `covr::package_coverage()`.
 - While this step is not really necessary, it is to make sure your tests runs once and any further problems do not come from the tests.
- Add the test-coverage.yaml `usethis::use_github_action("test-coverage")`
- Add the badge with `usethis::use_coverage("codecov")`

- This step should add a badge in your readme file.
- Or should give you a message in the console telling you to copy and paste some lines in the README.
- If nothing happen, you can add the line directly following the syntax or remove the `codecov.yaml` from the project folder and run `usethis::use_coverage("codecov")` again.

- Push!
- The GitHub action will push the report to Codecov, you can see the report by clicking on the badge.
 - Github and Codecov needs to sync for the percentage to appear



```

> usethis::use_coverage(type = c("codecov"))
v Writing 'codecov.yaml'
v Adding Codecov test coverage badge
[1] "https://app.codecov.io/gh/yannsay-impact/testc12/branch/main/graph/badge.svg"

```

Badge link can only be printed to screen.
Copy and paste the following lines into 'README':

```

<!-- badges: start -->
[[codecov test coverage]](https://codecov.io/gh/yannsay-impact/testc12/branch/main/graph/badge.svg)
<!-- badges: end -->

```

[copied to clipboard]