

# A Minimal Book Example

Yihui Xie

2022-11-23



# Contents

<b>1</b>	<b>Prerequisites</b>	<b>5</b>
<b>2</b>	<b>R CMD check</b>	<b>7</b>
2.1	R-CMD-check . . . . .	7
2.2	Prerequisite . . . . .	7
2.3	Steps . . . . .	7
<b>3</b>	<b>Shiny deploy</b>	<b>9</b>
3.1	shiny-deploy . . . . .	9
3.2	Prerequisite . . . . .	9
3.3	Steps . . . . .	9
<b>4</b>	<b>Literature</b>	<b>13</b>
<b>5</b>	<b>Methods</b>	<b>15</b>
<b>6</b>	<b>Applications</b>	<b>17</b>
6.1	Example one . . . . .	17
6.2	Example two . . . . .	17
<b>7</b>	<b>Final Words</b>	<b>19</b>



# Chapter 1

## Prerequisites

This is a *sample* book written in **Markdown**. You can use anything that Pandoc's Markdown supports, e.g., a math equation  $a^2 + b^2 = c^2$ .

The **bookdown** package can be installed from CRAN or Github:

```
install.packages("bookdown")  
# or the development version  
# devtools::install_github("rstudio/bookdown")
```

Remember each Rmd file contains one and only one chapter, and a chapter is defined by the first-level heading #.

To compile this example to PDF, you need XeLaTeX. You are recommended to install TinyTeX (which includes XeLaTeX): <https://yihui.org/tinytex/>.



## Chapter 2

# R CMD check

### 2.1 R-CMD-check

Quick how-to to set a github action for a R CMD check each time there is merge into the **main** (or **master**) branch using **r-lib** check-release.yaml or check-standard.yaml

### 2.2 Prerequisite

None in particular but could be good to have some tests already.

### 2.3 Steps

- Create your package.
- Try to test your package `devtools::test()` or `devtools::check()`
  - While this step is not really necessary, it is to make sure your tests runs once and any further problems do not come from the tests.
- Add the check-release.yaml `usethis::use_github_action("check-release")` or check-standard.yaml `usethis::use_github_action("check-standard")`
  - check-release.yaml will run R CMD check on Ubuntu and current R version

- `check-standard.yaml` will run R CMD check on 3 OS: mac and Windows with the current R version, Ubuntu with the current, development and previous version of R. This what you would want for CRAN.
- Add the badge with `usethis::use_github_actions_badge("check-release")` or `usethis::use_github_actions_badge("check-standard")`
- Push!



## Chapter 3

# Shiny deploy

### 3.1 shiny-deploy

Quick how to set a github action for a shiny deployment each time there is merge into the **main** (or **master**) branch using **r-lib** shiny-deploy.yaml

### 3.2 Prerequisite

Make sure you have the rsconnect information.

- <https://shiny.rstudio.com/articles/shinyapps.html>

### 3.3 Steps

- Create your app using **renv** (The yaml use assume **renv** is used).
  - *It is probably also a best practice to use renv.*
- Try to deploy your app (either with the publish/redeploy button) or **rsconnect::deployApp()**
  - While this step is not really necessary, it is to make sure your app runs once and any further problems do not come from the app itself.
- Add a description **usethis::use\_description(check\_name = F)**.
  - *check\_name = F to avoid checking name valid for CRAN.*

- Add the shiny-deploy.yaml `usethis::use_github_action("shiny-deploy.yaml")`
- Edit the shiny-deploy.yaml, especially the following part.
  - You can either fill in for the APPNAME, ACCOUNT, SERVER.

```
- name: Authorize and deploy app
  env:
    # Provide your app name, account name, and server to be deployed below
    APPNAME: your-app-name
    ACCOUNT: your-account-name
    SERVER: shinyapps.io # server to deploy
  run: |
    rsconnect::setAccountInfo("${{ secrets.RSCONNECT_USER }}", "${{ secrets.RSCONNECT_PASSWORD }}")
    rsconnect::deployApp(appName = "${{ env.APPNAME }}", account = "${{ env.ACCOUNT }}", server = "${{ env.SERVER }}")
  shell: Rscript {0}
```

- Or you can remove the env block and change the `rsconnect::deployApp` call.

```
- name: Authorize and deploy app
  run: |
    rsconnect::setAccountInfo("${{ secrets.RSCONNECT_USER }}", "${{ secrets.RSCONNECT_PASSWORD }}")
    rsconnect::deployApp()
  shell: Rscript {0}
```

- Specify the R version.
  - *I have a problem with the update of 4.2 from the 30.10.2022, so I have added a step to specify the same R version to be installed on the github action rather than the latest one. This should be a temporary measure while something better is figured out.*

```
- uses: r-lib/actions/setup-r@v2
  with:
    use-public-rspm: true
```

To

```
- uses: r-lib/actions/setup-r@v2
  with:
    r-version: '4.1.0'
    use-public-rspm: true
```

- Add 3 secrets in the repository to store you account, token and secret (see prerequisite). They should have those names
  - `RSCONNECT_USER`, `RSCONNECT_TOKEN`, and secret `RSCONNECT_SECRET`
  - You can follow these guides if needed
- Link the shiny app folder to the github repo (add the remote and origin) (if you have not done it already).
- Push!



## Chapter 4

# Literature

Here is a review of existing methods.



## Chapter 5

# Methods

We describe our methods in this chapter.





## Chapter 6

# Applications

Some *significant* applications are demonstrated in this chapter.

### 6.1 Example one

### 6.2 Example two



## Chapter 7

# Final Words

We have finished a nice book.