

# Intro to Computer Science and Software Engineering

# **HTTP and WWW**

Dr Yubei Lin
yupilin@scut.edu.cn
School of Software Engineering

# **HTTP and WWW**



- Hypertext Transfer Protocol (HTTP) is a clientserver program that is used to access and transfer documents on the World Wide Web.
- Uniform Resource Locator (URL)
  - Addressing a document on WWW.
- WWW (World Wide Web)
  - Hypertext documents (static, dynamic and active)
  - Links (to form a Web)
  - Browsers

# WWW



#### The Web

An infrastructure of information combined and the network software used to access it

# Web page

A document that contains or references various kinds of data

Links A connection between one web page and another

What are the links used for?

# WWW



#### Website

A collection of related web pages

#### Web browser

A software tool that retrieves and displays eb pages

#### Web server

A computer set up to respond to requests for web pages

# WWW



# **Uniform Resource Locator (URL)**

A standard way of specifying the location of a Web page, containing the hostname, "/", and a file




Figure A browser retrievinga Web page

What is the relationship between the Internet and the Web?

# **Search Engines**



### **Search Engine**

A website that helps you find other websites

Can you name at least two?

How do they work?

# **Instant Messaging**



# Instant messaging (IM)

An application that allows people to send and receive messages in real time

- Both sender and receiver must have an IM running
- Most IM applications use a proprietary protocol that dictates the precise format and structure of the messages sent
- Instant messages are not secure

# Weblogs



### **Blog or Weblog**

An online journal or newsletter that is frequently updated and intended for public consumption

Do you have a blog?

Do you read blogs?

# **Cookies**



#### Cookie

A small text file that a web server stores on your local computer's hard disk

- A cookie contains information about your visit to the site
- Cookies can be used
  - to determine number of unique visitors to the site
  - to customize the site for future visits
  - to implement shopping carts that can be maintained from visit to visit
- Cookies are not dangerous



# **Hypertext Markup Language (HTML)**

The language used to create or build a Web page

# Markup language

A language that uses tags to annotate the information in a document

### **Tags**

The syntactic element in a markup language that indicates how information should be displayed



Final Report

European Conference on Expert Systems

boldface

Submitted by Justin Parker

First of all, our thanks go out to the following sponsors for their support of the conference and its supplemental activities.


Allied Interactive
Sybernetics, Inc.

Dynamic Solutions of New Jersey

make these bullets

The conference was a great success It ran a full four days, including workshops and special sessions. Subjective feedback from conference attendees was largely positive, and financially the revenues resulted in a surplus of over \$10,000.





Plan to participate in our upcoming events:

- Visit Children's Hospital (March 23)
- · Help clean renovated school grounds (April 4)
- Continue the K-12 outreach program. UPDATED

You should be involved! Help our active and energetic team make a difference in the lives of people. Our executive board is always willing to answer any questions you may have.

How can we help you? What suggestions do you have regarding new activities? Let us know!

We are always in need of donations: equipment, money, or (better yet) you!

Join us for our Spring Picnic in May!

Figure The Student Dynamics Web page as displayed in Netscape Navigator



```
<HTML>
   <HEAD>
      <TITLE>Student Dynamics</TITLE>
   </HEAD>
   <BODY>
      <CENTER><IMG SRC="stuDynamics.gif"></CENTER>
      <HR>
      <CENTER><I>A student-based community organization.</I></CENTER>
      <HR>
      P>Plan to participate in our upcoming events:
      <!!!>
         <LI>Visit Children's Hospital (March 23)</LI>
         <LI>Help clean renovated school grounds (April 4)</LI>
         ⟨LI⟩Continue the ⟨a href="outreach.html"⟩K-12 outreach
             program.</a> <IMG SRC="updated.gif"></LI>
      </UL>
      \langle P \rangle \langle B \rangle \langle I \rangle You should be involved!\langle B \rangle \langle I \rangle Help our active and
         energetic team make a difference in the lives of people. Our
         <a href="execBoard.html">executive board</a> is always willing
         to answer any questions you may have. </P>
      Yes the can we help you? What suggestions do you have regarding
         new activities? <a href="suggestions.html">Let us know!</a></P>
      Ye are always in need of donations: equipment, money, or
         (better yet) you!</P>
      <CENTER><H3>Join us for our Spring Picnic in May!</H3></CENTER>
   </BODY>
</HTML>
```



Tags are enclosed in angle brackets (<...>).

Words such as HEAD, TITLE, and BODY are called **elements** and specify the type of the tag Tags are often used in pairs, with a start tag such as <BODY> and a corresponding end tag with a / before the element name, such as </BODY>



The browser determines how the page should be displayed based on the tags

#### The browser

- Ignores the way we format the HTML document using carriage returns, extra spaces, and blank lines
- Takes into account the width and height of the browser window
- Reformats the contents to fit your browser window

# **Basic HTML Formatting**



- <P>... </P> specify that text should be treated as a separate paragraph
- <CENTER> . . . </CENTER> center information in the browser window
- <B>...</B> bold information
- <l>...</l> italicize information
- <HR> insert horizontal rule across page

# **Basic HTML Formatting**



```
<UL>...</UL> unordered list
<Ul>...</Ul> list item
<H1>...</H1> information as H1 head
...
<H8>...</H8> information as H8 head
```

# **Image and Links**



#### **Attribute**

Part of a tag that provides additional information about the element

```
attribute-name = value
<IMG SRC = "myPicture.gif">
```

inserts the image stored in file "myPicture.gif"

# **Image and Links**



A link is specified using the element A, (which stands for anchor) and attribute HREF that specifies the URL of the destination document.

<P><A

HREF="http://www.cs.utexas.edu/users/ndale/labs/factori al/FactByte. htm">Factorial-Byte</A></P>



#### **New Tags**

- <section> to define section of pages
- <header> to define the header of a page
- <footer> to define the footer of a page
- <nav> to define the navigation elements on a page
- <article> to define an article or primary content of a page
- <aside> to define secondary content that might appear in a sidebar
- <figure> to define images that annotate an article

# **Java Applets**



### Java applet

A Java program designed to be embedded into an HTML document, transferred over the Web, and executed in a browser

## **Example**

Contents of FactByte.htm:

<H1>Factorial with Byte Result</H1>

FactByte.class contains the Java applet

<P>Enter increasing values beginning with 0 and record the results of the Factorial of your input. At some point, the answer will seem strange. Record what seems strange about the answer and return to the previous page.

<P><APPLET code = "FactByte.class" width=250 height=150></APPLET></P>

# **Java Server Pages**



### **JSP Scriptlet**

A portion of code embedded in an HTML document designed to dynamically contribute to the content of the web page

### **Java Server Page**

A web page that has a JSP scriptlet interwoven among the HTML content

# **Java Server Pages**



A JSP scriptlet is encased in special tags beginning with <% and ending with %>

Imagine JSP scriptlets as having the expressive power of a full programming language

```
<H3>
<%
out.println ("hello there");
%>
</H3>
```

# **Java Server Pages**



JSPs are executed on the server side where the web page resides

By the time it arrives at your computer, all active processing has taken place, producing a static (though dynamically created) web page

JSPs are particularly good for coordinating the interaction between a web page and an underlying database

Compare and contrast Java applets and JSP scriptlets



# HTML不可扩展、可读性差、不可描述数据、搜索时间长



### **Extensible Markup Language (XML)**

A language that allows the user to describe the content of a document

- HTML describes how a document should look
- XML describes a document's meaning

### Metalanguage

A language for talking about, or defining, other languages XML is a metalanguage

# **XML**



```
<?xm1 version="1.0" ?>
<!DOCTYPE books SYSTEM "books.dtd">
 <books>
<br/>book>
<title>The Hobbit</title>
<authors>
 ⟨author⟩J.R.R. Tolkien⟨/author⟩
</authors>
<publisher>Ballantine
<pages>287</pages>
\(\isbn\)0-345-27257-9\(\isbn\)
<price currency="USD">7.95</price>
</hook>
<book>
<title>A Beginner's Guide to Bass Fishing</title>
(authors)
 <author>J. T. Angler
 ⟨author⟩Ross G. Clearwater⟨/author⟩
</authors>
<publisher>Quantas Publishing
<pages>750</pages>
<isbn>0-781-40211-7</isbn>
<price currency="USD">24.00</price>
</book>
</hooks>
```

Like HTML, an XML document is made up of tagged data

Figure An XML document containing data about books

# **XML**



#### **Document Type Definition (DTD)**

A specification of the organization of the document

The structure of a particular XML document is described by its corresponding DTD document

```
<!ELEMENT books (book*) >
<!ELEMENT book (title, authors, publisher, pages, isbn, price)>
<!ELEMENT authors (author+)>
<!ELEMENT title (#PCDATA)>
<!ELEMENT author (#PCDATA)>
<!ELEMENT publisher (#PCDATA)>
<!ELEMENT pages (#PCDATA)>
<!ELEMENT isbn (#PCDATA)>
<!ELEMENT price (#PCDATA)>
<!ELEMENT price (#PCDATA)>
```

Figure The DTD document corresponding to the XML books document

# **XML**



XML represents a standard format for organizing data without tying it to any particular type of output

#### **Extensible Stylesheet Language (or XSL)**

A language for defining transformations from XML documents to other output formats




Figure An XML document can be transformed into many output formats