EE140 Introduction to Communication Systems

Lecture 5

Instructor: Prof. Lixiang Lian
ShanghaiTech University, Fall 2025

Contents

- Random signals
  - Review of probability and random variables
  - Random processes: basic concepts
  - Gaussian white processes

Recall: Gaussian Distribution

- Gaussian or normal distribution is a continuous r.v. with pdf

$$f_X(x) = \frac{1}{\sqrt{2\pi\sigma_x^2}} \exp[-\frac{1}{2\sigma_x^2}(x - m_x)^2]$$



- A Gaussian r.v. is completely determined by its mean and variance, and hence usually denoted as

$$x \sim N(m_x, \sigma_x^2)$$

Gaussian Process

- Definition: $X(t)$ is a Gaussian process if for all n and all $t_1, t_2, \ldots, t_n$ the sample values $X(t_1), X(t_2), \ldots,$ $X(t_n)$ have a joint Gaussian density function

$C_{ij} = \mu(X(t_i)X(t_j))$

$$f_{X(t_1)X(t_2),\cdots,X(t_n)}(x_1, x_2, \ldots, x_n) = \frac{1}{(2\pi)^{n/2}(\det(\mathbf{C}))^{1/2}} \exp\left[-\frac{(x-\mathbf{m})^T\mathbf{C}^{-1}(x-\mathbf{m})}{2}\right]$$

- Properties:
  - If it is wide-sense stationary, it is also strictly stationary (Gaussian process is completely defined by its first order statistics $\mathbf{m}$ and second order statistics $\mathbf{C}$.)

Gaussian Process

- Properties:
  - If the samples of Gaussian process $X(t_1), X(t_2), \ldots, X(t_n)$ are uncorrelated in time, they are also independent

$$f_{X(t_1)X(t_2),\cdots,X(t_n)}(x_1, x_2, \ldots, x_n) = \prod_{k=1}^{n} \frac{1}{\sqrt{2\pi}\sigma_k} \exp[-\frac{(x_k - a_k)^2}{2\sigma_k^2}]$$

$$= f_{X(t_1)}(x_1) \cdot f_{X(t_2)}(x_2) \cdot \cdots \cdot f_{X(t_n)}(x_n)$$

  - If the input to a linear system is a Gaussian process, the output is also a Gaussian process

$$Y_o(t) = \int_{-\infty}^{\infty} h(\tau) X_i(t - \tau) d\tau$$

Noise

- Gaussian Noise:
  - often modeled as Gaussian and stationary with 0 mean



- White noise (stationary and zero mean)

Noise

- White Noise (stationary and zero mean)

$$S_n(f) = \frac{N_0}{2} \quad \Longrightarrow \quad R_n(\tau) = \frac{N_0}{2}\delta(\tau)$$

Infinite power





White noise is completely uncorrelated!

$N_0 = KT = 4.14 \times 10^{-21}$
$= -174\,\text{dBm/Hz}$

N_0: single-sided power spectral density
$\frac{N_0}{2}$: two-sided power spectral density

completely Independent

- White Gaussian Noise (stationary and zero mean)

Nw(f)

AWGN



$y(f) = x(f) + n_w(f)$

Filtering $\Rightarrow \begin{cases} x(f) \text{ pass} \\ n_w(f) \text{ filter} \end{cases}$



SNR = 0

$n_w(f)$: white Gaussian noise

1. stationary
2. $E[n_w(f)] = 0$
3. $S_{n_w}(f) = \frac{N_0}{2}$ $\quad R_{n_w}(\tau) = \frac{N_0}{2}\delta(\tau)$
4. uncorrelated / Independent
5. $f(n_w(t_1), n_w(t_2) \cdots n_w(t_n))$

$$= \prod_{i=1}^{n} f(n_w(t_i)) = \prod_{i=1}^{n} N(0, \sigma^2)$$

6. $P = \infty \Leftarrow$ Bandwidth $= \infty$



Modulation $\Rightarrow$







Demodulation $\Leftarrow$



$n_w(t) \longrightarrow$ Filter $H(f) \longrightarrow n(t)$

① $n_w(t)$ Gaussian $\longrightarrow$ $n(t)$ Gaussian

② $n_w(t)$ stationary, zero mean $\longrightarrow$ $n(t)$ stationary, zero mean

③ $n_w(t)$ white $\longrightarrow$ $S_n(f) = |H(f)|^2 S_{n_w}(f)$



Colored Noise

Case 1: $x(t)$ Lowpass signal, B

Bandlimited Noise



$\longrightarrow$



$P = R_n(0) = N_0 B$



$\tau' = \frac{k}{2B} \Rightarrow R_n(\tau') = 0$

$\Rightarrow$ uncorrelated / Independent

Case 2 $X(f)$ is Band pass signal. B $f_0 \gg B$





Bandpass Noise / Narrowband Noise

$$P = R_n(0) = \frac{N_0}{2} \cdot 2B = N_0 B$$



Bandlimited Noise





(a)



(b)

$$R_n(\tau) = N_0 B sinc(2B\tau)$$

- Q1. At what rate to sample the noise can we get uncorrelated realizations? (2B/second)
- Q2. What is the power of each sample? (BN_0)

Noise Equivalent Bandwidth

- White noise: zero mean, two-sided PSD=$\frac{N_0}{2}$
- Arbitrary filter: $H(f)$
- Average output noise power

$$P_{n_o} = \int_{-\infty}^{\infty} \frac{N_0}{2} |H(f)|^2 \, df = N_0 \int_0^{\infty} |H(f)|^2 \, df$$

$|H(f)| = |H(-f)|$, if $h(t)$ is real.

- Ideal filter: B_N, H_0

$$P_{n_o} = N_0 H_0^2 B_N$$

$\frac{N_0}{2} \times |H_0|^2 \cdot B_N \times 2$

- Noise equivalent bandwidth

$$B_N = \frac{\int_0^{\infty} |H(f)|^2 df}{H_0^2}$$



Narrowband Noise







Sample function

- Two specific representation of narrowband noise
  - In-phase and quadrature components
  - Envelope and phase

$$\boxed{x(t) = x_R(t)\cos 2\pi f_0 t - x_I(t)\sin 2\pi f_0 t}$$

Narrowband Noise



- Canonical form of a band-pass noise process

$$n(t) = n_c(t)\cos(2\pi f_0 t + \theta) - n_s(t)\sin(2\pi f_0 t + \theta)$$

In-phase component

Quadrature component

Low-pass noise process

θ is an arbitrary phase angle

Narrowband Noise

- How to produce $n_c(t)$ and $n_s(t)$





Why equality holds? (Proof: Page 712, Appendix C)

$$\boxed{E\left\{\left[n(t) - [n_c(t)\cos(2\pi f_0 t + \theta) - n_s(t)\sin(2\pi f_0 t + \theta)]\right]^2\right\} = 0}$$

$$z_1(t) = n(t)\cdot 2\cos(w_0 t+\theta)$$
$$= 2n_c(t)\cos^2(2\pi f_0 t+\theta) - 2n_s(t)\sin(2\pi f_0 t+\theta)\cos(2\pi f_0 t+\theta)$$
$$= n_c(t) + n_c(t)\cos(4\pi f_0 t+2\theta) - n_s(t)\sin(4\pi f_0 t+2\theta)$$

$$n(t) = n_c(t)\cos(2\pi f_0 t+\theta) - n_s(t)\sin(2\pi f_0 t+\theta)$$



$$z_2(t) = n(t)\cdot(-2\sin(2\pi f_0 t+\theta))$$
$$= -2n_c(t)\sin(2\pi f_0 t+\theta)\cos(2\pi f_0 t+\theta) + 2n_s(t)\sin^2(2\pi f_0 t+\theta)$$
$$= -n_c(t)\sin(4\pi f_0 t+2\theta) + n_s(t) - n_s(t)\cos(4\pi f_0 t+\theta)$$

Properties

If $n(t)$ is Gaussian RP → $n_s(t)$ and $n_c(t)$ are joint Gaussian RP

If $n(t)$ is stationary → $n_s(t)$ and $n_c(t)$ are jointly stationary

$E[n_s(t)]$
$E[n_c(t)]$
$R_{n_s}(\tau)$
$R_{n_c}(\tau)$
$\rightarrow R_{n_c n_s}(\tau)$

$n_s(t)$ and $n_c(t)$

- Zero mean
- Same PSD (autocorrelation, variance)

$$S_{n_c}(f) = S_{n_s}(f)$$
$$= \mathrm{Lp}[S_n(f - f_0) + S_n(f + f_0)]$$

- Cross-PSD (odd Cross-correlation)

$$S_{n_c n_s}(f) = j\mathrm{Lp}[S_n(f - f_0) - S_n(f + f_0)]$$



$$z_1(t) = 2n(t)\cos(w_0 t + \theta) \qquad E[z_1(t)] = 0$$

$$n_c(t) = LP[z_1(t)] \qquad E[n_c(t)] = 0$$

$$z_2(t) = -2n(t)\sin(w_0 t + \theta) \qquad E[z_2(t)] = 0$$

$$n_s(t) = LP[z_2(t)] \qquad E[n_s(t)] = 0$$

$$R_{z_1}(t, t+\tau) = E[4n(t)n(t+\tau)\cos(w_0 t + \theta)\cos(w_0(t+\tau) + \theta)]$$
$$= 2R_n(\tau)\cos(2\pi f_0 \tau)$$

$$R_{z_2}(t, t+\tau) = E[4n(t)n(t+\tau)\sin(2\pi f_0 t + \theta)\sin(2\pi f_0(t+\tau) + \theta)]$$
$$= 2R_n(\tau)\left(\cos(2\pi f_0 \tau) - E[\cos(2\pi f_0(2t+\tau) + \theta)]\right)$$
$$= 2R_n(\tau)\cos(2\pi f_0 \tau)$$

$$R_{z_1 z_2}(t, t+\tau) = E[z_1(t)z_2(t+\tau)]$$
$$= -2R_n(\tau)\, E[2\cos(w_0 t + \theta)\sin(w_0(t+\tau) + \theta)]$$
$$= -2R_n(\tau)\sin(2\pi f_0 \tau)$$



$z_1(t) = 2n(t)\cos(\omega_0 t+\theta)$

$n_c(t) = LP[z_1(t)]$

$z_2(t) = -2n(t)\sin(\omega_0 t+\theta)$

$n_s(t) = LP[z_2(t)]$

$P = N_0 B$



$\Downarrow$

$S_{z_1}(f) = S_{z_2}(f)$

$R_{z_1}(\tau) = 2R_n(\tau)\cos(2\pi f_0\tau)$

$\xrightarrow{F}$ $S_{z_1}(f) = S_n(f-f_0)+S_n(f+f_0)$

$S_{n_c}(f) = LP[S_n(f-f_0)+S_n(f+f_0)]$



$\Downarrow$ $S_{n_c}(f) = S_{n_s}(f)$

$R_{z_2}(\tau) = 2R_n(\tau)\cos(2\pi f_0\tau)$

$S_{z_2}(f) = S_n(f-f_0)+S_n(f+f_0)$

$S_{n_s}(f) = LP[S_n(f-f_0)+S_n(f+f_0)]$

$P = N_0 B$



$S_{n_c}(f) = S_{n_s}(f)$ $P = N_0 B$



$z_1(t) = 2n(t)\cos(w_0 t+\theta)$

$n_c(t) = LP[z_1(t)]$

$z_2(t) = -2n(t)\sin(w_0 t+\theta)$

$n_s(t) = LP[z_2(t)]$



$R_{z_1 z_2}(t, t+\tau) = -2R_n(\tau)\sin(2\pi f_0 \tau)$

$S_{z_1 z_2}(f) = S_n(f) * [j\delta(f-f_0) - j\delta(f+f_0)]$

$= j[S_n(f-f_0) - S_n(f+f_0)]$

$R_{n_c n_s}(\tau) = E[\underbrace{h(t)*z_1(t)}_{n_c(t)} \cdot \underbrace{h(t)*z_2(t+\tau)}_{n_s(t+\tau)}]$

$= E\int_{t_1}\int_{t_2} h(t_1)h(t_2)z_1(t-t_1)z_2(t+\tau-t_2)\,dt_1 dt_2$

FT

$= \int\int h(t_1)h(t_2)R_{z_1 z_2}(\tau+t_1-t_2)\,dt_1 dt_2$

$= \int h(t_1)\cdot[h(\tau)*R_{z_1 z_2}(\tau+t_1)]\,dt_1$

$= h(-\tau)*h(\tau)*R_{z_1 z_2}(\tau)$

$S_{n_c n_s}(f) = |H(f)|^2 S_{z_1 z_2}(f) = jLP[S_n(f-f_0) - S_n(f+f_0)]$

$S_n(f)$



ref. freq. $f_0 + \frac{B}{2}$



① odd
② pure imaginary



$S_{n_c n_s}(f) = 0 \Rightarrow R_{n_c n_s}(\tau) = 0 \ \forall \tau$

$n_c(t), \ n_s(t)$



$R_{n_c n_s}(\tau)$



$R_{n_c n_s}(0) = 0$



Properties

- Let n(t) be a zero-mean, stationary and Gaussian noise, then $n_c(t)$ and $n_s(t)$ satisfy the following properties
  - $n_c(t)$ and $n_s(t)$ are zero-mean, jointly stationary and jointly Gaussian process
  - Means: $E[n(t)] = E[n_c(t)] = E[n_s(t)] = 0$
  - PSD: $S_{n_c}(f) = S_{n_s}(f) = \mathrm{Lp}[S_n(f - f_0) + S_n(f + f_0)]$
  - Variances(power): $E[n^2(t)] = E[n_c^2(t)] = E[n_s^2(t)] = \mathrm{N}_0 B \triangleq \sigma^2$
  - Correlation function:
    - $R_{n_c}(\tau) = R_{n_s}(\tau)$, $R_n(0) = R_{n_c}(0) = R_{n_s}(0) = N_0 B$
    - $R_{n_c n_s}(\tau) = -R_{n_c n_s}(-\tau)$ (odd), $R_{sc}(0) = R_{cs}(0) = 0.$
  - Cross-PSD: $S_{n_c n_s}(f) = j\mathrm{Lp}[S_n(f - f_0) - S_n(f + f_0)]$
    - $R_{n_c n_s}(\tau) \equiv 0, \forall \tau,\ \ \text{if } \mathrm{Lp}[S_n(f - f_0) - S_n(f + f_0)] = 0.$

Properties

- Let n(t) be a zero-mean, stationary and Gaussian noise, then $n_c(t)$ and $n_s(t)$ satisfy the following properties
  - $n_c(t)$ and $n_s(t)$ are uncorrelated (independent) Gaussian process

1. If PSD of n(t) is symmetric about f_0

$$R_{n_c n_s}(\tau) \equiv 0, \forall \tau$$



2. $\{\tau: R_{n_c n_s}(\tau)=0\}$.



Example: Ideal band-pass filtered white noise

- Consider a white Gaussian noise of zero mean and PSD N0/2, which is passed through an ideal band-pass filter.
- Determine the autocorrelation function of n(t) and its in-phase and quadrature components.





Example: Ideal band-pass filtered white noise





$$R_n(\tau) = N_0 B sinc(B\tau)\cos(2\pi f_0 \tau)$$

$$S_{n_c}(f) = S_{n_s}(f)$$





$$R_{n_c}(\tau) = R_{n_s}(\tau) = N_0 B sinc(B\tau)$$

Envelope and Phase

$$\begin{cases} n_c(t) = R(t)\cos\varphi(t) \\ n_s(t) = R(t)\sin\varphi(t) \end{cases}$$

- Angular representation of n(t)

$n(t) = n_c(t)\cos(2\pi f_0 t + \theta) - n_s(t)\sin(2\pi f_0 t + \theta)$

$$n(t) = R(t)\cos(\omega_0 t + \theta + \varphi(t)) = R(t)\cos(2\pi f_0 t + \theta)\cos\varphi(t) - R(t)\sin(2\pi f_0 t + \theta)\sin\varphi(t)$$

$$\text{where} \begin{cases} R(t) = \sqrt{n_c^2(t) + n_s^2(t)} & \text{envelope} \\ \varphi(t) = \tan^{-1}\dfrac{n_s(t)}{n_c(t)}, [0 \le \varphi(t) \le 2\pi] & \text{phase} \end{cases}$$

$Z = X + jY$

$X, Y \sim N(0, \sigma^2)$

$|Z| \sim$ Rayleigh Dis.

$\angle Z \sim$ uniform



Example

- Let n(t) be a zero-mean, stationary Gaussian process, find the statistics of the envelop and phase
- Result: $f(R(t), \varphi(t)) = f(R(t))f(\varphi(t))$
  - Envelop follows Rayleigh distribution
  - Phase follows uniform distribution



$$\begin{cases} f(R) = \int_0^{2\pi} f(R,\varphi)d\varphi = \dfrac{R}{\sigma^2}\exp\left\{-\dfrac{R^2}{2\sigma^2}\right\}, R \geq 0 \\ f(\varphi) = \int_0^{\infty} f(R,\varphi)dR = \dfrac{1}{2\pi}, 0 \leq \varphi \leq 2\pi \end{cases}$$

- For the same t, the envelop variable R and phase variable φ are independent (but not the two processes)

Rayleigh fading channel: model the fading channel with random scatters.

Derivation

$R_{n_c n_s}(0) = 0,$

- Derivation

$f(n_c(t), n_s(t)) = f(n_c(t)) f(n_s(t))$

$$f(R,\varphi) = f(n_c, n_s)\left|\frac{\partial(n_c, n_s)}{\partial(R,\varphi)}\right|$$

$$f(n_c, n_s) = f(n_c)\cdot f(n_s) = \frac{1}{2\pi\sigma^2}\exp\left[-\frac{n_c^2 + n_s^2}{2\sigma^2}\right]$$

$\sigma^2 = P = N_0 B$

$$\left|\frac{\partial(n_c, n_s)}{\partial(R,\varphi)}\right| = \begin{vmatrix} \frac{\partial n_c}{\partial R} & \frac{\partial n_s}{\partial R} \\ \frac{\partial n_c}{\partial \varphi} & \frac{\partial n_s}{\partial \varphi} \end{vmatrix} = \begin{vmatrix} \cos\varphi & \sin\varphi \\ -R\sin\varphi & R\cos\varphi \end{vmatrix} = R$$

$$f(R,\varphi) = Rf(n_c, n_s) = \frac{R}{2\pi\sigma^2}\exp\left[-\frac{(R\cos\varphi)^2 + (R\sin\varphi)^2}{2\sigma^2}\right]$$

$$= \frac{R}{2\pi\sigma^2}\exp\left\{-\frac{R^2}{2\sigma^2}\right\}$$

$$f(R(t)) = \frac{R}{\sigma^2}\exp\left\{-\frac{R^2}{2\sigma^2}\right\}, f(\varphi(t)) = \frac{1}{2\pi}$$

Summary

- For WSS:

$$S_X(f) \leftrightarrow R_X(\tau)$$

- WSS transmission through a linear system



$$R_Y(\tau) = h(-\tau) * h(\tau) * R_X(\tau)$$

$$S_Y(f) = |H(f)|^2 S_X(f)$$

- White noise (zero-mean)
  - Bandlimited noise
  - Narrowband noise: Gaussian, stationary and zero-mean
  - Non-Gaussian?

$|h|$

$h = h_{LOS} + h_{NLOS}$

Sine Wave with Bandpass Noise

- Received signal

$$r(t) = A\cos(\omega_c t + \theta) + n(t)$$

where A, ω_c are deterministic, θ is random phase uniformly distributed in $[-\pi, \pi]$, $n(t)$ is narrowband noise (zero-mean, stationary Gaussian process).

$$\begin{aligned} r(t) &= [A\cos\theta + n_c(t)]\cos\omega_c t - [A\sin\theta + n_s(t)]\sin\omega_c t \\ &= z_c(t)\cos\omega_c t - z_s(t)\sin\omega_c t \\ &= z(t)\cos[\omega_c t + \varphi(t)] \end{aligned}$$

$$z_c(t) = A\cos\theta + n_c(t)$$

$$z_s(t) = A\sin\theta + n_s(t)$$

Sine Wave with Bandpass Noise (cont'd)

- Envelop

$$z(t) = \sqrt{z_c^2(t) + z_s^2(t)}, z \geq 0$$

- Phase

$$\varphi(t) = \tan^{-1} \frac{z_s(t)}{z_c(t)}$$

- Given θ

$$E[z_c] = A\cos\theta$$
$$E[z_s] = A\sin\theta$$
$$\sigma_c^2 = \sigma_s^2 = \sigma_n^2$$

- Joint distribution

$$f(z_c, z_s|\theta) = \frac{1}{2\pi\sigma_n^2} \exp\left\{-\frac{1}{2\sigma_n^2}\left[(z_c - A\cos\theta)^2 + (z_s - A\sin\theta)^2\right]\right\}$$

PDF of the Amplitude

$$f(z_c, z_s|\theta) = \frac{1}{2\pi\sigma_n^2} \exp\left\{-\frac{1}{2\sigma_n^2}\left[(z_c - A\cos\theta)^2 + (z_s - A\sin\theta)^2\right]\right\}$$

$$f(z, \varphi|\theta) = f(z_c, z_s|\theta)\left|\frac{\partial(z_c, z_s)}{\partial(z, \varphi)}\right|$$

$$= \begin{vmatrix} \cos\varphi & \sin\varphi \\ -z\sin\varphi & z\cos\varphi \end{vmatrix} f(z_c, z_s|\theta) = z \cdot f(z_c, z_s|\theta)$$

- For PDF of the amplitude

$$f(z|\theta) = \int_0^{2\pi} f(z, \varphi|\theta)\,d\varphi$$

$$= \frac{z}{2\pi\sigma_n^2} \exp\left[-\frac{z^2 + A^2}{2\sigma_n^2}\right] \int_0^{2\pi} \exp\left[\frac{Az}{\sigma_n^2}\cos(\theta - \varphi)\right] d\varphi$$

PDF of the Amplitude (cont'd)

- Amplitude

$r(t) = A\cos(2\pi f_0 t + \theta)$

$+ n(t)$

$$f(z|\theta) = \int_0^{2\pi} f(z, \varphi|\theta) d\phi$$

$$= \frac{z}{2\pi\sigma_n^2} \exp\left[-\frac{z^2+A^2}{2\sigma_n^2}\right] \int_0^{2\pi} \exp\left[\frac{Az}{\sigma_n^2}\cos(\theta - \phi)\right] d\phi$$

$$= \frac{z}{2\pi\sigma_n^2} \exp\left[-\frac{z^2 + A^2}{2\sigma_n^2}\right] I_0\left(\frac{Az}{\sigma_n^2}\right)$$

$\frac{A}{\sigma_n^2} = SNR$

Ricean distribution

$I_0\left(\frac{Az}{\sigma_n^2}\right)$ 0th order Bessel functions of the first kind

PDF of the Amplitude (cont'd)

SINR = 0

- A small,

$$I_0\left(\frac{Az}{\sigma_n^2}\right) \approx 1$$

Rayleigh distribution

- A large,

$$I_0(x) \approx \frac{e^x}{\sqrt{2\pi x}}$$

Gaussian distribution

Ricean fading channel: model the fading channel with a direct path and scatters.

PDF of the Phase (cont'd)



- A small, Uniform distribution
- A large, Concentrate around θ

Ricean fading channel: model the fading channel with a direct path and scatters.

Thanks for your kind attention!

Questions?