One-Shot Coding over General Noisy Networks

Yanxiao Liu Cheuk Ting Li


The Chinese University of Hong Kong



Key Questions in Information Theory

Some key questions at the heart of information theory.


Key Question 1: Blocklength in Information Theory



One-shot information theory [2, 3]: network is only used once!

- Error probability cannot be driven to zero!
- No law of large number \rightarrow no typicality!
- No time-sharing!
- No memoryless/ergodic assumption!
- **Objective:** One-shot achievabilities that can imply existing (first/second order) asymptotic/finite-blocklength bounds?


Key Question 2: Noisy network coding



Noisy network coding [4]:

- What is the capacity of a noisy network?
- What coding scheme can achieve the capacity?

Key Question 3: Unified Coding Scheme



A unified coding schemes [1]:

- A unified node operation in networks?
- Unify channel coding, source coding, and coding for computing?
- Automated machine-proving tools?

A Unified One-Shot Coding Scheme

To answer the key questions on the left, our scheme [5] combines:

- 1. One-shot/finite-blocklength network information theory
- 2. Noisy network coding
- 3. Unified coding scheme (source/channel coding)

Main Theorem

For any acyclic discrete network $(P_{Y_i|X^{i-1},Y^{i-1}})_{i\in[N]}$, we provide a one-shot achievability result: For any collection of indices $(a_{i,j})_{i\in[N],j\in[d_i]}$ where $(a_{i,j})_{j\in[d_i]}$ is a sequence of distinct indices in [i-1] for each i, any sequence $(d_i')_{i\in[N]}$ with $0 \leq d_i' \leq d_i$ and any collection of conditional distributions $(P_{U_i|Y_i,\overline{U}_i'},P_{X_i|Y_i,U_i,\overline{U}_i'})_{i\in[N]}$ (where $\overline{U}_{i,\mathcal{S}}:=(U_{a_{i,j}})_{j\in\mathcal{S}}$ for $\mathcal{S}\subseteq[d_i]$ and $\overline{U}_i':=\overline{U}_{i,[d_i']}$), which induces the joint distribution of X^N,Y^N,U^N (the "ideal distribution"), there exists a public-randomness coding scheme $(P_W,(f_i)_{i\in[N]})$ such that the joint distribution of \tilde{X}^N,\tilde{Y}^N induced by the scheme (the "actual distribution") satisfies

$$\delta_{\text{TV}}(P_{X^N,Y^N}, P_{\tilde{X}^N,\tilde{Y}^N}) \le \mathbf{E} \Big[\min \Big\{ \sum_{i=1}^N \sum_{j=1}^{d_i'} B_{i,j}, 1 \Big\} \Big],$$

where $\gamma_{i,j}:=\prod_{k=j+1}^{d_i}(\ln |\mathcal{U}_{a_{i,k}}|+1)$, and

$$B_{i,j} := \gamma_{i,j} \prod_{k=j}^{d_i} \left(2^{-\iota(\overline{U}_{i,k}; \overline{U}_{i,[d_i]\setminus[j..k]}, Y_i) + \iota(\overline{U}_{i,k}; \overline{U}'_{a_{i,k}}, Y_{a_{i,k}})} + \mathbf{1}\{k > j\} \right).$$

Techniques

1. Poisson functional representation [3]: Let $\mathbf{U} := (Z_u)_{u \in \mathcal{U}}$ be i.i.d. $\mathrm{Exp}(1)$ random variables. Given a distribution P over finite \mathcal{U} ,

$$\mathbf{U}_P := \operatorname{argmin}_u \frac{Z_u}{P(u)}.$$

- 2. Each node is associated with an exponential process.
- 3. Exponential Process Refinement: For $Q_{V,U}$ over a finite $\mathcal{V} \times \mathcal{U}$, $\forall v \in \mathcal{V}$,

$$\mathbf{E}\left[\frac{1}{Q_{V,U}^{\mathbf{U}}(v,\mathbf{U}_P)}\middle|\mathbf{U}_P\right] \le \frac{\ln|\mathcal{U}|+1}{Q_V(v)}\left(\frac{P(\mathbf{U}_P)}{Q_{U|V}(\mathbf{U}_P|v)}+1\right).$$

 $Q_{U,V}$ (prior) \longrightarrow refine by \mathbf{U} (soft decoding) $\longrightarrow Q_{V,U}^{\mathbf{U}}$ (posterior)


References

- [1] Si-Hyeon Lee and Sae-Young Chung. A unified random coding bound. IEEE Transactions on Information Theory, 64(10):6779–6802, 2018.
- [2] Cheuk Ting Li and Venkat Anantharam. A unified framework for one-shot achievability via the poisson matching lemma. *IEEE Transactions on Information Theory*, 67(5):2624–2651, 2021.
- [3] Cheuk Ting Li and Abbas El Gamal. Strong functional representation lemma and applications to coding theorems. *IEEE Transactions on Information Theory*, 64(11):6967–6978, 2018.
- [4] Sung Hoon Lim, Young-Han Kim, Abbas El Gamal, and Sae-Young Chung. Noisy network coding. *IEEE Transactions on Information Theory*, 57(5):3132–3152, 2011.
- [5] Yanxiao Liu and Cheuk Ting Li. One-shot coding over general noisy networks. arXiv preprint arXiv:2402.06021, 2024.

Examples

The main theorem can be applied to any combination of source coding, channel coding and coding for computing. Note $\iota(x;y|z) := \log \frac{P(x,y|z)}{(P(x|z)P(y|z))}$.

Channel Coding with State Info at Encoder




Fix $P_{U|S}$ and $x: \mathcal{U} \times \mathcal{S} \to \mathcal{X}$. For $M \sim \text{Unif}[L], S \sim P_S$, let $U_1 = (U, M)$,

 $P_e := \mathbf{P}(\tilde{X}_2 \neq M) \leq \mathbf{E} \left[\min \left\{ L2^{-\iota(U;Y) + \iota(U;S)}, 1 \right\} \right].$

It attains the best known second-order result.

It also covers coding for computing problems.

Source Coding with Side Info at Decoder




Fix $P_{U|X}$ and $z: \mathcal{U} \times \mathcal{Y} \to \mathcal{Z}$. For $X \sim P_X, T \sim P_{T|X}, M \in [L]$, $P_e := \mathbf{P}\{d(X, \tilde{Z}) > \mathsf{D}\} \leq \mathbf{E}\Big[\min\Big\{\mathbf{1}\{d(X, Z) > \mathsf{D}\} + \mathsf{L}^{-1}2^{-\iota(U;T) + \iota(U;X)}, 1\Big\}\Big].$

Multiple Access Channel

For MAC $P_{Y|X_1,X_2}$ and $M_j \sim \mathrm{Unif}[\mathsf{L}_j]$ for j=1,2, with $\gamma:=\ln(\mathsf{L}_1|\mathcal{X}_1|)+1$, $P_e \leq \mathbf{E}\Big[\min\Big\{\gamma\mathsf{L}_1\mathsf{L}_22^{-\iota(X_1,X_2;Y)}+\gamma\mathsf{L}_22^{-\iota(X_2;Y|X_1)}+\mathsf{L}_12^{-\iota(X_1;Y|X_2)},1\Big\}\Big].$ It recovers the asymptotic capacity region.

One-Shot Relay Channel



Let $U_1 := (X, M)$, $U_2 := U$, Main Theorem gives a compress-forward bound:

$$P_e \le \mathbf{E} \Big[\min \Big\{ \gamma \mathsf{L} 2^{-\iota(X;U,Y)} \Big(2^{-\iota(U;Y) + \iota(U;Y_r)} + 1 \Big), 1 \Big\} \Big]$$

where $\gamma=\ln |\mathcal{U}|+1$, $(X,Y_{\mathrm{r}},U,X_{\mathrm{r}},Y)\sim P_X P_{Y_{\mathrm{r}}|X} P_{U|Y_{\mathrm{r}}} \delta_{x_{\mathrm{r}}(Y_{\mathrm{r}},U)} P_{Y|X,Y_{\mathrm{r}},X_{\mathrm{r}}}$.

- It is a one-shot version of relay-with-unlimited-look-ahead.
- If Y = (Y', Y'') and $P_{Y|X,X_r,Y_r} = P_{Y'|X,Y_r}P_{Y''|X_r}$, it is a one-shot version of primitive relay channel.
- By message splitting, we can also have a partial-decode-forward bound.