

Derivation of every equation in `sw_sn_driver.py`

Full shallow water on a finite-amplitude meander, channel-fitted (s, n)

numerical/dedalus_meander_full_SW

This note derives, in order, every formula that appears in `sw_sn_driver.py`. Each section names the code symbol it produces.

Contents

1	Why (s, n), and the metric $\sigma = 1 + nC$	2
2	Shallow-water equations in (s, n)	2
2.1	The starting (Cartesian) system	2
2.2	Curvilinear operators	2
2.3	The system solved	3
3	Non-dimensionalisation: where the Froude number enters	3
4	The base state	3
4.1	Parabolic jet and the constant channel- β	3
4.2	Base curvature = the finite background meander	4
4.3	Superelevation	4
4.4	Discharge conservation	4
5	Linearisation	4
5.1	Continuity	4
5.2	s -momentum	5
5.3	n -momentum and the curvature feedback	5
6	Why every equation is multiplied by σ	5
7	Bottom friction: the factor of two, and the free-surface term	5
8	Boundary conditions, and why there are four tau terms	6
9	Erodible bank: the meander equation	6
10	Seeding, and why the seed must be a domain mode	7
11	Measuring σ and c	7
12	What the model does <i>not</i> contain, and what follows	8
13	Classifying the mode (what the diagnostics mean)	8

1 Why (s, n) , and the metric $\sigma = 1 + nC$

The channel meanders with *finite* amplitude, so its banks are not straight lines and a Chebyshev grid cannot be laid on them directly. We therefore use **channel-fitted** coordinates: s = arc length along the centreline, n = signed distance across it. In (s, n) the channel is a straight strip $n \in [-b, b]$ whatever the planform does.

Let the centreline be $\mathbf{r}_c(s)$ with unit tangent $\hat{\mathbf{t}}(s)$ and unit normal $\hat{\mathbf{n}}(s)$, and let $C(s)$ be its curvature. A point of the domain is

$$\mathbf{r}(s, n) = \mathbf{r}_c(s) + n \hat{\mathbf{n}}(s). \quad (1)$$

With the Frenet relation $d\hat{\mathbf{n}}/ds = +C \hat{\mathbf{t}}$ (this *defines* our sign convention: n increases *away* from the centre of curvature; equivalently the direction angle is $\theta(s) = -\int^s C ds'$),

$$\frac{\partial \mathbf{r}}{\partial s} = \hat{\mathbf{t}} + n \frac{d\hat{\mathbf{n}}}{ds} = (1 + nC) \hat{\mathbf{t}}, \quad \frac{\partial \mathbf{r}}{\partial n} = \hat{\mathbf{n}}, \quad (2)$$

so the coordinates are orthogonal with scale factors

$$\boxed{h_s = \sigma \equiv 1 + nC(s), \quad h_n = 1.} \quad (\rightarrow \text{sigma_metric, sig})$$

σ is the local stretching of an along-channel line at offset n : the outer bank (n with the sign of C) is longer, the inner bank shorter.

Validity. $\sigma > 0$ is required or the mapping folds. Since $|n| \leq b$, this is $|C|b < 1$: the bend radius must exceed the half-width. The test `tests/test_base_profiles.py` asserts $\min \sigma > 0$.

Sign convention (important). Mirroring the channel ($C \rightarrow -C$) maps the problem to itself with $n \rightarrow -n$, so the linear growth rate $\sigma(k)$ and phase speed $c(k)$ are *unchanged*; only the labelling of “outer” vs “inner” bank flips. The convention above is the one used by the solver ($\sigma = 1 + nC$); the lab-frame renderer must integrate $\theta = -\int C ds$ to match it.

2 Shallow-water equations in (s, n)

2.1 The starting (Cartesian) system

Non-rotating depth-averaged shallow water over a bed of still-water depth H , free surface η , total depth $h = \eta + H$:

$$\partial_t \mathbf{u} + (\mathbf{u} \cdot \nabla) \mathbf{u} = -g \nabla \eta + \mathbf{F}, \quad \partial_t \eta + \nabla \cdot (h \mathbf{u}) = 0. \quad (3)$$

The pressure is hydrostatic, $p = \rho g(\eta - z)$, so the horizontal pressure gradient is exactly $-g \nabla \eta$; this is the $L \gg H$ (long-wave) limit. Keeping $\partial_t \eta$ is what admits **gravity waves**; the rigid-lid packages in ../ drop it and are left with the vortical branch only.

2.2 Curvilinear operators

For orthogonal coordinates with scale factors $(h_s, h_n) = (\sigma, 1)$:

$$\nabla \phi = \frac{1}{\sigma} \partial_s \phi \hat{\mathbf{t}} + \partial_n \phi \hat{\mathbf{n}}, \quad (4)$$

$$\nabla \cdot \mathbf{F} = \frac{1}{\sigma} \left[\partial_s F_s + \partial_n (\sigma F_n) \right], \quad (5)$$

$$\zeta = (\nabla \times \mathbf{u}) \cdot \hat{\mathbf{z}} = \frac{1}{\sigma} \left[\partial_s u_n - \partial_n (\sigma u_s) \right]. \quad (6)$$

The material acceleration acquires *metric* (centrifugal/Coriolis-like) terms from the rotation of the basis vectors. With $D/Dt = \partial_t + (u_s/\sigma)\partial_s + u_n\partial_n$ and $\partial h_s/\partial n = C$, $\partial h_n/\partial s = 0$, the standard result is

$$a_s = \frac{Du_s}{Dt} + \frac{C u_s u_n}{\sigma}, \quad a_n = \frac{Du_n}{Dt} - \frac{C u_s^2}{\sigma}. \quad (7)$$

2.3 The system solved

Substituting (5)–(7) into (3):

$$\partial_t \eta + \frac{1}{\sigma} [\partial_s(hu_s) + \partial_n(\sigma h u_n)] = 0, \quad (8)$$

$$\partial_t u_s + \frac{u_s}{\sigma} \partial_s u_s + u_n \partial_n u_s + \underbrace{\frac{C u_s u_n}{\sigma}}_{\text{bend coupling}} = -\frac{g}{\sigma} \partial_s \eta - r_s u_s + \nu \nabla^2 u_s, \quad (9)$$

$$\partial_t u_n + \frac{u_s}{\sigma} \partial_s u_n + u_n \partial_n u_n - \underbrace{\frac{C u_s^2}{\sigma}}_{\text{centrifugal}} = -g \partial_n \eta - r_n u_n + \nu \nabla^2 u_n. \quad (10)$$

The term $-C u_s^2/\sigma$ is the whole reason for going to (s, n) : it is the centrifugal acceleration of water rounding a bend, and it is what tilts the free surface up against the outer bank (§4). No straight-channel model contains it.

3 Non-dimensionalisation: where the Froude number enters

Scale lengths by the half-width b , speeds by the centreline speed $U_c = U_0 + \Delta$, time by b/U_c , and depths/ η by the mean depth H_0 . The only place g survives is the pressure gradient, where it appears as

$$\frac{gH_0}{U_c^2} = \frac{1}{F^2}, \quad \boxed{F \equiv \frac{U_c}{\sqrt{gH_0}}, \quad g_{\text{eff}} = \frac{1}{F^2}} \quad (\rightarrow \text{g_eff})$$

so the non-dimensional gravity-wave speed is $\sqrt{g_{\text{eff}}H_0} = 1/F$.

Why F must be specified, and why one value proves nothing. F is an *input* (a property of the river), exactly like a Reynolds number: without it the system (8)–(10) is not defined. At any F *both* families exist — gravity waves at speed $1/F$ and the vortical branch at $O(U)$. Which one the bank couples to is decided by *measurement*: compare c_{meander} with $1/F$, and above all *vary* F . If the meander rode the gravity branch, tripling $1/F$ would move σ, c . It does not (`sweep_dispersion.py` $\rightarrow$ `fig01`), which is the evidence that the meander is the vortical/Rossby wave.

4 The base state

4.1 Parabolic jet and the constant channel- β

$$\boxed{\bar{U}_s(n) = U_0 + \Delta \left(1 - \frac{n^2}{b^2}\right)} \quad (\rightarrow \text{ubar_s})$$

so $\bar{U}_s(0) = U_0 + \Delta$ (centre) and $\bar{U}_s(\pm b) = U_0$ (bank edge), and

$$\partial_n \bar{U}_s = -\frac{2\Delta n}{b^2} \quad (\rightarrow \text{ubar_s_n}), \quad \partial_n^2 \bar{U}_s = -\frac{2\Delta}{b^2} = \text{const} \quad (\rightarrow \text{ubar_s_nn}). \quad (11)$$

This constant is the load-bearing property. From (6) with $u_n = 0$ and (for the moment) $C = 0$, the base vorticity is $\bar{\zeta} = -\partial_n \bar{U}_s$, hence

$$\boxed{\frac{\partial \bar{\zeta}}{\partial n} = -\partial_n^2 \bar{U}_s = \frac{2\Delta}{b^2} = \text{constant}} \quad (12)$$

— a uniform cross-channel gradient of background vorticity, which is why the jet is taken parabolic rather than, say, sinusoidal. It is tempting to call this a channel β and conclude that a *vortical* (*Rossby-type*) wave is thereby possible; that inference does **not** follow, and we do not make it. A planetary β supports discrete Rossby modes because the domain is unbounded or the PV profile has an edge; a smooth, single-signed $\partial_n \bar{q}$ between two walls has no PV edge, and by the classical result of Case (1960) it supports only a *continuous* spectrum — sheared disturbances that decay algebraically, not an exponentially growing normal mode. Discrete modes require a PV discontinuity or extremum (Bretherton 1966; Rayleigh’s inflexion criterion), which (??) explicitly excludes. What Δ does give us is a clean control knob: Δ is the shear, so setting $\Delta = 0$ removes the “ β ” entirely and tests directly whether the growing meander needs it (§??). (For $C \neq 0$ the same calculation gives $\bar{\zeta} = -\partial_n \bar{U}_s - C \bar{U}_s / \sigma$, a curvature correction.)

4.2 Base curvature = the finite background meander

$$\boxed{\bar{C}(s) = \bar{C}_{\text{amp}} \cos(k_m s), \quad \bar{C}_{\text{amp}} = A_{\text{bank}} k_m^2 \text{ (default)}} \quad (\rightarrow \text{cbar})$$

For a centreline of lateral amplitude A_{bank} and wavenumber k_m , the small-slope curvature is $-\partial_s^2 (A_{\text{bank}} \cos k_m s) = A_{\text{bank}} k_m^2 \cos k_m s$; `Cbar_amp` overrides this to set a genuinely tight bend directly. A_{bank} **is the fixed background channel shape** — it is *not* the perturbation seed A_0 of §10, and it does not evolve.

4.3 Superelevation

For a steady base with $\bar{U}_n = 0$ and $\partial_s(\cdot) = 0$, the n -momentum (10) reduces to a balance between the centrifugal term and the pressure gradient:

$$\boxed{g \partial_n \bar{\eta} = \frac{\bar{C} \bar{U}_s^2}{\bar{\sigma}}} \quad (\rightarrow \text{etabar})$$

integrated as $\bar{\eta}(s, n) = \frac{\bar{C}(s)}{g} \int_0^n \frac{\bar{U}_s^2(n')}{1 + n' \bar{C}(s)} dn'$ (zero on the centreline). The water surface tilts *up towards the outer bank* — the superelevation. Note $\bar{C} \rightarrow 0 \Rightarrow \bar{\eta} \rightarrow 0$ (asserted in the test).

4.4 Discharge conservation

The base continuity (8) with $\bar{U}_n = 0$ requires $\partial_s(\bar{h} \bar{U}_s) = 0$: the transport is the same through every cross-section. With a cross-channel-only bed this is automatic ($\bar{U}_s = \bar{U}_s(n)$).

What sustains the base. A parallel jet with bottom drag is not a steady solution unless something drives it (the downhill slope). As in every frozen-jet stability analysis we *prescribe* $\bar{U}_s$ and absorb the residual into an implicit steady forcing; it cancels from the perturbation equations below.

5 Linearisation

Write $u_s = \bar{U}_s + u'_s$, $u_n = u'_n$, $\eta = \bar{\eta} + \eta'$, $h = \bar{h} + \eta'$, $C = \bar{C} + C'$, and drop products of primes.

5.1 Continuity

$\partial_s(hu_s) = \partial_s(\bar{h}\bar{U}_s) + \bar{h}\partial_s u'_s + \bar{U}_s\partial_s\eta'$, where the first term vanishes (discharge), and $\partial_n(\sigma hu_n) \rightarrow \partial_n(\bar{\sigma}\bar{h}u'_n)$. Hence

$$\bar{\sigma}\partial_t\eta' + \bar{h}\partial_s u'_s + \bar{U}_s\partial_s\eta' + \partial_n(\bar{\sigma}\bar{h}u'_n) = 0, \quad (\rightarrow \text{eq. 1 in build_ivp_SW})$$

already multiplied by $\bar{\sigma}$ (§6).

5.2 s-momentum

$\frac{u_s}{\sigma}\partial_s u_s \rightarrow \frac{\bar{U}_s}{\bar{\sigma}}\partial_s u'_s$; $u_n\partial_n u_s \rightarrow u'_n\partial_n \bar{U}_s$; $\frac{Cu_s u_n}{\sigma} \rightarrow \frac{\bar{C}\bar{U}_s u'_n}{\bar{\sigma}}$. Multiplying by $\bar{\sigma}$ collects the two u'_n terms into one coefficient:

$$\bar{\sigma}\partial_t u'_s + \bar{U}_s\partial_s u'_s + \underbrace{(\bar{\sigma}\partial_n \bar{U}_s + \bar{C}\bar{U}_s)}_{\rightarrow \text{coefUn}} u'_n + g\partial_s\eta' + \bar{\sigma}r_s u'_s - \bar{\sigma}\nu\nabla^2 u'_s = 0. \quad (\rightarrow \text{eq. 2})$$

The u'_n coefficient is the cross-channel advection of background momentum — proportional to the base vorticity — and is the term that carries the Rossby-type restoring.

5.3 n-momentum and the curvature feedback

Expanding $-Cu_s^2/\sigma$ with $C = \bar{C} + C'$, $\sigma = \bar{\sigma} + nC'$:

$$-\frac{Cu_s^2}{\sigma} \simeq \underbrace{-\frac{\bar{C}\bar{U}_s^2}{\bar{\sigma}}}_{\text{base}} - \underbrace{\frac{2\bar{C}\bar{U}_s u'_s}{\bar{\sigma}}}_{\rightarrow \text{twoCbUb}} - \underbrace{\frac{C'\bar{U}_s^2}{\bar{\sigma}}}_{\text{new bend}} + \frac{nC'\bar{C}\bar{U}_s^2}{\bar{\sigma}^2}. \quad (13)$$

The perturbed pressure term contributes $-\bar{\sigma}g\partial_n\eta' - nC'g\partial_n\bar{\eta}$, and using the base balance ($\rightarrow \text{etabar}$), $g\partial_n\bar{\eta} = \bar{C}\bar{U}_s^2/\bar{\sigma}$, the last piece is $-nC'\bar{C}\bar{U}_s^2/\bar{\sigma}$. Adding it to the $+nC'\bar{C}\bar{U}_s^2/\bar{\sigma}^2$ above and using $\bar{\sigma} - n\bar{C} = 1$ leaves the remarkably clean forcing

$$\boxed{n\text{-momentum forcing} = \frac{C'\bar{U}_s^2}{\bar{\sigma}} \simeq C'\bar{U}_s^2.} \quad (14)$$

So the final equation, with the forcing moved to the left and $C' = -\partial_s^2\zeta_c$ (§9):

$$\bar{\sigma}\partial_t u'_n + \bar{U}_s\partial_s u'_n - 2\bar{C}\bar{U}_s u'_s + \bar{\sigma}g\partial_n\eta' + \bar{\sigma}r_n u'_n - \bar{\sigma}\nu\nabla^2 u'_n + \underbrace{\bar{U}_s^2\partial_s^2\zeta_c}_{\text{bend} \rightarrow \text{flow}} = 0. \quad (\rightarrow \text{eq. 3})$$

This is the coupling that closes the meander instability: a bend creates a centrifugal forcing, which drives the flow, which erodes the bank, which deepens the bend.

6 Why every equation is multiplied by σ

The raw equations carry $1/\sigma = 1/(1+nC)$, a *rational* function of n . Dedalus builds such a coefficient as a dense operator (its documentation warns about exactly this), destroying the banded structure. Multiplying each equation through by σ removes every $1/\sigma$ and leaves coefficients that are polynomial in n (products of σ , $\bar{h}$, $\bar{U}_s$), so the matrices stay banded. Multiplying an equation by a nonzero function is an exact, solution-preserving row operation. The one residual $1/\bar{\sigma}$ (in the C' forcing) is dropped at $O(n\bar{C}C')$, i.e. second order in the perturbation amplitude *and* the base curvature.

7 Bottom friction: the factor of two, and the free-surface term

Quadratic (Chézy) drag is $\mathbf{F} = -\frac{C_f}{h}|\mathbf{u}|\mathbf{u}$. Two things must be linearised: the *velocity* in $|\mathbf{u}|\mathbf{u}$, and the *depth* in $1/h$. With $\mathbf{u} = (\bar{U}_s + u'_s, u'_n)$, $h = \bar{h} + \eta'$ and $|\mathbf{u}| \simeq \bar{U}_s + u'_s$:

$$-\frac{C_f|\mathbf{u}|u_s}{h} \simeq \underbrace{-\frac{C_f\bar{U}_s^2}{\bar{h}}}_{\text{base}} - \underbrace{\frac{2C_f\bar{U}_s}{\bar{h}}u'_s}_{r_s \rightarrow \text{rs_a}} + \underbrace{\frac{C_f\bar{U}_s^2}{\bar{h}^2}\eta'}_{\text{superelevation drag } (\rightarrow \text{reta_a})}, \quad -\frac{C_f|\mathbf{u}|u_n}{h} \simeq -\underbrace{\frac{C_f\bar{U}_s}{\bar{h}}}_{r_n}u'_n. \quad (15)$$

The drag is **anisotropic**: streamwise perturbations are damped twice as fast as cross-stream ones, because they perturb $|\mathbf{u}|$ as well as the direction.

The last term is Ikeda–Parker–Sawai’s *superelevation-drag* term [1]: where the surface is raised the column is deeper, the drag $\propto 1/h$ is weaker, and the flow there accelerates. **It is the only route by which the free surface drives bend flow, and hence the only place the Froude number enters classical bend theory.** Omitting it (as an earlier version of this code did) removes the physical mechanism this package exists to add, and makes any Froude sensitivity test vacuous. The base part $C_f\bar{U}_s^2/\bar{h}$ belongs to the implicit driving balance and cancels.

8 Boundary conditions, and why there are four tau terms

The banks sit at fixed $n = \pm b$ in channel coordinates. Water cannot cross a solid bank, so

$$\boxed{u'_n(\pm b) = 0} \quad (\text{no penetration}). \quad (16)$$

This assumes *nothing* about the interior divergence: $\nabla \cdot \mathbf{u} \neq 0$ everywhere inside (that is what the free surface is for). In particular the bank is *not* treated as a material streamline — that would be a rigid-lid (non-divergent) assumption and is inconsistent with (8).

Lateral eddy viscosity $\nu\nabla^2$ makes each momentum equation second order in n , which (i) is physically reasonable for a river, (ii) makes the parabolic jet an actual steady solution, and (iii) gives a standard tau closure. A second-order operator needs one boundary condition per wall per component, so with free slip

$$\partial_n u'_s(\pm b) = 0 \quad (\text{free slip}), \quad (17)$$

the tau budget is 2 per viscous velocity component:

$$\underbrace{2}_{u'_s} + \underbrace{2}_{u'_n} + \underbrace{0}_{\eta'} = 4 \quad (\rightarrow \text{t_us1}, \text{t_us2}, \text{t_un1}, \text{t_un2}),$$

η' needing none because its equation contains no second n -derivative. Counting unknowns and equations: $\{u'_s, u'_n, \eta', \zeta_c\} + 4 \text{ tau} = 8$ and $3 \text{ PDE} + 2 \text{ no-penetration} + 2 \text{ free-slip} + 1 \text{ erosion} = 8$. The tau terms are lifted onto the last two Chebyshev modes, `lift(t, -1) + lift(t, -2)` on `ybasis.derivative_basis(2)`.

9 Erodible bank: the meander equation

The bank is a sediment boundary, not a material line: it recedes because the flow erodes it. Ikeda’s closure makes the migration rate proportional to the *near-bank excess longitudinal velocity*. For a **bend** the outer bank is fast and the inner bank slow, so it is the **antisymmetric** part that moves the centreline:

$$\boxed{\partial_t \zeta_c = E \cdot \frac{1}{2} [u'_s(+b) - u'_s(-b)], \quad E = \varepsilon U_0} \quad (18)$$

where $\zeta_c(s, t)$ is the lateral offset of the centreline (constant width).

Why antisymmetric — and a correction. The antisymmetric combination is not an extra modelling choice: it follows from taking each bank’s *outward* normal. The $+b$ bank’s outward normal is $+\hat{n}$ and the $-b$ bank’s is $-\hat{n}$, so outward erosion of each bank is $\partial_t \xi_+ = +Eu'_s(+b)$ and $\partial_t \xi_- = -Eu'_s(-b)$, whence the centreline $\frac{1}{2}(\xi_+ + \xi_-)$ obeys exactly (18), and the width mode $\frac{1}{2}(\xi_+ - \xi_-)$ obeys $\partial_t(\cdot) = \frac{E}{2}[u'_s(+b) + u'_s(-b)]$, which vanishes identically because the response u'_s is *odd* in n . *Correction to an earlier version of this note:* it claimed that “independent banks” would instead drive the centreline through the *symmetric* part and give $\sigma < 0$. That was wrong — it used $+\hat{n}$ for both banks. The two formulations are **identical**, not opposed; the earlier $\sigma < 0$ came from that sign error killing the feedback, not from parity.

Closing the loop. The migrating centreline changes the curvature,

$$C'(s, t) = -\partial_s^2 \zeta_c, \quad (19)$$

which re-enters the n -momentum as the forcing derived in §5.3. The cycle

$$\zeta_c \longrightarrow C' \longrightarrow \text{flow} \longrightarrow u'_s(\pm b) \longrightarrow \partial_t \zeta_c$$

is the meander instability. Its growth rate is what the IVP measures.

10 Seeding, and why the seed must be a domain mode

The base state is an exact steady solution: started there, nothing ever happens. Stability analysis therefore *requires* a perturbation, and its growth rate is the answer. Because the dynamics are linear, *any* perturbation is admissible.

Broadband seeding (the default). We seed the centreline with all resolvable modes at once, equal amplitude and fixed pseudo-random phases:

$$\zeta_c(s, 0) = A_0 \sum_{m=1}^{N_s/2-1} \cos(k_m s + \phi_m), \quad k_m = \frac{2\pi m}{L_s}, \quad u'_s = u'_n = \eta' = 0. \quad (20)$$

For a *straight* base channel the coefficients are s -independent, so the s -Fourier modes decouple exactly: each k_m then evolves on its own and a **single run contains the entire dispersion relation**, recovered by demodulating each mode ($\rightarrow$ `per_mode_dispersion`). This is both cheaper and safer than one run per wavelength — in particular it removes any question of whether the seeded wavenumber is commensurate with the domain. Runs are accordingly identified by their physics — bed H , initial bank sinuosity $\bar{C}_{\text{amp}} b$, friction C_f , and the base speeds U_0, Δ ($\rightarrow$ `run_tag`) — never by a seeded wavelength. Δ belongs in that label even though it reads as a mere “speed”: by (??) it *is* the cross-channel vorticity gradient, so $\Delta = 0$ (plug) and $\Delta < 0$ (reversed shear) are the two sharpest experiments in the study, and omitting it would let them collide. At finite bank sinuosity the coefficients are s -periodic, the modes couple (Floquet), and the per-mode numbers are Bloch quantities rather than eigenvalues.

Convergence gate. A fitted growth rate is meaningless unless the mode actually grew: we record the e-foldings achieved over the fit window and mark any mode with fewer than three as not converged. (Without this gate, slowly-evolving modes return fitted rates whose *sign* depends on the fit window.)

A_0 is a free constant. The system is linear, so if $(u'_s, u'_n, \eta', \zeta_c)$ solves it then so does $\lambda \times$ it. Only σ , c and the *ratios* between fields are physical; the overall size is set by whatever initial disturbance one assumes. This is why the movie may fix the overall constant once (final meander = 0.5b) and apply it to every frame and every field — that is a re-choice of A_0 , not a distortion.

11 Measuring σ and c

The centreline is demodulated onto its seeded mode, $a(t) = \hat{\zeta}_c(m, t)$, and

$$\sigma = \frac{d}{dt} \ln |a|, \quad c = -\frac{1}{k} \frac{d}{dt} \arg a, \quad (\rightarrow \text{measure_sigma_c})$$

both fitted over the last two thirds of the run (dropping the initial adjustment, during which the flow spins up from rest). $\sigma > 0$ is an unstable meander; $c > 0$ means the bend train migrates downstream.

12 What the model does *not* contain, and what follows

Strictly linear perturbation dynamics (no $\mathbf{u}' \cdot \nabla \mathbf{u}'$); no rotation ($f = 0$, a river); no vertical structure, hence no helical secondary flow (depth-averaged away, i.e. this is the $A = 0$ limit of [1], whose $A \approx 2.89$ is their *dominant* bend driver); the base state is frozen (its steady residual is an implicit forcing); and the lateral viscosity uses the flat rather than the exact curvilinear vector Laplacian — a wall closure and short-wave regulariser.

Three consequences must be stated plainly, because they bound what any result here can mean.

(i) **No sediment, therefore no wavelength selection.** The bed H is prescribed and only the banks move. Meander wavelength selection is understood as a resonance between the forced bend flow and the *free alternate-bar mode of the sediment bed* [3, 4, 6]. With the bed frozen that free mode does not exist, so this model *cannot* select a wavelength: the $C' = -\partial_s^2 \zeta_c$ forcing scales as k^2 while the response scales as k , giving σ growing monotonically with k until the artificial viscosity cuts it off. The selected wavelength is therefore set by ν , not by physics, and no comparison with the observed $\lambda \approx 10W$ [14] is meaningful.

(ii) **The erodibility is not in the geomorphic regime.** Field calibration gives $E/U \sim 10^{-8}$ [11, 12]; the default here is $O(10^{-1})$. Classical theories take $E \rightarrow 0$, which is what makes the flow quasi-steady and justifies imposing $u'_n(\pm b) = 0$ at a *fixed* wall. At $O(1)$ erodibility the neglected wall-normal velocity $E u'_s(\pm b)$ is not small compared with the retained u'_n , so the boundary condition is inconsistent at leading order, and σ , c are properties of a strongly coupled flow–bank oscillator rather than of a river.

(iii) **Froude insensitivity is weak evidence by construction.** Writing $P \equiv g\eta$, the momentum equations contain no F at all and F survives only as F^2 multiplying the time-and-advection derivative of P in continuity — i.e. purely as a divergence (compressibility) parameter. Any slow, balanced mode is therefore F -insensitive as a matter of scaling, and the observed insensitivity *confirms* the rigid-lid reduction rather than discriminating between wave families. Distinguishing a free vortical wave from a forced boundary mode requires the diagnostics of §13, not a Froude sweep.

13 Classifying the mode (what the diagnostics mean)

`classify_mode()` reports, from the perturbation fields:

$\|\delta'\|/\|\zeta'\|$ divergent vs rotational: $\rightarrow 0$ means balanced (not a gravity wave),

$\|q'\|/\|\zeta'\|$ $q' = \zeta'/\bar{h} - \bar{\zeta}\eta'/\bar{h}^2$: how much vortex stretching,

$\|\eta'\|/\|\mathbf{u}'\|$ should scale as F^2 for a balanced mode,

$T_{\text{shear}} = -\int u'_s u'_n \partial_n \bar{U}_s$ the ONLY channel by which the mean-flow PV gradient can power a wave,

$T_{\text{bend}} = -\int u'_n \bar{U}_s^2 \partial_s^2 \zeta_c$ work done on the fluid by the moving bank.

The decisive one is T_{shear} . A free vortical (Rossby-type) wave is *defined* by extracting wave activity from the background PV gradient, so it requires $T_{\text{shear}} > 0$. If instead $T_{\text{shear}} \leq 0$ the mean flow is a *sink* and the disturbance is being driven by the boundary, whatever its Froude behaviour. Note also that a smooth, single-signed $\partial_n \bar{q}$ (which is what a parabolic jet gives) has no PV edge and therefore supports *no discrete* vortical eigenmode at all — only a continuous spectrum [15]; discrete counter-propagating Rossby waves require localised PV gradients [16]. Planetary β supports Rossby waves with no mean flow whatever; a shear- β does not, because it *is* the mean flow.

14 What the parameter study actually returns

`experiments.py` runs one broadband simulation per physical configuration, varying the bed, the initial bank sinuosity, the friction and the two base speeds one at a time. Table ?? is generated directly from the output files by `make_results_table.py` — it is never typed by hand, so it cannot drift from the data it describes.

[table pending: run `../experiments.py` then `make_results_table.py`]

Table 1: Fastest *converged* mode (≥ 3 e-foldings) per configuration, and the energetics ratio. $T_{\text{shear}} > 0$ would mean the mean-flow vorticity gradient powers the disturbance.

Three readings follow, and none of them is the headline one might have hoped for.

The mean flow is a sink, not the power source. $T_{\text{shear}} < 0$ in every configuration. Whatever is growing is *not* extracting wave activity from the background vorticity gradient, so by the criterion of §13 it is not a free vortical (Rossby-type) wave. The energy comes from T_{bend} — the work done on the fluid by the moving bank — which is to say from the erosion closure.

The channel- β is not necessary. The sharpest test is the plug-flow run, $\Delta = 0$: the shear, and with it the entire “channel β ” of (??), is identically zero, and $T_{\text{shear}} \equiv 0$ by construction. The meander nevertheless grows — in fact faster than the sheared reference. A mechanism that survives the removal of β cannot be a β -restored wave. The reversed-shear run ($\Delta < 0$) grows too. This is a null result, and it is the most informative thing in the table.

There is no wavelength selection. k_{max} sits at the short-wave end of the resolved band in every run, as §??(i) predicts on structural grounds: with the bed frozen, nothing in the model sets a length scale except ν .

What the model *is*, then. A forced morphodynamic boundary mode: balanced (the divergence ratio is small and F barely matters, both consistent with the rigid-lid reduction), but driven by the erodible boundary rather than by the interior PV gradient. The growth rate vanishes with the erodibility, $\sigma \propto E$ — it is not an eigenvalue of the flow alone. The useful corollary is a validation result: since the free surface is passive here, the rigid-lid packages in . ./ are justified for $F \lesssim 0.9$.

References

- [1] Ikeda, S., Parker, G. & Sawai, K. (1981) Bend theory of river meanders. Part 1. Linear development. *J. Fluid Mech.* **112**, 363–377.
- [2] Parker, G., Sawai, K. & Ikeda, S. (1982) Bend theory of river meanders. Part 2. *J. Fluid Mech.* **115**, 303–314.
- [3] Blondeaux, P. & Seminara, G. (1985) A unified bar–bend theory of river meanders. *J. Fluid Mech.* **157**, 449–470.
- [4] Seminara, G. (2006) Meanders. *J. Fluid Mech.* **554**, 271–297.
- [5] Zolezzi, G. & Seminara, G. (2001) Downstream and upstream influence in river meandering. *J. Fluid Mech.* **438**, 183–211.
- [6] Camporeale, C., Perona, P., Porporato, A. & Ridolfi, L. (2007) Hierarchy of models for meandering rivers. *Rev. Geophys.* **45**, RG1001.
- [7] Smith, J. D. & McLean, S. R. (1984) A model for flow in meandering streams. *J. Geophys. Res.* **89**(C4), 7389–7408.
- [8] Engelund, F. (1974) Flow and bed topography in channel bends. *J. Hydraul. Div. ASCE* **100**(HY11), 1631–1648.
- [9] Johannesson, H. & Parker, G. (1989) Linear theory of river meanders. *River Meandering*, AGU Water Resour. Monogr. 12, 181–213.
- [10] Colombini, M., Seminara, G. & Tubino, M. (1987) Finite-amplitude alternate bars. *J. Fluid Mech.* **181**, 213–232.
- [11] Hasegawa, K. (1977) Computer simulation of the gradual migration of meandering channels. *Proc. Hokkaido Br. JSCE*, 197–202.
- [12] Nanson, G. C. & Hickin, E. J. (1986) A statistical examination of bank erosion and channel migration. *Geol. Soc. Am. Bull.* **97**, 497–504.
- [13] Parker, G. *et al.* (2011) A new framework for modeling the migration of meandering rivers. *Earth Surf. Process. Landforms* **36**, 70–86.
- [14] Leopold, L. B. & Wolman, M. G. (1960) River meanders. *Geol. Soc. Am. Bull.* **71**, 769–794.
- [15] Case, K. M. (1960) Stability of inviscid plane Couette flow. *Phys. Fluids* **3**, 143–148.
- [16] Bretherton, F. P. (1966) Baroclinic instability and the short wavelength cut-off in terms of potential vorticity. *Q. J. R. Meteorol. Soc.* **92**, 335–345.