

# Arrhythmia Heartbeat Classification Using Deep Learning Hybrid Structure with Massive Unannotated Electrocardiography Samples

Yan Yan, *Student Member, IEEE*, and Lei Wang

**Abstract**—Plenty of samples with the diagnosis can be used to improve the CAD systems' performance. These ECG signal samples were able to be easily acquired from routine medical examinations or Holter monitoring applications. However, making annotations one by one for the massive ECG signal samples could be time-consuming and inefficient, which would bring heavy burden for medical experts. In the mobile healthcare or e-healthcare applications, the medical experts based ECG analysis method would be impossible to handle the growing data from the large user population.

**Index Terms**—ECG Classification, Deep Learning, Arrhythmia Analysis

## I. INTRODUCTION

The research of the electrocardiogram (ECG) signal provides valuable insights for cardiac function and condition understandings. Heart function analysis is of particular concern in the diagnosis of cardiovascular disease. The ECG computer-aided diagnosis (CAD) systems provide indispensable assist in long-term clinical monitoring, and a large number of approaches had been proposed for the task, easing the determination of arrhythmic changes as well as further inspection, e.g., heart rate variability or heart turbulence analysis[1]. As the wearable techniques promoted the accumulation of ECG data from personal and mobile healthcare applications, the automated ECG signal analysis techniques featured CAD systems tend to be more important [2], [3]. Machine learning techniques had been widely used in data analysis and applied in ECG-CAD systems. These methods learn representations from the diagnosed samples collected from medical examinations, to assist the decision making of medical experts.

Plenty of samples with the diagnosis can be used to improve the CAD systems' performance. These ECG signal samples were able to be easily acquired from routine medical examinations or Holter monitoring applications. However, making

annotations one by one for the massive ECG signal samples could be time-consuming and inefficient, which would bring heavy burden for medical experts. In the mobile healthcare or e-healthcare applications, the medical experts based ECG analysis method would be impossible to handle the growing data from the large user population.

The possible solution for massive ECG automated analysis is to learn hypothesis from a few of samples annotated by medical experts (the labeled data) and then utilize the massive undiagnosed samples (the unlabeled data) to enhance the performance of the learned hypothesis. In machine learning, this technique is called learning with labeled (supervised learning) and unlabeled data (unsupervised learning). While the semi-supervised learning method could enhance the performance of the learned hypothesis by using the labeled and unlabeled data together. Deep learning is one kind of machine learning methods which becomes quite popular in recent research in computer vision and acoustic signal analysis applications. Deep learning refers to a rather broad class of machine learning techniques and architectures, with the hallmark of using many layers of non-linear information processing that are hierarchical in nature [4].

The results from the intelligent algorithms or models were not amenable to expert labelling, as well as for the identification of complex relationships between subjects and clinical conditions [5]. But for the ambulatory electrocardiography clinical application, as well as the usual use in daily healthcare monitoring for cardiac function or early warning of heart disease, an automated algorithm or model would have significant meaning. The application of artificial intelligence methods has become a significant trend in electrocardiography for the recognition and classification of different arrhythmia types [5]. The data explosion puts forward the new request to the method of data processing and information mining. Deep learning techniques are super-star in the recent years for its ability in

The rest of the paper is organized as follows: Section II briefly reviews the arrhythmia diagnosis methods and deep learning techniques. Section III presents the datasets description. Section IV reports the experimental methods of deep learning techniques. Section V describes the results and performance assessment. Finally, Section VI concludes the paper.

## II. BACKGROUND

Over the past decades computational techniques proliferated in the pattern recognition field, simultaneously the applications

Y. Yan is with the Shenzhen Key Laboratory for Low-cost Healthcare, Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences. No. 1068, Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, China-mail: (yan.yan@siat.ac.cn).

X. Qin is with the Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences. No. 1068, Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, China.

J. Fan is with the Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences. No. 1068, Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, China.

L. Wang is with the Shenzhen Key Laboratory for Low-cost Healthcare, Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences. No. 1068, Xueyuan Road, Nanshan District, Shenzhen, Guangdong Province, China.

Manuscript received ;

in ECG recognition, detection and classification of relevant trends, patterns, and outliers. Most of the literature in the ECG classification task were focused on the supervised learning methods, as in unsupervised scenarios lots of effort needed in labelling data. In this part, we first review the typical methods in the classification task, then deep learning methods are illustrated shortly.

#### A. Related Works

Since ECG is an essential diagnostic tool in cardiac disease, the development of accurate automated ECG analysis computational algorithms or models have been a challenge for decades. Most of the approaches are based on the supervised machine learning perspective, features were extracted and then through the optimizing process to train a classifier. The classifiers include the simple classifier such as linear discriminants [6] and kNN [7], more complex classifiers like neural networks [8], [9], [10], [11], fuzzy inference engines [11], [12], hidden Markov models [13], [14], independent component analysis [15], and support vector machine [16], [17], [18].

The performance of a recognition system highly depends on the determination of extracted electrocardiography features. The extracted features can be divided into two categories: features based on the ECG morphology, and those features based on the cardiac rhythm or inter-beat intervals [19]. Time domain features like morphological features include shapes, amplitudes, and durations were adapted primarily in [20], [21], [22], frequency domain features like wavelet transformation were used [23], [24], in [25] stationary features like higher-order statistics also had been developed. Principal component analysis [26] and Hermite functions [27] have been used in electrocardiography classification and related analysis technologies as well. Most literature proposed several new features in classification task, or a new combination rule with the existing ones [1].

#### B. Deep Learning

The backpropagation neural network architecture had been widely applied since 1989 by its multidimensional mapping ability [28]. The deep learning techniques are based on the research on artificial neural network. Until 2006, deep architectures have not been discussed much in the machine learning literature, because of poor training and generalisation errors obtained using the standard random initialization of the parameters [29]. Great successes in speech recognition [30], image recognition [31] had been accomplished via this powerful structure due to the proposed proper training algorithms by Hinton [32].

In this paper, the deep learning techniques involved are based on the three categories of deep networks. From the massive unlabeled ECG samples, the deep networks were trained for high accuracy classification for heartbeat classification in arrhythmia analysis.

### III. DATASETS AND PRE-PROCESSING

The heart is comprised of the myocardium that rhythmically contract and thus drive the circulation of blood throughout the human body. A wave of electrical current passes through the entire heart, which triggers myocardial contraction [5]. Electrical propagation spreads over the whole heart in a coordinated pattern generate changes on the body surface potentials which can be measured and illustrated as an electrocardiogram (ECG, or sometimes EKG). Metabolic abnormalities (a lack of oxygen, or ischemia, etc.) and pathological changes of the heart engender a variety of ECG. Consequently, ECG analysis has been a routine part of any complete medical evaluation or healthcare applications.

In this study, part of the ECG datasets adapted are from the MIT/BIH arrhythmia database. The benchmark database contain 48 records, each containing two-channel ECG signals for 30-min duration selected from 24-hour recordings of 47 individuals. The continues ECG signals are band-pass filtered at 0.1-100 Hz. The database contains annotation for both timing information and beat class information verified by independent experts.

### IV. METHODOLOGY

#### A. Autoencoder based Deep Neural Networks

1) *Autoencoder*: The first research on the potential benefits of unsupervised learning based pre-training might date back to 1987, in which the first unsupervised autoencoder hierarchies were proposed [33]. The deep autoencoder is a special type of the deep neural networks, whose output vectors have the same dimensionality as the input vectors. For example, the lowest-level autoencoder neural network is a single hidden layer that is trained to map input patterns to themselves. Internally, it has a hidden layer  $\mathbf{h}$  that describes a code used to represent the input. The autoencoder network can be viewed as consisting of two parts: an encoder function  $\mathbf{h} = f(\mathbf{x})$  and a decoder that produces a reconstruction  $\mathbf{r} = g(\mathbf{h})$  [34].

Actually the autoencoder network outputs  $g(f(\mathbf{x}))$  would not be equal to the input  $\mathbf{x}$ . The outputs of the decoder are not typically our concern, while the outputs of the encoder  $\mathbf{h}$  are taking on useful properties. Useful features can be learned by constraining  $\mathbf{h}$  to have smaller dimension than the input  $\mathbf{x}$ , which can be called undercomplete autoencoder [34]. The regularized autoencoders use a loss function that encourages the model to learn useful properties when the dimension of  $\mathbf{h}$  bigger than the input  $\mathbf{x}$ , which are called overcomplete. The encodings are useful because the models were trained to reconstruct the inputs rather than a simple copy process.

Sparse autoencoders are typically used to learn features for classification tasks.

#### 2) Training method for deep neural networks:

#### B. Restricted Boltzmann Machines based Deep Belief Networks

##### 1) Restricted Boltzmann Machine:

##### 2) Training Method for deep belief networks:

## C. Deep Feature Combined Hybrid Model

### V. EXPERIMENTS

### VI. CONCLUSIONS

### APPENDIX A

#### PROOF OF THE FIRST ZONKLAR EQUATION

Appendix one text goes here.

### APPENDIX B

Appendix two text goes here.

### ACKNOWLEDGMENT

The authors would like to thank...

### REFERENCES

- [1] T. Mar, S. Zauneder, J. P. Martinez, M. Llamedo, and R. Poll, "Optimization of ecg classification by means of feature selection," *IEEE Transactions on Biomedical Engineering*, vol. 58, no. 8, pp. 2168–2177, Aug 2011.
- [2] S. Jankowski, A. Oreziak, A. Skorupski, H. Kowalski, Z. Szymanski, and E. Piatkowska-Janko, "Computer-aided morphological analysis of holter ecg recordings based on support vector learning system," in *Computers in Cardiology*, 2003, Sept 2003, pp. 597–600.
- [3] E. S. Winokur, M. K. Delano, and C. G. Sodini, "A wearable cardiac monitor for long-term data acquisition and analysis," *IEEE Transactions on Biomedical Engineering*, vol. 60, no. 1, pp. 189–192, Jan 2013.
- [4] L. Deng and D. Yu, "Deep learning: Methods and applications," *Found. Trends Signal Process.*, vol. 7, no. 3&#8211;4, pp. 197–387, Jun. 2014. [Online]. Available: <http://dx.doi.org/10.1561/20000000039>
- [5] G. D. Clifford, F. Azuaje, and P. McSharry, *Advanced Methods And Tools for ECG Data Analysis*. Norwood, MA, USA: Artech House, Inc., 2006.
- [6] M. F. Shinwari, N. Ahmed, H. Humayun, I. ul Haq, S. Haider, and A. ul Anam, "Classification algorithm for feature extraction using linear discriminant analysis and cross-correlation on ecg signals," *International Journal of Advanced Science and Technology*, vol. 48, pp. 149–161, 2012.
- [7] M. R. Homaeinezhad, S. Atyabi, E. Tavakkoli, H. N. Toosi, A. Ghaffari, and R. Ebrahimpour, "Ecg arrhythmia recognition via a neuro-svm-knn hybrid classifier with virtual qrs image-based geometrical features," *Expert Systems with Applications*, vol. 39, no. 2, pp. 2047–2058, 2012.
- [8] W. Jiang and S. Kong, "Block-based neural networks for personalized ecg signal classification," *Neural Networks, IEEE Transactions on*, vol. 18, no. 6, pp. 1750–1761, 2007.
- [9] T. Olmez, "Classification of ecg waveforms by using rce neural network and genetic algorithms," *Electronics Letters*, vol. 33, no. 18, pp. 1561–1562, Aug 1997.
- [10] C.-W. Lin, Y.-T. Yang, J.-S. Wang, and Y.-C. Yang, "A wearable sensor module with a neural-network-based activity classification algorithm for daily energy expenditure estimation," *Information Technology in Biomedicine, IEEE Transactions on*, vol. 16, no. 5, pp. 991–998, Sept 2012.
- [11] S. Osowski and T. H. Linh, "Ecg beat recognition using fuzzy hybrid neural network," *Biomedical Engineering, IEEE Transactions on*, vol. 48, no. 11, pp. 1265–1271, Nov 2001.
- [12] M. Kundu, M. Nasipuri, and D. Basu, "A knowledge-based approach to ecg interpretation using fuzzy logic," *Systems, Man, and Cybernetics, Part B: Cybernetics, IEEE Transactions on*, vol. 28, no. 2, pp. 237–243, Apr 1998.
- [13] R. Andreao, B. Dorizzi, and J. Boudy, "Ecg signal analysis through hidden markov models," *Biomedical Engineering, IEEE Transactions on*, vol. 53, no. 8, pp. 1541–1549, 2006.
- [14] D. Coast, R. Stern, G. Cano, and S. Briller, "An approach to cardiac arrhythmia analysis using hidden markov models," *Biomedical Engineering, IEEE Transactions on*, vol. 37, no. 9, pp. 826–836, 1990.
- [15] Y. Zhu, A. Shayan, W. Zhang, T. L. Chen, T.-P. Jung, J.-R. Duann, S. Makeig, and C.-K. Cheng, "Analyzing high-density ecg signals using ica," *Biomedical Engineering, IEEE Transactions on*, vol. 55, no. 11, pp. 2528–2537, Nov 2008.
- [16] F. Melgani and Y. Bazi, "Classification of electrocardiogram signals with support vector machines and particle swarm optimization," *Information Technology in Biomedicine, IEEE Transactions on*, vol. 12, no. 5, pp. 667–677, Sept 2008.
- [17] A. Kampouraki, G. Manis, and C. Nikou, "Heartbeat time series classification with support vector machines," *Information Technology in Biomedicine, IEEE Transactions on*, vol. 13, no. 4, pp. 512–518, 2009.
- [18] A. Khandoker, M. Palaniswami, and C. Karmakar, "Support vector machines for automated recognition of obstructive sleep apnea syndrome from ecg recordings," *Information Technology in Biomedicine, IEEE Transactions on*, vol. 13, no. 1, pp. 37–48, Jan 2009.
- [19] J. Oster, J. Behar, O. Sayadi, S. Nemati, A. E. W. Johnson, and G. D. Clifford, "Semisupervised ecg ventricular beat classification with novelty detection based on switching kalman filters," *IEEE Transactions on Biomedical Engineering*, vol. 62, no. 9, pp. 2125–2134, Sept 2015.
- [20] I. Jekova, G. Bortolan, and I. Christov, "Assessment and comparison of different methods for heartbeat classification," *Medical Engineering & Physics*, vol. 30, no. 2, pp. 248–257, 2008.
- [21] I. Christov, G. Gomez-Herrero, I. Krasteva, I. Jekova, A. Gotchev, and K. Egiazarian, "Comparative study of morphological and time frequency ecg descriptors for heartbeat classification," *Medical Engineering & Physics*, vol. 28, no. 9, pp. 876–887, 2006.
- [22] C. Ye, B. Kumar, and M. Coimbra, "Heartbeat classification using morphological and dynamic features of ecg signals," *Biomedical Engineering, IEEE Transactions on*, vol. 59, no. 10, pp. 2930–2941, Oct 2012.
- [23] O. T. Inan, L. Giovangrandi, and G. T. A. Kovacs, "Robust neural-network-based classification of premature ventricular contractions using wavelet transform and timing interval features," *IEEE Transactions on Biomedical Engineering*, vol. 53, no. 12, pp. 2507–2515, 2006.
- [24] S. Banerjee and M. Mitra, "Application of cross wavelet transform for ecg pattern analysis and classification," *IEEE Transactions on Instrumentation and Measurement*, vol. 63, no. 2, pp. 326–333, 2014.
- [25] E. D. Übeyli, "Detecting variabilities of ecg signals by lyapunov exponents," *Neural Computing and Applications*, vol. 18, no. 7, pp. 653–662, 2009. [Online]. Available: <http://dx.doi.org/10.1007/s00521-008-0229-8>
- [26] T. Stamkopoulos, K. Diamantaras, N. Maglaveras, and M. Stryntzis, "Ecg analysis using nonlinear pca neural networks for ischemia detection," *Signal Processing, IEEE Transactions on*, vol. 46, no. 11, pp. 3058–3067, Nov 1998.
- [27] M. Lagerholm, C. Peterson, G. Braccini, L. Edenbrandt, and L. Sornmo, "Clustering ecg complexes using hermite functions and self-organizing maps," *Biomedical Engineering, IEEE Transactions on*, vol. 47, no. 7, pp. 838–848, Jul 2000.
- [28] R. Hecht-Nielsen, "Theory of the backpropagation neural network," in *Neural Networks, 1989. IJCNN., International Joint Conference on*, 1989, pp. 593–605 vol.1.
- [29] Y. Bengio, "Learning deep architectures for ai," *Found. Trends Mach. Learn.*, vol. 2, no. 1, pp. 1–127, Jan. 2009.
- [30] G. Hinton, L. Deng, D. Yu, G. E. Dahl, A.-r. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. N. Sainath *et al.*, "Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups," *Signal Processing Magazine, IEEE*, vol. 29, no. 6, pp. 82–97, 2012.
- [31] D. C. Ciresan, U. Meier, L. M. Gambardella, and J. Schmidhuber, "Deep, big, simple neural nets for handwritten digit recognition," *Neural computation*, vol. 22, no. 12, pp. 3207–3220, 2010.
- [32] G. E. Hinton and R. R. Salakhutdinov, "Reducing the dimensionality of data with neural networks," *Science*, vol. 313, no. 5786, pp. 504–507, Jul 2006.
- [33] D. H. Ballard, "Modular learning in neural networks," in *AAAI*, 1987, pp. 279–284.
- [34] G. Ian, B. Yoshua, and C. Aaron, "Deep learning," 2016, book in preparation for MIT Press. [Online]. Available: <http://www.deeplearningbook.org>



**Yan Yan** received the B.Eng. degree and the MSc in Instrument Engineering at the Harbin Institute of Technology in 2010 and 2012 respectively. He worked as research assistance at the Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences from 2012 to 2014. He is working on his PhD in Computer Science started from 2014. His research interests are digital signal processing, machine learning, and control system.

PLACE  
PHOTO  
HERE

**Zhou Lin** received the B.Eng degree in Electronic information engineering at Wuhan University of Technology in 2014. she is studying for a master's degree at Wuhan university of technology from 2014 to now. Her research interests are digital signal processing and pattern recognition.

PLACE  
PHOTO  
HERE

**Zhou Lin** received the B.Eng degree in Electronic information engineering at Wuhan university of technology in 2014. she is studying for a master's degree at Wuhan university of technology from 2014 to now. her research interests are digital signal processing and pattern recognition.



**Lei Wang** received the B.Eng. degree in information and control engineering, and the Ph.D. degree in biomedical engineering from Xian Jiaotong University, Xian, China, in 1995 and 2000, respectively. He was with the University of Glasgow, Glasgow, U.K., and Imperial College London, London, U.K., from 2000 to 2008. He is currently a full professor with the Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences, Shenzhen, China. He has published over 200 scientific papers, authored four book chapters, and holds 60 patents. His current research interests include body sensor network, digital signal processing, and biomedical engineering