

Portable Protocol Verification Guide v0.3

This synthetic guide contains rich-text sections that describe verification patterns and native inst

---PATTERN---

PATTERN_ID: RESET_STABILITY

OBJECTIVE: Verify that reset deassertion leads to ready within the allowed window.

NATIVE: DRIVE RESET LOW 5ns; DRIVE RESET HIGH; EXPECT READY WITHIN 20 CYCLES

EXPECTED: ready == 1 within 20 cycles after reset release

HUMAN_REVIEW: Confirm reset deassertion timing with the design owner.

---END---

---PATTERN---

PATTERN_ID: BURST_WRITE_ACK

OBJECTIVE: Verify that four consecutive writes receive acknowledgements.

NATIVE: LOOP 4 WRITE ADDR++ DATA++; EXPECT ACK EACH WRITE

EXPECTED: ack == 1 for every write operation

HUMAN_REVIEW: Confirm whether address wraparound is legal.

---END---

---PATTERN---

PATTERN_ID: CLOCK_JITTER_TOLERANCE

OBJECTIVE: Verify that the block remains stable when clock jitter is applied within environment limi

NATIVE: SET CLOCK_JITTER MAX_ALLOWED; RUN 100 CYCLES; EXPECT READY STABLE

EXPECTED: ready remains stable during jitter run

HUMAN_REVIEW: Confirm jitter distribution and measurement method.

---END---

Do not infer

- Do not infer voltage levels.
- Do not infer coverage completeness.
- Do not infer signoff readiness.