

Z[®]-45 XC[™]

SELF-PROPELLED ARTICULATING BOOMS

ACCESS SOLUTIONS

Experience | Safety | Innovation

Models	Z-45 XC	
Measurements	US	Metric
Working height maximum*	51 ft 6 in	15.86 m
Platform height maximum	45 ft 6 in	13.86 m
Horizontal reach maximum	24 ft 9 in	7.55 m
Up and over clearance maximum	24 ft 5 in	7.44 m
A Platform length	2 ft 6 in	0.76 m
B Platform width	6 ft	1.83 m
C Height - stowed	7 ft 4 in	2.25 m
D Length - stowed	21 ft 10 in	6.65 m
E Width	7 ft 6 in	2.29 m
F Wheelbase	6 ft 8 in	2.03 m
G Ground clearance - center	14.8 in	0.37 m

Productivity

Maximum lift capacity - unrestricted	660 lb	300 kg
- restricted	1,000 lb	454 kg
Platform rotation	160°	
Vertical Jib rotation	133°	
Turntable rotation	355° non-continuous	
Turntable tailswing	zero	
Drive speed - stowed	4.5 mph	7.24 km/h
Drive speed - raised **	0.61 mph	0.98 km/h
Gradeability - 4WD - stowed***	45%	
Turning radius - inside	5 ft 6 in	1.68 m
Turning radius - outside	14 ft 9 in	4.50 m
Controls	12 V DC proportional	
Tires	315/55 D20	

Power

Power source	49 hp (36.5 kW) Deutz D2.9L4 diesel T4f 60 hp (44.7 kW) Ford MSG425 Gas/LPG Dual Fuel 48 hp (35.8 kW) Perkins 404F-E22T diesel T4f	
Auxiliary power unit	12 V DC	
Hydraulic tank capacity	22 gal	83 L
Fuel tank capacity	17 gal	64.4 L


Weight****

4WD	16,360 lb	7,421 kg
-----	-----------	----------



Standards Compliance

ANSI A92.2, CSA B354.6

Range Of Motion Z-45 XC



* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** In lift mode (platform raised), the machine is designed to operate on firm, level surfaces only.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.



ACCESS SOLUTIONS

0800 656 343 www.accesssolutions.co.nz

AUCKLAND
 100 Leonard Road
 Mt Wellington
 Auckland

WELLINGTON
 33 Broken Hill Road
 Porirua
 Wellington

CHRISTCHURCH
 28 Nga Mahi Road
 Sockburn
 Christchurch

Z[®]-45 XC[™]

SELF-PROPELLED ARTICULATING BOOMS

**ACCESS
SOLUTIONS**

Experience | Safety | Innovation

Features

Standard Features

Measurements

Z-45 XC

- 51 ft 6 in (15.86 m) working height
- 24 ft 9 in (7.55 m) horizontal reach
- 24 ft 5 in (7.44 m) up and over clearance
- 660 lb (300 kg) unrestricted and 1,000 lb (454 kg) restricted lift capacity

Productivity

- 5 ft (1.52 m) jib boom
- 4WD
- Active oscillation
- Self-leveling platform
- 160° Hydraulic platform rotation
- Proportional joystick controls
- Drive enable
- AC power cord to platform
- Alarm package: Flashing beacon and travel alarm
- Horn
- Hour meter
- Tilt alarm
- Descent alarm
- Flashing beacons and travel alarm
- 355° non-continuous turntable rotation
- Positive traction drive
- Two speed wheel motors
- Work tray
- Platform entry toeboard
- Lift Guard[™] Contact Alarm
- Dual parallelogram for vertical wall tracking
- Load Sense

Power

- 12 V DC auxiliary power
- Swing out engine tray
- Intake air heater (Deutz engine only)

Easily Configured To Meet Your Needs

Platform Options

- Steel 6 ft (1.83 m) dual entry with side swing gate (standard)

Engine Options

- 49 hp (36.5 kW) Deutz T4f diesel (standard)
- 60 hp (44.7 kW) Ford MSG425 Gas/LP Dual Fuel
- 48 hp (35.8 kW) Perkins 404F-E22T T4f diesel

Tire Options

- Rough terrain foam-filled (standard)
- Rough terrain non-marking (foam-filled)



Options & Accessories

Productivity

- Lift Power[™]
 - 3 kW AC Generator
 - 12 kW 240 V / 60 Hz Welder Ready package
 - 12 kW Welder Equipped, Select Lincoln or Miller (12 kW options include a fire extinguisher and fireproof sleeves)
- Lift Guard Platform Mesh - Half
- Lift Guard Platform Mesh - Full
- Platform top auxiliary rail
- Air line to platform
- Thumb rocker steer
- Specialty hydraulic oil (Cold weather, fire resistant or biodegradable)
- Aircraft protection package*
- Hostile environment kit
- Panel cradle package
- Light package
- Lockable platform control box cover
- Tow package
- Operator Protective Structure**
- Fall Arrest Bar
- Florescent tube caddy**
- Pipe cradle (pair)**
- Lift Tools Expo Installer**

Power

- Engine gauge package (Ford engine only)
- Cold Weather Packages
- LPG tank 33.5 lb (15.19 kg) capacity
- Positive air shut off system (Deutz engine only)

* Reduces platform capacity to 600 lb (max outreach zone) and 940 lb (max capacity zone)

** Available through aftermarket parts only

ACCESS SOLUTIONS

0800 656 343 www.accesssolutions.co.nz

AUCKLAND

100 Leonard Road
Mt Wellington
Auckland

WELLINGTON

33 Broken Hill Road
Porirua
Wellington

CHRISTCHURCH

28 Nga Mahi Road
Sockburn
Christchurch