# 1500SJ ULTRA SERIES BOOM LIFT



### **Performance**

Platform Height 45.75 m Horizontal Outreach 24.38 m Swing 360° Continuous

Platform Capacity-Restricted 450 kg
Platform Capacity-Unrestricted 230 kg
Platform Rotator 180° Hydraulic
Jib Length 4.62–7.62 m

 Jib Length
 4.62–7.62 m

 Jib Range of Articulation
 120° (+75, -45)

 Weight¹
 21,772 kg

 Drive Speed
 4.5 km/h

 Gradeability
 40%

Turning Radius (Inside)

Axles Retracted 4.4 m Axles Extended 2.4 m

Turning Radius (Outside)

Axles Retracted 6.8 m Axles Extended 5.9 m

1. Certain options or country standards increase weight

# **Standard Specifications**

#### **Power Source**

 Diesel Engine
 75 hp
 56 kW

 Fuel Tank Capacity
 200 L

#### **Hydraulic System**

Hydraulic Tank Capacity
 208 L

#### **Tyres**

• Standard 445/50D710 24 ply Urethane-Filled

# **Standard Features**

- Platform 0.91 m x 2.44 m
- Inward Self Closing Swing Gate
- Selectable Capacity Envelope
- Drive-Out Extendable Axles
- 180° Hydraulic Platform Rotator
- AC Receptacle in Platform
- Tilt Light and Alarm
- Swing-Out Engine Tray
- 12V-DC Auxiliary Power
- Hourmeter
- Control ADE® System
- Full-Time 4WD
- 3 Selectable Steering Modes
- Proportional Controls

- Gull-Wing Steel Hoods
- 445/50D710 Foam-Filled Rim Protector Lug Tread Tyres
- Platform Console Machine Status Light Panel\*
- Lifting/Tie Down Lugs
- All Motion Alarm
- Glow Plugs
- LCD Panel at Operator's Platform Contol Console
- Flashing Amber Beacon
- 5.5kVA Generator
- Cylinder Bellows
- Tool Tray
- \* Provides indicator lights at platform control console for system distress, fuel level, low fuel, 5 degree tilt light, and foot switch status.



- More Capacity With a dual 450/230 kg capacity, the platform can handle more workers, tools or materials.
- More Maneuverability Full-time four-wheel drive gets you over rough terrain.
- Ease of Transport No oversized load permit needed.

#### **Accessories & Options**


- .91 x 1.83 m Platform Entry
- Mesh to Mid Rail
- Light Package<sup>1</sup>
- Soft Touch System
- Special Hydraulic Oils
- Console Cover
- Corner Storage Trav
- ClearSky<sup>®</sup>
- SkyGuard™
- Pipe Rack
- Accessory Packages:
  - SkyWelder® Package
  - Nite Bright® Package
  - SkyGlazier®
- 1. Includes platform mounted worklights and drive/backup lights.


# 1500SJ ULTRA SERIES BOOM LIFT



## **Dimensions**

All dimensions are approximate.





A. Platform Size	0.91 x 2.44 m
B. Overall Width Axles Retracted	2.49 m
Overall Width Axles Extended	3.81 m
<b>C.</b> Tailswing	1.67 m
<b>D.</b> Stowed Height	3.05 m
E. Overall Length Jib Stowed	13.11 m
Overall Length Jib Deployed	18.82 m
<b>F.</b> Wheel Base	3.81 m
<b>G.</b> Ground Clearance	
Axle	30 cm
Chassis	65 cm

# **Load Chart**

