

14M 4045R SCISSOR LIFT



Experience | Safety | Innovation

| _ | | | | | |
|-----|------|-----|----|-------|--------|
| 100 | - | | na | _ | _ |
| - | 1111 | 144 | | 1 a I | er 2.1 |

| Platform Height (Indoor) | 39 ft 3 in. | 11.97 m |
|--------------------------------|---------------|-------------------------|
| Platform Height (Outdoor) | 29 ft | 8.8 m |
| Platform Capacity (Indoor) | 770 lb | 350 kg |
| Platform Capacity (Outdoor) | 550 lb | 250 kg |
| Capacity on Platform Extension | 250 lb | 113 kg |
| Lift/Lower Time | 73/48 Seconds | |
| Maximum Drive Height (Outdoor) | 29 ft | 8.8 m |
| Maximum Drive Height (Indoor) | Full Height | |
| Weight* | 7,000 lb | 3,175 kg |
| Ground Bearing Pressure | 135 psi | 9.49 kg/cm ² |
| Drive Speed–Elevated | 0.5 mph | 0.8 km/h |
| Drive Speed–Lowered | 2 mph | 3.2 km/h |
| Gradeability | 25% | |
| Turning Radius (Inside) | Zero | |
| Turning Radius (Outside) | 100 in. | 2.54 m |
| | | |

^{*} Certain options or country standards will increase weight.

Standard Specifications

Power Source

| Batteries | 24V DC (4 x 12V, 150 amp-hr batteries) |
|-----------|--|
| Charger | 27 amp High Frequency Charger |
| Drive | Hydraulic Front-wheel |

Hydraulic Reservoir

| Capacity | 7.9 gal. | 30 L |
|------------------------------|-------------------------|------|
| • Pump | Fixed Displacement Gear | |
| Tires | | |

11103

• Tire Size/Type (Non-Marking) 16 x 5 in. 406 x 127 mm

Brakes

• Multi-Disc Friction

Standard Features

- Proportional Controls
- · Battery Condition Indicator
- 110V-AC Receptacle in Platform
- · All Motion Alarm
- 27 amp Multi-Function Universal Charger
- Horn
- Hourmeter
- Tilt Alarm and Light
- Lanyard Attach Points
- Movable, Removable Platform Control
- · Nickel Plated Pins
- Lubrication Free Scissor Arm Bushings
- Scissor Maintenance Prop

- Self-centering arm stack
- Active Pothole Protection System
- Lifting and Tie Down Points
- Fork Lift Pockets
- 36 in. (91 cm) Foot-Actuated Deck Extension
- · Steel Swing-Out Doors
- Variable Tilt Window
- Manual Descent Cable
- Diamond Tread Steel Deck
- Greaseless Kingpin Joints
- Analyzer Port for Diagnostics
- Dynamic Braking
- · Removable Ladder



Accessories & Options

- · Coiled Platform Control Box Cable
- Drive Motor Covers
- Extension Deployment Handles
- Fire Extinguisher
- Flashing Amber Beacon
- MDI (Ground)
- Anti-Vandalism PKG
- · Eagle Performance Charger
- 900W Inverter
- Ambient Noise Alarm
- Platform Work Lights
- Batteries (12V 185AH)
- Batteries (AGM) (12V 150AH)
- · Platform Padding
- Pipe Racks
- Panel Carrier
- JLG WorkStation






14M 4045R SCISSOR LIFT


1.40 m 1.132 m 2.53 m 1.9 m 1.05 m x 2.43 m 91 cm



Dimensions

All dimensions are approximate.





| A. Platform Height–Lowered | 55 in. |
|--------------------------------|-----------------|
| B. Platform Railing Height | 44 in. |
| C. Overall Height | 100 in. |
| D. Stowed Height, Rails Folded | 75 in. |
| E. Platform Size | 41 in. X 96 in. |
| F Platform Extension | 36 in. |
| | |

| in. 114.3 c | m |
|-------------|---|
| | |
| in. 2.56 m | 1 |
| in. 2.03 m | 1 |
| ı. 12.7 cn | n |
| | in. 114.3 c 5 in. 2.71 m in. 2.56 m in. 2.03 m n. 12.7 cn |