

# Fashion-MNIST Classification based on Manifold Learning

CSIC 5011 Final Project

FAN Junyi and XIAN Zhuozhi

Department of Mathematics  
The Hong Kong University of Science and Technology

May 21, 2021

# Overview

1. Introduction
2. Methodology
3. Results
4. Further analysis
5. Conclusion

# Data Description

- The Fashion-MNIST dataset contains
  - 60,000 training images and 10,000 test images
  - size 28-by-28 in grayscale
  - labels for 10 distinct types
- Select 10,000 images for our project



Samples in the Fashion-MNIST Dataset

# Goal

1. Apply several manifold learning methods to find the lower-dimensional embedding of the high-dimensional Fashion-MNIST dataset
2. Conduct the classification for the types of the fashion based on the embedding results
3. Estimate the intrinsic dimension of the dataset by using residual variance


# Manifold Learning

- Find the manifold on which the high dimensional dataset resides and the corresponding embedding
- Reconstruct the low dimensional manifold
- Dimensionality reduction and data visualization


# Methods

- Principal Component Analysis (PCA)
- Multidimensional Scaling (MDS)
- Isometric Maps method (ISOMAP)
- Locally Linear Embedding (LLE)
- Modified Locally Linear Embedding (MLLE)
- Hessian Locally Linear Embedding (Hessian LLE)
- Laplacian Eigenmaps
- Local Tangent Space Alignment (LTSA)
- Diffusion Maps
- t-Distributed Stochastic Neighbor Embedding (t-SNE)


# Embedding



PCA



MDS




ISOMAP




t-SNE


# Embedding




LLE




Hessian LLE




MLLE



Laplacian Eigenmaps



LTSA



Diffusion Maps




# Classification

Methods for embedding	Accuracy via Random Forest	Accuracy via SVM
PCA	49.5%	54.5%
MDS	53.4%	57.3%
ISOMAP	56.8%	59.7%
LLE	67.4%	50.2%
MLLE	64.3%	61.6%
Hessian LLE	10.3%	10.3%
Laplacian Eigenmaps	55.4%	58.0%
LTSA	10.9%	10.6%
Diffusion Maps	14.1%	16.4%
t-SNE	59.2%	56.1%
None	84.7%	84.5%

Table: Classification Accuracy

# Residual Variance vs. Intrinsic dimension



Residual Variance

- Residual variance  $R_v$ :

$$R_v = 1 - R^2,$$

where  $R$  is the linear correlation for all the data points of original graph distances and embedded euclidean distances.

- The intrinsic dimension of the data can be estimated from the figures about the residual variances for different embedding dimensions. Here the approximation of intrinsic dimension is 2.

# Conclusion

1. Perform different manifold learning methods to embed the high dimensional Fashion-MNIST dataset into two dimensional space and visualize it
2. Classify the types of the fashion by using different combinations of embedding methods and classifiers, where LLE + Random Forest obtains the highest accuracy
3. Calculate the residual variances for different embedding dimensions to estimate intrinsic dimension of the dataset

# References



Belkin, M., & Niyogi, P. (2003). Laplacian eigenmaps for dimensionality reduction and data representation. *Neural computation*, 15(6), 1373-1396.



Coifman, R. R., & Lafon, S. (2006). Diffusion maps. *Applied and computational harmonic analysis*, 21(1), 5-30.



Donoho, D. L., & Grimes, C. (2003). Hessian eigenmaps: Locally linear embedding techniques for high-dimensional data. *Proceedings of the National Academy of Sciences*, 100(10), 5591-5596.



Roweis, S. T., & Saul, L. K. (2000). Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500), 2323-2326.



Tenenbaum, J. B., De Silva, V., & Langford, J. C. (2000). A global geometric framework for nonlinear dimensionality reduction. *science*, 290(5500), 2319-2323.



Thakre, S., Harshith, V., & Kanjarla, A. K. (2021). Intrinsic Dimensionality of Microstructure Data. *Integrating Materials and Manufacturing Innovation*, 10(1), 44-57.



Van der Maaten, L., & Hinton, G. (2008). Visualizing data using t-SNE. *Journal of machine learning research*, 9(11).



Zhang, Z., & Wang, J. (2007). MLLE: Modified locally linear embedding using multiple weights. In *Advances in neural information processing systems* (pp. 1593-1600).

Thank you.