Direct Vs. Indirect Recursion

This lesson goes over two different types of recursion: direct and indirect recursion.

We'll cover the following

Direct Recursion

Direct recursion occurs when a function calls itself.

This results in a **one-step** recursive call, meaning that the function makes a recursive call inside its own function body.

Syntax of Direct Recursion

```
def function1(p1, p2, ..., pn) :
  # Some code here
  function1(p1, p2, ..., pn)
  # Some code here
```

Printing Natural Numbers from 1 to n Using Direct Recursion

Let's take a look at an example of a function that prints natural numbers from 1 to n:

```
def printNaturalNumbers(lowerRange, upperRange):
  # Base Case
  if lowerRange > upperRange :
    return

  print(lowerRange)

  # Recursive Case
  printNaturalNumbers(lowerRange + 1, upperRange);

# Driver Code
n = 5
printNaturalNumbers(1, n)
```

In the code snippet above, if `lowerRange` is less than `upperRange`, we print the `lowerRange`, increase it, and call the function again. If `lowerRange` is greater than `upperRange`, we halt all function calls.

The slides below show how function calls are being performed and returned.



Function calls of direct recursion method

1 of 11



2 of 11


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
printNaturalNumbers(4, 5)


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
printNaturalNumbers(4, 5)
print(4)
printNaturalNumbers(5, 5)


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
printNaturalNumbers(4, 5)
print(4)
printNaturalNumbers(5, 5)
print(5)
# Base condition satisfied


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
printNaturalNumbers(4, 5)
print(4)
# Function returned


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
# Function returned


printNaturalNumbers(1, 5)
print(1)
printNaturalNumbers(2, 5)
print(2)
# Function returned


printNaturalNumbers(1, 5)
print(1)
# Function returned

```
# Function returned
```


Indirect Recursion

Indirect recursion (also called **mutual recursion**) occurs when a function calls another function until the original function is called, again.

For example, if function `function1()` calls another function, `function2()`, `function2()` eventually calls the original function `function1()` - This completes the process of indirect recursion.

Syntax of Indirect Recursion

```
def function1(p1, p2, ..., pn) :
  # Some code here
  function2(p1, p2, ..., pn)
  # Some code here

def function2(p1, p2, ..., pn) :
  # Some code here
  function1(p1, p2, ..., pn)
  # Some code here
```

Printing Natural Numbers from 1 to n Using Indirect Method

Let's take a look at an example that prints natural numbers from 1 to n:

```
1  def printNaturalNumbers(lowerRange, upperRange) :
2    if lowerRange <= upperRange :
3      print(lowerRange)
4      lowerRange += 1
5      helperFunction(lowerRange, upperRange)
6    else :
```

```
    return

def helperFunction(lowerRange, upperRange) :
  if lowerRange <= upperRange :
    print(lowerRange)
    lowerRange += 1
    printNaturalNumbers(lowerRange, upperRange)
  else :
      return

# Driver Program
n = 5
printNaturalNumbers(1, n)
```

Printing numbers from 1 to n using indirect recursion

In this code snippet, we have two functions: `printNaturalNumbers()` and `helperFunction()`. Both functions will check if `lowerRange` is greater than `upperRange`. If not, they will `lowerRange` and call the other function.

This may not look like **recursion** at first, but, if we analyze the code flow, we see that the first function always calls itself *indirectly*.

$printNaturalNumbers() -> helperFunction() -> printNaturalNumbers -> ... $

Take a look at the code flow:



Indirect recursion method



The function printNaturalNumbers() first calls the function print()
and prints the current number
then it calls the function helperFunction()




printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
helperFunction(4, 5)


printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
helperFunction(4, 5)
print(4)
printNaturalNumbers(5, 5)


printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
helperFunction(4, 5)
print(4)
printNaturalNumbers(5, 5)
print(5)
# Base condition satisfied


printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
helperFunction(4, 5)
print(4)
# Function returned


printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
printNaturalNumbers(3, 5)
print(3)
# Function returned


printNaturalNumbers(1, 5)
print(1)
helperFunction(2, 5)
print(2)
# Function returned



10 of 11



11 of 11

Now that we have gone over the concept of direct and indirect recursion, let's move on to the next lesson and find out when we should use recursion.

Back

Recursion and Memory Visualization

Next

When to Use Recursion?