

String Permutations by changing case (medium)

We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
 - Time complexity
 - Space complexity

Problem Statement

Given a string, find all of its permutations preserving the character sequence but changing case.

Example 1:

```
Input: "ad52"
Output: "ad52", "Ad52", "AD52"
```

Example 2:

```
Input: "ab7c"
Output: "ab7c", "Ab7c", "AB7c", "ab7C", "Ab7C", "aB7C", "AB7C"
```

Try it yourself

Try solving this question here:

```
👙 Java
           Python3
                                    G C++
                        Js JS
 1 def find_letter_case_string_permutations(str):
      permutations = []
 2
      # TODO: Write your code here
      return permutations
 5
 6
 7 def main():
 8
      print("String permutations are: " +
 9
            str(find_letter_case_string_permutations("ad52")))
10
      print("String permutations are: " +
11
            str(find_letter_case_string_permutations("ab7c")))
    educative
    main()
```

 \triangleright





This problem follows the Subsets

(https://www.educative.io/collection/page/5668639101419520/5671464854355968/567024937861 1200) pattern and can be mapped to Permutations

(https://www.educative.io/collection/page/5668639101419520/5671464854355968/5720758194012160/).

Let's take Example-2 mentioned above to generate all the permutations. Following a **BFS** approach, we will consider one character at a time. Since we need to preserve the character sequence, we can start with the actual string and process each character (i.e., make it uppercase or lower-case) one by one:


- 1. Starting with the actual string: "ab7c"
- 2. Processing the first character ('a'), we will get two permutations: "ab7c", "Ab7c"
- 3. Processing the second character ('b'), we will get four permutations: "ab7c", "Ab7c", "aB7c", "AB7c"
- 4. Since the third character is a digit, we can skip it.
- 5. Processing the fourth character ('c'), we will get a total of eight permutations: "ab7c", "

Let's analyze the permutations in the 3rd and the 5th step. How can we generate the permutations in the 5th step from the permutations in the 3rd step?

If we look closely, we will realize that in the 5th step, when we processed the new character ('c'), we took all the permutations of the previous step (3rd) and changed the case of the letter ('c') in them to create four new permutations.


Here is the visual representation of this algorithm:





Code

Here is what our algorithm will look like:








Since we can have 2^N permutations at the most and while processing each permutation we convert it into a character array, the overall time complexity of the algorithm will be $O(N*2^N)$.

Space complexity

All the additional space used by our algorithm is for the output list. Since we can have a total of $O(2^N)$ permutations, the space complexity of our algorithm is $O(N*2^N)$.



Could not connect to the reCAPTCHA service. Please check your internet connection and reload to get a reCAPTCHA challenge.