

Solution Review: Problem Challenge 2

We'll cover the following



- Structurally Unique Binary Search Trees (hard)
- Solution
- Code
 - Time complexity
 - Space complexity
- Memoized version

Structurally Unique Binary Search Trees (hard)


Given a number 'n', write a function to return all structurally unique Binary Search Trees (BST) that can store values 1 to 'n'?

Example 1:

Input: 2

Output: List containing root nodes of all structurally unique BSTs.

Explanation: Here are the 2 structurally unique BSTs storing all numbers from 1 to 2:




Example 2:

Input: 3

Output: List containing root nodes of all structurally unique BSTs.

Explanation: Here are the 5 structurally unique BSTs storing all numbers from 1 to 3:



Solution





This problem follows the Subsets

(<https://www.educative.io/collection/page/5668639101419520/5671464854355968/5670249378611200>) pattern and is quite similar to Evaluate Expression

(<https://www.educative.io/collection/page/5668639101419520/5671464854355968/5712272949248000/>). Following a similar approach, we can iterate from 1 to 'n' and consider each number as the root of a tree. All smaller numbers will make up the left sub-tree and bigger numbers will make up the right sub-tree. We will make recursive calls for the left and right sub-trees

Code





Here is what our algorithm will look like:

 Java
  Python3
  C++
  JS

```

4      self.val = val
5      self.left = None
6      self.right = None
7
8
9  def find_unique_trees(n):
10     if n <= 0:
11         return []
12     return findUnique_trees_recursive(1, n)
13
14
15 def findUnique_trees_recursive(start, end):
16     result = []
17     # base condition, return 'None' for an empty sub-tree
18     # consider n = 1, in this case we will have start = end = 1, this means we should have 0
19     # we will have two recursive calls, findUniqueTreesRecursive(1, 0) & (2, 1)
20     # both of these should return 'None' for the left and the right child
21     if start > end:
22         result.append(None)
23         return result
24
25     for i in range(start, end+1):
26         # making 'i' the root of the tree
27         leftSubtrees = findUnique_trees_recursive(start, i - 1)
28         rightSubtrees = findUnique_trees_recursive(i + 1, end)
29         for leftTree in leftSubtrees:
30             for rightTree in rightSubtrees:
31                 root = TreeNode(i)

```

Time complexity

The time complexity of this algorithm will be exponential and will be similar to Balanced Parentheses

(<https://www.educative.io/collection/page/5668639101419520/5671464854355968/5753264117121024/>). Estimated time complexity will be $O(n * 2^n)$ but the actual time complexity ($O(4^n / \sqrt{n})$) is bounded by the Catalan number

(https://en.wikipedia.org/wiki/Catalan_number) and is beyond the scope of a coding interview.

See more details here (https://en.wikipedia.org/wiki/Central_binomial_coefficient).



The space complexity of this algorithm will be exponential too, estimated at $O(2^n)$, but the actual will be $(O(4^n / \sqrt{n}))$.

Memoized version

Since our algorithm has overlapping subproblems, can we use memoization to improve it? We could, but every time we return the result of a subproblem from the cache, we have to clone the result list because these trees will be used as the left or right child of a tree. This cloning is equivalent to reconstructing the trees, therefore, the overall time complexity of the memoized algorithm will also be the same.

[← Back](#)[Next →](#)[Problem Challenge 2](#)[Problem Challenge 3](#)[☒ Mark as Completed](#) [Report an Issue](#) [Ask a Question
\(\[https://discuss.educative.io/tag/solution-review-problem-challenge-2__pattern-subsets__grokking-the-coding-interview-patterns-for-coding-questions\]\(https://discuss.educative.io/tag/solution-review-problem-challenge-2__pattern-subsets__grokking-the-coding-interview-patterns-for-coding-questions\)\)](#)