Max Heap: Introduction

This lesson will give a brief introduction to Max-Heaps and how their elements are inserted or removed from Max-Heaps.


We'll cover the following


- Building a Max-Heap
- Insertion in a Max-Heap
- Remove Maximum in a Max Heap

Building a Max-Heap

As mentioned in the previous lesson, max heaps follow the max heap property which means that the key at the parent node is always greater than the keys at the child nodes. Heaps can be implemented using lists or using node and tree classes. Although they are generally implemented using lists or arrays as that is the more space efficient approach! To build a heap, start with an empty one and successively <code>insert()</code> all the elements.

For a visual demonstration of heap creation, check out the following illustration.












Compare 15 and 20



20 > 15, so swap them




4 of 18



5 of 18


Compare 8 and 5








5 < 8, so move ahead




Compare 8 and 1




8 of 18

1 < 8, so move ahead



9 of 18


Compare 2 and 8








8 > 2, check if right child of 2 is greater than 8




Compare 20 with 2 and 8




12 of 18

20 > 2 and 20 > 8, so swap 2 and 20




13 of 18







Compare 2 and 15



15 > 2, so swap them




16 of 18



17 of 18

It's a Max Heap!





Insertion in a Max-Heap


Here is a high-level description of the algorithm to insert elements into a heap and maintain the heap property.

- Create a new child node at the end of the heap
- Place the new key at that node
- Then, restore the heap property by swapping parent and child values if the parent key is smaller than the child key. We call this 'percolating up'.
- Continue to percolate up until the heap property is restored.


For a clearer picture, here's a visual representation of inserting in a max heap,








Apply max heap property till root




4 of 11




5 of 11

Compare 15 and 30




6 of 11

30 > 15, so swap them







Compare 20 and 30



30 > 20, so swap them




9 of 11



10 of 11

It's a Max Heap!







Remove Maximum in a Max Heap


Here is the algorithm that you will follow to make sure the heap property still holds after deleting the root element


- Delete the root node
- Move the key of last child node at last level to the root
- Now compare the key with its children and if the key is smaller than the key at any of the child nodes, swap values. We call this 'max heapifying.'
- Continue to max heapify until the heap property is restored.

For better understanding, here's the visual representation of what we just said:











Move 2 to root




of 13



of 13


Apply Max Heap property








Compare 2 and 8




8 of 13

8 > 2, so we check if right child of 2 is greater than 8




9 of 13

Compare 15 with 2 and 8





10 of 13

15 > 2 and 15 > 8, so we swap 2 and 15









[]

In the next chapter, we will implement a max heap in Python!

