

Basic Linked List Operations

This lesson lists the various operations that can be performed on linked lists

We'll cover the following ^

- `get_head()`
 - Time complexity
- `is_empty()`
 - Explanation
 - Time complexity

The primary operations which are generally a part of the `LinkedList` class are listed below:

- `get_head()` - returns the head of the list
- `insert_at_tail(data)` - inserts an element at the end of the linked list
- `insert_at_head(data)` - inserts an element at the start/head of the linked list
- `delete(data)` - deletes an element with your specified value from the linked list
- `delete_at_head()` - deletes the first element of the list
- `search(data)` - searches for an element with the specified value in the linked list
- `is_empty()` - returns true if the linked list is empty

If you observe the list of functions mentioned above, `get_head()` and `is_empty()` are helper functions that will prove useful in all the others.

So let's define them first.

`get_head()`

This method simply returns the head node of our linked list:

LinkedList.py

Node.py

```
1  from Node import Node
2
3
4  class LinkedList:
5      def __init__(self):
6          self.head_node = None
7
8      def get_head(self):
9          return self.head_node
10
11
12  lst = LinkedList() # Linked List created
13  print(lst.get_head()) # Returns None since headNode does not contain any data
14
```



Time complexity

The time complexity for `get_head()` is $O(1)$ as we simply return the `head`.

`is_empty()`

The basic condition for our list to be considered empty is that there are no nodes in the list. This implies that `head` points to `None`.

With that in mind, let's write down the simple implementation for `is_empty()`:

LinkedList.py

Node.py

```
1 from Node import Node
2
3
4 class LinkedList:
5     def __init__(self):
6         self.head_node = None
7
8     def get_head(self):
9         return self.head_node
10
11     def is_empty(self):
12         if self.head_node is None: # Check whether the head is None
13             return True
14         else:
15             return False
16
17
18 lst = LinkedList() # Linked List created
19 print(lst.is_empty()) # Returns true
20
```

Explanation

Nothing tricky going on here. The crux of the code lies in the `if` condition on **line 12**. We merely check if the `head` points to `None`.

Note: Even when a linked list is empty, the `head` must always exist.

Time complexity

It will be in $O(1)$ as all we need to do is check whether the `head` node points to `None` or not.

This is just the tip of the iceberg. We'll tackle each of the remaining methods in the following lessons and apply them in relevant problems.



In the next lesson, we'll begin our discussion on linked list insertion functions.

← Back

Next →

Linked Lists vs. Lists

Singly Linked List Insertion

☒ Mark as Completed



Report an
Issue



Ask a Question

(https://discuss.educative.io/tag/basic-linked-list-operations__introduction-to-linked-lists__data-structures-for-coding-interviews-in-python)