

CS4246 / CS5446

Tutorial Week 6

Muhammad **Rizki** Maulana
rizki@u.nus.edu

First

Modeling with MDPs. Specify each of the following problems as a Markov decision process, i.e. specify the state space, the actions, the transition functions, and the reward function. What is the (approximate) size of the state space and the action space?

- (c) Atari games. Atari games have 128 bytes of RAM, 18 actions, and 33,728 screen pixels taking values from 0-127.

Question

Modeling with MDPs. Specify each of the following problems as a Markov decision process, i.e. specify the state space, the actions, the transition functions, and the reward function. What is the (approximate) size of the state space and the action space?

- (c) Atari games. Atari games have 128 bytes of RAM, 18 actions, and 33,728 screen pixels taking values from 0-127.

1 byte = 256 values (-128 ... 127)

State:

Ram

256^{128}

Modeling with MDPs. Specify each of the following problems as a Markov decision process, i.e. specify the state space, the actions, the transition functions, and the reward function. What is the (approximate) size of the state space and the action space?

- (c) Atari games. Atari games have 128 bytes of RAM, 18 actions, and 33,728 screen pixels taking values from 0-127.

State:

| | |
|--------|-------------|
| Ram | 256^{128} |
| Pixels | not MDP |

Only contains position
information, no velocity
and acceleration!



Image credit: ATARI Games, breakout

Modeling with MDPs. Specify each of the following problems as a Markov decision process, i.e. specify the state space, the actions, the transition functions, and the reward function. What is the (approximate) size of the state space and the action space?

- (c) Atari games. Atari games have 128 bytes of RAM, 18 actions, and 33,728 screen pixels taking values from 0-127.

State:

Ram 256^{128}

Pixels not MDP, might need to consider more than one frames

2 frames can capture velocity:

$$v_t = \text{pos}_t - \text{pos}_{t-1}$$

4 frames can capture acceleration:

$$a_t = v_t - v_{t-1}$$



Image credit: ATARI Games, breakout

Modeling with MDPs. Specify each of the following problems as a Markov decision process, i.e. specify the state space, the actions, the transition functions, and the reward function. What is the (approximate) size of the state space and the action space?

- (c) Atari games. Atari games have 128 bytes of RAM, 18 actions, and 33,728 screen pixels taking values from 0-127.

State:

Ram 256^{128}

Pixels not MDP, might need to consider more than one frames


Actions: 18


Transitions & Rewards: depends on the game





Image credit: ATARI Games, breakout

Second











Discount factor : 0.9






Discount factor : 0.9


- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?

Question



Discount factor : 0.9

- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?




Discount factor : 0.9

- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?

$$V_1(s_1) = 1$$

Discount factor : 0.9





- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?

$$V_1(s_1) = 1 \qquad a^*(s_1) = a_1$$

Discount factor : 0.9


- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?

$$V_1(s_1) = 1 \quad a^*(s_1) = a_1$$



Discount factor : 0.9


- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?




$$V_1(s_1) = 1$$

$$a^*(s_1) = a_1$$

$$V_1(s_2) = 3$$



Discount factor : 0.9




- (a) Assume a finite horizon problem with horizon 1 (only 1 action is to be taken). What is the value function and the optimal action in each state?


$$V_1(s_1) = 1$$

$$a^*(s_1) = a_1$$

$$V_1(s_2) = 3$$

$$a^*(s_2) = a_1 \text{ or } a_2$$





Discount factor : 0.9


- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?

Question

Discount factor : 0.9

- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?


$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$




Discount factor : 0.9

- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?

$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$





Discount factor : 0.9

- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?

$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$

For state 1 action 1

$$value = 1 + 0.9(0.9 * 1 + 0.1 * 3) = 2.08.$$

Discount factor : 0.9

- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?


$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$

For state 1 action 1


$$value = 1 + 0.9(0.9 * 1 + 0.1 * 3) = 2.08.$$

For state 1 action 2

$$value = 0 + 0.9(0.9 * 3 + 0.1 * 1) = 2.52.$$



Discount factor : 0.9



- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?

$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$

For state 1 action 1

$$value = 1 + 0.9(0.9 * 1 + 0.1 * 3) = 2.08.$$

For state 1 action 2

$$value = 0 + 0.9(0.9 * 3 + 0.1 * 1) = 2.52.$$

Max = 2.52 (action 2)

Discount factor : 0.9

- (b) Assume a finite horizon problem with horizon 2 (2 actions is to be taken). What is the value function and the optimal action in each state?

$$V_2(s_i) = \max_a (R(s_i, a) + \gamma \sum_{j=1}^2 P(s_j | s_i, a) V_1(s_j)).$$

For state 1 action 1



$$value = 1 + 0.9(0.9 * 1 + 0.1 * 3) = 2.08.$$


For state 1 action 2

$$value = 0 + 0.9(0.9 * 3 + 0.1 * 1) = 2.52.$$

Max = 2.52 (action 2)

$$value = 3 + 0.9 * 3 = 5.7.$$







Discount factor : 0.9

(c) What is the optimal infinite horizon policy?

Question



Discount factor : 0.9

(c) What is the optimal infinite horizon policy?




Discount factor : 0.9

(c) What is the optimal infinite horizon policy?




$$V(s_2) = 3 + 0.9(3 + 0.9(\dots))$$




Discount factor : 0.9

(c) What is the optimal infinite horizon policy?




$$V(s_2) = 3 + 0.9(3 + 0.9(\dots))$$

Geometric series




Discount factor : 0.9

(c) What is the optimal infinite horizon policy?




$$V(s_2) = 3 + \underbrace{0.9(3 + 0.9(\dots))}_{\text{Geometric series}} = \frac{3}{1 - 0.9} = \frac{3}{0.1} = 30$$

Geometric series




Discount factor : 0.9

(c) What is the optimal infinite horizon policy?



$$V(s_2) = 3 + \underbrace{0.9(3 + 0.9(\dots))}_{\text{Geometric series}} = \frac{3}{1 - 0.9} = \frac{3}{0.1} = 30$$




Discount factor : 0.9

(c) What is the optimal infinite horizon policy?


If action a_1 is taken, the value of the policy must satisfy

$$V(s_1) = 1 + 0.9(0.9V(s_1) + 0.1 * 30)$$

giving $V(s_1) = 19.47$.



$$V(s_2) = 3 + \underbrace{0.9(3 + 0.9(\dots))}_{\text{Geometric series}} = \frac{3}{1 - 0.9} = \frac{3}{0.1} = 30$$



Discount factor : 0.9

(c) What is the optimal infinite horizon policy?

If action a_1 is taken, the value of the policy must satisfy


$$V(s_1) = 1 + 0.9(0.9V(s_1) + 0.1 * 30)$$

giving $V(s_1) = 19.47$.

If action a_2 is taken, the value of the policy must satisfy


$$V(s_1) = 0 + 0.9(0.9 * 30 + 0.1V(s_1))$$

giving $V(s_1) = 26.7$.



$$V(s_2) = 3 + 0.9(3 + 0.9(\dots)) = \frac{3}{1 - 0.9} = \frac{3}{0.1} = 30$$

Geometric series



Discount factor : 0.9

(c) What is the optimal infinite horizon policy?

If action a_1 is taken, the value of the policy must satisfy

$$V(s_1) = 1 + 0.9(0.9V(s_1) + 0.1 * 30)$$


giving $V(s_1) = 19.47$.

If action a_2 is taken, the value of the policy must satisfy

$$V(s_1) = 0 + 0.9(0.9 * 30 + 0.1V(s_1))$$

giving $V(s_1) = 26.7$.

Best



$$V(s_2) = 3 + 0.9(3 + 0.9(\dots)) = \frac{3}{1 - 0.9} = \frac{3}{0.1} = 30$$

Geometric series

Third

State:  \leftarrow n values



M


State:



← n values






M




State:  ← n values



M






State:  $\leftarrow n \text{ values}$

M




- a) What is the size of the state space of this MDP? Can this MDP be efficiently solvable with value iteration as M grows?

Question


State:  $\leftarrow n \text{ values}$

M




- a) What is the size of the state space of this MDP? Can this MDP be efficiently solvable with value iteration as M grows?

$$n^M$$

State:  $\leftarrow n$ values



M



- a) What is the size of the state space of this MDP? Can this MDP be efficiently solvable with value iteration as M grows?



$$n^M$$

Value iteration: runtime exponential in M (not good!)






- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?

Question






- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?







- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?





State:  $\leftarrow n \text{ values}$

 M






- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?








- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?








- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?








- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?








- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?







- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?



State:  ...  ← n values



- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?





$O(2^2)$


$O((2^2)^2)$


$O((2^2)^3)$


Exponential growth in D !




- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?






State:  $\leftarrow n$ values


 M





- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?







- b) A search tree of depth D (number of actions from the root to any leaf is D) is constructed from an initial state s . What is the size of the search tree (the number of nodes and edges) as a function of M and D , in O -notation? Can online search be done efficiently as M grows if D is a fixed small constant?





Doesn't depend on M , if D is small then all good!






- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?

Question






- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?








- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MTCS is performed up to a search depth of D , as a function of M , D and T in O -notation?








- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MTCS is performed up to a search depth of D , as a function of M , D and T in O -notation?







- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?







- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?






State:  $\leftarrow n \text{ values}$


 M




- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MTCS is performed up to a search depth of D , as a function of M , D and T in O -notation?





State:  $\leftarrow n \text{ values}$





- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?






State:  $\leftarrow n \text{ values}$

 M






- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?






- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?




State:  ...  ← n values
 M





- c) MCTS is used for solving this MDP. What is the size of the search tree if T trials of MCTS is performed up to a search depth of D , as a function of M , D and T in O -notation?



$O(DT)$



Number of nodes $\leq D + D + D + \dots$ (T times) $= O(DT)$





- d) Consider a search tree where the reward is zero everywhere except at the leaves. When a MCTS trial goes through a node, we say that an action at the node wins if the trial ends in a leaf with reward 1. Consider an MCTS simulation where a node has been visited 16 times and has two actions, A and B. Action A has won 2 out of 4 times whereas action B has won 8 out of 12 times. Which action will the MCTS algorithm choose given the exploration parameter c is set to 1? Give the values of π_{UCT} for the node (consider log base 2 in UCT bound).



- d) Consider a search tree where the reward is zero everywhere except at the leaves. When a MCTS trial goes through a node, we say that an action at the node wins if the trial ends in a leaf with reward 1. Consider an MCTS simulation where a node has been visited 16 times and has two actions, A and B. Action A has won 2 out of 4 times whereas action B has won 8 out of 12 times. Which action will the MCTS algorithm choose given the exploration parameter c is set to 1? Give the values of π_{UCT} for the node (consider log base 2 in UCT bound).

$$\pi_{UCT}(n) = \underset{a}{\operatorname{argmax}} \left(\hat{Q}(n, a) + c \sqrt{\frac{\log(N(n))}{N(n, a)}} \right)$$



Question




- d) Consider a search tree where the reward is zero everywhere except at the leaves. When a MCTS trial goes through a node, we say that an action at the node wins if the trial ends in a leaf with reward 1. Consider an MCTS simulation where a node has been visited 16 times and has two actions, A and B. Action A has a won 2 out 4 times whereas action B has won 8 out of 12 times. Which action will the MCTS algorithm chose given the exploration parameter c is set to 1? Give the values of π_{UCT} for the node (consider log base 2 in UCT bound).

$$\pi_{UCT}(n) = \underset{a}{\operatorname{argmax}} \left(\hat{Q}(n, a) + c \sqrt{\frac{\log(N(n))}{N(n, a)}} \right)$$

A: $\frac{2}{4} + \sqrt{\frac{\log 16}{4}} = 1.5$

State:  ...  ← n values





- d) Consider a search tree where the reward is zero everywhere except at the leaves. When a MCTS trial goes through a node, we say that an action at the node wins if the trial ends in a leaf with reward 1. Consider an MCTS simulation where a node has been visited 16 times and has two actions, A and B. Action A has won 2 out of 4 times whereas action B has won 8 out of 12 times. Which action will the MCTS algorithm choose given the exploration parameter c is set to 1? Give the values of π_{UCT} for the node (consider log base 2 in UCT bound).


$$\pi_{UCT}(n) = \underset{a}{\operatorname{argmax}} \left(\hat{Q}(n, a) + c \sqrt{\frac{\log(N(n))}{N(n, a)}} \right)$$

$$A: \frac{2}{4} + \sqrt{\frac{\log 16}{4}} = 1.5$$

$$B: \frac{8}{12} + \sqrt{\frac{\log 16}{12}} = 1.244$$


State:  $\leftarrow n \text{ values}$





- d) Consider a search tree where the reward is zero everywhere except at the leaves. When a MCTS trial goes through a node, we say that an action at the node wins if the trial ends in a leaf with reward 1. Consider an MCTS simulation where a node has been visited 16 times and has two actions, A and B. Action A has won 2 out of 4 times whereas action B has won 8 out of 12 times. Which action will the MCTS algorithm choose given the exploration parameter c is set to 1? Give the values of π_{UCT} for the node (consider log base 2 in UCT bound).

$$\pi_{UCT}(n) = \underset{a}{\operatorname{argmax}} \left(\hat{Q}(n, a) + c \sqrt{\frac{\log(N(n))}{N(n, a)}} \right)$$

A: $\frac{2}{4} + \sqrt{\frac{\log 16}{4}} = 1.5$ 

B: $\frac{8}{12} + \sqrt{\frac{\log 16}{12}} = 1.244$

Question?

<EOF>