

CS3244 Exam 1: Part 1


28 Sep 2020

Please do not turn to the next page until you are told to do so by your proctor.

- This exam part is worth **25** marks out of a **75** mark total for all three parts.
- This exam part is estimated to take you about **25** minutes to complete.
- This exam part has a total of **13** questions.
- This exam part contains only multiple choice questions (MCQs) and multiple response questions (MRQ). Please key these into the assessment system.
- You can visit <http://www.comp.nus.edu.sg/~cs3244/2010/e1.part1.html> to reach the entry form for this survey if you lose your browser window.
- Do remember that you will need to key in and submit your answers to the according assessment system as designated by your proctor or by exam central.

- (MRQ with 4 options; 2 marks) Tribes of ML. Mark which tribes' algorithms use some form of randomization as taught in lecture.
 - Analogyzer.
 - Connectionist.
 - Symbolist.
 - Bayesian.
- (MRQ with 4 options; 3 marks) Which of the following statements is true regarding KNN?
 - KNN can be applied on regression tasks.
 - Using smaller k value leads to a smoother classification boundary.
 - As the k value increases, the classification accuracy will be higher.
 - The time complexity for training KNN is $O(1)$ and $O(n)$ for testing, where n is the number of test examples.

- (MRQ with 5 options; 2 marks) Mark all correct associations with the diagrams below, where the diagrams are labeled left (L), middle (M), and right (R).



- L — high bias
- R — high variance
- L — high variance
- M — ideal
- R — high bias

[Questions 4–7] (MCQ; 1 mark each) Mark (a) for true and (b) for false for each of the following statements.

- Supervised learning requires labeled data while unsupervised learning does not.
- KNN and K-means are both examples of unsupervised learning algorithms.
- The goal of supervised learning is to learn a target function that approximates the hypothesis function.
- SVM can penalise instances that are correctly classified.
- (MCQ; 2 marks) For which of the following tasks should you **not** use machine learning?
 - Create an agent that can fly a plane in a flight simulator.
 - Sort a list of random numbers.
 - Determine whether a student's transcript fulfills graduation requirements.
 - Predict the next number in a game of roulette after observing many rounds.
 - Predict the winner of a soccer tournament based on player statistics.
 - Predict the score of a student's machine learning exam given forum participation.

9. (MCQ; 2 marks) KNN may overfit datasets of high dimensionality. Which option would you choose to handle this problem?
- (a) Non-linear mapping to fewer dimensions (dimensionality reduction).
 - (b) Using a smaller K.
 - (c) Both non-linear mapping to fewer dimensions and using a smaller K.
 - (d) Neither of them.
10. (MCQ; 2 marks) Suppose a perceptron with two input features does not have a bias weight. Mark the implication of this design choice.
- (a) It will require, on average, 1.5 times as many training examples compared to if it had a bias weight.
 - (b) It will function as a sigmoid unit.
 - (c) Its decision boundary will pass through the origin.
 - (d) It will require, on average, 0.67 times as many training examples compared to if it had a bias weight.
11. (MCQ; 2 marks) In which of the following tasks should you **not** use unsupervised machine learning techniques?
- (a) Identify irregular packet traffic on a network.
 - (b) Group customer data.
 - (c) Predict lottery results.
 - (d) Help a farmer sort produce based on camera footage.
 - (e) We can use it for all of the above.
12. (MRQ with 5 options; 3 marks) SVM Knowledge. Mark the correct statement(s).
- (a) The hard SVM, like the perceptron, requires the dataset to be linearly separable.
 - (b) SVMs achieve can find non-linear classification boundaries using a kernel function to map a \mathcal{Z} space.
 - (c) The margin is defined as the distance between the closest positive and closest negative point(s) in a training dataset to the optimal separative hyperplane.
 - (d) The SVM penalises misclassifications more when they are further away from the margin boundary of their correct class.
 - (e) The margin is defined to have unit (1) distance for convenience. Other values would also work.
13. (MRQ with 5 options; 3 marks) By running the Candidate-Elimination algorithm on a task, a version space is produced with a specific S boundary sets and a general boundary set G . Given a new input instance x , which of the following statements are correct?
- (a) If x satisfies none of the members of G , then x satisfies none of the hypotheses in the version space.
 - (b) If x satisfies every member of S , then x satisfies every hypothesis in the version space.
 - (c) If x satisfies every member of G , then x satisfies every hypothesis in the version space.
 - (d) If x satisfies none of the members of S , then x satisfies none of the hypotheses in the version space.
 - (e) If x satisfies both S and G , there is only one hypothesis remaining in the version space.

This marks the end of this part of the exam.
These is no additional material beyond this point.