

CS3223 Lab 2 Report

Group 63

Team Member Name	Matric Number
1. Eugene Tan Yew Chin	A0136174H
2. Yap Dian Hao	A0184679H
3. Chiew Kok Seng	A0190705H

File to Change	Changes
CreateStudentDB.java	<ul style="list-style-type: none">Added <code>hash</code> index on student name field of table <code>STUDENT</code>.Added <code>btree</code> index on student id field of table <code>STUDENT</code>.Added <code>hash</code> index on major id field of table <code>STUDENT</code>.Added <code>btree</code> index on grad year field of table <code>STUDENT</code>.Added <code>btree</code> index on department id field of table <code>DEPT</code>.Added <code>hash</code> index on department name field of table <code>DEPT</code>.Added <code>btree</code> index on student id field of table <code>ENROLL</code>.
simplifiedb/metadata/IndexInfo.java	<ul style="list-style-type: none">Added a new field, <code>indexType</code>Overloaded a constructor to accept the new field as the argument to determine which index type (hash / btree) to create.Modified the function <code>open()</code> to return a relevant index according to the <code>indexType</code>.Modified the function <code>blockAccessed()</code> to use the relevant index's methods accordingly.

<code>simplifiedb/metadata/IndexMgr.java</code>	<ul style="list-style-type: none"> Added a new field, <code>indexType</code> in the index manager's schema. Passed in a new argument <code>indexType</code> to store the type of index in the <code>createIndex</code> routine. The <code>getIndexInfo</code> routine now uses the new field, <code>indexType</code> , when retrieving the <code>IndexInfo</code>.
<code>simplifiedb/metadata/MetadataMgr.java</code>	<ul style="list-style-type: none"> Modified the <code>createIndex</code> routine to accept a new argument, <code>indexType</code> to match with the index manager's <code>createIndex</code> routine.
<code>simplifiedb/metadata/MetadataMgrTest.java</code>	<ul style="list-style-type: none"> Modified the test cases to pass in new arguments, the index type in the <code>MetadataMgr</code> 's <code>createIndex</code> routine.
<code>simplifiedb/parse/Lexer.java</code>	<ul style="list-style-type: none"> Added new keyword <code>using</code> to support the new SQL command syntax to create specified indexes of hash / btree.
<code>simplifiedb/parse/CreateIndexData.java</code>	<ul style="list-style-type: none"> Added a new field, <code>indexType</code> Modified the constructor to accept this new <code>indexType</code> field of the specified index. Added a getter method for <code>indexType</code> .
<code>simplifiedb/parse/Parser.java</code>	<ul style="list-style-type: none"> Modified the <code>createIndex</code> routine to consume the keyword <code>using</code> and the <code>indexType</code> (which specifies the type of index to create). <code>createIndex</code> now passes <code>indexType</code> to the modified constructor of <code>CreateIndexData</code> .
<code>simplifiedb/index/planner/IndexUpdatePlanner.java</code>	<ul style="list-style-type: none"> Modified the <code>createIndex</code> routine call of <code>MetadataMgr</code> in the <code>executeCreateIndex</code> routine to now also take in an additional argument indicating the index type.
<code>simplifiedb/server/SimpleDB.java</code>	<ul style="list-style-type: none"> Commented out and uncommented the relevant lines to use the appropriate pair of <code>QueryPlanner</code> , <code>UpdatePlanner</code> as instructed in step 2 of the assignment docs.